



Integration of Offline Partial Deduction and Functional Conversion for miniKanren

Aleksandr Shefer, Ekaterina Verbitskaia

JetBrains Research, Programming Languages and Program Analysis Lab

April 7, 2024

Search is More Complicated than Verification

The Tower of Hanoi Puzzle

`verify [1 → 2, 1 → 3, 2 → 3] ⇒ True`

`verify [1 → 2, 1 → 2] ⇒ False`

`solve True ⇒ [1 → 2, 1 → 3, 2 → 3, ...]`

Search is Dual to Verification

$$\text{solve} \approx \text{verify}^{-1}$$

Logic Programming Highlights the Duality

`hanoio candidate result`

`verify = run q (hanoio [1 → 2, 1 → 3, 2 → 3] q) ⇒ q = True`

`solve = run q (hanoio q True) ⇒ q = [1 → 2, 1 → 3, 2 → 3, ...]`

Program Interpretation and Synthesis

Verifier

```
eval st (Conj x y) =  
  eval st x && eval st y  
...
```


Solver

```
synth st res = do  
  (u, v) ← [(u, v) |  
    u ← [False, True],  
    v ← [False, True],  
    u && v == res]  
  x ← synth st u  
  y ← synth st v  
  return (Conj x y)  
...
```

Relational Interpreters for Search

```
eval st (Conj x y) =  
  eval st x && eval st y  
...
```

```
evalo st fm u = fresh (x y v w)  
  (fm ≡ Conj x y ∧  
   evalo st x v ∧  
   evalo st y w ∧  
   ando v w u);  
...
```




Relational Interpreters for Search: the Issue

It is slow

Relational Programming in MINIKANREN

- Pure logic programming
- Complete search: interleaving

MINIKANREN Syntax

 relation

```
evalo st fm u =  
  fresh (x y v w z)  
    (fm ≡ Conj x y ∧  
      evalo st x v ∧  
      evalo st y w ∧  
      ando v w u) ∨  
    ...
```

MINIKANREN Syntax

$\text{eval}^o \text{ st fm u} =$
 fresh (x y v w z)
 (fm \equiv Conj x y \wedge
 eval^o st x v \wedge
 eval^o st y w \wedge
 and^o v w u) \vee
 ...

relation call

relation

MINIKANREN Syntax


Diagram illustrating the MINIKANREN syntax for a relation definition:

```
evalo st fm u =  
  fresh (x y v w z)  
    (fm ≡ Conj x y ∧  
      evalo st x v ∧  
      evalo st y w ∧  
      ando v w u) ∨  
    ...
```


Annotations:


- relation**: Points to the entire definition line `evalo st fm u =`.
- term unification**: Points to the unification constraint `(fm ≡ Conj x y ∧ ...)`.
- relation call**: Points to the call to the relation `evalo st x v`.

MINIKANREN Syntax



MINIKANREN Syntax






Sources of Inefficiency


- Running backwards is slow
- Order of clauses influences performance
- Constant arguments (`evalo [] q True`)

Solution: specialization


Specialization Scheme



Specialization Scheme



Specialization Scheme



Mode Analysis

- Variable modes:
- Ground term: True
 - Free variable: x

$$\text{eval}^\circ [] \text{ fm True} \rightarrow \text{eval}^\circ \text{ g f g}$$

$$\begin{aligned} \text{eval}^\circ \text{ st fm u} = & \\ \text{fresh } (x \ y \ v \ w \ z) & \\ (\text{fm} \equiv \text{Conj } x \ y \wedge & \\ \text{eval}^\circ \text{ st x v} \wedge & \\ \text{eval}^\circ \text{ st y w} \wedge & \\ \text{and}^\circ \text{ v w u}) \vee & \text{ u = True} \\ \dots & \end{aligned}$$


$$\begin{aligned} \text{eval}^\circ \text{ st fm u} = & \\ \text{fresh } (x \ y \ v \ w \ z) & \\ (\text{and}^\circ \text{ v w u} \wedge & \text{ u = True} \\ \text{eval}^\circ \text{ st x v} \wedge & \text{ v = True} \\ \text{eval}^\circ \text{ st y w} \wedge & \text{ w = True} \\ \text{fm} \equiv \text{Conj } x \ y) \vee & \\ \dots & \end{aligned}$$

Partial Deduction


```
evalo st fm u =  
  safe ando a b u &  
  unsafe evalo st x a &  
  unsafe evalo st y b &  
  fm ≡ Conj x y |  
  ...
```

```
evalo [] fm true
```


Partial Deduction



Partial Deduction



Partial Deduction: Trees Construction




Binding Time Analysis

- Call annotations:
- Safe: continue unfolding
 - Unsafe: **possibly** stop unfolding

```
evalo st fm u =  
  fresh (x y v w z)  
  ( safe ando a b u &  
    unsafe evalo st x a &  
    unsafe evalo st y b &  
    fm ≡ Conj x y) |  
  ...
```

Partial Deduction with Annotations



Functional Conversion

```
eval_trueo fm =  
  fresh (x y)  
    (eval_trueo x ∧  
      eval_trueo y ∧  
      fm ≡ Conj x y) ∨  
  ...
```

⇒

```
eval_true = do  
  x ← eval_true  
  y ← eval_true  
  return (Conj x y)  
  ...
```

- Functional Conversion
- Online Partial Deduction and Functional Conversion
- Our approach: Offline Partial Deduction and Functional Conversion

Evaluation: Propositional Evaluator

	Functional conversion	Translation with partial deduction	
		Online	Offline
10 formulas	4.05 μ s	0.33 μ s	0.37 μ s
100 formulas	56.00 μ s	7.40 μ s	7.73 μ s
1000 formulas	645.00 μ s	108.00 μ s	108.00 μ s

Evaluation: the Tower of Hanoi puzzle

	Functional conversion	Translation with partial deduction	
		Online	Offline
3 disks	153 000.00 μ s	125 000.00 μ s	1.67 μ s
4 disks	⌚timeout	⌚timeout	3.12 μ s

Evaluataion: Other Benchmarks (DPPD¹)

	Functional conversion	Translation with partial deduction	
		Online	Offline
appLast	1.13 μ s	0.08 μ s	0.09 μ s
contains	14.70 μ s	0.78 μ s	0.77 μ s
doubleAppend	⊕timeout	2910.00 μ s	2.00 μ s
exDepth	⊕timeout	⊕timeout	3.09 μ s
nthOpt	0.10 μ s	0.08 μ s	0.10 μ s
...			

¹Dozens of Problems for Partial Deduction benchmark: <https://github.com/leuschel/DPPD>

- We integrated the Functional Conversion and Offline Partial Deduction approaches
- We conducted a preliminary evaluation of the approach
- The effectiveness of the integration has been shown