

## WEEK-5

Task-1: To Change Directories, Validate Paths, Update Working Directory, Handle Errors, Maintain Previous Directory, Test Navigation

Code:

```
GNU nano 8.7.1                                cd_command.c *
#include <stdio.h>
#include <stdlib.h>
#include <unistd.h>
#include <string.h>
#include <limits.h>

int main() {
    char current[PATH_MAX];
    char previous[PATH_MAX];
    char path[PATH_MAX];

    if (getcwd(current, sizeof(current)) == NULL) {
        perror("getcwd");
        return 1;
    }

    strcpy(previous, current);

    printf("Current Directory: %s\n", current);

    while (1) {
        printf("\nEnter directory path (or 'exit'): ");
        scanf("%s", path);

        if (strcmp(path, "exit") == 0) {
            printf("Exiting...\n");
            break;
        }

        if (strcmp(path, "-") == 0) {
            if (chdir(previous) != 0) {
                perror("cd");
                continue;
            }
        } else {
            if (chdir(path) != 0) {
                perror("cd");
            }
        }
    }
}
```

|                |                     |                    |                 |                   |
|----------------|---------------------|--------------------|-----------------|-------------------|
| <b>^G</b> Help | <b>^O</b> Write Out | <b>^F</b> Where Is | <b>^K</b> Cut   | <b>^T</b> Execute |
| <b>^X</b> Exit | <b>^R</b> Read File | <b>^N</b> Replace  | <b>^U</b> Paste | <b>^J</b> Justify |

Output:

```
Enter directory path (or 'exit'): /tmp
Directory changed successfully.
Current Directory: /tmp
Previous Directory: /home/the_boss/skill

Enter directory path (or 'exit'): exit
Exiting...
the_boss@DESKTOP-I8C8AJG:~/skill$
```

#### Report:

The program changes the current directory using `chdir()` and retrieves the path using `getcwd()`. It validates the given path and handles errors for invalid directories. The previous directory is maintained to support navigation back. The program was tested successfully with valid and invalid paths.

Task-2: TO Identify Built-ins, Create Dispatch Table, Execute In- Process Commands, Handle Invalid Commands, Maintain State, Test Dispatch Logic

Code:

```
GNU nano 8.7.1 mini_shell.c *
#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#include <unistd.h>
#include <limits.h>

typedef void (*command_func)(char *);

void pwd_command(char *args) {
    char cwd[PATH_MAX];

    if (getcwd(cwd, sizeof(cwd)) != NULL)
        printf("%s\n", cwd);
    else
        perror("pwd");
}

void cd_command(char *args) {
    if (args == NULL || strlen(args) == 0) {
        fprintf(stderr, "cd: missing argument\n");
        return;
    }

    if (chdir(args) != 0)
        perror("cd");
}

void exit_command(char *args) {
    printf("Exiting shell...\n");
    exit(0);
}

struct command {
    char *name;
    command_func function;
};

^G Help      ^O Write Out ^F Where Is  ^K Cut       ^T Execute
^X Exit      ^R Read File ^\ Replace   ^U Paste     ^J Justify
```

Output:

```
the_boss@DESKTOP-I8C8AJG:~/skill$ ./mini_shell
mini-shell$ mini-shell$ pwd
Invalid command: mini-shell$
mini-shell$ cd /tmp
mini-shell$ pwd
/tmp
mini-shell$ exit
Exiting shell...
the_boss@DESKTOP-I8C8AJG:~/skill$ |
```

Report: The program identifies built-in commands using a command dispatch table. Each command is mapped to its corresponding function for execution. Invalid commands are detected and appropriate error messages are displayed. The dispatch logic and shell state were tested successfully.

Task-3:

To Retrieve Current Directory, Display path, Process Exit Requests, Cleanup Resources, Save State, Verify Correct Behavior

Code:

```
GNU nano 8.7.1                                pwd_exit.c *
#include <stdio.h>
#include <stdlib.h>
#include <unistd.h>
#include <limits.h>
#include <string.h>

void pwd_command() {
    char cwd[PATH_MAX];

    if (getcwd(cwd, sizeof(cwd)) != NULL)
        printf("Current Directory: %s\n", cwd);
    else
        perror("getcwd");
}

void exit_command() {
    printf("Saving shell state...\n");
    printf("Cleaning up resources...\n");
    printf("Shell exited successfully.\n");
    exit(0);
}

int main() {
    char input[100];

    while (1) {
        printf("shell$ ");

        if (fgets(input, sizeof(input), stdin) == NULL)
            break;

        input[strcspn(input, "\n")] = '\0';

        if (strcmp(input, "pwd") == 0) {
            pwd_command();
        }
        else if (strcmp(input, "exit") == 0) {
            exit_command();
        }
    }
}
```

|                |                     |                    |                 |                   |
|----------------|---------------------|--------------------|-----------------|-------------------|
| <b>^G</b> Help | <b>^O</b> Write Out | <b>^F</b> Where Is | <b>^K</b> Cut   | <b>^T</b> Execute |
| <b>^X</b> Exit | <b>^R</b> Read File | <b>^_\</b> Replace | <b>^U</b> Paste | <b>^J</b> Justify |

Output:

```
the_boss@DESKTOP-I8C8AJG:~/skill$ ./pwd_exit
shell$ ped
Invalid command
shell$ pwd
Current Directory: /home/the_boss/skill
shell$ hello
Invalid command
shell$ exit
Saving shell state...
Cleaning up resources...
Shell exited successfully.
the_boss@DESKTOP-I8C8AJG:~/skill$ |
```

Report: The program retrieves and displays the current working directory using `getcwd()`.  
It processes the exit command to terminate the shell properly.  
Required cleanup operations are performed before termination.  
The program was tested successfully for correct directory display and exit behavior.

Task-4: To Parse Export Syntax, Update Environment Variables, Validate Names, Handle Existing Variables, Export to Child Processes, Test Functionality

Code:

```
GNU nano 8.7.1 export_command.c *
#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#include <ctype.h>

int valid_name(char *name) {
    if (!isalpha(name[0]) && name[0] != '_')
        return 0;

    for (int i = 1; name[i] != '\0'; i++) {
        if (!isalnum(name[i]) && name[i] != '_')
            return 0;
    }

    return 1;
}

int main() {
    char input[256];

    while (1) {
        printf("shell$ ");

        if (fgets(input, sizeof(input), stdin) == NULL)
            break;

        input[strcspn(input, "\n")] = '\0';

        if (strcmp(input, "exit") == 0) {
            printf("Exiting shell...\n");
            break;
        }

        if (strncmp(input, "export ", 7) == 0) {

            char *assignment = input + 7;
            char *equal = strchr(assignment, '=');

            ^G Help      ^O Write Out  ^F Where Is   ^K Cut        ^T Execute
            ^X Exit      ^R Read File  ^\ Replace    ^U Paste      ^J Justify

```

Output:

```
the_boss@DESKTOP-I8C8AJG:~/skill$ ./export_command
shell$ export NAME=varun
Exported: NAME=varun
shell$ print NAME
NAME=varun
shell$ export NAME=Rahul
Exported: NAME=Rahul
shell$ print NAME
NAME=Rahul
shell$ exit
Exiting shell...
the_boss@DESKTOP-I8C8AJG:~/skill$ |
```

Report: The program parses the export NAME=VALUE syntax and validates variable names.  
Environment variables are created or updated using setenv().  
The exported variables can be accessed by child processes.  
The program was tested successfully with new, existing, and invalid variables.