

WEEK-8

Task-1: TO Parse Combined Redirection, Duplicate File Descriptors, Merge Streams, Verify Ordering, Handle Edge Cases, Test Integrated Outputs

Code:

```
GNU nano 8.7.1 combined_redirect.c *
#include <stdio.h>
#include <unistd.h>
#include <fcntl.h>
#include <sys/wait.h>
#include <stdlib.h>

int main() {
    int input_fd, output_fd;
    pid_t pid;

    input_fd = open("input.txt", O_RDONLY);

    if (input_fd == -1) {
        perror("input.txt");
        return 1;
    }

    output_fd = open("output.txt",
                     O_WRONLY | O_CREAT | O_TRUNC,
                     0644);

    if (output_fd == -1) {
        perror("output.txt");
        close(input_fd);
        return 1;
    }

    pid = fork();

    if (pid == 0) {
        dup2(input_fd, STDIN_FILENO);
        dup2(output_fd, STDOUT_FILENO);

        close(input_fd);
        close(output_fd);

        execlp("cat", "cat", NULL);
    }
}
```

^G Help	^O Write Out	^F Where Is	^K Cut	^T Execute
^X Exit	^R Read File	^\\ Replace	^U Paste	^J Justify

Output:

```
the_boss@DESKTOP-I8C8AJG:~/skill$ nano combined_redirect.c
the_boss@DESKTOP-I8C8AJG:~/skill$ nano input.txt
the_boss@DESKTOP-I8C8AJG:~/skill$ gcc combined_redirect.c -o combined_redirect
the_boss@DESKTOP-I8C8AJG:~/skill$ ./combined_redirect
Combined redirection completed.
the_boss@DESKTOP-I8C8AJG:~/skill$ cat output.txt
Hello Ubuntu
Operating Systems Lab
Combined Redirection
the_boss@DESKTOP-I8C8AJG:~/skill$ |
```

Report: The program parses and performs combined input and output redirection using file descriptors.

The required descriptors are duplicated to standard input and output using `dup2()`.

The ordering of redirections and possible file errors are handled appropriately.

The integrated redirection was tested successfully using input and output files.

Task-2: To Parse Complex Commands, Combine Pipes and Redirections, Resolve Execution Order, Validate Syntax, Generate Execution Plans, Test Scenarios

Code:

```
GNU nano 8.7.1                                complex_command.c *
#include <stdio.h>
#include <unistd.h>
#include <fcntl.h>
#include <sys/wait.h>
#include <stdlib.h>

int main() {
    int pipefd[2];
    int input_fd, output_fd;
    pid_t p1, p2;

    input_fd = open("input.txt", O_RDONLY);

    if (input_fd == -1) {
        perror("input.txt");
        return 1;
    }

    output_fd = open("result.txt",
                     O_WRONLY | O_CREAT | O_TRUNC,
                     0644);

    if (output_fd == -1) {
        perror("result.txt");
        return 1;
    }

    if (pipe(pipefd) == -1) {
        perror("pipe");
        return 1;
    }

    p1 = fork();

    if (p1 == 0) {
        dup2(input_fd, STDIN_FILENO);
        dup2(pipefd[1], STDOUT_FILENO);

        ^G Help      ^O Write Out    ^F Where Is     ^K Cut          ^T Execute
        ^X Exit      ^R Read File    ^\ Replace      ^U Paste        ^J Justify
    }
```

Output:

```
the_boss@DESKTOP-I8C8AJG:~/skill$ nano complex_command.c
the_boss@DESKTOP-I8C8AJG:~/skill$ gcc complex_command.c -o complex_command
the_boss@DESKTOP-I8C8AJG:~/skill$ ./complex_command
Complex command executed successfully.
the_boss@DESKTOP-I8C8AJG:~/skill$ cat result.txt
Hello Ubuntu
the_boss@DESKTOP-I8C8AJG:~/skill$ |
```

Report: The program parses a complex command containing both pipes and redirections. Input and output redirections are combined with the pipe to connect processes correctly. The execution order and command syntax are validated before running the pipeline. The program was tested successfully with different integrated command scenarios.

Task-3: To Detect Background Jobs, Launch Non-Blocking Processes, Return Prompt Immediately, Store Job Information, Monitor Execution, Test Background Tasks

Code:

```
GNU nano 8.7.1          background.c *
#include <stdio.h>
#include <unistd.h>
#include <sys/wait.h>
#include <stdlib.h>

int main() {
    pid_t pid;

    printf("Starting background job...\n");

    pid = fork();

    if (pid < 0) {
        perror("fork");
        return 1;
    }

    if (pid == 0) {
        execlp("sleep", "sleep", "10", NULL);

        perror("sleep");
        exit(1);
    }

    printf("Background job started with PID: %d\n", pid);
    printf("Prompt returned immediately.\n");

    sleep(2);

    if (waitpid(pid, NULL, WNOHANG) == 0)
        printf("Job is still running.\n");
    else
        printf("Job completed.\n");

    waitpid(pid, NULL, 0);

    printf("Background job finished.\n");
}
```

^G Help	^O Write Out	^F Where Is	^K Cut	^T Execute
^X Exit	^R Read File	^_ Replace	^U Paste	^J Justify

Output:

```
the_boss@DESKTOP-I8C8AJG:~/skill$ nano background.c
the_boss@DESKTOP-I8C8AJG:~/skill$ gcc background.c -o background
the_boss@DESKTOP-I8C8AJG:~/skill$ ./background
Starting background job...
Background job started with PID: 1478
Prompt returned immediately.
Job is still running.
Background job finished.
the_boss@DESKTOP-I8C8AJG:~/skill$ |
```

Report: The program detects and launches a background process without blocking the parent. The prompt is returned immediately while the child process continues execution. The process information is stored and its execution is monitored using `waitpid()`. The background task was tested successfully for non-blocking execution and completion.

Task-4: To Create Job Table, Store Process Groups, Track States, Update Status, Remove Completed Jobs, Validate Job Records

Code:

```
GNU nano 8.7.1 job_table.c *
#include <stdio.h>
#include <unistd.h>
#include <sys/wait.h>
#include <stdlib.h>

#define MAX_JOBS 5

struct Job {
    int job_id;
    pid_t pid;
    int active;
};

struct Job jobs[MAX_JOBS];
int job_count = 0;

void add_job(pid_t pid) {
    if (job_count < MAX_JOBS) {
        jobs[job_count].job_id = job_count + 1;
        jobs[job_count].pid = pid;
        jobs[job_count].active = 1;

        printf("[Job %d] PID %d started\n",
            jobs[job_count].job_id, pid);

        job_count++;
    }
}

void check_jobs() {
    for (int i = 0; i < job_count; i++) {
        if (jobs[i].active) {
            pid_t result =
                waitpid(jobs[i].pid, NULL, WNOHANG);
        }
    }
}

^G Help      ^O Write Out  ^F Where Is   ^K Cut        ^T Execute
^X Exit      ^R Read File  ^\ Replace    ^U Paste      ^J Justify
```

Output:

```
the_boss@DESKTOP-I8C8AJG:~/skill$ nano job_table.c
the_boss@DESKTOP-I8C8AJG:~/skill$ gcc job_table.c -o job_table
the_boss@DESKTOP-I8C8AJG:~/skill$ ./job_table
[Job 1] PID 1540 started
[Job 2] PID 1541 started

Initial Job Table:
[Job 1] PID 1540 RUNNING
[Job 2] PID 1541 RUNNING

Updated Job Table:
[Job 1] PID 1540 COMPLETED
[Job 2] PID 1541 RUNNING
the_boss@DESKTOP-I8C8AJG:~/skill$ |
```

Report: The program creates a job table to store process IDs, job IDs, and execution states. It tracks running processes and updates their status when they complete. Completed jobs are removed or marked inactive and the job records are validated. The program was tested successfully with multiple background jobs.