

Introduction to Machine Learning

Hierarchical Clustering and Large Data Set Clustering

Andres Mendez-Vazquez

January 26, 2023

Outline

1 Hierarchical Clustering

- Definition
- Basic Ideas

2 Agglomerative Algorithms

- Introduction
- Two Categories of Agglomerative Algorithms
 - Matrix Based Algorithms
 - Single Linkage
 - Complete Linkage
 - Group Average Linkage
- Graph Based Algorithms
- Problems with Agglomerative Algorithms
 - Improving the Complexity

3 Divisive Algorithms

- Introduction
- Possible Complexity
- Monothetic Divisive Methods

4 Algorithms for Large Data Sets

- Introduction
- Clustering Using REpresentatives (CURE)
 - Shrinking Process
 - CURE Algorithm
 - Complexity
- DBSCAN
 - Density Based Notion of Clusters
 - Beyond K -NN Idea
 - Cluster and Noise Definition
 - Sustaining the Algorithm
 - The DBSCAN Algorithm
 - Complexity
 - Finding ϵ and $MinPts$



Outline

1 Hierarchical Clustering

- Definition
- Basic Ideas

2 Agglomerative Algorithms

- Introduction
- Two Categories of Agglomerative Algorithms
 - Matrix Based Algorithms
 - Single Linkage
 - Complete Linkage
 - Group Average Linkage
- Graph Based Algorithms
- Problems with Agglomerative Algorithms
 - Improving the Complexity

3 Divisive Algorithms

- Introduction
- Possible Complexity
- Monothetic Divisive Methods

4 Algorithms for Large Data Sets

- Introduction
- Clustering Using REpresentatives (CURE)
 - Shrinking Process
 - CURE Algorithm
 - Complexity
- DBSCAN
 - Density Based Notion of Clusters
 - Beyond K -NN Idea
 - Cluster and Noise Definition
 - Sustaining the Algorithm
 - The DBSCAN Algorithm
 - Complexity
 - Finding ϵ and $MinPts$



Hierarchical Clustering Algorithms

They are quite different from the previous clustering algorithms.



Hierarchical Clustering Algorithms

They are quite different from the previous clustering algorithms.

Actually

They produce a hierarchy of clusterings.



Dendrogram

Hierarchical Clustering

The clustering is obtained by cutting the **dendrogram** at a desired level:


- Each connected component forms a cluster.



Cinvestav

Example

Dendrogram



Outline

1 Hierarchical Clustering

- Definition
- Basic Ideas

2 Agglomerative Algorithms

- Introduction
- Two Categories of Agglomerative Algorithms
 - Matrix Based Algorithms
 - Single Linkage
 - Complete Linkage
 - Group Average Linkage
- Graph Based Algorithms
- Problems with Agglomerative Algorithms
 - Improving the Complexity

3 Divisive Algorithms

- Introduction
- Possible Complexity
- Monothetic Divisive Methods

4 Algorithms for Large Data Sets

- Introduction
- Clustering Using REpresentatives (CURE)
 - Shrinking Process
 - CURE Algorithm
 - Complexity
- DBSCAN
 - Density Based Notion of Clusters
 - Beyond K -NN Idea
 - Cluster and Noise Definition
 - Sustaining the Algorithm
 - The DBSCAN Algorithm
 - Complexity
 - Finding ϵ and $MinPts$



Basic Ideas

At each step t

A new clustering is obtained based on the clustering produced at the previous step $t - 1$



Cinvestav

Basic Ideas

At each step t

A new clustering is obtained based on the clustering produced at the previous step $t - 1$

Two Main Types

- 1 Agglomerative Algorithms.



Cinvestav

Basic Ideas

At each step t

A new clustering is obtained based on the clustering produced at the previous step $t - 1$

Two Main Types

- 1 Agglomerative Algorithms.
 - 1 Start with each item being a single cluster.



Cinvestav

Basic Ideas

At each step t

A new clustering is obtained based on the clustering produced at the previous step $t - 1$

Two Main Types

- 1 Agglomerative Algorithms.
 - 1 Start with each item being a single cluster.
 - 2 Eventually all items belong to the same cluster.



Cinvestav

Basic Ideas

At each step t

A new clustering is obtained based on the clustering produced at the previous step $t - 1$

Two Main Types

- ① Agglomerative Algorithms.
 - ① Start with each item being a single cluster.
 - ② Eventually all items belong to the same cluster.
- ② Divisive Algorithms



Basic Ideas

At each step t

A new clustering is obtained based on the clustering produced at the previous step $t - 1$

Two Main Types

- ① Agglomerative Algorithms.
 - ① Start with each item being a single cluster.
 - ② Eventually all items belong to the same cluster.
- ② Divisive Algorithms
 - ① Start with all items belong to the same cluster.



Cinvestav

Basic Ideas

At each step t

A new clustering is obtained based on the clustering produced at the previous step $t - 1$

Two Main Types

① Agglomerative Algorithms.

- ① Start with each item being a single cluster.
- ② Eventually all items belong to the same cluster.

② Divisive Algorithms

- ① Start with all items belong to the same cluster.
- ② Eventually each item forms a cluster on its own.



Remark

With hierarchical methods, divisions or fusions, once made

- They are irrevocable
 - ▶ Agglomerative algorithm has joined two individuals they cannot subsequently be separated.



Cinvestav

Remark

With hierarchical methods, divisions or fusions, once made

- They are irrevocable
 - ▶ Agglomerative algorithm has joined two individuals they cannot subsequently be separated.
 - ▶ A divisive algorithm has made a split it cannot be undone.



Remark

With hierarchical methods, divisions or fusions, once made

- They are irrevocable
 - ▶ Agglomerative algorithm has joined two individuals they cannot subsequently be separated.
 - ▶ A divisive algorithm has made a split it cannot be undone.

As Kaufman and Rousseeuw (1990) colourfully comment (Similar to Forward Feature Selection)

- “A hierarchical method suffers from the defect that it can never repair what was done in previous steps.”



Therefore

Given the previous ideas

It is necessary to define the concept of nesting!!!




Cinvestav

Therefore

Given the previous ideas

It is necessary to define the concept of nesting!!!

After all given a divisive and agglomerative procedure



Cinvestav

Nested Clustering

Definition

- 1 A clustering \mathcal{R}_i containing k clusters is said to be nested in the clustering \mathcal{R}_{i+1} , which contains $r < k$ clusters, if each cluster in \mathcal{R}_i , it is a subset of a set in \mathcal{R}_{i+1} .



Nested Clustering

Definition

- 1 A clustering \mathcal{R}_i containing k clusters is said to be nested in the clustering \mathcal{R}_{i+1} , which contains $r < k$ clusters, if each cluster in \mathcal{R}_i , it is a subset of a set in \mathcal{R}_{i+1} .
- 2 At least one cluster at \mathcal{R}_i is a proper subset of a set in \mathcal{R}_{i+1} .



Nested Clustering

Definition

- 1 A clustering \mathcal{R}_i containing k clusters is said to be nested in the clustering \mathcal{R}_{i+1} , which contains $r < k$ clusters, if each cluster in \mathcal{R}_i , it is a subset of a set in \mathcal{R}_{i+1} .
- 2 At least one cluster at \mathcal{R}_i is a proper subset of a set in \mathcal{R}_{i+1} .

This is written as

$$\mathcal{R}_i \sqsubset \mathcal{R}_{i+1} \quad (1)$$



Cinvestav

Example

We have

The following set $\{x_1, x_2, x_3, x_4, x_5\}$.



Example

We have

The following set $\{x_1, x_2, x_3, x_4, x_5\}$.

With the following structures

- $\mathfrak{R}_1 = \{\{x_1, x_3\}, \{x_4\}, \{x_2, x_5\}\}$



Cinvestav

Example

We have

The following set $\{x_1, x_2, x_3, x_4, x_5\}$.

With the following structures

- $\mathfrak{R}_1 = \{\{x_1, x_3\}, \{x_4\}, \{x_2, x_5\}\}$
- $\mathfrak{R}_2 = \{\{x_1, x_3, x_4\}, \{x_2, x_5\}\}$



Cinvestav

Example

We have

The following set $\{x_1, x_2, x_3, x_4, x_5\}$.

With the following structures

- $\mathcal{R}_1 = \{\{x_1, x_3\}, \{x_4\}, \{x_2, x_5\}\}$
- $\mathcal{R}_2 = \{\{x_1, x_3, x_4\}, \{x_2, x_5\}\}$

Again

Hierarchical Clustering produces a hierarchy of clusterings!!!



Cinvestav

Outline

1 Hierarchical Clustering

- Definition
- Basic Ideas

2 Agglomerative Algorithms

- Introduction
- Two Categories of Agglomerative Algorithms
 - Matrix Based Algorithms
 - Single Linkage
 - Complete Linkage
 - Group Average Linkage
- Graph Based Algorithms
- Problems with Agglomerative Algorithms
 - Improving the Complexity

3 Divisive Algorithms

- Introduction
- Possible Complexity
- Monothetic Divisive Methods

4 Algorithms for Large Data Sets

- Introduction
- Clustering Using REpresentatives (CURE)
 - Shrinking Process
 - CURE Algorithm
 - Complexity
- DBSCAN
 - Density Based Notion of Clusters
 - Beyond K -NN Idea
 - Cluster and Noise Definition
 - Sustaining the Algorithm
 - The DBSCAN Algorithm
 - Complexity
 - Finding ϵ and $MinPts$



Agglomerative Algorithms.

Initial State

- You have N clusters each containing an element of the data X .



Agglomerative Algorithms.

Initial State

- You have N clusters each containing an element of the data X .
 - ▶ At each step i , you have an \mathcal{R}_i structure with $N - i$.



Cinvestav

Agglomerative Algorithms.

Initial State

- You have N clusters each containing an element of the data X .
 - ▶ At each step i , you have an \mathcal{R}_i structure with $N - i$.
 - ▶ Then, a new clustering structure \mathcal{R}_{i+1} is generated.



Agglomerative Algorithms.

Initial State

- You have N clusters each containing an element of the data X .
 - ▶ At each step i , you have an \mathcal{R}_i structure with $N - i$.
 - ▶ Then, a new clustering structure \mathcal{R}_{i+1} is generated.

Thus


$\{\{x_1\}, \{x_2\}, \{x_3\}, \{x_4\}, \{x_5\}\}$

$\{\{x_1, x_2\}, \{x_3\}, \{x_4\}, \{x_5\}\}$

$\{\{x_1, x_2\}, \{x_3\}, \{x_4, x_5\}\}$

$\{\{x_1, x_2\}, \{x_3, x_4, x_5\}\}$

$\{\{x_1, x_2, x_3, x_4, x_5\}\}$



In that way...

We have

At each step, we have that each cluster \mathcal{R}_i is a proper subset of a cluster in \mathcal{R}_{i+1} or

$$\mathcal{R}_i \subset \mathcal{R}_{i+1} \quad (2)$$



Cinvestav

The Basic Algorithm for Agglomerative

For this

- We have a function $d(C_i, C_j)$ defined in all pair of cluster to measure similarity or dissimilarity.



The Basic Algorithm for Agglomerative

For this

- We have a function $d(C_i, C_j)$ defined in all pair of cluster to measure similarity or dissimilarity.
- t denotes the current level of the hierarchy.



The Basic Algorithm

We have

- 1 Initialization

The Basic Algorithm

We have

- 1 Initialization
- 2 Choose $\mathfrak{R}_0 = \{Ci = \{x_i\} | i = 1, \dots, N\}$

The Basic Algorithm

We have

- 1 Initialization
- 2 Choose $\mathfrak{R}_0 = \{Ci = \{x_i\} | i = 1, \dots, N\}$
- 3 $t = 0$

The Basic Algorithm

We have

- 1 Initialization
- 2 Choose $\mathfrak{R}_0 = \{Ci = \{x_i\} | i = 1, \dots, N\}$
- 3 $t = 0$
- 4 Repeat:

The Basic Algorithm

We have

- ① Initialization
- ② Choose $\mathfrak{R}_0 = \{Ci = \{x_i\} | i = 1, \dots, N\}$
- ③ $t = 0$
- ④ Repeat:
- ⑤ $t = t + 1$



The Basic Algorithm

We have

- 1 Initialization
- 2 Choose $\mathfrak{R}_0 = \{Ci = \{x_i\} | i = 1, \dots, N\}$
- 3 $t = 0$
- 4 Repeat:
- 5 $t = t + 1$
- 6 Find one pair of clusters

The Basic Algorithm

We have

- 1 Initialization
- 2 Choose $\mathcal{R}_0 = \{C_i = \{x_i\} \mid i = 1, \dots, N\}$
- 3 $t = 0$
- 4 Repeat:
- 5 $t = t + 1$
- 6 Find one pair of clusters
 (C_r, C_s) in \mathcal{R}_{t-1} such that
 $d(C_i, C_j) = \max, \min$ of a similarity
 or dissimilarity function
 over all pairs

The Basic Algorithm

We have

- 1 Initialization
- 2 Choose $\mathcal{R}_0 = \{C_i = \{x_i\} \mid i = 1, \dots, N\}$
- 3 $t = 0$
- 4 Repeat:
 - 5 $t = t + 1$
 - 6 Find one pair of clusters
 (C_i, C_j) in \mathcal{R}_{t-1} such that
 $d(C_i, C_j) = \max, \min$ of a similarity
or dissimilarity function
over all pairs
 - 7 Define $C_q = C_i \cup C_j, \mathcal{R}_t = \mathcal{R}_{t-1} - \{C_i, C_j\} \cup C_q$

The Basic Algorithm

We have

- 1 Initialization
- 2 Choose $\mathcal{R}_0 = \{C_i = \{x_i\} \mid i = 1, \dots, N\}$
- 3 $t = 0$
- 4 Repeat:
 - 5 $t = t + 1$
 - 6 Find one pair of clusters
 (C_r, C_s) in \mathcal{R}_{t-1} such that
 $d(C_i, C_j) = \max, \min$ of a similarity
or dissimilarity function
over all pairs
 - 7 Define $C_q = C_i \cup C_j, \mathcal{R}_t = \mathcal{R}_{t-1} - \{C_i, C_j\} \cup C_q$
- 8 Until all vectors lay in a single cluster

The Basic Algorithm

We have

- 1 Initialization
- 2 Choose $\mathcal{R}_0 = \{C_i = \{x_i\} \mid i = 1, \dots, N\}$
- 3 $t = 0$
- 4 Repeat:
 - 5 $t = t + 1$
 - 6 Find one pair of clusters (C_r, C_s) in \mathcal{R}_{t-1} such that $d(C_i, C_j) = \max, \min$ of a similarity or dissimilarity function over all pairs
- 7 Define $C_q = C_i \cup C_j, \mathcal{R}_t = \mathcal{R}_{t-1} - \{C_i, C_j\} \cup C_q$
- 8 Until all vectors lay in a single cluster

Additionally

Note the following

“We can say that if two vectors come together into a single cluster at level t of the hierarchy, they will remain in the same cluster for all subsequent clusterings.”



Cinvestav

Additionally

Note the following

“We can say that if two vectors come together into a single cluster at level t of the hierarchy, they will remain in the same cluster for all subsequent clusterings.”

Thus

$$\mathcal{R}_0 \sqsubset \mathcal{R}_1 \sqsubset \mathcal{R}_2 \sqsubset \dots \mathcal{R}_{N-1} \sqsubset \mathcal{R}_N \quad (3)$$



Additionally

Note the following

“We can say that if two vectors come together into a single cluster at level t of the hierarchy, they will remain in the same cluster for all subsequent clusterings.”

Thus

$$\mathcal{R}_0 \sqsubset \mathcal{R}_1 \sqsubset \mathcal{R}_2 \sqsubset \dots \mathcal{R}_{N-1} \sqsubset \mathcal{R}_N \quad (3)$$

Which Enforces

- The nesting property!!!



Outline

1 Hierarchical Clustering

- Definition
- Basic Ideas

2 Agglomerative Algorithms

- Introduction
- Two Categories of Agglomerative Algorithms
 - Matrix Based Algorithms
 - Single Linkage
 - Complete Linkage
 - Group Average Linkage
- Graph Based Algorithms
- Problems with Agglomerative Algorithms
 - Improving the Complexity

3 Divisive Algorithms

- Introduction
- Possible Complexity
- Monothetic Divisive Methods

4 Algorithms for Large Data Sets

- Introduction
- Clustering Using REpresentatives (CURE)
 - Shrinking Process
 - CURE Algorithm
 - Complexity
- DBSCAN
 - Density Based Notion of Clusters
 - Beyond K -NN Idea
 - Cluster and Noise Definition
 - Sustaining the Algorithm
 - The DBSCAN Algorithm
 - Complexity
 - Finding ϵ and $MinPts$



Two Categories of Agglomerative Algorithms

There are two

- 1 Matrix Theory Based.



Cinvestav

Two Categories of Agglomerative Algorithms

There are two

- 1 Matrix Theory Based.
- 2 Graph Theory Based.



Cinvestav

Outline

1 Hierarchical Clustering

- Definition
- Basic Ideas

2 Agglomerative Algorithms

- Introduction
- Two Categories of Agglomerative Algorithms
 - Matrix Based Algorithms
 - Single Linkage
 - Complete Linkage
 - Group Average Linkage
 - Graph Based Algorithms
- Problems with Agglomerative Algorithms
 - Improving the Complexity

3 Divisive Algorithms

- Introduction
- Possible Complexity
- Monothetic Divisive Methods

4 Algorithms for Large Data Sets

- Introduction
- Clustering Using REpresentatives (CURE)
 - Shrinking Process
 - CURE Algorithm
 - Complexity
- DBSCAN
 - Density Based Notion of Clusters
 - Beyond K -NN Idea
 - Cluster and Noise Definition
 - Sustaining the Algorithm
 - The DBSCAN Algorithm
 - Complexity
 - Finding ϵ and $MinPts$



In Matrix Theory Based

Dissimilarity Matrix

As the name says, they are based in dissimilarity matrix $P_0 = P(X)$ of $N \times N$.



Cinvestav

In Matrix Theory Based

Dissimilarity Matrix

As the name says, they are based in dissimilarity matrix $P_0 = P(X)$ of $N \times N$.

Merging Process

At each merging the matrix is reduced by one level $\Rightarrow P_t$ becomes a $N - t \times N - t$ matrix.



Matrix Based Algorithm

Matrix Updating Algorithmic Scheme (MUAS)

- 1 Initialization

Matrix Based Algorithm

Matrix Updating Algorithmic Scheme (MUAS)

- 1 Initialization
- 2 Choose $\mathcal{R}_0 = \{Ci = \{x_i\} \mid i = 1, \dots, N\}$

Matrix Based Algorithm

Matrix Updating Algorithmic Scheme (MUAS)

- 1 Initialization
- 2 Choose $\mathfrak{R}_0 = \{Ci = \{x_i\} \mid i = 1, \dots, N\}$
- 3 $P_0 = P(X)$

Matrix Based Algorithm

Matrix Updating Algorithmic Scheme (MUAS)

- 1 Initialization
- 2 Choose $\mathfrak{R}_0 = \{Ci = \{x_i\} \mid i = 1, \dots, N\}$
- 3 $P_0 = P(X)$
- 4 $t = 0$

Matrix Based Algorithm

Matrix Updating Algorithmic Scheme (MUAS)

- 1 Initialization
- 2 Choose $\mathfrak{R}_0 = \{Ci = \{x_i\} | i = 1, \dots, N\}$
- 3 $P_0 = P(X)$
- 4 $t = 0$
- 5 Repeat

Matrix Based Algorithm

Matrix Updating Algorithmic Scheme (MUAS)

- ① Initialization
- ② Choose $\mathfrak{R}_0 = \{Ci = \{x_i\} | i = 1, \dots, N\}$
- ③ $P_0 = P(X)$
- ④ $t = 0$
- ⑤ Repeat
- ⑥ $t = t + 1$

Matrix Based Algorithm

Matrix Updating Algorithmic Scheme (MUAS)

- 1 Initialization
- 2 Choose $\mathfrak{R}_0 = \{Ci = \{x_i\} \mid i = 1, \dots, N\}$
- 3 $P_0 = P(X)$
- 4 $t = 0$
- 5 Repeat
- 6 $t = t + 1$
- 7 Find one pair of clusters
 (C_r, C_s) in \mathfrak{R}_{t-1} such that

Matrix Based Algorithm

Matrix Updating Algorithmic Scheme (MUAS)

- 1 Initialization
- 2 Choose $\mathfrak{R}_0 = \{Ci = \{x_i\} \mid i = 1, \dots, N\}$
- 3 $P_0 = P(X)$
- 4 $t = 0$
- 5 Repeat
- 6 $t = t + 1$
- 7 Find one pair of clusters
 (C_r, C_s) in \mathfrak{R}_{t-1} such that
$$d(C_i, C_j) = \min_{r,s=1,\dots,N, r \neq s} d(C_r, C_s)$$

Matrix Based Algorithm

Matrix Updating Algorithmic Scheme (MUAS)

- 1 Initialization
- 2 Choose $\mathfrak{R}_0 = \{C_i = \{x_i\} \mid i = 1, \dots, N\}$
- 3 $P_0 = P(X)$
- 4 $t = 0$
- 5 Repeat
- 6 $t = t + 1$
- 7 Find one pair of clusters
 (C_r, C_s) in \mathfrak{R}_{t-1} such that
$$d(C_i, C_j) = \min_{r,s=1,\dots,N, r \neq s} d(C_r, C_s)$$
- 8 Define $C_q = C_i \cup C_j, \mathfrak{R}_t = \mathfrak{R}_{t-1} - \{C_i, C_j\} \cup C_q$

Matrix Based Algorithm

Matrix Updating Algorithmic Scheme (MUAS)

- 1 Initialization
- 2 Choose $\mathfrak{R}_0 = \{C_i = \{x_i\} \mid i = 1, \dots, N\}$
- 3 $P_0 = P(X)$
- 4 $t = 0$
- 5 Repeat
- 6 $t = t + 1$
- 7 Find one pair of clusters
 (C_r, C_s) in \mathfrak{R}_{t-1} such that
$$d(C_i, C_j) = \min_{r,s=1,\dots,N, r \neq s} d(C_r, C_s)$$
- 8 Define $C_q = C_i \cup C_j, \mathfrak{R}_t = \mathfrak{R}_{t-1} - \{C_i, C_j\} \cup C_q$
- 9 Define P_t by **STRATEGY**

Matrix Based Algorithm

Matrix Updating Algorithmic Scheme (MUAS)

- 1 Initialization
- 2 Choose $\mathfrak{R}_0 = \{Ci = \{x_i\} \mid i = 1, \dots, N\}$
- 3 $P_0 = P(X)$
- 4 $t = 0$
- 5 Repeat
- 6 $t = t + 1$
- 7 Find one pair of clusters
 (C_r, C_s) in \mathfrak{R}_{t-1} such that
$$d(C_i, C_j) = \min_{r,s=1,\dots,N, r \neq s} d(C_r, C_s)$$
- 8 Define $C_q = C_i \cup C_j$, $\mathfrak{R}_t = \mathfrak{R}_{t-1} - \{C_i, C_j\} \cup C_q$
- 9 Define P_t by **STRATEGY**
- 10 Until all vectors lay in a single cluster

STRATEGY

- 1 Delete the two rows and columns that correspond to the merged clusters.



Matrix Based Algorithm

STRATEGY

- 1 Delete the two rows and columns that correspond to the merged clusters.
- 2 Add new row and a new column that contain the distances between the newly formed cluster and the old (unaffected at this level) clusters.



Distance Used in These Schemes

It has been pointed out that there is only one general distance for these algorithms

$$d(C_q, C_s) = a_i d(C_i, C_s) + a_j d(C_j, C_s) + \dots \\ b d(C_i, C_j) + c |d(C_i, C_s) - d(C_j, C_s)|$$

Where different values of a_i , a_j , b and c correspond to different choices of the dissimilarity measures.



Cinvestav

Distance Used in These Schemes

It has been pointed out that there is only one general distance for these algorithms

$$d(C_q, C_s) = a_i d(C_i, C_s) + a_j d(C_j, C_s) + \dots \\ b d(C_i, C_j) + c |d(C_i, C_s) - d(C_j, C_s)|$$

Where different values of a_i , a_j , b and c correspond to different choices of the dissimilarity measures.

Using this distance is possible to generate several algorithms

- 1 The single link algorithm.

Distance Used in These Schemes

It has been pointed out that there is only one general distance for these algorithms

$$d(C_q, C_s) = a_i d(C_i, C_s) + a_j d(C_j, C_s) + \dots \\ bd(C_i, C_j) + c |d(C_i, C_s) - d(C_j, C_s)|$$

Where different values of a_i , a_j , b and c correspond to different choices of the dissimilarity measures.

Using this distance is possible to generate several algorithms

- 1 The single link algorithm.
- 2 The complete link algorithm.

Distance Used in These Schemes

It has been pointed out that there is only one general distance for these algorithms

$$d(C_q, C_s) = a_i d(C_i, C_s) + a_j d(C_j, C_s) + \dots \\ b d(C_i, C_j) + c |d(C_i, C_s) - d(C_j, C_s)|$$

Where different values of a_i , a_j , b and c correspond to different choices of the dissimilarity measures.

Using this distance is possible to generate several algorithms

- 1 The single link algorithm.
- 2 The complete link algorithm.
- 3 The weighted pair group method average.

Distance Used in These Schemes

It has been pointed out that there is only one general distance for these algorithms

$$d(C_q, C_s) = a_i d(C_i, C_s) + a_j d(C_j, C_s) + \dots \\ + b d(C_i, C_j) + c |d(C_i, C_s) - d(C_j, C_s)|$$

Where different values of a_i , a_j , b and c correspond to different choices of the dissimilarity measures.

Using this distance is possible to generate several algorithms

- 1 The single link algorithm.
- 2 The complete link algorithm.
- 3 The weighted pair group method average.
- 4 The unweighted pair group method centroid.

Distance Used in These Schemes

It has been pointed out that there is only one general distance for these algorithms

$$d(C_q, C_s) = a_i d(C_i, C_s) + a_j d(C_j, C_s) + \dots \\ + b d(C_i, C_j) + c |d(C_i, C_s) - d(C_j, C_s)|$$

Where different values of a_i , a_j , b and c correspond to different choices of the dissimilarity measures.

Using this distance is possible to generate several algorithms

- 1 The single link algorithm.
- 2 The complete link algorithm.
- 3 The weighted pair group method average.
- 4 The unweighted pair group method centroid.
- 5 Etc...

Outline

1 Hierarchical Clustering

- Definition
- Basic Ideas

2 Agglomerative Algorithms

- Introduction
- Two Categories of Agglomerative Algorithms
 - Matrix Based Algorithms
 - **Single Linkage**
 - Complete Linkage
 - Group Average Linkage
- Graph Based Algorithms
- Problems with Agglomerative Algorithms
 - Improving the Complexity

3 Divisive Algorithms

- Introduction
- Possible Complexity
- Monothetic Divisive Methods

4 Algorithms for Large Data Sets

- Introduction
- Clustering Using REpresentatives (CURE)
 - Shrinking Process
 - CURE Algorithm
 - Complexity
- DBSCAN
 - Density Based Notion of Clusters
 - Beyond K -NN Idea
 - Cluster and Noise Definition
 - Sustaining the Algorithm
 - The DBSCAN Algorithm
 - Complexity
 - Finding ϵ and $MinPts$



Single Linkage

Let G and H represent two such group sets



Cinvestav

Single Linkage

Let G and H represent two such group sets

We have that

- Single linkage (SL) agglomerative clustering takes the intergroup dissimilarity to be that of the closest (**Least Dissimilar**) pair:

$$d_{SL}(G, H) = \min_{x_i \in G, x_j \in H} d(x_i, x_j)$$



Cinvestav

Single Linkage

Let G and H represent two such group sets

We have that

- Single linkage (SL) agglomerative clustering takes the intergroup dissimilarity to be that of the closest (**Least Dissimilar**) pair:

$$d_{SL}(G, H) = \min_{x_i \in G, x_j \in H} d(x_i, x_j)$$

This is also known as

- This is also often called the nearest-neighbor technique.



For example

The single linkage clustering algorithm

This is obtained if we set $a_i = 1/2$, $a_j = 1/2$, $b = 0$, $c = -1/2$



Cinvestav

For example

The single linkage clustering algorithm

This is obtained if we set $a_i = 1/2$, $a_j = 1/2$, $b = 0$, $c = -1/2$

Thus, we have

$$d(C_q, C_s) = \min \{d(C_i, C_s), d(C_j, C_s)\} \quad (4)$$




Cinvestav

What clusters are produced?

First

- Distance Between closest elements in clusters
- It produces long chains $x_{i_1} \rightarrow x_{i_2} \rightarrow x_{i_3} \rightarrow x_{i_4} \rightarrow x_{i_5}$



Another Example of a Single Link Dissimilarity

This can be created using the following cluster distance

$$d_{\min}(C_i, C_j) = \min_{\mathbf{x} \in C_i, \mathbf{y} \in C_j} \|\mathbf{x} - \mathbf{y}\|^2$$




Another Example of a Single Link Dissimilarity

This can be created using the following cluster distance

$$d_{\min}(C_i, C_j) = \min_{x \in C_i, y \in C_j} \|x - y\|^2$$

Nearest Neighborhood (Single Linkage)

It produces Minimal Spanning Trees



Outline

1 Hierarchical Clustering

- Definition
- Basic Ideas

2 Agglomerative Algorithms

- Introduction
- Two Categories of Agglomerative Algorithms
 - Matrix Based Algorithms
 - Single Linkage
 - **Complete Linkage**
 - Group Average Linkage
- Graph Based Algorithms
- Problems with Agglomerative Algorithms
 - Improving the Complexity

3 Divisive Algorithms

- Introduction
- Possible Complexity
- Monothetic Divisive Methods

4 Algorithms for Large Data Sets

- Introduction
- Clustering Using REpresentatives (CURE)
 - Shrinking Process
 - CURE Algorithm
 - Complexity
- DBSCAN
 - Density Based Notion of Clusters
 - Beyond K -NN Idea
 - Cluster and Noise Definition
 - Sustaining the Algorithm
 - The DBSCAN Algorithm
 - Complexity
 - Finding ϵ and $MinPts$




Complete linkage (CL)

Complete Linkage agglomerative clustering (furthest-neighbor technique)

- It takes the intergroup dissimilarity to be that of the furthest (most dissimilar) pair

$$d_{CL}(G, H) = \max_{x_i \in G, x_j \in H} d(x_i, x_j)$$



- ▶ Distance between farthest elements in the clusters.
- ▶ Forces, Spherical clusters with consistent diameter.

Example

This can be created using the following cluster distance

$$d_{\max}(C_i, C_j) = \max_{\mathbf{x} \in C_i, \mathbf{y} \in C_j} \|\mathbf{x} - \mathbf{y}\|^2$$



Outline

1 Hierarchical Clustering

- Definition
- Basic Ideas

2 Agglomerative Algorithms

- Introduction
- Two Categories of Agglomerative Algorithms
 - Matrix Based Algorithms
 - Single Linkage
 - Complete Linkage
 - **Group Average Linkage**
- Graph Based Algorithms
- Problems with Agglomerative Algorithms
 - Improving the Complexity

3 Divisive Algorithms

- Introduction
- Possible Complexity
- Monothetic Divisive Methods

4 Algorithms for Large Data Sets

- Introduction
- Clustering Using REpresentatives (CURE)
 - Shrinking Process
 - CURE Algorithm
 - Complexity
- DBSCAN
 - Density Based Notion of Clusters
 - Beyond K -NN Idea
 - Cluster and Noise Definition
 - Sustaining the Algorithm
 - The DBSCAN Algorithm
 - Complexity
 - Finding ϵ and $MinPts$



Finally, a compromise

Group average (GA)

- Group average (GA) clustering uses the average dissimilarity between the groups

$$d_{CL}(G, H) = \frac{1}{N_G N_H} \sum_{x_i \in G} \sum_{x_j \in H} d(x_i, x_j)$$



Finally, a compromise

Group average (GA)

- Group average (GA) clustering uses the average dissimilarity between the groups

$$d_{CL}(G, H) = \frac{1}{N_G N_H} \sum_{x_i \in G} \sum_{x_j \in H} d(x_i, x_j)$$

Something Notable

- Average of all the pairwise distances
- Less affected by outliers



Outline

1 Hierarchical Clustering

- Definition
- Basic Ideas

2 Agglomerative Algorithms

- Introduction
- Two Categories of Agglomerative Algorithms
 - Matrix Based Algorithms
 - Single Linkage
 - Complete Linkage
 - Group Average Linkage
- **Graph Based Algorithms**
- Problems with Agglomerative Algorithms
 - Improving the Complexity

3 Divisive Algorithms

- Introduction
- Possible Complexity
- Monothetic Divisive Methods

4 Algorithms for Large Data Sets

- Introduction
- Clustering Using REpresentatives (CURE)
 - Shrinking Process
 - CURE Algorithm
 - Complexity
- DBSCAN
 - Density Based Notion of Clusters
 - Beyond K -NN Idea
 - Cluster and Noise Definition
 - Sustaining the Algorithm
 - The DBSCAN Algorithm
 - Complexity
 - Finding ϵ and $MinPts$



Agglomerative Algorithms Based on Graph Theory

Consider the following

- 1 Each node in the graph G correspond to a vector.



Cinvestav

Agglomerative Algorithms Based on Graph Theory

Consider the following

- 1 Each node in the graph G correspond to a vector.
- 2 Cluster are formed by connecting nodes.



Cinvestav

Agglomerative Algorithms Based on Graph Theory

Consider the following

- 1 Each node in the graph G correspond to a vector.
- 2 Cluster are formed by connecting nodes.
- 3 Certain property, $h(k)$, needs to be respected.



Agglomerative Algorithms Based on Graph Theory

Consider the following

- 1 Each node in the graph G correspond to a vector.
- 2 Cluster are formed by connecting nodes.
- 3 Certain property, $h(k)$, needs to be respected.

Common Properties: Node Connectivity

- The **node connectivity** of a connected subgraph is the largest integer k
 - ▶ All pairs of nodes are joined by at least k paths having no nodes in common.



Agglomerative Algorithms Based on Graph Theory

Common Properties: Edge Connectivity

The **edge connectivity** of a connected subgraph is the largest integer k such that all pairs of nodes are joined by at least k paths having no edges in common.



Cinvestav

Agglomerative Algorithms Based on Graph Theory

Common Properties: Edge Connectivity

The **edge connectivity** of a connected subgraph is the largest integer k such that all pairs of nodes are joined by at least k paths having no edges in common.

Common Properties: Node Degree

The **degree** of a connected subgraph is the largest integer k such that each node has at least k incident edges.



Cinvestav

Basically, We use the Same Scheme, But...

The function

$$d_{h(k)}(C_r, C_s) = \min_{x \in C_r, y \in C_s} \{d(x, y) \mid \text{Property}\} \quad (5)$$



Cinvestav

Basically, We use the Same Scheme, But...

The function

$$d_{h(k)}(C_r, C_s) = \min_{x \in C_r, y \in C_s} \{d(x, y) \mid \textit{Property}\} \quad (5)$$

Property

The G subgraph defined by $C_r \cup C_s$ is



Cinvestav

Basically, We use the Same Scheme, But...

The function

$$d_{h(k)}(C_r, C_s) = \min_{x \in C_r, y \in C_s} \{d(x, y) \mid \textit{Property}\} \quad (5)$$

Property

The G subgraph defined by $C_r \cup C_s$ is

- 1 It is connected and either



Cinvestav

Basically, We use the Same Scheme, But...

The function

$$d_{h(k)}(C_r, C_s) = \min_{x \in C_r, y \in C_s} \{d(x, y) \mid \text{Property}\} \quad (5)$$

Property

The G subgraph defined by $C_r \cup C_s$ is

- ① It is connected and either
 - ① It has the property $h(k)$ or



Cinvestav

Basically, We use the Same Scheme, But...

The function

$$d_{h(k)}(C_r, C_s) = \min_{x \in C_r, y \in C_s} \{d(x, y) \mid \text{Property}\} \quad (5)$$

Property

The G subgraph defined by $C_r \cup C_s$ is

- ① It is connected and either
 - ① It has the property $h(k)$ or
 - ② It is complete



Cinvestav

Examples

Again

① Single Link Algorithm

Examples

Again

- ① Single Link Algorithm
- ② Complete Link Algorithm



Cinvestav

Examples

Again

- ① Single Link Algorithm
- ② Complete Link Algorithm

There is other style of clustering

- Clustering Algorithms Based on the Minimum Spanning Tree



Cinvestav

Outline

1 Hierarchical Clustering

- Definition
- Basic Ideas

2 Agglomerative Algorithms

- Introduction
- Two Categories of Agglomerative Algorithms
 - Matrix Based Algorithms
 - Single Linkage
 - Complete Linkage
 - Group Average Linkage
- Graph Based Algorithms
- **Problems with Agglomerative Algorithms**
 - Improving the Complexity

3 Divisive Algorithms

- Introduction
- Possible Complexity
- Monothetic Divisive Methods

4 Algorithms for Large Data Sets

- Introduction
- Clustering Using REpresentatives (CURE)
 - Shrinking Process
 - CURE Algorithm
 - Complexity
- DBSCAN
 - Density Based Notion of Clusters
 - Beyond K -NN Idea
 - Cluster and Noise Definition
 - Sustaining the Algorithm
 - The DBSCAN Algorithm
 - Complexity
 - Finding ϵ and $MinPts$



Problems with Schema of Agglomerative Algorithms

First - Related to Nesting Property

No way to recover from a “poor” clustering that may have occurred in an earlier level of the hierarchy.



Cinvestav

Problems with Schema of Agglomerative Algorithms

First - Related to Nesting Property

No way to recover from a “poor” clustering that may have occurred in an earlier level of the hierarchy.

Second, if we use a Naive Scheme - **Full comparison at each level**

- At each level t , there are $N - t$ clusters.



Cinvestav

Problems with Schema of Agglomerative Algorithms

First - Related to Nesting Property

No way to recover from a “poor” clustering that may have occurred in an earlier level of the hierarchy.

Second, if we use a Naive Scheme - **Full comparison at each level**

- At each level t , there are $N - t$ clusters.
- Thus at level $t + 1$ the total number of pairs compared .



Cinvestav

Problems with Schema of Agglomerative Algorithms

First - Related to Nesting Property

No way to recover from a “poor” clustering that may have occurred in an earlier level of the hierarchy.

Second, if we use a Naive Scheme - **Full comparison at each level**

- At each level t , there are $N - t$ clusters.
- Thus at level $t + 1$ the total number of pairs compared .

$$\binom{N - t}{2} = \frac{(N - t)(N - t - 1)}{2} \quad (6)$$



Cinvestav

Problems with Schema of Agglomerative Algorithms

First - Related to Nesting Property

No way to recover from a “poor” clustering that may have occurred in an earlier level of the hierarchy.

Second, if we use a Naive Scheme - **Full comparison at each level**

- At each level t , there are $N - t$ clusters.
- Thus at level $t + 1$ the total number of pairs compared .

$$\binom{N - t}{2} = \frac{(N - t)(N - t - 1)}{2} \quad (6)$$

Total Number of pairs compared are

$$\sum_{t=0}^{N-1} \binom{N - t}{2} \quad (7)$$

Thus

We have that

$$\sum_{t=0}^{N-1} \binom{N-t}{2} = \sum_{k=1}^N \binom{k}{2} = \frac{(N-1)N(N+1)}{6} \quad (8)$$



Cinvestav

Thus

We have that

$$\sum_{t=0}^{N-1} \binom{N-t}{2} = \sum_{k=1}^N \binom{k}{2} = \frac{(N-1)N(N+1)}{6} \quad (8)$$

Thus

The complexity of this schema is $O(N^3)$



Cinvestav

Thus

We have that

$$\sum_{t=0}^{N-1} \binom{N-t}{2} = \sum_{k=1}^N \binom{k}{2} = \frac{(N-1)N(N+1)}{6} \quad (8)$$

Thus

The complexity of this schema is $O(N^3)$

However

You still depend on the nature of d .



Cinvestav

Then

We need to be able to improve the complexity of Aggregation

- From the Metric Algorithms and Data structures, there are possible solutions...



Cinvestav

Outline

1 Hierarchical Clustering

- Definition
- Basic Ideas

2 Agglomerative Algorithms

- Introduction
- Two Categories of Agglomerative Algorithms
 - Matrix Based Algorithms
 - Single Linkage
 - Complete Linkage
 - Group Average Linkage
- Graph Based Algorithms
- Problems with Agglomerative Algorithms
 - Improving the Complexity

3 Divisive Algorithms

- Introduction
- Possible Complexity
- Monothetic Divisive Methods

4 Algorithms for Large Data Sets

- Introduction
- Clustering Using REpresentatives (CURE)
 - Shrinking Process
 - CURE Algorithm
 - Complexity
- DBSCAN
 - Density Based Notion of Clusters
 - Beyond K -NN Idea
 - Cluster and Noise Definition
 - Sustaining the Algorithm
 - The DBSCAN Algorithm
 - Complexity
 - Finding ϵ and $MinPts$



The idea of using a middle point

In order to establish a better performance

- Every time, we join two clusters:
 - ▶ We can then use a representative for such join in the agglomeration



Cinvestav

The idea of using a middle point

In order to establish a better performance

- Every time, we join two clusters:
 - ▶ We can then use a representative for such join in the agglomeration

Therefore, we need a data structure to be able to support these updates

- We may use a Kd-tree...



Cinvestav

In this case, we assume a group average

We need a Kd-tree supporting insertions

- By Logarithmic Rebuilding...



Cinvestav

In this case, we assume a group average

We need a Kd-tree supporting insertions

- By Logarithmic Rebuilding...



This was born from the fact that

- It is necessary to modify the Kd-tree dynamically to maintain certain performance.



Cinvestav

Example



In order to keep performance, Logarithmic Rebuilding

We maintain at most $h = O(\log N)$ Kd-trees

- T_0, T_1, \dots, T_{h-1} such that the i^{th} ($i \in [1, h]$) tree stores precisely 2^i points.
- **Each point is stored in only one Kd-tree.**



Procedure

We have the following procedure

- To insert a new point p , we
 - ① Identify the smallest $i \geq 0$ such that T_i is empty
 - ② Destroy all of T_0, T_1, \dots, T_{i-1} . Collect all the points there into a set S .
 - ③ Construct T_i in $S \cup \{p\}$
 - ▶ Note $|T_i| = 2^i$



Amortized Analysis

Construction of T_i

- It takes $O(2^i \log 2^i)$ time



Amortized Analysis

Construction of T_i

- It takes $O(2^i \log 2^i)$ time

Charge the cost on the 2^i points in T_i

- Each of which is amortized $O(\log 2^i) = O(\log N)$ time.



Amortized Analysis

Construction of T_i

- It takes $O(2^i \log 2^i)$ time

Charge the cost on the 2^i points in T_i

- Each of which is amortized $O(\log 2^i) = O(\log N)$ time.

Each point can be charged only $O(\log n)$ when moving to a bigger tree

- Amortized insertion time per point $O(\log^2 N)$



Querying the Structure

Simply

- Search all of the h trees T_0, T_1, \dots, T_{h-1}



Querying the Structure

Simply

- Search all of the h trees T_0, T_1, \dots, T_{h-1}

Query Time

$$O\left(\sqrt{2^{h-1}} + \sqrt{2^{h-2}} + \dots + \sqrt{2^0} + k\right) = O\left(\sqrt{N} + k\right)$$

- Similar to the search on the original Kd-tree.



What if we avoid comparing all the elements using a Kd-Tree

Generation of the Structure

- $O(N \log^2 N)$ to get the data structure with space $O(N)$



What if we avoid comparing all the elements using a Kd-Tree

Generation of the Structure

- $O(N \log^2 N)$ to get the data structure with space $O(N)$


Query

- We get to query in $O(\sqrt{N} + k)$ in the worst case scenario.
 - ▶ Here k is the number of elements being reported.



Therefore

We have



Height points
to dissimilarity
using a similarity



Dendrogram




At Each Level

At each level calculate the new centroid

- Insert it

- ▶ Inserting takes $O(\log^2 N)$, but How many insertions?



We have...

Therefore

- We have total number of insertions assuming pair of them:

$$\frac{N}{2} + \frac{N}{2^2} + \dots + \frac{N}{2^{\log n}} = N \left(\frac{1 - \frac{1}{N}}{\frac{1}{2}} \right) - N = *$$



Cinvestav

We have...

Therefore

- We have total number of insertions assuming pair of them:

$$\frac{N}{2} + \frac{N}{2^2} + \dots + \frac{N}{2^{\log n}} = N \left(\frac{1 - \frac{1}{N}}{\frac{1}{2}} \right) - N = *$$

Therefore


$$* = 2(N - 1) - N = N - 2$$



Cinvestav

Final Complexity

We have after building the data structure



Cinvestav

Then, we have

The Clustering takes

$$O\left(N \log^2 N\right) + O\left(N^{3/2} + Nk\right) = O\left(N^{3/2}\right)$$



Cinvestav

Then, we have

The Clustering takes

$$O\left(N \log^2 N\right) + O\left(N^{3/2} + Nk\right) = O\left(N^{3/2}\right)$$

Given that you need to build a tree for each centroid structure

$$N \log^2 N + \frac{1}{2} N \log^2 \frac{N}{2} + \dots + \frac{1}{2^{\log N}} \log^2 \frac{N}{2^{\log^2}} = O\left(N \log^2 N\right)$$



Cinvestav

Outline

1 Hierarchical Clustering

- Definition
- Basic Ideas

2 Agglomerative Algorithms

- Introduction
- Two Categories of Agglomerative Algorithms
 - Matrix Based Algorithms
 - Single Linkage
 - Complete Linkage
 - Group Average Linkage
- Graph Based Algorithms
- Problems with Agglomerative Algorithms
 - Improving the Complexity

3 Divisive Algorithms

- Introduction
- Possible Complexity
- Monothetic Divisive Methods

4 Algorithms for Large Data Sets

- Introduction
- Clustering Using REpresentatives (CURE)
 - Shrinking Process
 - CURE Algorithm
 - Complexity
- DBSCAN
 - Density Based Notion of Clusters
 - Beyond K -NN Idea
 - Cluster and Noise Definition
 - Sustaining the Algorithm
 - The DBSCAN Algorithm
 - Complexity
 - Finding ϵ and $MinPts$



Divisive Algorithms

Reverse Strategy

- **Start with a single cluster split it iteratively.**



Cinvestav

Divisive Algorithms

Reverse Strategy

- **Start with a single cluster split it iteratively.**

They are less common than agglomerative methods

- However, Kaufman and Rousseeuw (1990) pointed out:
 - ▶ This is revealed when a divisive method is applied



Generalized Divisive Scheme

Algorithm PROBLEM what is wrong!!!

- 1 Initialization
- 2 Choose $\mathfrak{R}_0 = \{X\}$
- 3 $P_0 = P(X)$
- 4 $t = 0$

Generalized Divisive Scheme

Algorithm PROBLEM what is wrong!!!

- 1 Initialization
- 2 Choose $\mathfrak{R}_0 = \{X\}$
- 3 $P_0 = P(X)$
- 4 $t = 0$
- 5 Repeat
- 6 $t = t + 1$
- 7 For $i = 1$ to t
- 8 Given a partition $C_{t-1, i}$
- 9 Generate all possible clusters

Generalized Divisive Scheme

Algorithm PROBLEM what is wrong!!!

- 1 Initialization
- 2 Choose $\mathfrak{R}_0 = \{X\}$
- 3 $P_0 = P(X)$
- 4 $t = 0$
- 5 Repeat
- 6 $t = t + 1$
- 7 For $i = 1$ to t
- 8 Given a partition $C_{t-1,i}$
- 9 Generate all possible clusters
- 10 next i
- 11 Find the pair $C_{t-1,j}^1, C_{t-1,j}^2$ that
 maximize g

Generalized Divisive Scheme

Algorithm PROBLEM what is wrong!!!

- 1 Initialization
- 2 Choose $\mathfrak{R}_0 = \{X\}$
- 3 $P_0 = P(X)$
- 4 $t = 0$
- 5 Repeat
- 6 $t = t + 1$
- 7 For $i = 1$ to t
- 8 Given a partition $C_{t-1, i}$
- 9 Generate all possible clusters
- 10 next i
- 11 Find the pair $C_{t-1, j}^1, C_{t-1, j}^2$ that
 maximize g
- 12 Create
$$\mathfrak{R}_t = \mathfrak{R}_{t-1} - \{C_{t-1, j}\} \cup \{C_{t-1, j}^1, C_{t-1, j}^2\}$$

Generalized Divisive Scheme

Algorithm PROBLEM what is wrong!!!

- 1 Initialization
- 2 Choose $\mathfrak{R}_0 = \{X\}$
- 3 $P_0 = P(X)$
- 4 $t = 0$
- 5 Repeat
- 6 $t = t + 1$
- 7 For $i = 1$ to t
- 8 Given a partition $C_{t-1, i}$
- 9 Generate all possible clusters
- 10 next i
- 11 Find the pair $C_{t-1, j}^1, C_{t-1, j}^2$ that
 maximize g
- 12 Create
$$\mathfrak{R}_t = \mathfrak{R}_{t-1} - \{C_{t-1, j}\} \cup \{C_{t-1, j}^1, C_{t-1, j}^2\}$$
- 13 Until all vectors lie in a single cluster

Generalized Divisive Scheme

Again, we need to be smart

- 1 Initialization
- 2 Choose $\mathfrak{R}_0 = \{X\}$
- 3 $P_0 = P(X)$
- 4 $t = 0$

Generalized Divisive Scheme

Again, we need to be smart

- 1 Initialization
- 2 Choose $\mathfrak{R}_0 = \{X\}$
- 3 $P_0 = P(X)$
- 4 $t = 0$
- 5 Repeat
- 6 $t = t + 1$
- 7 For $i = 1$ to t
- 8 **Given a partition $C_{t-1, i}$**
- 9 **Generate all possible clusters**

Generalized Divisive Scheme

Again, we need to be smart

- 1 Initialization
- 2 Choose $\mathfrak{R}_0 = \{X\}$
- 3 $P_0 = P(X)$
- 4 $t = 0$
- 5 Repeat
- 6 $t = t + 1$
- 7 For $i = 1$ to t
- 8 **Given a partition $C_{t-1, i}$**
- 9 **Generate all possible clusters**
- 10 next i
- 11 Find the pair $C_{t-1, j}^1, C_{t-1, j}^2$ that
maximize g

Generalized Divisive Scheme

Again, we need to be smart

1 Initialization

2 Choose $\mathfrak{R}_0 = \{X\}$

3 $P_0 = P(X)$

4 $t = 0$

5 Repeat

6 $t = t + 1$

7 For $i = 1$ to t

8 **Given a partition $C_{t-1,i}$**

9 **Generate all possible clusters**

10 next i

11 Find the pair $C_{t-1,j}^1, C_{t-1,j}^2$ that
maximize g

12 Create

$$\mathfrak{R}_t = \mathfrak{R}_{t-1} - \{C_{t-1,j}\} \cup \{C_{t-1,j}^1, C_{t-1,j}^2\}$$

Generalized Divisive Scheme

Again, we need to be smart

1 Initialization

2 Choose $\mathfrak{R}_0 = \{X\}$

3 $P_0 = P(X)$

4 $t = 0$

5 Repeat

6 $t = t + 1$

7 For $i = 1$ to t

8 **Given a partition $C_{t-1,i}$**

9 **Generate all possible clusters**

10 next i

11 Find the pair $C_{t-1,j}^1, C_{t-1,j}^2$ that
maximize g

12 Create

$$\mathfrak{R}_t = \mathfrak{R}_{t-1} - \{C_{t-1,j}\} \cup \{C_{t-1,j}^1, C_{t-1,j}^2\}$$

13 Until all vectors lie in a single cluster

Outline

1 Hierarchical Clustering

- Definition
- Basic Ideas

2 Agglomerative Algorithms

- Introduction
- Two Categories of Agglomerative Algorithms
 - Matrix Based Algorithms
 - Single Linkage
 - Complete Linkage
 - Group Average Linkage
- Graph Based Algorithms
- Problems with Agglomerative Algorithms
 - Improving the Complexity

3 Divisive Algorithms

- Introduction
- **Possible Complexity**
- Monothetic Divisive Methods

4 Algorithms for Large Data Sets

- Introduction
- Clustering Using REpresentatives (CURE)
 - Shrinking Process
 - CURE Algorithm
 - Complexity
- DBSCAN
 - Density Based Notion of Clusters
 - Beyond K -NN Idea
 - Cluster and Noise Definition
 - Sustaining the Algorithm
 - The DBSCAN Algorithm
 - Complexity
 - Finding ϵ and $MinPts$



Possible Complexity

This is computationally demanding

- If all $2^{N_t^i} - 1$ possible division are considered:
 - ▶ With N_t^i is the number of elements in the cluster.



Cinvestav

Possible Complexity

This is computationally demanding

- If all $2^{N_t^i} - 1$ possible division are considered:
 - ▶ With N_t^i is the number of elements in the cluster.

However, for data consisting of d binary variables

- Relatively simple and computationally efficient methods exists
 - ▶ **Monothetic divisive methods**



Cinvestav

Outline

1 Hierarchical Clustering

- Definition
- Basic Ideas

2 Agglomerative Algorithms

- Introduction
- Two Categories of Agglomerative Algorithms
 - Matrix Based Algorithms
 - Single Linkage
 - Complete Linkage
 - Group Average Linkage
- Graph Based Algorithms
- Problems with Agglomerative Algorithms
 - Improving the Complexity

3 Divisive Algorithms

- Introduction
- Possible Complexity
- **Monothetic Divisive Methods**

4 Algorithms for Large Data Sets

- Introduction
- Clustering Using REpresentatives (CURE)
 - Shrinking Process
 - CURE Algorithm
 - Complexity
- DBSCAN
 - Density Based Notion of Clusters
 - Beyond K -NN Idea
 - Cluster and Noise Definition
 - Sustaining the Algorithm
 - The DBSCAN Algorithm
 - Complexity
 - Finding ϵ and $MinPts$



Monothetic Divisive Methods

They are based on

- These generally divide clusters according to the presence or absence of each of the d variables.
 - ▶ At each stage cluster members contain or not certain attributes.



Cinvestav

Monothetic Divisive Methods

They are based on

- These generally divide clusters according to the presence or absence of each of the d variables.
 - ▶ At each stage cluster members contain or not certain attributes.

Format of the data

- The data is in the form of a two-mode (binary) matrix.

$$\begin{array}{c} \text{members} \left\{ \begin{array}{c} \overbrace{\left(\begin{array}{ccccc} 1 & 0 & 1 & \dots & 0 \\ 0 & 1 & 0 & \dots & 0 \\ 0 & 0 & 0 & \dots & 1 \\ \vdots & \vdots & \vdots & \ddots & \vdots \\ 0 & 0 & 0 & \dots & 1 \end{array} \right)}^{\text{Attributes}} \end{array} \right.$$

Then, if we define

f_k = It is the number of individuals having k^{th} attribute

- We can define the following homogeneity criterion (Information Content):

$$C = dN \log N - \sum_{k=1}^d \{f_k \log f_k - (n - f_k) \log (n - f_k)\}$$



Cinvestav

Then, if we define

f_k = It is the number of individuals having k^{th} attribute

- We can define the following homogeneity criterion (Information Content):

$$C = dN \log N - \sum_{k=1}^d \{f_k \log f_k - (n - f_k) \log (n - f_k)\}$$

Therefore, if we split the original cluster into two groups A and B

- The reduction in C is $C_X - C_A - C_B$



Cinvestav

Then, if we define

f_k = It is the number of individuals having k^{th} attribute

- We can define the following homogeneity criterion (Information Content):

$$C = dN \log N - \sum_{k=1}^d \{f_k \log f_k - (n - f_k) \log (n - f_k)\}$$

Therefore, if we split the original cluster into two groups A and B

- The reduction in C is $C_X - C_A - C_B$

Therefore

- The ideal set of clusters would have members with identical attributes and C equal to zero.



Therefore

Clusters are split at each stage

- According to possession of the attribute which leads to the greatest reduction in C .



Cinvestav

Therefore

Clusters are split at each stage

- According to possession of the attribute which leads to the greatest reduction in C .

Other possible splitting can be done using

- Association Analysis (Ecology Term)



Cinvestav

For Example

For one pair of variables, v_i and $v_j \in [0, 1]$

	v_i	
v_j	1	0
1	f_{11}	f_{10}
0	f_{01}	f_{00}

- f_{ij} = the number of times v_i and v_j coincide or not.



For Example

For one pair of variables, v_i and $v_j \in [0, 1]$

	v_i	
v_j	1	0
1	f_{11}	f_{10}
0	f_{01}	f_{00}

- f_{ij} = the number of times v_i and v_j coincide or not.

Some common measures of association

$$m_1(\mathbf{f}) = |f_{11}f_{00} - f_{10}f_{01}|$$

$$m_2(\mathbf{f}) = [f_{11}f_{00} - f_{10}f_{01}]^2$$

Therefore

The split at each stage

- It is made according to the presence or absence of the attribute:
 - ▶ Thus, its association with the others is a maximum!!!



Cinvestav

Outline

1 Hierarchical Clustering

- Definition
- Basic Ideas

2 Agglomerative Algorithms

- Introduction
- Two Categories of Agglomerative Algorithms
 - Matrix Based Algorithms
 - Single Linkage
 - Complete Linkage
 - Group Average Linkage
- Graph Based Algorithms
- Problems with Agglomerative Algorithms
 - Improving the Complexity

3 Divisive Algorithms

- Introduction
- Possible Complexity
- Monothetic Divisive Methods

4 Algorithms for Large Data Sets

- **Introduction**
- Clustering Using REpresentatives (CURE)
 - Shrinking Process
 - CURE Algorithm
 - Complexity
- DBSCAN
 - Density Based Notion of Clusters
 - Beyond K -NN Idea
 - Cluster and Noise Definition
 - Sustaining the Algorithm
 - The DBSCAN Algorithm
 - Complexity
 - Finding ϵ and $MinPts$



Algorithms for Large Data Sets

There are several

- 1 The CURE Algorithm



Cinvestav

Algorithms for Large Data Sets

There are several

- 1 The CURE Algorithm
- 2 The DBSCAN Algorithm



Cinvestav

Algorithms for Large Data Sets

There are several

- 1 The CURE Algorithm
- 2 The DBSCAN Algorithm
- 3 The ROCK Algorithm



Cinvestav

Algorithms for Large Data Sets

There are several

- 1 The CURE Algorithm
- 2 The DBSCAN Algorithm
- 3 The ROCK Algorithm
- 4 The Chameleon Algorithm



Cinvestav

Algorithms for Large Data Sets

There are several

- 1 The CURE Algorithm
- 2 The DBSCAN Algorithm
- 3 The ROCK Algorithm
- 4 The Chameleon Algorithm
- 5 The BIRCH Algorithm



Cinvestav

Outline

1 Hierarchical Clustering

- Definition
- Basic Ideas

2 Agglomerative Algorithms

- Introduction
- Two Categories of Agglomerative Algorithms
 - Matrix Based Algorithms
 - Single Linkage
 - Complete Linkage
 - Group Average Linkage
- Graph Based Algorithms
- Problems with Agglomerative Algorithms
 - Improving the Complexity

3 Divisive Algorithms

- Introduction
- Possible Complexity
- Monothetic Divisive Methods

4 Algorithms for Large Data Sets

- Introduction
- **Clustering Using REpresentatives (CURE)**
 - Shrinking Process
 - CURE Algorithm
 - Complexity
- DBSCAN
 - Density Based Notion of Clusters
 - Beyond K -NN Idea
 - Cluster and Noise Definition
 - Sustaining the Algorithm
 - The DBSCAN Algorithm
 - Complexity
 - Finding ϵ and $MinPts$



Clustering Using REpresentatives (CURE)

Basic Idea

- Each cluster C_i has a set of representatives

$$R_{C_i} = \{ \mathbf{x}_1^{(i)}, \mathbf{x}_2^{(i)}, \dots, \mathbf{x}_K^{(i)} \} \text{ with } K > 1.$$



Clustering Using REpresentatives (CURE)

Basic Idea

- Each cluster C_i has a set of representatives

$$R_{C_i} = \{ \mathbf{x}_1^{(i)}, \mathbf{x}_2^{(i)}, \dots, \mathbf{x}_K^{(i)} \} \text{ with } K > 1.$$

What is happening

- By using multiple representatives for each cluster, the CURE algorithm tries to “capture” the shape of each one.



Clustering Using REpresentatives (CURE)

Basic Idea

- Each cluster C_i has a set of representatives
 $R_{C_i} = \{x_1^{(i)}, x_2^{(i)}, \dots, x_K^{(i)}\}$ with $K > 1$.

What is happening

- By using multiple representatives for each cluster, the CURE algorithm tries to “capture” the shape of each one.

However

- In order to avoid taking into account irregularities (For example, outliers) in the border of the cluster.

Clustering Using REpresentatives (CURE)

Basic Idea

- Each cluster C_i has a set of representatives

$$R_{C_i} = \{ \mathbf{x}_1^{(i)}, \mathbf{x}_2^{(i)}, \dots, \mathbf{x}_K^{(i)} \} \text{ with } K > 1.$$

What is happening

- By using multiple representatives for each cluster, the CURE algorithm tries to “capture” the shape of each one.

However

- In order to avoid taking into account irregularities (For example, outliers) in the border of the cluster.
 - The initially chosen representatives are “pushed” toward the mean of the cluster.

Therefore

This action is known

- As “Shrinking” in the sense that the volume of space “defined” by the representatives is shrunk toward the mean of the cluster.



Cinvestav

Outline

1 Hierarchical Clustering

- Definition
- Basic Ideas

2 Agglomerative Algorithms

- Introduction
- Two Categories of Agglomerative Algorithms
 - Matrix Based Algorithms
 - Single Linkage
 - Complete Linkage
 - Group Average Linkage
- Graph Based Algorithms
- Problems with Agglomerative Algorithms
 - Improving the Complexity

3 Divisive Algorithms

- Introduction
- Possible Complexity
- Monothetic Divisive Methods

4 Algorithms for Large Data Sets

- Introduction
- Clustering Using REpresentatives (CURE)
 - Shrinking Process
 - CURE Algorithm
 - Complexity
- DBSCAN
 - Density Based Notion of Clusters
 - Beyond K -NN Idea
 - Cluster and Noise Definition
 - Sustaining the Algorithm
 - The DBSCAN Algorithm
 - Complexity
 - Finding ϵ and $MinPts$



Shrinking Process

Given a cluster C

- Select the point $x \in C$ with the maximum distance from the mean of C and set $R_C = \{x\}$ (the set of representatives).



Cinvestav

Shrinking Process

Given a cluster C

- Select the point $x \in C$ with the maximum distance from the mean of C and set $R_C = \{x\}$ (the set of representatives).

Then

- 1 For $i = 2$ to $\min\{K, n_C\}$



Cinvestav

Shrinking Process

Given a cluster C

- Select the point $x \in C$ with the maximum distance from the mean of C and set $R_C = \{x\}$ (the set of representatives).

Then

- 1 For $i = 2$ to $\min\{K, n_C\}$
- 2 Determine $y \in C - R_C$ that lies farthest from the points in R_C



Shrinking Process

Given a cluster C

- Select the point $x \in C$ with the maximum distance from the mean of C and set $R_C = \{x\}$ (the set of representatives).

Then

- 1 For $i = 2$ to $\min \{K, n_C\}$
- 2 Determine $y \in C - R_C$ that lies farthest from the points in R_C
- 3 $R_C = R_C \cup \{y\}$



Shrinking Process

Given a cluster C

- Select the point $x \in C$ with the maximum distance from the mean of C and set $R_C = \{x\}$ (the set of representatives).

Then

- 1 For $i = 2$ to $\min \{K, n_C\}$
- 2 Determine $y \in C - R_C$ that lies farthest from the points in R_C
- 3 $R_C = R_C \cup \{y\}$



Shrinking Process

Do the Shrinking

- Shrink the points $x \in R_C$ toward the mean m_C in C by a factor α .



Cinvestav

Shrinking Process

Do the Shrinking

- Shrink the points $\mathbf{x} \in R_C$ toward the mean \mathbf{m}_C in C by a factor α .

Actually

$$\mathbf{x} = (1 - \alpha) \mathbf{x} + \alpha \mathbf{m}_C \quad \forall \mathbf{x} \in R_C \quad (9)$$



Cinvestav

Resulting set R_C

Thus

- The resulting set R_C is the set of representatives of C .



Cinvestav

Resulting set R_C

Thus

- The resulting set R_C is the set of representatives of C .

Thus the distance between two cluster is defined as

$$d(C_i, C_j) = \min_{x \in R_{C_i}, y \in R_{C_j}} d(x, y) \quad (10)$$



Outline

1 Hierarchical Clustering

- Definition
- Basic Ideas

2 Agglomerative Algorithms

- Introduction
- Two Categories of Agglomerative Algorithms
 - Matrix Based Algorithms
 - Single Linkage
 - Complete Linkage
 - Group Average Linkage
- Graph Based Algorithms
- Problems with Agglomerative Algorithms
 - Improving the Complexity

3 Divisive Algorithms

- Introduction
- Possible Complexity
- Monothetic Divisive Methods

4 Algorithms for Large Data Sets

- Introduction
- **Clustering Using REpresentatives (CURE)**
 - Shrinking Process
 - **CURE Algorithm**
 - Complexity
- DBSCAN
 - Density Based Notion of Clusters
 - Beyond K -NN Idea
 - Cluster and Noise Definition
 - Sustaining the Algorithm
 - The DBSCAN Algorithm
 - Complexity
 - Finding ϵ and $MinPts$



Clustering Using REpresentatives (CURE)

Basic Algorithm

Input : A set of points $X = \{x_1, x_2, \dots, x_N\}$

Clustering Using REpresentatives (CURE)

Basic Algorithm

Input : A set of points $X = \{x_1, x_2, \dots, x_N\}$

Output : \mathcal{C} clusters

Clustering Using REpresentatives (CURE)

Basic Algorithm

Input : A set of points $X = \{x_1, x_2, \dots, x_N\}$

Output : \mathcal{C} clusters

- 1 For every cluster $C_i = \{x_i\}$ store $C_i.m_C = \{x_i\}$ and $C_i.R_C = \{x_i\}$

Clustering Using REpresentatives (CURE)

Basic Algorithm

Input : A set of points $X = \{x_1, x_2, \dots, x_N\}$

Output : \mathcal{C} clusters

- 1 For every cluster $C_i = \{x_i\}$ store $C_i.m_C = \{x_i\}$ and $C_i.R_C = \{x_i\}$
- 2 $C_i.closest$ stores the cluster closest to C_i .

Clustering Using REpresentatives (CURE)

Basic Algorithm

Input : A set of points $X = \{x_1, x_2, \dots, x_N\}$

Output : \mathcal{C} clusters

- 1 For every cluster $C_i = \{x_i\}$ store $C_i.m_C = \{x_i\}$ and $C_i.R_C = \{x_i\}$
- 2 $C_i.closest$ stores the cluster closest to C_i .
- 3 All the input points are inserted into a $K - d$ tree T .

Clustering Using REpresentatives (CURE)

Basic Algorithm

Input : A set of points $X = \{x_1, x_2, \dots, x_N\}$

Output : \mathcal{C} clusters

- 1 For every cluster $C_i = \{x_i\}$ store $C_i.m_C = \{x_i\}$ and $C_i.R_C = \{x_i\}$
- 2 $C_i.closest$ stores the cluster closest to C_i .
- 3 All the input points are inserted into a $K - d$ tree T .
- 4 Insert each cluster into the heap Q . (Clusters are arranged in increasing order of distances between C_i and $C_i.closest$).

Clustering Using REpresentatives (CURE)

Basic Algorithm

Input : A set of points $X = \{x_1, x_2, \dots, x_N\}$

Output : C clusters

- 1 For every cluster $C_i = \{x_i\}$ store $C_i.m_C = \{x_i\}$ and $C_i.R_C = \{x_i\}$
- 2 $C_i.closest$ stores the cluster closest to C_i .
- 3 All the input points are inserted into a $K - d$ tree T .
- 4 Insert each cluster into the heap Q . (Clusters are arranged in increasing order of distances between C_i and $C_i.closest$).
- 5 While $size(Q) > C$

Clustering Using REpresentatives (CURE)

Basic Algorithm

Input : A set of points $X = \{x_1, x_2, \dots, x_N\}$

Output : C clusters

- ❶ *For every cluster $C_i = \{x_i\}$ store $C_i.m_C = \{x_i\}$ and $C_i.R_C = \{x_i\}$*
- ❷ *$C_i.closest$ stores the cluster closest to C_i .*
- ❸ *All the input points are inserted into a $K - d$ tree T .*
- ❹ *Insert each cluster into the heap Q . (Clusters are arranged in increasing order of distances between C_i and $C_i.closest$).*
- ❺ *While $size(Q) > C$*
 - ❻ *Remove the top element of Q , C_i and merge it with $C_j == C_i.closest$.*

Clustering Using REpresentatives (CURE)

Basic Algorithm

Input : A set of points $X = \{x_1, x_2, \dots, x_N\}$

Output : \mathcal{C} clusters

- ➊ *For every cluster $C_i = \{x_i\}$ store $C_i.m_C = \{x_i\}$ and $C_i.R_C = \{x_i\}$*
- ➋ *$C_i.closest$ stores the cluster closest to C_i .*
- ➌ *All the input points are inserted into a $K - d$ tree T .*
- ➍ *Insert each cluster into the heap Q . (Clusters are arranged in increasing order of distances between C_i and $C_i.closest$).*
- ➎ *While $size(Q) > \mathcal{C}$*
 - ➏ *Remove the top element of Q , C_i and merge it with $C_j == C_i.closest$.*
 - ➐ *Then compute the new representative points for the merged cluster $C_k = C_i \cup C_j$.*

Clustering Using REpresentatives (CURE)

Basic Algorithm

Input : A set of points $X = \{x_1, x_2, \dots, x_N\}$

Output : \mathcal{C} clusters

- ➊ *For every cluster $C_i = \{x_i\}$ store $C_i.m_C = \{x_i\}$ and $C_i.R_C = \{x_i\}$*
- ➋ *$C_i.closest$ stores the cluster closest to C_i .*
- ➌ *All the input points are inserted into a $K - d$ tree T .*
- ➍ *Insert each cluster into the heap Q . (Clusters are arranged in increasing order of distances between C_i and $C_i.closest$).*
- ➎ *While $size(Q) > \mathcal{C}$*
 - ➏ *Remove the top element of Q , C_i and merge it with $C_j == C_i.closest$.*
 - ➐ *Then compute the new representative points for the merged cluster $C_k = C_i \cup C_j$.*
 - ➑ *Also remove C_i and C_j from T and Q .*

Clustering Using REpresentatives (CURE)

Basic Algorithm

Input : A set of points $X = \{x_1, x_2, \dots, x_N\}$

Output : \mathcal{C} clusters

- ➊ *For every cluster $C_i = \{x_i\}$ store $C_i.m_C = \{x_i\}$ and $C_i.R_C = \{x_i\}$*
- ➋ *$C_i.closest$ stores the cluster closest to C_i .*
- ➌ *All the input points are inserted into a $K - d$ tree T .*
- ➍ *Insert each cluster into the heap Q . (Clusters are arranged in increasing order of distances between C_i and $C_i.closest$).*
- ➎ *While $size(Q) > \mathcal{C}$*
 - ➏ *Remove the top element of Q , C_i and merge it with $C_j == C_i.closest$.*
 - ➐ *Then compute the new representative points for the merged cluster $C_k = C_i \cup C_j$.*
 - ➑ *Also remove C_i and C_j from T and Q .*
 - ➒ *Also for all the clusters $C_h \in Q$, update $C_h.closest$ and relocate C_h .*

Clustering Using REpresentatives (CURE)

Basic Algorithm

Input : A set of points $X = \{x_1, x_2, \dots, x_N\}$

Output : \mathcal{C} clusters

- ➊ *For every cluster $C_i = \{x_i\}$ store $C_i.m_C = \{x_i\}$ and $C_i.R_C = \{x_i\}$*
- ➋ *$C_i.closest$ stores the cluster closest to C_i .*
- ➌ *All the input points are inserted into a $K - d$ tree T .*
- ➍ *Insert each cluster into the heap Q . (Clusters are arranged in increasing order of distances between C_i and $C_i.closest$).*
- ➎ *While $size(Q) > \mathcal{C}$*
 - ➏ *Remove the top element of Q , C_i and merge it with $C_j == C_i.closest$.*
 - ➐ *Then compute the new representative points for the merged cluster $C_k = C_i \cup C_j$.*
 - ➑ *Also remove C_i and C_j from T and Q .*
 - ➒ *Also for all the clusters $C_h \in Q$, update $C_h.closest$ and relocate C_h .*
 - ➓ *insert C_k into Q*

Outline

1 Hierarchical Clustering

- Definition
- Basic Ideas

2 Agglomerative Algorithms

- Introduction
- Two Categories of Agglomerative Algorithms
 - Matrix Based Algorithms
 - Single Linkage
 - Complete Linkage
 - Group Average Linkage
- Graph Based Algorithms
- Problems with Agglomerative Algorithms
 - Improving the Complexity

3 Divisive Algorithms

- Introduction
- Possible Complexity
- Monothetic Divisive Methods

4 Algorithms for Large Data Sets

- Introduction
- **Clustering Using REpresentatives (CURE)**
 - Shrinking Process
 - CURE Algorithm
 - **Complexity**
- DBSCAN
 - Density Based Notion of Clusters
 - Beyond K -NN Idea
 - Cluster and Noise Definition
 - Sustaining the Algorithm
 - The DBSCAN Algorithm
 - Complexity
 - Finding ϵ and $MinPts$



Complexity of Cure

Too Prohibitive

$$O\left(N^2 \log_2 N\right) \quad (11)$$



Cinvestav

Possible Solution

CURE does the following

- The technique adopted by the CURE algorithm, in order to reduce the computational complexity, is that of ***random sampling***.



Possible Solution

CURE does the following

- The technique adopted by the CURE algorithm, in order to reduce the computational complexity, is that of *random sampling*.

Actually

That is, a sample set X' is created from X , by choosing randomly N' out of the N points of X .



Cinvestav

Possible Solution

CURE does the following

- The technique adopted by the CURE algorithm, in order to reduce the computational complexity, is that of ***random sampling***.

Actually

That is, a sample set X' is created from X , by choosing randomly N' out of the N points of X .

However, one has to ensure that the probability of missing a cluster of X , due to this sampling

This can be guaranteed if the number of points N' is sufficiently large.



Cinvestav

Then

Having estimated N'

CURE forms a number of $p = \frac{N}{N'}$ sample data sets by successive random samples.



Cinvestav

Then

Having estimated N'

CURE forms a number of $p = \frac{N}{N'}$ sample data sets by successive random samples.

In other words

- X is partitioned randomly in p subsets.



Cinvestav

Then

Having estimated N'

CURE forms a number of $p = \frac{N}{N'}$ sample data sets by successive random samples.

In other words

- X is partitioned randomly in p subsets.

For this a parameter q is selected

- Then, the points in each partition p are clustered until $\frac{N'}{q}$ clusters are formed.
- The distance between the closest pair of clusters to be merged in the next iteration step exceeds a user-defined threshold.

Once this has been finished

A second clustering pass is done

One the at most $p \frac{N'}{q} = \frac{N}{q}$ clusters from all the subsets.



Cinvestav

Once this has been finished

A second clustering pass is done

One the at most $p \frac{N'}{q} = \frac{N}{q}$ clusters from all the subsets.

The Goal to apply the merging procedure described previously to all (at most) $\frac{N}{q}$

- Then, we end up with the required final number, C , of clusters.



Cinvestav

Once this has been finished

A second clustering pass is done

One the at most $p \frac{N'}{q} = \frac{N}{q}$ clusters from all the subsets.

The Goal to apply the merging procedure described previously to all (at most) $\frac{N}{q}$

- Then, we end up with the required final number, C , of clusters.

Finally

- We have the following strategy to assign to $x \in X$ to a cluster.



Cinvestav

Then

First

A random sample of representative points from each of the C clusters is chosen.



Cinvestav

Then

First

A random sample of representative points from each of the C clusters is chosen.

Then

Then, based on the previous representatives the point x is assigned to the cluster that contains the representative closest to it.



Cinvestav

Then

First

A random sample of representative points from each of the C clusters is chosen.

Then

Then, based on the previous representatives the point x is assigned to the cluster that contains the representative closest to it.

Experiments reported by Guha et al. show that CURE

- It is sensitive to parameter selection.



Cinvestav

Then

First

A random sample of representative points from each of the C clusters is chosen.

Then

Then, based on the previous representatives the point x is assigned to the cluster that contains the representative closest to it.

Experiments reported by Guha et al. show that CURE

- It is sensitive to parameter selection.
 - ▶ Specifically K must be large enough to capture the geometry of each cluster.



Cinvestav

Then

First

A random sample of representative points from each of the C clusters is chosen.

Then

Then, based on the previous representatives the point x is assigned to the cluster that contains the representative closest to it.

Experiments reported by Guha et al. show that CURE

- It is sensitive to parameter selection.
 - ▶ Specifically K must be large enough to capture the geometry of each cluster.
 - ▶ In addition, N' must be higher than a certain percentage $\approx 2.5\%$ of N .

Not only that

The value of α (Shrinking Factors) affects also CURE

- Small values, CURE looks similar than a Minimum Spanning Tree clustering.



Cinvestav

Not only that

The value of α (Shrinking Factors) affects also CURE

- Small values, CURE looks similar than a Minimum Spanning Tree clustering.
- Large values, CURE resembles an algorithm with a single representative.



Cinvestav

Not only that

The value of α (Shrinking Factors) affects also CURE

- Small values, CURE looks similar than a Minimum Spanning Tree clustering.
- Large values, CURE resembles an algorithm with a single representative.

The worst-case execution time for CURE increases with the sample size N'

$$O\left(N'^2 \log_2 N'\right) \quad (12)$$



Cinvestav

Outline

1 Hierarchical Clustering

- Definition
- Basic Ideas

2 Agglomerative Algorithms

- Introduction
- Two Categories of Agglomerative Algorithms
 - Matrix Based Algorithms
 - Single Linkage
 - Complete Linkage
 - Group Average Linkage
- Graph Based Algorithms
- Problems with Agglomerative Algorithms
 - Improving the Complexity

3 Divisive Algorithms

- Introduction
- Possible Complexity
- Monothetic Divisive Methods

4 Algorithms for Large Data Sets

- Introduction
- Clustering Using REpresentatives (CURE)
 - Shrinking Process
 - CURE Algorithm
 - Complexity
- DBSCAN
 - Density Based Notion of Clusters
 - Beyond K -NN Idea
 - Cluster and Noise Definition
 - Sustaining the Algorithm
 - The DBSCAN Algorithm
 - Complexity
 - Finding ϵ and $MinPts$



A Large Name

Density-based spatial clustering of applications with noise (DBSCAN)

- It is a data clustering algorithm proposed by Martin Ester, Hans-Peter Kriegel, Jörg Sander and Xiaowei Xu in 1996.



A Large Name

Density-based spatial clustering of applications with noise (DBSCAN)

- It is a data clustering algorithm proposed by Martin Ester, Hans-Peter Kriegel, Jörg Sander and Xiaowei Xu in 1996.

Something Notable

- It is a density-based clustering algorithm:



Cinvestav

A Large Name

Density-based spatial clustering of applications with noise (DBSCAN)

- It is a data clustering algorithm proposed by Martin Ester, Hans-Peter Kriegel, Jörg Sander and Xiaowei Xu in 1996.

Something Notable

- It is a density-based clustering algorithm:
 - ▶ Given a set of points in some space, it groups together points that are closely packed together.



Cinvestav

A Large Name

Density-based spatial clustering of applications with noise (DBSCAN)

- It is a data clustering algorithm proposed by Martin Ester, Hans-Peter Kriegel, Jörg Sander and Xiaowei Xu in 1996.

Something Notable

- It is a density-based clustering algorithm:
 - ▶ Given a set of points in some space, it groups together points that are closely packed together.
 - ▶ Marking as outliers points that lie alone in low-density regions.

Furthermore

Something Notable

- In 2014, the algorithm was awarded the test of time award at the leading data mining conference, KDD.



Cinvestav

Outline

1 Hierarchical Clustering

- Definition
- Basic Ideas

2 Agglomerative Algorithms

- Introduction
- Two Categories of Agglomerative Algorithms
 - Matrix Based Algorithms
 - Single Linkage
 - Complete Linkage
 - Group Average Linkage
- Graph Based Algorithms
- Problems with Agglomerative Algorithms
 - Improving the Complexity

3 Divisive Algorithms

- Introduction
- Possible Complexity
- Monothetic Divisive Methods




4 Algorithms for Large Data Sets

- Introduction
- Clustering Using REpresentatives (CURE)
 - Shrinking Process
 - CURE Algorithm
 - Complexity
- DBSCAN
 - **Density Based Notion of Clusters**
 - Beyond K -NN Idea
 - Cluster and Noise Definition
 - Sustaining the Algorithm
 - The DBSCAN Algorithm
 - Complexity
 - Finding ϵ and $MinPts$



Looking at clusters

We notice easily those clusters of points and noise points



Cinvestav

We are doing something quite human

The main reason why we recognize the clusters

- We use the higher densities to recognize the clusters



Cinvestav

We are doing something quite human

The main reason why we recognize the clusters

- We use the higher densities to recognize the clusters

Definition (ϵ -neighborhood of a point)

- Given a distance $\text{dist} : \mathbb{R}^d \times \mathbb{R}^d \rightarrow \mathbb{R}^+$, the ϵ -Neighborhood of a point \mathbf{x} , denoted $N_\epsilon(\mathbf{x})$, is defined as

$$N_\epsilon(\mathbf{x}) = \left\{ \mathbf{y} \in \mathbb{R}^d \mid \text{dist}(\mathbf{x}, \mathbf{y}) \leq \epsilon \right\}$$



Outline

1 Hierarchical Clustering

- Definition
- Basic Ideas

2 Agglomerative Algorithms

- Introduction
- Two Categories of Agglomerative Algorithms
 - Matrix Based Algorithms
 - Single Linkage
 - Complete Linkage
 - Group Average Linkage
- Graph Based Algorithms
- Problems with Agglomerative Algorithms
 - Improving the Complexity

3 Divisive Algorithms

- Introduction
- Possible Complexity
- Monothetic Divisive Methods

4 Algorithms for Large Data Sets

- Introduction
- Clustering Using REpresentatives (CURE)
 - Shrinking Process
 - CURE Algorithm
 - Complexity
- DBSCAN
 - Density Based Notion of Clusters
 - **Beyond K -NN Idea**
 - Cluster and Noise Definition
 - Sustaining the Algorithm
 - The DBSCAN Algorithm
 - Complexity
 - Finding ϵ and $MinPts$



Why not to use the idea of K -NN?

We could use our well know K -NN method

- Thus, we naively could require for each point in a cluster there at least a minimum number ($MinPts$) of points in the neighborhood of such point



Cinvestav

Why not to use the idea of K -NN?

We could use our well know K -NN method

- Thus, we naively could require for each point in a cluster there at least a minimum number ($MinPts$) of points in the neighborhood of such point


However, you have something more complex

- Points inside of the cluster (Core points)
- Points on the border of the cluster (Border points)



Example

Core points and Border points



Cinvestav

Therefore

In General

- An ϵ -neighborhood of a border point contains significantly less points than an ϵ -neighborhood of a core point.



Cinvestav

Therefore

In General

- An ϵ -neighborhood of a border point contains significantly less points than an ϵ -neighborhood of a core point.

Therefore

- *MinPts* varies in the presence of noise



Cinvestav

Thus, we can ask for a new restriction

Definition (Directly Density-Reachable)

- A point x is directly density reachable from a point y w.r.t. ϵ , *MinPts* if



Cinvestav

Thus, we can ask for a new restriction

Definition (Directly Density-Reachable)

- A point x is directly density reachable from a point y w.r.t. ϵ , $MinPts$ if
 - 1 $x \in N_{\epsilon}(y)$



Cinvestav

Thus, we can ask for a new restriction

Definition (Directly Density-Reachable)

- A point x is directly density reachable from a point y w.r.t. ϵ , $MinPts$ if
 - 1 $x \in N_{\epsilon}(y)$
 - 2 $|N_{\epsilon}(y)| \geq MinPts$ (Core point condition)



Cinvestav

Thus, we can ask for a new restriction

Definition (Directly Density-Reachable)

- A point x is directly density reachable from a point y w.r.t. ϵ , $MinPts$ if
 - 1 $x \in N_{\epsilon}(y)$
 - 2 $|N_{\epsilon}(y)| \geq MinPts$ (Core point condition)

Remarks

- 1 Directly density-reachable is symmetric for pairs of core points.



Cinvestav

Thus, we can ask for a new restriction

Definition (Directly Density-Reachable)

- A point x is directly density reachable from a point y w.r.t. ϵ , $MinPts$ if
 - 1 $x \in N_\epsilon(y)$
 - 2 $|N_\epsilon(y)| \geq MinPts$ (Core point condition)


Remarks

- 1 Directly density-reachable is symmetric for pairs of core points.
- 2 It is not symmetric if one core point and one border point are involved.



Example

Density-reachable



Now, Density Reachable

Definition (Density-Reachable)

- A point x is density-reachable from a point y wrt. ϵ and MinPts if there is a chain of points:

$$p_1, p_2, \dots, p_k \text{ with } p_1 = x, p_k = y$$

such that p_{i+1} is directly density-reachable from p_i .




Cinvestav

Therefore

Density-Reachability is a canonical extension of **Direct Density-Reachability**

- This relation is transitive, but it is not symmetric.



Then

Remark

- Two border points of the same cluster C are possibly not density reachable from each other:
 - ▶ The core point condition might not hold for both of them.

Then

Remark

- Two border points of the same cluster C are possibly not density reachable from each other:
 - ▶ The core point condition might not hold for both of them.

However

- There must be a core point in C from which both border points of C are density-reachable.



Cinvestav

Density-Connected

Definition (Density-Connected)

- A point x is density-connected to a point y w.r.t. ϵ and $MinPts$:
 - ▶ if there is a point o such that both, x and y are density-reachable from o w.r.t. ϵ and $MinPts$.




Density-Connected

Definition (Density-Connected)

- A point x is density-connected to a point y w.r.t. ϵ and $MinPts$:
 - ▶ if there is a point o such that both, x and y are density-reachable from o w.r.t. ϵ and $MinPts$.

Example



Symmetry in Density-Connectivity

Density-connectivity is a symmetric relation

- Also for density reachable points, the relation of density-connectivity is also reflexive.



Cinvestav

Symmetry in Density-Connectivity

Density-connectivity is a symmetric relation

- Also for density reachable points, the relation of density-connectivity is also reflexive.

We are ready to define the concept of Cluster

- From the point of view density-based

Symmetry in Density-Connectivity

Density-connectivity is a symmetric relation

- Also for density reachable points, the relation of density-connectivity is also reflexive.

We are ready to define the concept of Cluster

- From the point of view density-based

Remark

- Intuitively, a cluster is defined to be a set of density-connected points which is maximal w.r.t. density-reachability.
- Noise is simply the set of points in \mathbb{R}^d not belonging to any of its clusters.



Cinvestav

Outline

1 Hierarchical Clustering

- Definition
- Basic Ideas

2 Agglomerative Algorithms

- Introduction
- Two Categories of Agglomerative Algorithms
 - Matrix Based Algorithms
 - Single Linkage
 - Complete Linkage
 - Group Average Linkage
- Graph Based Algorithms
- Problems with Agglomerative Algorithms
 - Improving the Complexity

3 Divisive Algorithms

- Introduction
- Possible Complexity
- Monothetic Divisive Methods

4 Algorithms for Large Data Sets

- Introduction
- Clustering Using REpresentatives (CURE)
 - Shrinking Process
 - CURE Algorithm
 - Complexity
- DBSCAN
 - Density Based Notion of Clusters
 - Beyond K -NN Idea
 - **Cluster and Noise Definition**
 - Sustaining the Algorithm
 - The DBSCAN Algorithm
 - Complexity
 - Finding ϵ and $MinPts$



Cluster Definition

Definition

- A cluster C w.r.t. ϵ and $MinPts$ is a non-empty subset of \mathbb{R}^d satisfying the following conditions:
 - 1 $\forall x, y$: if $y \in C$ and x is density-reachable from y w.r.t. ϵ and $MinPts$ then $x \in C$ (Maximality).
 - 2 $\forall x, y \in C$, x is density-connected to y w.r.t. ϵ and $MinPts$ (Connectivity).



Noise Definition

Definition

- Let C_1, \dots, C_k be the clusters in \mathbb{R}^d w.r.t. parameters ϵ_i and $MinPts_i$, $i = 1, \dots, k$.
 - ▶ Then we define the noise as the set of points in \mathbb{R}^d not belonging to any cluster C_i :

$$Noise = \{\mathbf{x} \in \mathbb{R}^d | \forall i : \mathbf{x} \notin C_i\}$$



Something Notable

- Since C contains at least one point x .



Something Notable

- Since C contains at least one point x .
- x must be density-connected to itself via some point o .
 - ▶ which may be equal to x .



Something Notable

- Since C contains at least one point x .
- x must be density-connected to itself via some point o .
 - ▶ which may be equal to x .
- Thus, at least o has to satisfy the core point condition
 - ▶ Consequently, ϵ -Neighborhood of o contains at least $MinPts$



Outline

1 Hierarchical Clustering

- Definition
- Basic Ideas

2 Agglomerative Algorithms

- Introduction
- Two Categories of Agglomerative Algorithms
 - Matrix Based Algorithms
 - Single Linkage
 - Complete Linkage
 - Group Average Linkage
- Graph Based Algorithms
- Problems with Agglomerative Algorithms
 - Improving the Complexity

3 Divisive Algorithms

- Introduction
- Possible Complexity
- Monothetic Divisive Methods

4 Algorithms for Large Data Sets

- Introduction
- Clustering Using REpresentatives (CURE)
 - Shrinking Process
 - CURE Algorithm
 - Complexity
- DBSCAN
 - Density Based Notion of Clusters
 - Beyond K -NN Idea
 - Cluster and Noise Definition
 - Sustaining the Algorithm
 - The DBSCAN Algorithm
 - Complexity
 - Finding ϵ and $MinPts$



Supporting the idea of cluster

Lemma - Reachability

- Let \mathbf{y} be a point in \mathbb{R}^d and $|N_\epsilon(\mathbf{y})| \geq \text{MinPts}$. Then

$$O = \{\mathbf{o} | \mathbf{o} \in \mathbb{R}^d \text{ and } \mathbf{o} \text{ is density-reachable from } \mathbf{y} \text{ w.r.t. } \epsilon \text{ and } \text{MinPts}\}$$

is a cluster w.r.t. ϵ and MinPts .



Cinvestav

Proof

Given the definition of O

- We have the first part of the definition of Cluster w.r.t. ϵ and $MinPts$.



Cinvestav

Proof

Given the definition of O

- We have the first part of the definition of Cluster w.r.t. ϵ and $MinPts$.

Given the that two points $o_1, o_2 \in O$ are density-reachable from y

- o_1, o_2 are density connected.

Proof

Given the definition of O

- We have the first part of the definition of Cluster w.r.t. ϵ and $MinPts$.

Given the that two points $o_1, o_2 \in O$ are density-reachable from y

- o_1, o_2 are density connected.

Then

- O is a cluster w.r.t. ϵ and $MinPts$.



Cinvestav

Intuition

Given the parameters ϵ and $MinPts$, we can discover a cluster

- First, choose an arbitrary point from \mathbb{R}^d satisfying the core point condition as a seed.



Cinvestav

Intuition

Given the parameters ϵ and $MinPts$, we can discover a cluster

- First, choose an arbitrary point from \mathbb{R}^d satisfying the core point condition as a seed.

Then

- Retrieve all points that are density-reachable from the seed **obtaining the cluster** containing the seed.



Cinvestav

However, it is not enough

We need something else

- Given that it is not obvious that a cluster C w.r.t. ϵ and $MinPts$ is uniquely determined by any of its core points.

However, it is not enough

We need something else

- Given that it is not obvious that a cluster C w.r.t. ϵ and $MinPts$ is uniquely determined by any of its core points.

However

- Each point in C is density-reachable from any of the core points of C .

However, it is not enough

We need something else

- Given that it is not obvious that a cluster C w.r.t. ϵ and $MinPts$ is uniquely determined by any of its core points.

However

- Each point in C is density-reachable from any of the core points of C .
- A cluster C contains exactly the points which are density-reachable from an arbitrary core point of C .

Then

Lemma - Cluster Equality to O

- Let C be a cluster w.r.t. ϵ and $MinPts$. and let \mathbf{y} be any point in C with $|N_\epsilon(\mathbf{y})| \geq MinPts$
 - ▶ Then C equals to the set

$$O = \{\mathbf{o} | \mathbf{o} \in \mathbb{R}^d \text{ and } \mathbf{o} \text{ is density-reachable from } \mathbf{y} \text{ w.r.t. } \epsilon \text{ and } MinPts\}$$

Proof

Given $x \in C$

- We have two cases



Cinvestav

Proof

Given $x \in C$

- We have two cases

Case 1

- x is a Border point that is density reachable from y with $|N_\epsilon(y)| \geq MinPts$



Cinvestav

Proof

Given $x \in C$

- We have two cases

Case 1

- x is a Border point that is density reachable from y with $|N_\epsilon(y)| \geq MinPts$

Then

- $x \in O$



Cinvestav

Case 2

- x is a Core point then $|N_{\epsilon}(x)| \geq MinPts$



Case 2

- x is a Core point then $|N_\epsilon(x)| \geq MinPts$

Therefore

- By Definition x is density reachable from any y w.r.t. ϵ and $MinPts$.

Case 2

- x is a Core point then $|N_\epsilon(x)| \geq MinPts$

Therefore

- By Definition x is density reachable from any y w.r.t. ϵ and $MinPts$.

Therefore

- $C \subset O$ the other contention is similar



Outline

1 Hierarchical Clustering

- Definition
- Basic Ideas

2 Agglomerative Algorithms

- Introduction
- Two Categories of Agglomerative Algorithms
 - Matrix Based Algorithms
 - Single Linkage
 - Complete Linkage
 - Group Average Linkage
- Graph Based Algorithms
- Problems with Agglomerative Algorithms
 - Improving the Complexity

3 Divisive Algorithms

- Introduction
- Possible Complexity
- Monothetic Divisive Methods

4 Algorithms for Large Data Sets

- Introduction
- Clustering Using REpresentatives (CURE)
 - Shrinking Process
 - CURE Algorithm
 - Complexity
- DBSCAN
 - Density Based Notion of Clusters
 - Beyond K -NN Idea
 - Cluster and Noise Definition
 - Sustaining the Algorithm
 - The DBSCAN Algorithm
 - Complexity
 - Finding ϵ and $MinPts$



DBSCAN Algorithm

DBSCAN($X, \epsilon, MinPts$)

- ① $ClusterId = nextId(NOISE)$
- ② for $i = 1$ to $X.size$
- ③ $x = SetOfPoints.get(i)$
- ④ if $x.ClId$ is UNCLASSIFIED:
- ⑤ If **ExpandCluster**($SetPoints, x, ClusterId, \epsilon, MinPts$)
- ⑥ $ClusterId = nextId(ClusterId)$



Cinvestav

ExpandCluster(*SetPoints*, *Point*, *ClId*, ϵ , *MinPts*)

- ① *seed* = *SetOfPoints.regionQuery* (*Point*, ϵ)
- ② If *seeds.size* < *MinPts* Then
- ③ *SetPoints.changeClId* (*Point*, *NOISE*)
- ④ return FALSE

ExpandCluster(*SetPoints*, *Point*, *CIId*, ϵ , *MinPts*)

- ① *seed* = *SetOfPoints.regionQuery* (*Point*, ϵ)
- ② If *seeds.size* < *MinPts* Then
- ③ *SetPoints.changeCIId* (*Point*, *NOISE*)
- ④ return FALSE
- ⑤ else
- ⑥ *SetPoints.changeCIId* (*seeds*, *CIId*)
- ⑦ *seeds.delete* (*Point*)

ExpandCluster(*SetPoints*, *Point*, *CIId*, ϵ , *MinPts*)

- ① *seed* = *SetOfPoints.regionQuery* (*Point*, ϵ)
- ② If *seeds.size* < *MinPts* Then
- ③ *SetPoints.changeCIId* (*Point*, *NOISE*)
- ④ return FALSE
- ⑤ else
- ⑥ *SetPoints.changeCIId* (*seeds*, *CIId*)
- ⑦ *seeds.delete* (*Point*)
- ⑧ while *seeds* \neq NULL:
- ⑨ *currentP* = *seeds.first* ()
- ⑩ *result* = *SetOfPoints.regionQuery* (*currentP*, ϵ)

ExpandCluster(*SetPoints*, *Point*, *CIId*, ϵ , *MinPts*)

```
1  seed = SetOfPoints.regionQuery (Point,  $\epsilon$ )
2  If seeds.size < MinPts Then
3      SetPoints.changeCIId (Point, NOISE)
4      return FALSE
5  else
6      SetPoints.changeCIId (seeds, CIId)
7      seeds.delete (Point)
8      while seeds  $\neq$  NULL:
9          currentP = seeds.first ()
10         result = SetOfPoints.regionQuery (currentP,  $\epsilon$ )
11         if result.size () > MinPts then
12             for i = 1 to result.size:
```



ExpandCluster(*SetPoints*, *Point*, *ClId*, ϵ , *MinPts*)

```
1  seed = SetOfPoints.regionQuery (Point,  $\epsilon$ )
2  If seeds.size < MinPts Then
3      SetPoints.changeClId (Point, NOISE)
4      return FALSE
5  else
6      SetPoints.changeClId (seeds, ClId)
7      seeds.delete (Point)
8      while seeds  $\neq$  NULL:
9          currentP = seeds.first ()
10         result = SetOfPoints.regionQuery (currentP,  $\epsilon$ )
11         if result.size () > MinPts then
12             for i = 1 to result.size:
13                 resultP = result.get (i)
14                 if resultP.ClId  $\in$  {NOISE, UNCLASSIFIED} and
15                     resultP.ClId = UNCLASSIFIED
16                     seeds.append (resultP)
```

ExpandCluster(*SetPoints*, *Point*, *CIId*, ϵ , *MinPts*)

```
1  seed = SetOfPoints.regionQuery (Point,  $\epsilon$ )
2  If seeds.size < MinPts Then
3      SetPoints.changeCIId (Point, NOISE)
4      return FALSE
5  else
6      SetPoints.changeCIId (seeds, CIId)
7      seeds.delete (Point)
8      while seeds  $\neq$  NULL:
9          currentP = seeds.first ()
10         result = SetOfPoints.regionQuery (currentP,  $\epsilon$ )
11         if result.size () > MinPts then
12             for i = 1 to result.size:
13                 resultP = result.get (i)
14                 if resultP.CIId  $\in$  {NOISE, UNCLASSIFIED} and
15                     resultP.CIId = UNCLASSIFIED
16                     seeds.append (resultP)
17                     SetPoints.changeCIId (resultP, CIId)
18                 seeds.delete (currentP)
```

ExpandCluster(*SetPoints*, *Point*, *CIId*, ϵ , *MinPts*)

```
1  seed = SetOfPoints.regionQuery (Point,  $\epsilon$ )
2  If seeds.size < MinPts Then
3      SetPoints.changeCIId (Point, NOISE)
4      return FALSE
5  else
6      SetPoints.changeCIId (seeds, CIId)
7      seeds.delete (Point)
8      while seeds  $\neq$  NULL:
9          currentP = seeds.first ()
10         result = SetOfPoints.regionQuery (currentP,  $\epsilon$ )
11         if result.size () > MinPts then
12             for i = 1 to result.size:
13                 resultP = result.get (i)
14                 if resultP.CIId  $\in$  {NOISE, UNCLASSIFIED} and
15                     resultP.CIId = UNCLASSIFIED
16                     seeds.append (resultP)
17                     SetPoints.changeCIId (resultP, CIId)
18                     seeds.delete (currentP)
19 return TRUE
```

Outline

1 Hierarchical Clustering

- Definition
- Basic Ideas

2 Agglomerative Algorithms

- Introduction
- Two Categories of Agglomerative Algorithms
 - Matrix Based Algorithms
 - Single Linkage
 - Complete Linkage
 - Group Average Linkage
- Graph Based Algorithms
- Problems with Agglomerative Algorithms
 - Improving the Complexity

3 Divisive Algorithms

- Introduction
- Possible Complexity
- Monothetic Divisive Methods

4 Algorithms for Large Data Sets

- Introduction
- Clustering Using REpresentatives (CURE)
 - Shrinking Process
 - CURE Algorithm
 - Complexity
- DBSCAN
 - Density Based Notion of Clusters
 - Beyond K -NN Idea
 - Cluster and Noise Definition
 - Sustaining the Algorithm
 - The DBSCAN Algorithm
 - Complexity
 - Finding ϵ and $MinPts$



Complexity

x is a core point

- It can be implemented using kd-trees



Cinvestav

Complexity

x is a core point

- It can be implemented using kd-trees

Thus, given the complexities of Kd-trees

	Average	Worst case
Space	$O(n)$	$O(n)$
Search	$O(\log n)$	$O(n)$
Insert	$O(\log n)$	$O(n)$
Delete	$O(\log n)$	$O(n)$



Cinvestav

Therefore

The average Complexity of DBSCAN

- $O(dn \log n)$ to build the structure for query using a heapsort or mergesort
- $O\left(\left\{n^{1-\frac{1}{d}} + m\right\}\right)$ when m is the number of reported elements and d is the dimensionality of the points.



Cinvestav

Outline

1 Hierarchical Clustering

- Definition
- Basic Ideas

2 Agglomerative Algorithms

- Introduction
- Two Categories of Agglomerative Algorithms
 - Matrix Based Algorithms
 - Single Linkage
 - Complete Linkage
 - Group Average Linkage
- Graph Based Algorithms
- Problems with Agglomerative Algorithms
 - Improving the Complexity

3 Divisive Algorithms

- Introduction
- Possible Complexity
- Monothetic Divisive Methods

4 Algorithms for Large Data Sets

- Introduction
- Clustering Using REpresentatives (CURE)
 - Shrinking Process
 - CURE Algorithm
 - Complexity
- DBSCAN
 - Density Based Notion of Clusters
 - Beyond K -NN Idea
 - Cluster and Noise Definition
 - Sustaining the Algorithm
 - The DBSCAN Algorithm
 - Complexity
- Finding ϵ and $MinPts$



There is a problem

How do we estimate?

- ϵ and *MinPts*.



Cinvestav

There is a problem

How do we estimate?

- ϵ and *MinPts*.

In the original paper

- They develop a heuristic to determine the parameters ϵ and *MinPts* of the "thinnest"



Cinvestav

Heuristic

Let d be the distance of a point x

- to its k^{th} nearest neighbor.



Cinvestav

Heuristic

Let d be the distance of a point x

- to its k^{th} nearest neighbor.

Then, the d -neighborhood of x contains exactly

- $k + 1$ points for almost all points x .



Cinvestav

Heuristic

Let d be the distance of a point x

- to its k^{th} nearest neighbor.

Then, the d -neighborhood of x contains exactly

- $k + 1$ points for almost all points x .

The d -neighborhood of x contains more than $k + 1$ points

- Only if several points have exactly the same distance d from x which is quite unlikely.



Then

Furthermore

- Changing k for a point in a cluster does not result in large changes of d .



Cinvestav

Then

Furthermore

- Changing k for a point in a cluster does not result in large changes of d .

This only happens if the k^{th} nearest neighbors of x

- for $k = 1, 2, 3, \dots$ are located approximately
 - ▶ on a straight line which is in general not true for a point in a cluster.



Cinvestav

Then, we have

For a given k we define a function k -dist from \mathbb{R}^d to \mathbb{R}

- Mapping each point to the distance from its k^{th} nearest neighbor.



Cinvestav

Then, we have

For a given k we define a function k -dist from \mathbb{R}^d to \mathbb{R}


- Mapping each point to the distance from its k^{th} nearest neighbor.

When sorting the points of the database in descending order of their k -dist values

- The graph of this function gives some hints concerning the density distribution in the database.

Example of 4-dist

We set $MinPts = 4$ then we can calculate ϵ by looking



Therefore

For more in the heuristic look at the paper

- “A Density-Based Algorithm for Discovering Clusters in Large Spatial Databases with Noise” by Martin Ester, Hans-Peter Kriegel, Jorg Sander, Xiaowei Xu



Cinvestav

Therefore

For more in the heuristic look at the paper

- “A Density-Based Algorithm for Discovering Clusters in Large Spatial Databases with Noise” by Martin Ester, Hans-Peter Kriegel, Jorg Sander, Xiaowei Xu

However, the problem is the same

- Finding the correct number of hyperparameters for getting the correct number of clusters

Therefore

For more in the heuristic look at the paper

- “A Density-Based Algorithm for Discovering Clusters in Large Spatial Databases with Noise” by Martin Ester, Hans-Peter Kriegel, Jorg Sander, Xiaowei Xu

However, the problem is the same

- Finding the correct number of hyperparameters for getting the correct number of clusters

More advanced methods of clustering exist

- Spectral Clustering - Using the Graph Structure
- Dirichlet Processes - Based in the Generation of a Distribution
- etc