

Analysis of Algorithms

Skip Lists

Andres Mendez-Vazquez

September 27, 2020

Outline

1 Dictionaries

- Definitions
- Dictionary operations
- Dictionary implementation

2 Skip Lists

- Why Skip Lists?
- The Idea Behind All of It!!!
- Skip List Definition
- Skip list implementation
- Insertion for Skip Lists
- Deletion in Skip Lists
- Properties
- Search and Insertion Times
- Applications
- Summary



Outline

1 Dictionaries

● Definitions

- Dictionary operations
- Dictionary implementation

2 Skip Lists

- Why Skip Lists?
- The Idea Behind All of It!!!
- Skip List Definition
- Skip list implementation
- Insertion for Skip Lists
- Deletion in Skip Lists
- Properties
- Search and Insertion Times
- Applications
- Summary



Dictionaries

Definition

A dictionary is a collection of elements; each of which has a unique search key.

- Uniqueness criteria may be relaxed (multi-set).
- Do not force uniqueness.

Dictionaries

Definition

A dictionary is a collection of elements; each of which has a unique search key.

- Uniqueness criteria may be relaxed (multi-set).

- Do not force uniqueness.

Purpose

Dictionaries keep track of current members, with periodic insertions and deletions into the set (similar to a database).

Dictionaries

Definition

A dictionary is a collection of elements; each of which has a unique search key.

- Uniqueness criteria may be relaxed (multi-set).
- Do not force uniqueness.

Purpose

Dictionaries keep track of current members, with periodic insertions and deletions into the set (similar to a database).

Examples

- Membership in a club.
- Course records.
- Symbol table (with duplicates).
- Language dictionary (Webster, RAE, Oxford).

Dictionaries

Definition

A dictionary is a collection of elements; each of which has a unique search key.

- Uniqueness criteria may be relaxed (multi-set).
- Do not force uniqueness.

Purpose

Dictionaries keep track of current members, with periodic insertions and deletions into the set (similar to a database).

Examples

- Membership in a club.
- Course records.
- Symbol table (with duplicates).
- Language dictionary (Webster, RAE, Oxford).

Dictionaries

Definition

A dictionary is a collection of elements; each of which has a unique search key.

- Uniqueness criteria may be relaxed (multi-set).
- Do not force uniqueness.

Purpose

Dictionaries keep track of current members, with periodic insertions and deletions into the set (similar to a database).

Examples

- Membership in a club.
- Course records.
- Symbol table (with duplicates).
- Language dictionary (Webster, RAE, Oxford).

Dictionaries

Definition

A dictionary is a collection of elements; each of which has a unique search key.

- Uniqueness criteria may be relaxed (multi-set).
- Do not force uniqueness.

Purpose

Dictionaries keep track of current members, with periodic insertions and deletions into the set (similar to a database).

Examples

- Membership in a club.
- Course records.
- Symbol table (with duplicates).
- Language dictionary (Webster, RAE, Oxford).

Dictionaries

Definition

A dictionary is a collection of elements; each of which has a unique search key.

- Uniqueness criteria may be relaxed (multi-set).
- Do not force uniqueness.

Purpose

Dictionaries keep track of current members, with periodic insertions and deletions into the set (similar to a database).

Examples

- Membership in a club.
- Course records.
- Symbol table (with duplicates).
- Language dictionary (Webster, RAE, Oxford).

Dictionaries

Definition

A dictionary is a collection of elements; each of which has a unique search key.

- Uniqueness criteria may be relaxed (multi-set).
- Do not force uniqueness.

Purpose

Dictionaries keep track of current members, with periodic insertions and deletions into the set (similar to a database).

Examples

- Membership in a club.
- Course records.
- Symbol table (with duplicates).
- Language dictionary (Webster, RAE, Oxford).

Example: Course records

Dictionary with member records

key ID	Student Name	HW1	
123	Stan Smith	49	...
125	Sue Margolin	45	...
128	Billie King	24	...
⋮			
⋮			
190	Roy Miller	36	...



Outline

1 Dictionaries

- Definitions
- **Dictionary operations**
- Dictionary implementation

2 Skip Lists

- Why Skip Lists?
- The Idea Behind All of It!!!
- Skip List Definition
- Skip list implementation
- Insertion for Skip Lists
- Deletion in Skip Lists
- Properties
- Search and Insertion Times
- Applications
- Summary



The dictionary ADT operations

Some operations on dictionaries

- `size()`: Returns the size of the dictionary.
- `empty()`: Returns `TRUE` if the dictionary is empty.
- `findItem(key)`: Locates the item with the specified key.
- `findAllItems(key)`: Locates all items with the specified key.
- `removeItem(key)`: Removes the item with the specified key.
- `removeAllItems(key)`: Removes all items with the specified key.
- `insertItem(key,element)`: Inserts a new key-element pair.



The dictionary ADT operations

Some operations on dictionaries

- `size()`: Returns the size of the dictionary.
- `empty()`: Returns TRUE if the dictionary is empty.
- `findItem(key)`: Locates the item with the specified key.
- `findAllItems(key)`: Locates all items with the specified key.
- `removeItem(key)`: Removes the item with the specified key.
- `removeAllItems(key)`: Removes all items with the specified key.
- `insertItem(key,element)`: Inserts a new key-element pair.



The dictionary ADT operations

Some operations on dictionaries

- `size()`: Returns the size of the dictionary.
- `empty()`: Returns `TRUE` if the dictionary is empty.
- `findItem(key)`: Locates the item with the specified key.
- `findAllItems(key)`: Locates all items with the specified key.
- `removeItem(key)`: Removes the item with the specified key.
- `removeAllItems(key)`: Removes all items with the specified key.
- `insertItem(key,element)`: Inserts a new key-element pair.



The dictionary ADT operations

Some operations on dictionaries

- `size()`: Returns the size of the dictionary.
- `empty()`: Returns `TRUE` if the dictionary is empty.
- `findItem(key)`: Locates the item with the specified key.
- `findAllItems(key)`: Locates all items with the specified key.
- `removeItem(key)`: Removes the item with the specified key.
- `removeAllItems(key)`: Removes all items with the specified key.
- `insertItem(key,element)`: Inserts a new key-element pair.



The dictionary ADT operations

Some operations on dictionaries

- `size()`: Returns the size of the dictionary.
- `empty()`: Returns TRUE if the dictionary is empty.
- `findItem(key)`: Locates the item with the specified key.
- `findAllItems(key)`: Locates all items with the specified key.
- `removeItem(key)`: Removes the item with the specified key.
- `removeAllItems(key)`: Removes all items with the specified key.
- `insertItem(key,element)`: Inserts a new key-element pair.



The dictionary ADT operations

Some operations on dictionaries

- `size()`: Returns the size of the dictionary.
- `empty()`: Returns TRUE if the dictionary is empty.
- `findItem(key)`: Locates the item with the specified key.
- `findAllItems(key)`: Locates all items with the specified key.
- `removeItem(key)`: Removes the item with the specified key.
- `removeAllItems(key)`: Removes all items with the specified key.
- `insertItem(key,element)`: Inserts a new key-element pair.



The dictionary ADT operations

Some operations on dictionaries

- `size()`: Returns the size of the dictionary.
- `empty()`: Returns `TRUE` if the dictionary is empty.
- `findItem(key)`: Locates the item with the specified key.
- `findAllItems(key)`: Locates all items with the specified key.
- `removeItem(key)`: Removes the item with the specified key.
- `removeAllItems(key)`: Removes all items with the specified key.
- `insertItem(key,element)`: Inserts a new key-element pair.



Example of unordered dictionary

Example

Consider an empty unordered dictionary, we have then...

Operation	Dictionary	Output
InsertItem(5, A)	{(5, A)}	
InsertItem(7, B)	{(5, A), (7, B)}	
findItem(7)	{(5, A), (7, B)}	B
findItem(4)	{(5, A), (7, B)}	No Such Key
size()	{(5, A), (7, B)}	2
removeItem(5)	{(7, B)}	A
findItem(4)	{(7, B)}	No Such Key



Outline

1 Dictionaries

- Definitions
- Dictionary operations
- **Dictionary implementation**

2 Skip Lists

- Why Skip Lists?
- The Idea Behind All of It!!!
- Skip List Definition
- Skip list implementation
- Insertion for Skip Lists
- Deletion in Skip Lists
- Properties
- Search and Insertion Times
- Applications
- Summary



How to implement a dictionary?

There are many ways of implementing a dictionary

- Sequences / Arrays
 - ▶ Ordered
 - ▶ Unordered
- Binary search trees
- Skip lists
- Hash tables



How to implement a dictionary?

There are many ways of implementing a dictionary

- Sequences / Arrays
 - ▶ Ordered
 - ▶ Unordered
- Binary search trees
- Skip lists
- Hash tables



How to implement a dictionary?

There are many ways of implementing a dictionary

- Sequences / Arrays
 - ▶ Ordered
 - ▶ Unordered
- Binary search trees
- Skip lists

• Hash tables



How to implement a dictionary?

There are many ways of implementing a dictionary

- Sequences / Arrays
 - ▶ Ordered
 - ▶ Unordered
- Binary search trees
- Skip lists
- Hash tables



Recall Arrays...

Unordered array

34

14

12

22

18



Recall Arrays...

Unordered array

34	14	12	22	18
----	----	----	----	----

Complexity

- Searching and removing takes $O(n)$.
- Inserting takes $O(1)$.



Recall Arrays...

Unordered array

34	14	12	22	18
----	----	----	----	----

Complexity

- Searching and removing takes $O(n)$.
- Inserting takes $O(1)$.

Applications

This approach is good for log files where insertions are frequent but searches and removals are rare.



Recall Arrays...

Unordered array

34	14	12	22	18
----	----	----	----	----

Complexity

- Searching and removing takes $O(n)$.
- Inserting takes $O(1)$.

Applications

This approach is good for log files where insertions are frequent but searches and removals are rare.



More Arrays

Ordered array

12	14	18	22	34
----	----	----	----	----



More Arrays

Ordered array

12	14	18	22	34
----	----	----	----	----

Complexity

- Searching takes $O(\log n)$ time (binary search).

• Insert and removing takes $O(n)$ time.



More Arrays

Ordered array

12	14	18	22	34
----	----	----	----	----

Complexity

- Searching takes $O(\log n)$ time (binary search).
- Insert and removing takes $O(n)$ time.

Applications

This approach is good for look-up tables where searches are frequent but insertions and removals are rare.



More Arrays

Ordered array

12	14	18	22	34
----	----	----	----	----

Complexity

- Searching takes $O(\log n)$ time (binary search).
- Insert and removing takes $O(n)$ time.

Applications

This approach is good for look-up tables where searches are frequent but insertions and removals are rare.



Binary searches

Features

- Narrow down the search range in stages
- “High-low” game.



Binary searches

Example find Element(22)

2	4	5	7	8	9	12	14	17	19	22	25	27	28	33
---	---	---	---	---	---	----	----	----	----	----	----	----	----	----

↑
LOW

↑
MID

↑
HIGH

2	4	5	7	8	9	12	14	17	19	22	25	27	28	33
---	---	---	---	---	---	----	----	----	----	----	----	----	----	----

↑
LOW

↑
MID

↑
HIGH

2	4	5	7	8	9	12	14	17	19	22	25	27	28	33
---	---	---	---	---	---	----	----	----	----	----	----	----	----	----

↑
LOW

↑
MID

↑
HIGH

2	4	5	7	8	9	12	14	17	19	22	25	27	28	33
---	---	---	---	---	---	----	----	----	----	----	----	----	----	----

↑
LOW=MID=HIGH

Binary searches

Example find Element(22)

2	4	5	7	8	9	12	14	17	19	22	25	27	28	33
---	---	---	---	---	---	----	----	----	----	----	----	----	----	----

↑
LOW

↑
MID

↑
HIGH

2	4	5	7	8	9	12	14	17	19	22	25	27	28	33
---	---	---	---	---	---	----	----	----	----	----	----	----	----	----

↑
LOW

↑
MID

↑
HIGH

2	4	5	7	8	9	12	14	17	19	22	25	27	28	33
---	---	---	---	---	---	----	----	----	----	----	----	----	----	----

↑
LOW

↑
MID

↑
HIGH

2	4	5	7	8	9	12	14	17	19	22	25	27	28	33
---	---	---	---	---	---	----	----	----	----	----	----	----	----	----

↑
LOW=MID=HIGH

Binary searches

Example find Element(22)

2	4	5	7	8	9	12	14	17	19	22	25	27	28	33
---	---	---	---	---	---	----	----	----	----	----	----	----	----	----

↑
LOW

↑
MID

↑
HIGH

2	4	5	7	8	9	12	14	17	19	22	25	27	28	33
---	---	---	---	---	---	----	----	----	----	----	----	----	----	----

↑
LOW

↑
MID

↑
HIGH

2	4	5	7	8	9	12	14	17	19	22	25	27	28	33
---	---	---	---	---	---	----	----	----	----	----	----	----	----	----

↑
LOW

↑
MID

↑
HIGH

2	4	5	7	8	9	12	14	17	19	22	25	27	28	33
---	---	---	---	---	---	----	----	----	----	----	----	----	----	----

↑
LOW=MID=HIGH

Binary searches

Example find Element(22)

2	4	5	7	8	9	12	14	17	19	22	25	27	28	33
---	---	---	---	---	---	----	----	----	----	----	----	----	----	----

↑
LOW

↑
MID

↑
HIGH

2	4	5	7	8	9	12	14	17	19	22	25	27	28	33
---	---	---	---	---	---	----	----	----	----	----	----	----	----	----

↑
LOW

↑
MID

↑
HIGH

2	4	5	7	8	9	12	14	17	19	22	25	27	28	33
---	---	---	---	---	---	----	----	----	----	----	----	----	----	----

↑
LOW

↑
MID

↑
HIGH

2	4	5	7	8	9	12	14	17	19	22	25	27	28	33
---	---	---	---	---	---	----	----	----	----	----	----	----	----	----

↑
LOW=MID=HIGH

Recall binary search trees

Implement a dictionary with a BST

A binary search tree is a binary tree T such that:

- Each internal node stores an item (k, e) of a dictionary.
- Keys stored at nodes in the left subtree of v are less than or equal to k .
- Keys stored at nodes in the right subtree of v are greater than or equal to k .



Recall binary search trees

Implement a dictionary with a BST

A binary search tree is a binary tree T such that:

- Each internal node stores an item (k, e) of a dictionary.
- Keys stored at nodes in the left subtree of v are less than or equal to k .
- Keys stored at nodes in the right subtree of v are greater than or equal to k .



Recall binary search trees

Implement a dictionary with a BST

A binary search tree is a binary tree T such that:

- Each internal node stores an item (k, e) of a dictionary.
- Keys stored at nodes in the left subtree of v are less than or equal to k .
- Keys stored at nodes in the right subtree of v are greater than or equal to k .



Recall binary search trees

Implement a dictionary with a BST


A binary search tree is a binary tree T such that:

- Each internal node stores an item (k, e) of a dictionary.
- Keys stored at nodes in the left subtree of v are less than or equal to k .
- Keys stored at nodes in the right subtree of v are greater than or equal to k .



Binary searches Trees

Problem!!! Keeping a Well Balanced Binary Search Tree can be difficult!!!



Not only that...

Binary Search Trees

- They are not so well suited for parallel environments.
 - ▶ Unless a heavy modifications are done



Not only that...

Binary Search Trees

- They are not so well suited for parallel environments.
 - ▶ Unless a heavy modifications are done

In addition

We want to have a

- Compact Data Structure.
- Using as little memory as possible



Not only that...

Binary Search Trees

- They are not so well suited for parallel environments.
 - ▶ Unless a heavy modifications are done

In addition

We want to have a

- Compact Data Structure.
- Using as little memory as possible



Not only that...

Binary Search Trees

- They are not so well suited for parallel environments.
 - ▶ Unless a heavy modifications are done

In addition

We want to have a

- Compact Data Structure.
- Using as little memory as possible



Thus, we have the following possibilities

Unordered array complexities

Insertion: $O(1)$

Search: $O(n)$

Ordered array complexities

Insertion: $O(n)$

Search: $O(\log n)$

Well balanced binary trees complexities

Insertion: $O(\log n)$

Search: $O(\log n)$

Big Drawback - Complex parallel Implementation and waste of memory.

Thus, we have the following possibilities

Unordered array complexities

Insertion: $O(1)$

Search: $O(n)$

Ordered array complexities

Insertion: $O(n)$

Search: $O(\log n)$

Well balanced binary trees complexities

Insertion: $O(\log n)$

Search: $O(\log n)$

Big Drawback - Complex parallel Implementation and waste of memory.

Thus, we have the following possibilities

Unordered array complexities

Insertion: $O(1)$

Search: $O(n)$

Ordered array complexities

Insertion: $O(n)$

Search: $O(\log n)$

Well balanced binary trees complexities

Insertion: $O(\log n)$

Search: $O(\log n)$

Big Drawback - Complex parallel Implementation and waste of memory.

We want something better!!!

For this

We will present a probabilistic data structure known as Skip List!!!



Outline

- 1 Dictionaries
 - Definitions
 - Dictionary operations
 - Dictionary implementation

- 2 Skip Lists
 - Why Skip Lists?
 - The Idea Behind All of It!!!
 - Skip List Definition
 - Skip list implementation
 - Insertion for Skip Lists
 - Deletion in Skip Lists
 - Properties
 - Search and Insertion Times
 - Applications
 - Summary



Starting from Scratch

First

- Imagine that you only require to have searches.
- A first approximation to it is the use of a link list for it ($\Theta(n)$ search complexity).
- Then, using this How do we speed up searches?

Starting from Scratch

First

- Imagine that you only require to have searches.
- A first approximation to it is the use of a link list for it ($\Theta(n)$ search complexity).
- Then, using this How do we speed up searches?

Something Notable

- Use two link list, one a subsequence of the other.

Starting from Scratch

First

- Imagine that you only require to have searches.
- A first approximation to it is the use of a link list for it ($\Theta(n)$ search complexity).
- Then, using this How do we speed up searches?

Something Notable

- Use two link list, one a subsequence of the other.

Imagine the two lists as a road system

- The Bottom is the normal road system, L_2 .
- The Top is the high way system, L_1 .

Starting from Scratch

First

- Imagine that you only require to have searches.
- A first approximation to it is the use of a link list for it ($\Theta(n)$ search complexity).
- Then, using this How do we speed up searches?

Something Notable

- Use two link list, one a subsequence of the other.

Imagine the two link as a road system

- The Bottom is the normal road system, L_2 .
- The Top is the high way system, L_1 .

Starting from Scratch

First

- Imagine that you only require to have searches.
- A first approximation to it is the use of a link list for it ($\Theta(n)$ search complexity).
- Then, using this How do we speed up searches?

Something Notable

- Use two link list, one a subsequence of the other.

Imagine the two lists as a road system

- 1 The Bottom is the normal road system, L_2 .

2 The Top is the high way system, L_1 .

Starting from Scratch

First

- Imagine that you only require to have searches.
- A first approximation to it is the use of a link list for it ($\Theta(n)$ search complexity).
- Then, using this How do we speed up searches?

Something Notable

- Use two link list, one a subsequence of the other.

Imagine the two lists as a road system

- 1 The Bottom is the normal road system, L_2 .
- 2 The Top is the high way system, L_1 .


Outline

- 1 Dictionaries
 - Definitions
 - Dictionary operations
 - Dictionary implementation
- 2 Skip Lists
 - Why Skip Lists?
 - **The Idea Behind All of It!!!**
 - Skip List Definition
 - Skip list implementation
 - Insertion for Skip Lists
 - Deletion in Skip Lists
 - Properties
 - Search and Insertion Times
 - Applications
 - Summary



Example

High-Bottom Way System



Thus, we have...

The following rule

To Search first search in the top one (L_1) as far as possible, then go down and search in the bottom one (L_2).



We can use a little bit of optimization

We have the following worst cost

Search Cost High-Bottom Way System = Cost Searching Top +...

Cost Search Bottom

Or

Search Cost = $length(L_1)$ + Cost Search Bottom

The interesting part is "Cost Search Bottom"

This can be calculated by the following quotient:

$$\frac{length(L_2)}{length(L_1)}$$



We can use a little bit of optimization

We have the following worst cost

Search Cost High-Bottom Way System = Cost Searching Top +...

Cost Search Bottom

Or

Search Cost = $length(L_1)$ + Cost Search Bottom

The interesting part is “Cost Search Bottom”


This can be calculated by the following quotient:

$$\frac{length(L_2)}{length(L_1)}$$



Why?

If we think we are jumping



Then cost of searching each of the bottom segments = 2


Thus the ratio is a “decent” approximation to the worst case search

$$\frac{\text{length}(L_2)}{\text{length}(L_1)} = \frac{5}{3} = 1.66$$



Why?

If we think we are jumping



Then cost of searching each of the bottom segments = 2

Thus the ratio is a “decent” approximation to the worst case search

$$\frac{\text{length}(L_2)}{\text{length}(L_1)} = \frac{5}{3} = 1.66$$



Thus, we have...

Then, the cost for a search (when $\text{length}(L_2) = n$)

$$\text{Search Cost} = \text{length}(L_1) + \frac{\text{length}(L_2)}{\text{length}(L_1)} = \text{length}(L_1) + \frac{n}{\text{length}(L_1)} \quad (1)$$

Taking the derivative with respect to $\text{length}(L_1)$ and making the result equal 0

$$1 - \frac{n}{\text{length}^2(L_1)} = 0$$



Thus, we have...

Then, the cost for a search (when $\text{length}(L_2) = n$)

$$\text{Search Cost} = \text{length}(L_1) + \frac{\text{length}(L_2)}{\text{length}(L_1)} = \text{length}(L_1) + \frac{n}{\text{length}(L_1)} \quad (1)$$

Taking the derivative with respect to $\text{length}(L_1)$ and making the result equal 0

$$1 - \frac{n}{\text{length}^2(L_1)} = 0$$



Final Cost

We have that the optimal length for L_1

$$\text{length}(L_1) = \sqrt{n}$$

Plugging back in (Eq. 1)

$$\text{Search Cost} = \sqrt{n} + \frac{n}{\sqrt{n}} = \sqrt{n} + \sqrt{n} = 2 \times \sqrt{n}$$



Final Cost

We have that the optimal length for L_1

$$\text{length}(L_1) = \sqrt{n}$$


Plugging back in (Eq. 1)

$$\text{Search Cost} = \sqrt{n} + \frac{n}{\sqrt{n}} = \sqrt{n} + \sqrt{n} = 2 \times \sqrt{n}$$



Data structure with a Square Root Relation

Something like this



Now

For a three layer link list data structure

We get a search cost of $3 \times \sqrt[3]{n}$

In general for k layers, we have

$$k \times \sqrt[k]{n}$$

Thus, if we make $k = \log_2 n$ we get

$$\begin{aligned}\text{Search Cost} &= \log_2 n \times \sqrt[\log_2 n]{n} \\ &= \log_2 n \times (n)^{1/\log_2 n} \\ &= \log_2 n \times (n)^{\log_n 2} \\ &= \log_2 n \times 2 \\ &= \Theta(\log_2 n)\end{aligned}$$

Now

For a three layer link list data structure

We get a search cost of $3 \times \sqrt[3]{n}$

In general for k layers, we have

$$k \times \sqrt[k]{n}$$

Thus, if we make $k = \log_2 n$ we get

$$\begin{aligned}\text{Search Cost} &= \log_2 n \times \sqrt[\log_2 n]{n} \\ &= \log_2 n \times (n)^{1/\log_2 n} \\ &= \log_2 n \times (n)^{\log_n 2} \\ &= \log_2 n \times 2 \\ &= \Theta(\log_2 n)\end{aligned}$$

Now

For a three layer link list data structure

We get a search cost of $3 \times \sqrt[3]{n}$

In general for k layers, we have

$$k \times \sqrt[k]{n}$$

Thus, if we make $k = \log_2 n$, we get

$$\begin{aligned}\text{Search Cost} &= \log_2 n \times \sqrt[\log_2 n]{n} \\ &= \log_2 n \times (n)^{1/\log_2 n} \\ &= \log_2 n \times (n)^{\log_n 2} \\ &= \log_2 n \times 2 \\ &= \Theta(\log_2 n)\end{aligned}$$

Thus


Something Notable

We get the advantages of the binary search trees with a simpler architecture!!!



Thus


Binary Search Trees




New Architecture

Thus

Binary Search Trees



New Architecture



Now

We are ready to give a

Definition for Skip List



Outline

- 1 Dictionaries
 - Definitions
 - Dictionary operations
 - Dictionary implementation
- 2 Skip Lists
 - Why Skip Lists?
 - The Idea Behind All of It!!!
 - **Skip List Definition**
 - Skip list implementation
 - Insertion for Skip Lists
 - Deletion in Skip Lists
 - Properties
 - Search and Insertion Times
 - Applications
 - Summary



A Little Bit of History

Skip List

They were invented by William Worthington "Bill" Pugh Jr.!!!



A Little Bit of History

Skip List

They were invented by William Worthington "Bill" Pugh Jr.!!!

How is him?

- He is is an American computer scientist who invented the skip list and the Omega test for deciding Presburger arithmetic.
- He was the co-author of the static code analysis tool FindBugs.
- He was highly influential in the development of the current memory model of the Java language together with his PhD student Jeremy Manson.



A Little Bit of History

Skip List

They were invented by William Worthington "Bill" Pugh Jr.!!!

How is him?

- He is is an American computer scientist who invented the skip list and the Omega test for deciding Presburger arithmetic.
- He was the co-author of the static code analysis tool FindBugs.
- He was highly influential in the development of the current memory model of the Java language together with his PhD student Jeremy Manson.



A Little Bit of History

Skip List

They were invented by William Worthington "Bill" Pugh Jr.!!!

How is him?

- He is is an American computer scientist who invented the skip list and the Omega test for deciding Presburger arithmetic.
- He was the co-author of the static code analysis tool FindBugs.
- He was highly influential in the development of the current memory model of the Java language together with his PhD student Jeremy Manson.



Skip List Definition

Definition

A skip list for a set S of distinct (key,element) items is a series of lists S_0, S_1, \dots, S_h such that:

- Each list S_i contains the special keys $+\infty$ and $-\infty$
- List S_0 contains the keys of S in nondecreasing order
- Each list is a subsequence of the previous one
 - ▶ $S_0 \supseteq S_1 \supseteq S_2 \supseteq \dots \supseteq S_h$
- List S_h contains only the two special keys



Skip List Definition

Definition

A skip list for a set S of distinct (key,element) items is a series of lists S_0, S_1, \dots, S_h such that:

- Each list S_i contains the special keys $+\infty$ and $-\infty$
- List S_0 contains the keys of S in nondecreasing order
- Each list is a subsequence of the previous one
 - ▶ $S_0 \supseteq S_1 \supseteq S_2 \supseteq \dots \supseteq S_h$
- List S_h contains only the two special keys



Skip List Definition

Definition

A skip list for a set S of distinct (key,element) items is a series of lists S_0, S_1, \dots, S_h such that:

- Each list S_i contains the special keys $+\infty$ and $-\infty$
- List S_0 contains the keys of S in nondecreasing order
- Each list is a subsequence of the previous one
 - ▶ $S_0 \supseteq S_1 \supseteq S_2 \supseteq \dots \supseteq S_h$
- List S_h contains only the two special keys



Skip List Definition

Definition

A skip list for a set S of distinct (key,element) items is a series of lists S_0, S_1, \dots, S_h such that:

- Each list S_i contains the special keys $+\infty$ and $-\infty$
- List S_0 contains the keys of S in nondecreasing order
- Each list is a subsequence of the previous one

$$\rightarrow S_0 \supseteq S_1 \supseteq S_2 \supseteq \dots \supseteq S_h$$

- List S_h contains only the two special keys



Skip List Definition

Definition

A skip list for a set S of distinct (key,element) items is a series of lists S_0, S_1, \dots, S_h such that:

- Each list S_i contains the special keys $+\infty$ and $-\infty$
- List S_0 contains the keys of S in nondecreasing order
- Each list is a subsequence of the previous one
 - ▶ $S_0 \supseteq S_1 \supseteq S_2 \supseteq \dots \supseteq S_h$

• List S_h contains only the two special keys



Skip List Definition

Definition


A skip list for a set S of distinct (key,element) items is a series of lists S_0, S_1, \dots, S_h such that:

- Each list S_i contains the special keys $+\infty$ and $-\infty$
- List S_0 contains the keys of S in nondecreasing order
- Each list is a subsequence of the previous one
 - ▶ $S_0 \supseteq S_1 \supseteq S_2 \supseteq \dots \supseteq S_h$
- List S_h contains only the two special keys



Skip List Definition

Example



Skip list search

We search for a key x in a skip list as follows

- We start at the first position of the top list.
- At the current position p , we compare x with $y == p.next.key$
 - ▶ $x == y$: we return $p.next.element$
 - ▶ $x > y$: we scan forward
 - ▶ $x < y$: we “drop down”
- If we try to drop down past the bottom list, we return *null*.



Skip list search

We search for a key x in a skip list as follows

- We start at the first position of the top list.
- At the current position p , we compare x with $y == p.next.key$
 - ▶ $x == y$: we return $p.next.element$
 - ▶ $x > y$: we scan forward
 - ▶ $x < y$: we “drop down”
- If we try to drop down past the bottom list, we return *null*.



Skip list search

We search for a key x in a skip list as follows

- We start at the first position of the top list.
- At the current position p , we compare x with $y == p.next.key$
 - ▶ $x == y$: we return $p.next.element$
 - ▶ $x > y$: we scan forward
 - ▶ $x < y$: we “drop down”
- If we try to drop down past the bottom list, we return *null*.



Skip list search

We search for a key x in a skip list as follows

- We start at the first position of the top list.
- At the current position p , we compare x with $y == p.next.key$
 - ▶ $x == y$: we return $p.next.element$
 - ▶ $x > y$: we scan forward
 - ▶ $x < y$: we “drop down”
- If we try to drop down past the bottom list, we return *null*.



Skip list search

We search for a key x in a skip list as follows

- We start at the first position of the top list.
- At the current position p , we compare x with $y == p.next.key$
 - ▶ $x == y$: we return $p.next.element$
 - ▶ $x > y$: we scan forward
 - ▶ $x < y$: we “drop down”
- If we try to drop down past the bottom list, we return *null*.



Skip list search


We search for a key x in a skip list as follows

- We start at the first position of the top list.
- At the current position p , we compare x with $y == p.next.key$
 - ▶ $x == y$: we return $p.next.element$
 - ▶ $x > y$: we scan forward
 - ▶ $x < y$: we “drop down”
- If we try to drop down past the bottom list, we return *null*.




Example search for 78

$x < p.next.key$: "drop down"




Example search for 78

$x > p.next.key$: "scan forward"




Example search for 78

$x < p.next.key$: "drop down"




Example search for 78

$x > p.next.key$: "scan forward"




Example search for 78

$x > p.next.key$: "scan forward"




Example search for 78

$x < p.next.key$: "drop down"



Example search for 78

$x == y$: we return $p.next.element$



Outline

- 1 Dictionaries
 - Definitions
 - Dictionary operations
 - Dictionary implementation
- 2 Skip Lists
 - Why Skip Lists?
 - The Idea Behind All of It!!!
 - Skip List Definition
 - **Skip list implementation**
 - Insertion for Skip Lists
 - Deletion in Skip Lists
 - Properties
 - Search and Insertion Times
 - Applications
 - Summary



How do we implement this data structure?

We can implement a skip list with quad-nodes

A quad-node stores:

- Entry Value
- Link to the previous node
- Link to the next node
- Link to the above node
- Link to the below node

Also we define special keys PLUS_INF and MINUS_INF, and we modify the key comparator to handle them.



How do we implement this data structure?

We can implement a skip list with quad-nodes

A quad-node stores:

- Entry Value
- Link to the previous node
- Link to the next node
- Link to the above node
- Link to the below node

Also we define special keys PLUS_INF and MINUS_INF, and we modify the key comparator to handle them.



How do we implement this data structure?

We can implement a skip list with quad-nodes

A quad-node stores:

- Entry Value
- Link to the previous node
- Link to the next node
- Link to the above node
- Link to the below node

Also we define special keys PLUS_INF and MINUS_INF, and we modify the key comparator to handle them.



How do we implement this data structure?

We can implement a skip list with quad-nodes

A quad-node stores:

- Entry Value
- Link to the previous node
- Link to the next node
- Link to the above node
- Link to the below node

Also we define special keys PLUS_INF and MINUS_INF, and we modify the key comparator to handle them.



How do we implement this data structure?

We can implement a skip list with quad-nodes

A quad-node stores:

- Entry Value
- Link to the previous node
- Link to the next node
- Link to the above node
- Link to the below node

Also we define special keys PLUS_INF and MINUS_INF, and we modify the key comparator to handle them.



How do we implement this data structure?

We can implement a skip list with quad-nodes

A quad-node stores:

- Entry Value
- Link to the previous node
- Link to the next node
- Link to the above node
- Link to the below node

Also we define special keys PLUS_INF and MINUS_INF, and we modify the key comparator to handle them.



How do we implement this data structure?

We can implement a skip list with quad-nodes

A quad-node stores:


- Entry Value
- Link to the previous node
- Link to the next node
- Link to the above node
- Link to the below node

Also we define special keys PLUS_INF and MINUS_INF, and we modify the key comparator to handle them.



Example

Quad-Node Example



Skip lists uses Randomization

Use of randomization

We use a randomized algorithm to insert items into a skip list.

Running time

We analyze the expected running time of a randomized algorithm under the following assumptions:

- The coins are unbiased.
- The coin tosses are independent.

Skip lists uses Randomization

Use of randomization

We use a randomized algorithm to insert items into a skip list.

Running time

We analyze the expected running time of a randomized algorithm under the following assumptions:

- The coins are unbiased.
- The coin tosses are independent.

Worst case running time

The worst case running time of a randomized algorithm is often large but has very low probability.

- e.g. It occurs when all the coin tosses give "heads."

Skip lists uses Randomization

Use of randomization

We use a randomized algorithm to insert items into a skip list.

Running time

We analyze the expected running time of a randomized algorithm under the following assumptions:

- The coins are unbiased.
- The coin tosses are independent.

Worst case running time

The worst case running time of a randomized algorithm is often large but has very low probability.

- e.g. It occurs when all the coin tosses give "heads."

Skip lists uses Randomization

Use of randomization

We use a randomized algorithm to insert items into a skip list.

Running time

We analyze the expected running time of a randomized algorithm under the following assumptions:

- The coins are unbiased.
- The coin tosses are independent.

Worst case running time

The worst case running time of a randomized algorithm is often large but has very low probability.

- e.g. It occurs when all the coin tosses give "heads."

Skip lists uses Randomization

Use of randomization

We use a randomized algorithm to insert items into a skip list.

Running time

We analyze the expected running time of a randomized algorithm under the following assumptions:

- The coins are unbiased.
- The coin tosses are independent.

Worst case running time

The worst case running time of a randomized algorithm is often large but has very low probability.

• e.g. It occurs when all the coin tosses give "heads."

Skip lists uses Randomization

Use of randomization

We use a randomized algorithm to insert items into a skip list.

Running time

We analyze the expected running time of a randomized algorithm under the following assumptions:

- The coins are unbiased.
- The coin tosses are independent.

Worst case running time

The worst case running time of a randomized algorithm is often large but has very low probability.

- e.g. It occurs when all the coin tosses give “**heads.**”

Outline

- 1 Dictionaries
 - Definitions
 - Dictionary operations
 - Dictionary implementation
- 2 Skip Lists
 - Why Skip Lists?
 - The Idea Behind All of It!!!
 - Skip List Definition
 - Skip list implementation
 - **Insertion for Skip Lists**
 - Deletion in Skip Lists
 - Properties
 - Search and Insertion Times
 - Applications
 - Summary



To insert

To insert an entry $(key, object)$ into a skip list, we use a randomized algorithm:

- We repeatedly toss a coin until we get tails:
 - ▶ We denote with i the number of times the coin came up heads.
- If $i \geq h$, we add to the skip list new lists S_{h+1}, \dots, S_{i+1} :
 - ▶ Each containing only the two special keys.
- We search for x in the skip list and find the positions p_0, p_1, \dots, p_i of the items with largest key less than x in each lists S_0, S_1, \dots, S_i .
- For $j \leftarrow 0, \dots, i$, we insert item $(key, object)$ into list S_j after position p_j .



Insertion

To insert

To insert an entry $(key, object)$ into a skip list, we use a randomized algorithm:

- We repeatedly toss a coin until we get tails:
 - ▶ We denote with i the number of times the coin came up heads.
- If $i \geq h$, we add to the skip list new lists S_{h+1}, \dots, S_{i+1} :
 - ▶ Each containing only the two special keys.
- We search for x in the skip list and find the positions p_0, p_1, \dots, p_i of the items with largest key less than x in each lists S_0, S_1, \dots, S_i .
- For $j \leftarrow 0, \dots, i$, we insert item $(key, object)$ into list S_j after position p_j .



Insertion

To insert

To insert an entry $(key, object)$ into a skip list, we use a randomized algorithm:

- We repeatedly toss a coin until we get tails:
 - ▶ We denote with i the number of times the coin came up heads.
- If $i \geq h$, we add to the skip list new lists S_{h+1}, \dots, S_{i+1} :
 - ▶ Each containing only the two special keys.
- We search for x in the skip list and find the positions p_0, p_1, \dots, p_i of the items with largest key less than x in each lists S_0, S_1, \dots, S_i .
- For $j \leftarrow 0, \dots, i$, we insert item $(key, object)$ into list S_j after position p_j .



Insertion

To insert

To insert an entry $(key, object)$ into a skip list, we use a randomized algorithm:

- We repeatedly toss a coin until we get tails:
 - ▶ We denote with i the number of times the coin came up heads.
- If $i \geq h$, we add to the skip list new lists S_{h+1}, \dots, S_{i+1} :
 - ▶ Each containing only the two special keys.
- We search for x in the skip list and find the positions p_0, p_1, \dots, p_i of the items with largest key less than x in each lists S_0, S_1, \dots, S_i .
- For $j \leftarrow 0, \dots, i$, we insert item $(key, object)$ into list S_j after position p_j .



Insertion

To insert

To insert an entry $(key, object)$ into a skip list, we use a randomized algorithm:

- We repeatedly toss a coin until we get tails:
 - ▶ We denote with i the number of times the coin came up heads.
- If $i \geq h$, we add to the skip list new lists S_{h+1}, \dots, S_{i+1} :
 - ▶ Each containing only the two special keys.
- We search for x in the skip list and find the positions p_0, p_1, \dots, p_i of the items with largest key less than x in each lists S_0, S_1, \dots, S_i .
- For $j \leftarrow 0, \dots, i$, we insert item $(key, object)$ into list S_j after position p_j .



Insertion

To insert

To insert an entry $(key, object)$ into a skip list, we use a randomized algorithm:

- We repeatedly toss a coin until we get tails:
 - ▶ We denote with i the number of times the coin came up heads.
- If $i \geq h$, we add to the skip list new lists S_{h+1}, \dots, S_{i+1} :
 - ▶ Each containing only the two special keys.
- We search for x in the skip list and find the positions p_0, p_1, \dots, p_i of the items with largest key less than x in each lists S_0, S_1, \dots, S_i .
 - For $j \leftarrow 0, \dots, i$, we insert item $(key, object)$ into list S_j after position p_j .



Insertion

To insert

To insert an entry $(key, object)$ into a skip list, we use a randomized algorithm:

- We repeatedly toss a coin until we get tails:
 - ▶ We denote with i the number of times the coin came up heads.
- If $i \geq h$, we add to the skip list new lists S_{h+1}, \dots, S_{i+1} :
 - ▶ Each containing only the two special keys.
- We search for x in the skip list and find the positions p_0, p_1, \dots, p_i of the items with largest key less than x in each lists S_0, S_1, \dots, S_i .
- For $j \leftarrow 0, \dots, i$, we insert item $(key, object)$ into list S_j after position p_j .



Insertion

To insert


To insert an entry $(key, object)$ into a skip list, we use a randomized algorithm:

- We repeatedly toss a coin until we get tails:
 - ▶ We denote with i the number of times the coin came up heads.
- If $i \geq h$, we add to the skip list new lists S_{h+1}, \dots, S_{i+1} :
 - ▶ Each containing only the two special keys.
- We search for x in the skip list and find the positions p_0, p_1, \dots, p_i of the items with largest key less than x in each lists S_0, S_1, \dots, S_i .
- For $j \leftarrow 0, \dots, i$, we insert item $(key, object)$ into list S_j after position p_j .




Example: Insertion of 15 in the skip list

First, we use $i = 2$ to insert S_3 into the skip list




Example: Insertion of 15 in the skip list

Clearly, you first search for the predecessor key!!!




Example: Insertion of 15 in the skip list

Insert the necessary Quad-Nodes and necessary information




Example: Insertion of 15 in the skip list

Insert the necessary Quad-Nodes and necessary information




Example: Insertion of 15 in the skip list

Insert the necessary Quad-Nodes and necessary information



Example: Insertion of 15 in the skip list

Finally!!!



Outline

- 1 Dictionaries
 - Definitions
 - Dictionary operations
 - Dictionary implementation
- 2 Skip Lists
 - Why Skip Lists?
 - The Idea Behind All of It!!!
 - Skip List Definition
 - Skip list implementation
 - Insertion for Skip Lists
 - **Deletion in Skip Lists**
 - Properties
 - Search and Insertion Times
 - Applications
 - Summary



Deletion

To remove an entry with key x from a skip list, we proceed as follows

- We search for x in the skip list and find the positions p_0, p_1, \dots, p_i of the items with key x , where position p_j is in list S_j .
- We remove positions p_0, p_1, \dots, p_i from the lists S_0, S_1, \dots, S_i .
- We remove all but one list containing only the two special keys



Deletion

To remove an entry with key x from a skip list, we proceed as follows

- We search for x in the skip list and find the positions p_0, p_1, \dots, p_i of the items with key x , where position p_j is in list S_j .
- We remove positions p_0, p_1, \dots, p_i from the lists S_0, S_1, \dots, S_i .

• We remove all but one list containing only the two special keys



Deletion


To remove an entry with key x from a skip list, we proceed as follows

- We search for x in the skip list and find the positions p_0, p_1, \dots, p_i of the items with key x , where position p_j is in list S_j .
- We remove positions p_0, p_1, \dots, p_i from the lists S_0, S_1, \dots, S_i .
- We remove all but one list containing only the two special keys




Example: Delete of 34 in the skip list

We search for 34 in the skip list and find the positions p_0, p_1, \dots, p_2 of the items with key 34




Example: Delete of 34 in the skip list

We search for 34 in the skip list and find the positions p_0, p_1, \dots, p_2 of the items with key 34




Example: Delete of 34 in the skip list

We start doing the deletion!!!




Example: Delete of 34 in the skip list

One Quad-Node after another




Example: Delete of 34 in the skip list

One Quad-Node after another




Example: Delete of 34 in the skip list

One Quad-Node after another



Example: Delete of 34 in the skip list

Remove One Level



Outline

- 1 Dictionaries
 - Definitions
 - Dictionary operations
 - Dictionary implementation
- 2 Skip Lists
 - Why Skip Lists?
 - The Idea Behind All of It!!!
 - Skip List Definition
 - Skip list implementation
 - Insertion for Skip Lists
 - Deletion in Skip Lists
 - **Properties**
 - Search and Insertion Times
 - Applications
 - Summary



Space usage

Space usage

The space used by a skip list depends on the random bits used by each invocation of the insertion algorithm.



Space : $O(n)$

Theorem

The expected space usage of a skip list with n items is $O(n)$.

Space : $O(n)$

Theorem

The expected space usage of a skip list with n items is $O(n)$.

Proof

We use the following two basic probabilistic facts:

- Fact 1: The probability of getting i consecutive heads when flipping a coin is $\frac{1}{2^i}$.
- Fact 2: If each of n entries is present in a set with probability p , the expected size of the set is np .
- How? Remember $X = X_1 + X_2 + \dots + X_n$ where X_i is an indicator function for event $A_i =$ the i element is present in the set. Thus:

$$E[X] = \underbrace{\sum_{i=1}^n E[X_i]}_{\text{Equivalence } E[X_i] \text{ and } Pr\{A_i\}} = \sum_{i=1}^n Pr\{A_i\} = \sum_{i=1}^n p = np$$

Equivalence $E[X_i]$ and $Pr\{A_i\}$

Space : $O(n)$

Theorem

The expected space usage of a skip list with n items is $O(n)$.

Proof

We use the following two basic probabilistic facts:

① *Fact 1:* The probability of getting i consecutive heads when flipping a coin is $\frac{1}{2^i}$.

② *Fact 2:* If each of n entries is present in a set with probability p , the expected size of the set is np .

③ How? Remember $X = X_1 + X_2 + \dots + X_n$ where X_i is an indicator function for event $A_i =$ the i element is present in the set. Thus:

$$E[X] = \underbrace{\sum_{i=1}^n E[X_i]}_{\text{Equivalence } E[X_i] \text{ and } Pr\{A_i\}} = \sum_{i=1}^n Pr\{A_i\} = \sum_{i=1}^n p = np$$

Equivalence $E[X_i]$ and $Pr\{A_i\}$

Space : $O(n)$

Theorem

The expected space usage of a skip list with n items is $O(n)$.

Proof

We use the following two basic probabilistic facts:

- ① *Fact 1:* The probability of getting i consecutive heads when flipping a coin is $\frac{1}{2^i}$.
- ② *Fact 2:* If each of n entries is present in a set with probability p , the expected size of the set is np .

⊙ How? Remember $X = X_1 + X_2 + \dots + X_n$ where X_i is an indicator function for event $A_i =$ the i element is present in the set. Thus:

$$E[X] = \underbrace{\sum_{i=1}^n E[X_i]}_{\text{Equivalence } E[X_i] \text{ and } Pr\{A_i\}} = \sum_{i=1}^n Pr\{A_i\} = \sum_{i=1}^n p = np$$

Equivalence $E[X_i]$ and $Pr\{A_i\}$

Space : $O(n)$

Theorem

The expected space usage of a skip list with n items is $O(n)$.

Proof

We use the following two basic probabilistic facts:

- ① *Fact 1:* The probability of getting i consecutive heads when flipping a coin is $\frac{1}{2^i}$.
- ② *Fact 2:* If each of n entries is present in a set with probability p , the expected size of the set is np .
 - ① How? Remember $X = X_1 + X_2 + \dots + X_n$ where X_i is an indicator function for event $A_i =$ the i element is present in the set. Thus:

$$E[X] = \underbrace{\sum_{i=1}^n E[X_i]}_{\text{Equivalence } E[X_i] \text{ and } Pr(A_i)} = \sum_{i=1}^n Pr\{A_i\} = \sum_{i=1}^n p = np$$

Space : $O(n)$

Theorem

The expected space usage of a skip list with n items is $O(n)$.

Proof

We use the following two basic probabilistic facts:

- ① *Fact 1:* The probability of getting i consecutive heads when flipping a coin is $\frac{1}{2^i}$.
- ② *Fact 2:* If each of n entries is present in a set with probability p , the expected size of the set is np .
 - ① How? Remember $X = X_1 + X_2 + \dots + X_n$ where X_i is an indicator function for event $A_i =$ the i element is present in the set. Thus:

$$E[X] = \underbrace{\sum_{i=1}^n E[X_i]}_{\text{Equivalence } E[X_A] \text{ and } Pr\{A\}} = \sum_{i=1}^n Pr\{A_i\} = \sum_{i=1}^n p = np$$

Equivalence $E[X_A]$ and $Pr\{A\}$

Proof

Now consider a skip list with n entries

Using Fact 1, an element is inserted in list S_i with a probability of

$$\frac{1}{2^i}$$

Now by Fact 2

The expected size of list S_i is

$$\frac{n}{2^i}$$



Proof

Now consider a skip list with n entries

Using Fact 1, an element is inserted in list S_i with a probability of

$$\frac{1}{2^i}$$

Now by Fact 2

The expected size of list S_i is

$$\frac{n}{2^i}$$



Proof

The expected number of nodes used by the skip list with height h

$$\sum_{i=0}^h \frac{n}{2^i} = n \sum_{i=0}^h \frac{1}{2^i}$$

Here, we have a problem!!! What is the value of h ?



Height h

First

The running time of the search and insertion algorithms is affected by the height h of the skip list.

Second

We show that with high probability, a skip list with n items has height $O(\log n)$.



Height h

First

The running time of the search and insertion algorithms is affected by the height h of the skip list.

Second

We show that with high probability, a skip list with n items has height $O(\log n)$.



For this, we have the following fact!!!

We use the following Fact 3

We can view the level $l(x_i) = \max \{j \mid \text{where } x_i \in S_j\}$ of the elements in the skip list as the following random variable

$$X_i = l(x_i)$$

for each element x_i in the skip list.



For this, we have the following fact!!!

We use the following Fact 3

We can view the level $l(x_i) = \max \{j | \text{where } x_i \in S_j\}$ of the elements in the skip list as the following random variable

$$X_i = l(x_i)$$

for each element x_i in the skip list.

And this is a random variable!!!

- Remember the insertions!!! Using an unbiased coin!!
- Thus, all X_i have a geometric distribution.



For this, we have the following fact!!!

We use the following Fact 3

We can view the level $l(x_i) = \max \{j | \text{where } x_i \in S_j\}$ of the elements in the skip list as the following random variable

$$X_i = l(x_i)$$

for each element x_i in the skip list.


And this is a random variable!!!

- Remember the insertions!!! Using an unbiased coin!!
- Thus, all X_i have a geometric distribution.



Example for $l(x_i)$

We have



BTW What is the geometric distribution?

k failures where

$$k = \{1, 2, 3, \dots\}$$

Probability mass function

$$Pr(X = k) = (1 - p)^{k-1} p$$



BTW What is the geometric distribution?

k failures where

$$k = \{1, 2, 3, \dots\}$$


Probability mass function

$$Pr(X = k) = (1 - p)^{k-1} p$$



Probability Mass Function

For Different Probabilities



Then

We have the following inequality for the geometric variables

$$\Pr [X_i > t] \leq (1 - p)^t \quad \forall i = 1, 2, \dots, n$$

Because if the cdf $F(t) = P(X \leq t) = 1 - (1 - p)^{t+1}$

Then we have

$$\Pr \left\{ \max_i X_i > t \right\} \leq n(1 - p)^t$$

This comes from $F_{\max_i X_i}(t) = (F(t))^n$



Then

We have the following inequality for the geometric variables

$$Pr [X_i > t] \leq (1 - p)^t \quad \forall i = 1, 2, \dots, n$$

Because if the cdf $F(t) = P(X \leq t) = 1 - (1 - p)^{t+1}$

Then, we have

$$Pr \left\{ \max_i X_i > t \right\} \leq n(1 - p)^t$$

This comes from $F_{\max_i X_i}(t) = (F(t))^n$



How?

We have that

$$\begin{aligned} Pr \left\{ \max_i X_i > t \right\} &= Pr \{ \max \{X_1, X_2, \dots, X_n\} > t \} \\ &= \sum_{i=1}^n Pr \{ X_i > t \text{ and } X_i = \max \{X_1, X_2, \dots, X_n\} \} \end{aligned}$$

Now, if we assume only two variables

$$\{ \max (X_1, X_2) > t \} = \{ X_1 > t \text{ and } X_1 > X_2 \text{ or exclusive } X_2 > t \text{ and } X_2 > X_1 \}$$

- Yes, you need to remember that the max is a single element not both...



How?

We have that

$$\begin{aligned} Pr \left\{ \max_i X_i > t \right\} &= Pr \{ \max \{X_1, X_2, \dots, X_n\} > t \} \\ &= \sum_{i=1}^n Pr \{ X_i > t \text{ and } X_i = \max \{X_1, X_2, \dots, X_n\} \} \end{aligned}$$

Now, if we assume only two variables

$$\{ \max (X_1, X_2) > t \} = \{ X_1 > t \text{ and } X_1 > X_2 \text{ or exclusive } X_2 > t \text{ and } X_2 > X_1 \}$$

- Yes, you need to remember that the max is a single element not both...



Therefore

Then

$$\begin{aligned} Pr \{X_1 > t \text{ and } X_1 > X_2 \text{ or exclusive } X_2 > t\} &= Pr \{X_1 > t \text{ and } X_1 > X_2\} + \dots \\ &\quad Pr \{X_2 > t \text{ and } X_2 > X_1\} \end{aligned}$$

Assuming exclusivity between phenomena X_1 , X_2 and X_3

$$\begin{aligned} Pr \{X_1 > t \text{ and } X_1 > X_2 \text{ or exclusive } X_2 > t\} &= P(X_1 > t) P(X_1 > X_2) + \dots \\ &\quad P(X_2 > t) P(X_2 > X_1) \\ &\leq P(X_1 > t) + P(X_2 > t) \end{aligned}$$



Therefore

Then

$$\begin{aligned} Pr \{X_1 > t \text{ and } X_1 > X_2 \text{ or exclusive } X_2 > t\} = & Pr \{X_1 > t \text{ and } X_1 > X_2\} + \dots \\ & Pr \{X_2 > t \text{ and } X_2 > X_1\} \end{aligned}$$

Assuming exclusivity between phenomena $X_i > X_j$ and $X_1 > t$

$$\begin{aligned} Pr \{X_1 > t \text{ and } X_1 > X_2 \text{ or exclusive } X_2 > t\} = & P(X_1 > t) P(X_1 > X_2) + \dots \\ & P(X_2 > t) P(X_2 > X_1) \\ \leq & P(X_1 > t) + P(X_2 > t) \end{aligned}$$



Finally

We have by $Pr \{X_i > t \text{ and } X_i = \max \{X_i\}_{i=1}^n\} \leq Pr \{X_i > t\}$



$$\sum_{i=1}^n Pr \{X_i > t\} \leq \sum_{i=1}^n (1-p)^t = n (1-p)^t$$



Observations

The $\max_i X_i$

It represents the list with the one entry apart from the special keys.



Observations

REMEMBER!!!

We are talking about a fair coin, thus $p = \frac{1}{2}$.



Height: $3 \log_2 n$ with probability at least $1 - \frac{1}{n^2}$

Theorem

A skip list with n entries has height at most $3 \log_2 n$ with probability at least $1 - \frac{1}{n^2}$



Proof

Consider a skip list with n entries

By Fact 3, the probability that list S_t has at least one item (The $\max_i X_i > t$) is at most $\frac{n}{2^t}$.

$$P(|S_t| \geq 1) = P\left(\max_i X_i > t\right) \leq \frac{n}{2^t}.$$

By picking $t = \log_2 n$

We have that the probability that $S_{\log_2 n}$ has at least one entry is at most:

$$\frac{n}{2^{\log_2 n}} = \frac{n}{n} = 1.$$



Proof

Consider a skip list with n entries

By Fact 3, the probability that list S_t has at least one item (The $\max_i X_i > t$) is at most $\frac{n}{2^t}$.

$$P(|S_t| \geq 1) = P\left(\max_i X_i > t\right) \leq \frac{n}{2^t}.$$

By picking $t = 3 \log n$

We have that the probability that $S_{3 \log_2 n}$ has at least one entry is at most:

$$\frac{n}{2^{3 \log_2 n}} = \frac{n}{n^3} = \frac{1}{n^2}.$$



Look at we want to model

We want to model

- The height of the Skip List is at most $t = 3 \log_2 n$
- Equivalent to the negation of having list $S_{3 \log_2 n}$



Look at we want to model

We want to model

- The height of the Skip List is at most $t = 3 \log_2 n$
- Equivalent to the negation of having list $S_{3 \log_2 n}$

Then, the probability that the height $h = 3 \log_2 n$ of the skip list is

$$P(\text{Skip List height } 3 \log_2 n) = 1 - \frac{1}{n^2}$$



Look at we want to model

We want to model

- The height of the Skip List is at most $t = 3 \log_2 n$
- Equivalent to the negation of having list $S_{3 \log_2 n}$

Then, the probability that the height $h = 3 \log_2 n$ of the skip list is

$$P(\text{Skip List height } 3 \log_2 n) = 1 - \frac{1}{n^2}$$



Finally

The expected number of nodes used by the skip list with height h

- Given that $h = 3 \log_2 n$

$$\sum_{i=0}^{3 \log_2 n} \frac{n}{2^i} = n \sum_{i=0}^{3 \log_2 n} \frac{1}{2^i}$$

Given the geometric sum

$$S_m = \sum_{k=0}^m r^k = \frac{1 - r^{m+1}}{1 - r}$$



Finally

The expected number of nodes used by the skip list with height h

- Given that $h = 3 \log_2 n$

$$\sum_{i=0}^{3 \log_2 n} \frac{n}{2^i} = n \sum_{i=0}^{3 \log_2 n} \frac{1}{2^i}$$

Given the geometric sum

$$S_m = \sum_{k=0}^m r^k = \frac{1 - r^{m+1}}{1 - r}$$



We have finally

The Upper Bound on the number of nodes

$$\begin{aligned} n \sum_{i=0}^{3 \log_2 n} \frac{1}{2^i} &= n \left(\frac{1 - \left(\frac{1}{2}\right)^{3 \log_2 n + 1}}{1 - 1/2} \right) \\ &= n \left(\frac{1 - \frac{1}{2^{3 \log_2 n + 1}}}{1/2} \right) \\ &= n \left(\frac{1 - \frac{1}{(2^{\log_2 n})^3 2}}{1/2} \right) \\ &= n \left(\frac{1 - \frac{1}{2n^3}}{1/2} \right) = n \left(\frac{2 [2n^3 - 1]}{2n^3} \right) \end{aligned}$$

We have finally

The Upper Bound on the number of nodes

$$\begin{aligned}n \sum_{i=0}^{3 \log_2 n} \frac{1}{2^i} &= n \left(\frac{1 - \left(\frac{1}{2}\right)^{3 \log_2 n + 1}}{1 - 1/2} \right) \\&= n \left(\frac{1 - \frac{1}{2^{3 \log_2 n + 1}}}{1/2} \right) \\&= n \left(\frac{1 - \frac{1}{(2^{\log_2 n})^3 2}}{1/2} \right) \\&= n \left(\frac{1 - \frac{1}{2n^3}}{1/2} \right) = n \left(\frac{2 [2n^3 - 1]}{2n^3} \right)\end{aligned}$$

We have finally

The Upper Bound on the number of nodes

$$\begin{aligned}n \sum_{i=0}^{3 \log_2 n} \frac{1}{2^i} &= n \left(\frac{1 - \left(\frac{1}{2}\right)^{3 \log_2 n + 1}}{1 - 1/2} \right) \\&= n \left(\frac{1 - \frac{1}{2^{3 \log_2 n + 1}}}{1/2} \right) \\&= n \left(\frac{1 - \frac{1}{(2^{\log_2 n})^3 2}}{1/2} \right) \\&= n \left(\frac{1 - \frac{1}{2n^3}}{1/2} \right) = n \left(\frac{2 [2n^3 - 1]}{2n^3} \right)\end{aligned}$$

We have finally

The Upper Bound on the number of nodes

$$\begin{aligned} n \sum_{i=0}^{3 \log_2 n} \frac{1}{2^i} &= n \left(\frac{1 - \left(\frac{1}{2}\right)^{3 \log_2 n + 1}}{1 - 1/2} \right) \\ &= n \left(\frac{1 - \frac{1}{2^{3 \log_2 n + 1}}}{1/2} \right) \\ &= n \left(\frac{1 - \frac{1}{(2^{\log_2 n})^3 2}}{1/2} \right) \\ &= n \left(\frac{1 - \frac{1}{2n^3}}{1/2} \right) = n \left(\frac{2[2n^3 - 1]}{2n^3} \right) \end{aligned}$$

Finally

We have

$$\left(\frac{2n^3 - 1}{n^2} \right) = 2n - \frac{1}{n^2} \leq 2n$$

The Upper Bound with probability 1 –

$$2n - \frac{1}{n^2} \leq 2n = O(n)$$



Finally

We have

$$\left(\frac{2n^3 - 1}{n^2} \right) = 2n - \frac{1}{n^2} \leq 2n$$

The Upper Bound with probability $1 - \frac{1}{n^2}$

$$2n - \frac{1}{n^2} \leq 2n = O(n)$$



Outline

- 1 Dictionaries
 - Definitions
 - Dictionary operations
 - Dictionary implementation
- 2 Skip Lists
 - Why Skip Lists?
 - The Idea Behind All of It!!!
 - Skip List Definition
 - Skip list implementation
 - Insertion for Skip Lists
 - Deletion in Skip Lists
 - Properties
 - **Search and Insertion Times**
 - Applications
 - Summary



Search and Insertion Times

Fact 4

The expected number of coin tosses required in order to get tails is 2:

$$\text{Given } x \sim G\left(\frac{1}{2}\right) \implies E[x] = \frac{1}{\frac{1}{2}} = 2$$

We use this

To prove that a search in a skip list takes $O(\log n)$ expected time.

- After all insertions require searches!!!



Search and Insertion Times

Fact 4

The expected number of coin tosses required in order to get tails is 2:

$$\text{Given } x \sim G\left(\frac{1}{2}\right) \implies E[x] = \frac{1}{\frac{1}{2}} = 2$$

We use this

To prove that a search in a skip list takes $O(\log n)$ expected time.

- After all insertions require searches!!!



Search and Insertions times

Search time

The search time in skip list is proportional to

the number of drop-down steps + the number of scan-forward steps

Drop-down steps

The drop-down steps are bounded by the height of the skip list and thus are $O(\log_2 n)$ with high probability.

Theorem

A search in a skip list takes $O(\log_2 n)$ expected time.



Search and Insertions times

Search time

The search time in skip list is proportional to

the number of drop-down steps + the number of scan-forward steps

Drop-down steps

The drop-down steps are bounded by the height of the skip list and thus are $O(\log_2 n)$ with high probability.

Theorem

A search in a skip list takes $O(\log_2 n)$ expected time.



Search and Insertions times

Search time

The search time in skip list is proportional to

the number of drop-down steps + the number of scan-forward steps

Drop-down steps

The drop-down steps are bounded by the height of the skip list and thus are $O(\log_2 n)$ with high probability.

Theorem

A search in a skip list takes $O(\log_2 n)$ expected time.



Proof

First

When we scan forward in a list, the destination key does not belong to a higher list.

A scan-forward step is associated with a former coin toss that gave tails.

By Fact 4, in each list the expected number of scan-forward steps is 2.



Proof

First

When we scan forward in a list, the destination key does not belong to a higher list.

A scan-forward step is associated with a former coin toss that gave tails

By Fact 4, in each list the expected number of scan-forward steps is 2.



Why?

Given the list S_i

Then, the scan-forward intervals (Jumps between x_i and x_{i+1}) to the right of S_i are

$$I_1 = [x_1, x_2], I_2 = [x_2, x_3] \dots I_k = [x_k, +\infty]$$

Then

These interval exist at level i if and only if all x_1, x_2, \dots, x_k belong to S_i .



Why?

Given the list S_i

Then, the scan-forward intervals (Jumps between x_i and x_{i+1}) to the right of S_i are

$$I_1 = [x_1, x_2], I_2 = [x_2, x_3] \dots I_k = [x_k, +\infty]$$

Then


These interval exist at level i if and only if all x_1, x_2, \dots, x_k belong to S_i .



We introduce the following concept based on these intervals

Scan-forward siblings

These are element that you find in the search path before finding an element in the upper list.



Now

Given that a search is being done, S_i contains l forward siblings

It must be the case that given x_1, \dots, x_l scan-forward siblings, we have that

$$x_1, \dots, x_l \notin S_{i+1}$$

and $x_{l+1} \in S_{i+1}$



Thus

We have

Since each element of S_i is independently chosen to be in S_{i+1} with probability $p = \frac{1}{2}$.

We have

The number of scan-forward siblings is bounded by a geometric random variable X_i with parameter $p = \frac{1}{2}$.

- Imagine the fact that you have multiple fails... then $x_1, \dots, x_i \notin S_{i+1}$ is modeled by X_i

Thus, we have that

The expected number of scan-forward siblings is bounded by 2!!!

$$\text{Expected \# Scan-Fordward Siblings at } i \leq \underbrace{E[X_i]}_{\text{Mean}} = \frac{1}{1/2} = 2$$

Thus

We have

Since each element of S_i is independently chosen to be in S_{i+1} with probability $p = \frac{1}{2}$.

We have

The number of scan-forward siblings is bounded by a geometric random variable X_i with parameter $p = \frac{1}{2}$.

- Imagine the fact that you have multiple fails... then $x_1, \dots, x_l \notin S_{i+1}$ is modeled by X_i

Thus, we have that

The expected number of scan-forward siblings is bounded by 2!!!

$$\text{Expected \# Scan-Fordward Siblings at } i \leq \underbrace{E[X_i]}_{\text{Mean}} = \frac{1}{1/2} = 2$$

Thus

We have

Since each element of S_i is independently chosen to be in S_{i+1} with probability $p = \frac{1}{2}$.

We have

The number of scan-forward siblings is bounded by a geometric random variable X_i with parameter $p = \frac{1}{2}$.

- Imagine the fact that you have multiple fails... then $x_1, \dots, x_l \notin S_{i+1}$ is modeled by X_i

Thus, we have that

The expected number of scan-forward siblings is bounded by 2!!!

$$\text{Expected \# Scan-Fordward Siblings at } i \leq \underbrace{E[X_i]}_{\text{Mean}} = \frac{1}{1/2} = 2$$

Then

In the worst case scenario

A search is bounded by $O(\log_2 n) + 2\log_2 n = O(\log_2 n)$

And given that a insertion is a (search) + (deletion bounded by the height)

Thus, an insertion is bounded by $2\log_2 n + 3\log_2 n = O(\log_2 n)$



Then

In the worst case scenario

A search is bounded by $O(\log_2 n) + 2\log_2 n = O(\log_2 n)$

An given that a insertion is a **(search) + (deletion bounded by the height)**

Thus, an insertion is bounded by $2\log_2 n + 3\log_2 n = O(\log_2 n)$



Outline

- 1 Dictionaries
 - Definitions
 - Dictionary operations
 - Dictionary implementation
- 2 Skip Lists
 - Why Skip Lists?
 - The Idea Behind All of It!!!
 - Skip List Definition
 - Skip list implementation
 - Insertion for Skip Lists
 - Deletion in Skip Lists
 - Properties
 - Search and Insertion Times
 - **Applications**
 - Summary



Applications

We have

- Cyrus IMAP servers offer a "skiplist" backend Data Base implementation.
- Lucene uses skip lists to search delta-encoded posting lists in logarithmic time.
- Redis, an ANSI-C open-source persistent key/value store for Posix systems, uses skip lists in its implementation of ordered sets.
- leveldb, a fast key-value storage library written at Google that provides an ordered mapping from string keys to string values.
- Skip lists are used for efficient statistical computations of running medians.



Applications

We have

- Cyrus IMAP servers offer a "skiplist" backend Data Base implementation.
- Lucene uses skip lists to search delta-encoded posting lists in logarithmic time.
- Redis, an ANSI-C open-source persistent key/value store for Posix systems, uses skip lists in its implementation of ordered sets.
- leveldb, a fast key-value storage library written at Google that provides an ordered mapping from string keys to string values.
- Skip lists are used for efficient statistical computations of running medians.



Applications

We have

- Cyrus IMAP servers offer a "skiplist" backend Data Base implementation.
- Lucene uses skip lists to search delta-encoded posting lists in logarithmic time.
- Redis, an ANSI-C open-source persistent key/value store for Posix systems, uses skip lists in its implementation of ordered sets.
- leveldb, a fast key-value storage library written at Google that provides an ordered mapping from string keys to string values.
- Skip lists are used for efficient statistical computations of running medians.



Applications

We have

- Cyrus IMAP servers offer a "skiplist" backend Data Base implementation.
- Lucene uses skip lists to search delta-encoded posting lists in logarithmic time.
- Redis, an ANSI-C open-source persistent key/value store for Posix systems, uses skip lists in its implementation of ordered sets.
- leveldb, a fast key-value storage library written at Google that provides an ordered mapping from string keys to string values.
- Skip lists are used for efficient statistical computations of running medians.



Applications

We have

- Cyrus IMAP servers offer a "skiplist" backend Data Base implementation.
- Lucene uses skip lists to search delta-encoded posting lists in logarithmic time.
- Redis, an ANSI-C open-source persistent key/value store for Posix systems, uses skip lists in its implementation of ordered sets.
- leveldb, a fast key-value storage library written at Google that provides an ordered mapping from string keys to string values.
- Skip lists are used for efficient statistical computations of running medians.



Outline

- 1 Dictionaries
 - Definitions
 - Dictionary operations
 - Dictionary implementation
- 2 Skip Lists
 - Why Skip Lists?
 - The Idea Behind All of It!!!
 - Skip List Definition
 - Skip list implementation
 - Insertion for Skip Lists
 - Deletion in Skip Lists
 - Properties
 - Search and Insertion Times
 - Applications
 - **Summary**



Summary

Summary

- A skip list is a data structure for dictionaries that uses a randomized insertion algorithm.
- In a skip list with n entries:
 - ▶ The expected space used is $O(n)$
 - ▶ The expected search, insertion and deletion time is $O(\log n)$
- Skip list are fast and simple to implement in practice.



Summary

Summary

- A skip list is a data structure for dictionaries that uses a randomized insertion algorithm.
- In a skip list with n entries:
 - ▶ The expected space used is $O(n)$
 - ▶ The expected search, insertion and deletion time is $O(\log n)$
- Skip list are fast and simple to implement in practice.



Summary

Summary

- A skip list is a data structure for dictionaries that uses a randomized insertion algorithm.
- In a skip list with n entries:
 - ▶ The expected space used is $O(n)$
 - ▶ The expected search, insertion and deletion time is $O(\log n)$
- Skip list are fast and simple to implement in practice.



Summary

Summary

- A skip list is a data structure for dictionaries that uses a randomized insertion algorithm.
- In a skip list with n entries:
 - ▶ The expected space used is $O(n)$
 - ▶ The expected search, insertion and deletion time is $O(\log n)$
- Skip list are fast and simple to implement in practice.



Summary

Summary

- A skip list is a data structure for dictionaries that uses a randomized insertion algorithm.
- In a skip list with n entries:
 - ▶ The expected space used is $O(n)$
 - ▶ The expected search, insertion and deletion time is $O(\log n)$
- Skip list are fast and simple to implement in practice.



Summary

Summary

- A skip list is a data structure for dictionaries that uses a randomized insertion algorithm.
- In a skip list with n entries:
 - ▶ The expected space used is $O(n)$
 - ▶ The expected search, insertion and deletion time is $O(\log n)$
- Skip list are fast and simple to implement in practice.



Thanks

Questions?

