

# Analysis of Algorithms

## Skip Lists

Andres Mendez-Vazquez

October 23, 2020

# Outline

## 1 Dictionaries

- Definitions
- Dictionary operations
- Dictionary implementation

## 2 Skip Lists

- Why Skip Lists?
- The Idea Behind All of It!!!
- A Little of Optimization
- Skip List Definition
- Skip list implementation
- Insertion for Skip Lists
- Deletion in Skip Lists
- Properties
- The Height of the Skip List
- Search and Insertion Times
- Applications
- Summary



# Outline

## 1 Dictionaries

### • Definitions

- Dictionary operations
- Dictionary implementation

## 2 Skip Lists

- Why Skip Lists?
- The Idea Behind All of It!!!
- A Little of Optimization
- Skip List Definition
- Skip list implementation
- Insertion for Skip Lists
- Deletion in Skip Lists
- Properties
- The Height of the Skip List
- Search and Insertion Times
- Applications
- Summary



# Dictionaries

## Definition

A dictionary is a collection of elements; each of which has a unique search key.

- Uniqueness criteria may be relaxed (multi-set).
- Do not force uniqueness.

# Dictionaries

## Definition

A dictionary is a collection of elements; each of which has a unique search key.

- Uniqueness criteria may be relaxed (multi-set).

- Do not force uniqueness.

## Purpose

Dictionaries keep track of current members, with periodic insertions and deletions into the set (similar to a database).

# Dictionaries

## Definition

A dictionary is a collection of elements; each of which has a unique search key.

- Uniqueness criteria may be relaxed (multi-set).
- Do not force uniqueness.

## Purpose

Dictionaries keep track of current members, with periodic insertions and deletions into the set (similar to a database).

## Examples

- Membership in a club.
- Course records.
- Symbol table (with duplicates).
- Language dictionary (Webster, RAE, Oxford).

# Dictionaries

## Definition

A dictionary is a collection of elements; each of which has a unique search key.

- Uniqueness criteria may be relaxed (multi-set).
- Do not force uniqueness.

## Purpose

Dictionaries keep track of current members, with periodic insertions and deletions into the set (similar to a database).

## Examples

- Membership in a club.
- Course records.
- Symbol table (with duplicates).
- Language dictionary (Webster, RAE, Oxford).

# Dictionaries

## Definition

A dictionary is a collection of elements; each of which has a unique search key.

- Uniqueness criteria may be relaxed (multi-set).
- Do not force uniqueness.

## Purpose

Dictionaries keep track of current members, with periodic insertions and deletions into the set (similar to a database).

## Examples

- Membership in a club.
- Course records.
- Symbol table (with duplicates).
- Language dictionary (Webster, RAE, Oxford).



# Dictionaries

## Definition

A dictionary is a collection of elements; each of which has a unique search key.

- Uniqueness criteria may be relaxed (multi-set).
- Do not force uniqueness.

## Purpose

Dictionaries keep track of current members, with periodic insertions and deletions into the set (similar to a database).

## Examples

- Membership in a club.
- Course records.
- Symbol table (with duplicates).
- Language dictionary (Webster, RAE, Oxford).

# Dictionaries

## Definition

A dictionary is a collection of elements; each of which has a unique search key.

- Uniqueness criteria may be relaxed (multi-set).
- Do not force uniqueness.

## Purpose

Dictionaries keep track of current members, with periodic insertions and deletions into the set (similar to a database).

## Examples

- Membership in a club.
- Course records.
- Symbol table (with duplicates).
- Language dictionary (Webster, RAE, Oxford).

# Dictionaries

## Definition

A dictionary is a collection of elements; each of which has a unique search key.

- Uniqueness criteria may be relaxed (multi-set).
- Do not force uniqueness.

## Purpose

Dictionaries keep track of current members, with periodic insertions and deletions into the set (similar to a database).

## Examples

- Membership in a club.
- Course records.
- Symbol table (with duplicates).
- Language dictionary (Webster, RAE, Oxford).

## Example: Course records

### Dictionary with member records

key ID	Student Name	HW1	
123	Stan Smith	49	...
125	Sue Margolin	45	...
128	Billie King	24	...
⋮			
⋮			
190	Roy Miller	36	...



# Outline

## 1 Dictionaries

- Definitions
- **Dictionary operations**
- Dictionary implementation

## 2 Skip Lists

- Why Skip Lists?
- The Idea Behind All of It!!!
- A Little of Optimization
- Skip List Definition
- Skip list implementation
- Insertion for Skip Lists
- Deletion in Skip Lists
- Properties
- The Height of the Skip List
- Search and Insertion Times
- Applications
- Summary



# The dictionary ADT operations

## Some operations on dictionaries

- `size()`: Returns the size of the dictionary.
- `empty()`: Returns `TRUE` if the dictionary is empty.
- `findItem(key)`: Locates the item with the specified key.
- `findAllItems(key)`: Locates all items with the specified key.
- `removeItem(key)`: Removes the item with the specified key.
- `removeAllItems(key)`: Removes all items with the specified key.
- `insertItem(key,element)`: Inserts a new key-element pair.



# The dictionary ADT operations

## Some operations on dictionaries

- `size()`: Returns the size of the dictionary.
- `empty()`: Returns TRUE if the dictionary is empty.
- `findItem(key)`: Locates the item with the specified key.
- `findAllItems(key)`: Locates all items with the specified key.
- `removeItem(key)`: Removes the item with the specified key.
- `removeAllItems(key)`: Removes all items with the specified key.
- `insertItem(key,element)`: Inserts a new key-element pair.



# The dictionary ADT operations

## Some operations on dictionaries

- `size()`: Returns the size of the dictionary.
- `empty()`: Returns `TRUE` if the dictionary is empty.
- `findItem(key)`: Locates the item with the specified key.
- `findAllItems(key)`: Locates all items with the specified key.
- `removeItem(key)`: Removes the item with the specified key.
- `removeAllItems(key)`: Removes all items with the specified key.
- `insertItem(key,element)`: Inserts a new key-element pair.





# The dictionary ADT operations

## Some operations on dictionaries

- `size()`: Returns the size of the dictionary.
- `empty()`: Returns TRUE if the dictionary is empty.
- `findItem(key)`: Locates the item with the specified key.
- `findAllItems(key)`: Locates all items with the specified key.
- `removeItem(key)`: Removes the item with the specified key.
- `removeAllItems(key)`: Removes all items with the specified key.
- `insertItem(key,element)`: Inserts a new key-element pair.



# The dictionary ADT operations

## Some operations on dictionaries

- `size()`: Returns the size of the dictionary.
- `empty()`: Returns `TRUE` if the dictionary is empty.
- `findItem(key)`: Locates the item with the specified key.
- `findAllItems(key)`: Locates all items with the specified key.
- `removeItem(key)`: Removes the item with the specified key.
- `removeAllItems(key)`: Removes all items with the specified key.
- `insertItem(key,element)`: Inserts a new key-element pair.



# The dictionary ADT operations

## Some operations on dictionaries

- `size()`: Returns the size of the dictionary.
- `empty()`: Returns TRUE if the dictionary is empty.
- `findItem(key)`: Locates the item with the specified key.
- `findAllItems(key)`: Locates all items with the specified key.
- `removeItem(key)`: Removes the item with the specified key.
- `removeAllItems(key)`: Removes all items with the specified key.
- `insertItem(key,element)`: Inserts a new key-element pair.



# The dictionary ADT operations

## Some operations on dictionaries

- `size()`: Returns the size of the dictionary.
- `empty()`: Returns `TRUE` if the dictionary is empty.
- `findItem(key)`: Locates the item with the specified key.
- `findAllItems(key)`: Locates all items with the specified key.
- `removeItem(key)`: Removes the item with the specified key.
- `removeAllItems(key)`: Removes all items with the specified key.
- `insertItem(key,element)`: Inserts a new key-element pair.



# Example of unordered dictionary

## Example

Consider an empty unordered dictionary, we have then...

Operation	Dictionary	Output
InsertItem(5, A)	{(5, A)}	
InsertItem(7, B)	{(5, A), (7, B)}	
findItem(7)	{(5, A), (7, B)}	B
findItem(4)	{(5, A), (7, B)}	No Such Key
size()	{(5, A), (7, B)}	2
removeItem(5)	{(7, B)}	A
findItem(4)	{(7, B)}	No Such Key



# Outline

## 1 Dictionaries

- Definitions
- Dictionary operations
- **Dictionary implementation**

## 2 Skip Lists

- Why Skip Lists?
- The Idea Behind All of It!!!
- A Little of Optimization
- Skip List Definition
- Skip list implementation
- Insertion for Skip Lists
- Deletion in Skip Lists
- Properties
- The Height of the Skip List
- Search and Insertion Times
- Applications
- Summary



# How to implement a dictionary?

## There are many ways of implementing a dictionary

- Sequences / Arrays
  - ▶ Ordered
  - ▶ Unordered
- Binary search trees
- Skip lists
- Hash tables



# How to implement a dictionary?

## There are many ways of implementing a dictionary

- Sequences / Arrays
  - ▶ Ordered
  - ▶ Unordered
- Binary search trees
- Skip lists
- Hash tables





# How to implement a dictionary?

## There are many ways of implementing a dictionary

- Sequences / Arrays
  - ▶ Ordered
  - ▶ Unordered
- Binary search trees
- Skip lists

• Hash tables



# How to implement a dictionary?

## There are many ways of implementing a dictionary

- Sequences / Arrays
  - ▶ Ordered
  - ▶ Unordered
- Binary search trees
- Skip lists
- Hash tables



## Recall Arrays...

Unordered array

34	14	12	22	18
----	----	----	----	----



# Recall Arrays...

## Unordered array

34	14	12	22	18
----	----	----	----	----

## Complexity

- Searching and removing takes  $O(n)$ .
- Inserting takes  $O(1)$ .



# Recall Arrays...

## Unordered array

34	14	12	22	18
----	----	----	----	----

## Complexity

- Searching and removing takes  $O(n)$ .
- Inserting takes  $O(1)$ .

## Applications

This approach is good for log files where insertions are frequent but searches and removals are rare.



# Recall Arrays...

## Unordered array

34	14	12	22	18
----	----	----	----	----

## Complexity

- Searching and removing takes  $O(n)$ .
- Inserting takes  $O(1)$ .

## Applications

This approach is good for log files where insertions are frequent but searches and removals are rare.



# More Arrays

Ordered array

12	14	18	22	34
----	----	----	----	----



# More Arrays

## Ordered array

12	14	18	22	34
----	----	----	----	----

## Complexity

- Searching takes  $O(\log n)$  time (binary search).
- Insert and removing takes  $O(n)$  time.





# More Arrays

## Ordered array

12	14	18	22	34
----	----	----	----	----

## Complexity

- Searching takes  $O(\log n)$  time (binary search).
- Insert and removing takes  $O(n)$  time.

## Applications

This approach is good for look-up tables where searches are frequent but insertions and removals are rare.



# More Arrays

## Ordered array

12	14	18	22	34
----	----	----	----	----

## Complexity

- Searching takes  $O(\log n)$  time (binary search).
- Insert and removing takes  $O(n)$  time.

## Applications

This approach is good for look-up tables where searches are frequent but insertions and removals are rare.



# Binary searches

## Features

- Narrow down the search range in stages
- “High-low” game.



# Binary searches

## Example find Element(22)

2	4	5	7	8	9	12	14	17	19	22	25	27	28	33
---	---	---	---	---	---	----	----	----	----	----	----	----	----	----

↑  
*LOW*

↑  
*MID*

↑  
*HIGH*

2	4	5	7	8	9	12	14	17	19	22	25	27	28	33
---	---	---	---	---	---	----	----	----	----	----	----	----	----	----

↑  
*LOW*

↑  
*MID*

↑  
*HIGH*

2	4	5	7	8	9	12	14	17	19	22	25	27	28	33
---	---	---	---	---	---	----	----	----	----	----	----	----	----	----

↑  
*LOW*

↑  
*MID*

↑  
*HIGH*

2	4	5	7	8	9	12	14	17	19	22	25	27	28	33
---	---	---	---	---	---	----	----	----	----	----	----	----	----	----

↑  
*LOW=MID=HIGH*

# Binary searches

## Example find Element(22)

2	4	5	7	8	9	12	14	17	19	22	25	27	28	33
---	---	---	---	---	---	----	----	----	----	----	----	----	----	----

↑  
*LOW*

↑  
*MID*

↑  
*HIGH*

2	4	5	7	8	9	12	14	17	19	22	25	27	28	33
---	---	---	---	---	---	----	----	----	----	----	----	----	----	----

↑  
*LOW*

↑  
*MID*

↑  
*HIGH*

2	4	5	7	8	9	12	14	17	19	22	25	27	28	33
---	---	---	---	---	---	----	----	----	----	----	----	----	----	----

↑  
*LOW*

↑  
*MID*

↑  
*HIGH*

2	4	5	7	8	9	12	14	17	19	22	25	27	28	33
---	---	---	---	---	---	----	----	----	----	----	----	----	----	----

↑  
*LOW=MID=HIGH*

# Binary searches

## Example find Element(22)

2	4	5	7	8	9	12	14	17	19	22	25	27	28	33
---	---	---	---	---	---	----	----	----	----	----	----	----	----	----

↑  
*LOW*

↑  
*MID*

↑  
*HIGH*

2	4	5	7	8	9	12	14	17	19	22	25	27	28	33
---	---	---	---	---	---	----	----	----	----	----	----	----	----	----

↑  
*LOW*

↑  
*MID*

↑  
*HIGH*

2	4	5	7	8	9	12	14	17	19	22	25	27	28	33
---	---	---	---	---	---	----	----	----	----	----	----	----	----	----

↑  
*LOW*

↑  
*MID*

↑  
*HIGH*

2	4	5	7	8	9	12	14	17	19	22	25	27	28	33
---	---	---	---	---	---	----	----	----	----	----	----	----	----	----

↑  
*LOW=MID=HIGH*

# Binary searches

## Example find Element(22)

2	4	5	7	8	9	12	14	17	19	22	25	27	28	33
---	---	---	---	---	---	----	----	----	----	----	----	----	----	----

↑  
*LOW*

↑  
*MID*

↑  
*HIGH*

2	4	5	7	8	9	12	14	17	19	22	25	27	28	33
---	---	---	---	---	---	----	----	----	----	----	----	----	----	----

↑  
*LOW*

↑  
*MID*

↑  
*HIGH*

2	4	5	7	8	9	12	14	17	19	22	25	27	28	33
---	---	---	---	---	---	----	----	----	----	----	----	----	----	----

↑  
*LOW*

↑  
*MID*

↑  
*HIGH*

2	4	5	7	8	9	12	14	17	19	22	25	27	28	33
---	---	---	---	---	---	----	----	----	----	----	----	----	----	----

↑  
*LOW=MID=HIGH*

# Recall binary search trees

## Implement a dictionary with a BST

A binary search tree is a binary tree  $T$  such that:

- Each internal node stores an item  $(k, e)$  of a dictionary.
- Keys stored at nodes in the left subtree of  $v$  are less than or equal to  $k$ .
- Keys stored at nodes in the right subtree of  $v$  are greater than or equal to  $k$ .





# Recall binary search trees

## Implement a dictionary with a BST

A binary search tree is a binary tree  $T$  such that:

- Each internal node stores an item  $(k, e)$  of a dictionary.
- Keys stored at nodes in the left subtree of  $v$  are less than or equal to  $k$ .
- Keys stored at nodes in the right subtree of  $v$  are greater than or equal to  $k$ .



# Recall binary search trees

## Implement a dictionary with a BST

A binary search tree is a binary tree  $T$  such that:

- Each internal node stores an item  $(k, e)$  of a dictionary.
- Keys stored at nodes in the left subtree of  $v$  are less than or equal to  $k$ .
- Keys stored at nodes in the right subtree of  $v$  are greater than or equal to  $k$ .



# Recall binary search trees

## Implement a dictionary with a BST


A binary search tree is a binary tree  $T$  such that:

- Each internal node stores an item  $(k, e)$  of a dictionary.
- Keys stored at nodes in the left subtree of  $v$  are less than or equal to  $k$ .
- Keys stored at nodes in the right subtree of  $v$  are greater than or equal to  $k$ .



# Binary searches Trees

Problem!!! Keeping a Well Balanced Binary Search Tree can be difficult!!!



Not only that...

## Binary Search Trees

- They are not so well suited for parallel environments.
  - ▶ Unless a heavy modifications are done



Not only that...

## Binary Search Trees

- They are not so well suited for parallel environments.
  - ▶ Unless a heavy modifications are done

## In addition

We want to have a

- Compact Data Structure.
- Using as little memory as possible



Not only that...

## Binary Search Trees

- They are not so well suited for parallel environments.
  - ▶ Unless a heavy modifications are done

## In addition

We want to have a

- Compact Data Structure.
- Using as little memory as possible



Not only that...

## Binary Search Trees

- They are not so well suited for parallel environments.
  - ▶ Unless a heavy modifications are done

## In addition

We want to have a

- Compact Data Structure.
- Using as little memory as possible





Thus, we have the following possibilities

### Unordered array complexities

Insertion:  $O(1)$

Search:  $O(n)$

### Ordered array complexities

Insertion:  $O(n)$

Search:  $O(\log n)$

### Well balanced binary trees complexities

Insertion:  $O(\log n)$

Search:  $O(\log n)$

**Big Drawback - Complex parallel Implementation and waste of memory.**

Thus, we have the following possibilities

### Unordered array complexities

Insertion:  $O(1)$

Search:  $O(n)$

### Ordered array complexities

Insertion:  $O(n)$

Search:  $O(\log n)$

### Well balanced binary trees complexities

Insertion:  $O(\log n)$

Search:  $O(\log n)$

Big Drawback - Complex parallel Implementation and waste of memory.

Thus, we have the following possibilities

### Unordered array complexities

Insertion:  $O(1)$

Search:  $O(n)$

### Ordered array complexities

Insertion:  $O(n)$

Search:  $O(\log n)$

### Well balanced binary trees complexities

Insertion:  $O(\log n)$

Search:  $O(\log n)$

**Big Drawback - Complex parallel Implementation and waste of memory.**

We want something better!!!

For this

**We will present a probabilistic data structure known as Skip List!!!**



# Outline

## 1 Dictionaries

- Definitions
- Dictionary operations
- Dictionary implementation

## 2 Skip Lists

### • Why Skip Lists?

- The Idea Behind All of It!!!
- A Little of Optimization
- Skip List Definition
- Skip list implementation
- Insertion for Skip Lists
- Deletion in Skip Lists
- Properties
- The Height of the Skip List
- Search and Insertion Times
- Applications
- Summary



# Starting from Scratch

## First

- Imagine that you only require to have searches.
- A first approximation to it is the use of a link list for it ( $\Theta(n)$  search complexity).
- Then, using this How do we speed up searches?

# Starting from Scratch

## First

- Imagine that you only require to have searches.
- A first approximation to it is the use of a link list for it ( $\Theta(n)$  search complexity).
- Then, using this How do we speed up searches?

## Something Notable

- Use two link list, one a subsequence of the other.

# Starting from Scratch

## First

- Imagine that you only require to have searches.
- A first approximation to it is the use of a link list for it ( $\Theta(n)$  search complexity).
- Then, using this How do we speed up searches?

## Something Notable

- Use two link list, one a subsequence of the other.

## Imagine the two lists as a road system

- The Bottom is the normal road system,  $L_2$ .
- The Top is the high way system,  $L_1$ .



# Starting from Scratch

## First

- Imagine that you only require to have searches.
- A first approximation to it is the use of a link list for it ( $\Theta(n)$  search complexity).
- Then, using this How do we speed up searches?

## Something Notable

- Use two link list, one a subsequence of the other.

Imagine the two link as a road system

- The Bottom is the normal road system,  $L_2$ .
- The Top is the high way system,  $L_1$ .

# Starting from Scratch

## First

- Imagine that you only require to have searches.
- A first approximation to it is the use of a link list for it ( $\Theta(n)$  search complexity).
- Then, using this How do we speed up searches?

## Something Notable

- Use two link list, one a subsequence of the other.

## Imagine the two lists as a road system

- 1 The Bottom is the normal road system,  $L_2$ .

2 The Top is the high way system,  $L_1$ .

# Starting from Scratch

## First

- Imagine that you only require to have searches.
- A first approximation to it is the use of a link list for it ( $\Theta(n)$  search complexity).
- Then, using this How do we speed up searches?

## Something Notable

- Use two link list, one a subsequence of the other.

## Imagine the two lists as a road system

- 1 The Bottom is the normal road system,  $L_2$ .
- 2 The Top is the high way system,  $L_1$ .

# Outline

## 1 Dictionaries

- Definitions
- Dictionary operations
- Dictionary implementation


## 2 Skip Lists

- Why Skip Lists?
- **The Idea Behind All of It!!!**
- A Little of Optimization
- Skip List Definition
- Skip list implementation
- Insertion for Skip Lists
- Deletion in Skip Lists
- Properties
- The Height of the Skip List
- Search and Insertion Times
- Applications
- Summary



# Example

## High-Bottom Way System



Thus, we have...

The following rule

**To Search first search in the top one ( $L_1$ ) as far as possible, then go down and search in the bottom one ( $L_2$ ).**



# We can use a little bit of optimization

## We have the following worst cost

Search Cost High-Bottom Way System = Cost Searching Top +...

Cost Search Bottom

Or

Search Cost =  $length(L_1)$  + Cost Search Bottom

The interesting part is "Cost Search Bottom"

This can be calculated by the following quotient:

$$\frac{length(L_2)}{length(L_1)}$$



# We can use a little bit of optimization

## We have the following worst cost

Search Cost High-Bottom Way System = Cost Searching Top +...

Cost Search Bottom

Or

Search Cost =  $length(L_1)$  + Cost Search Bottom

## The interesting part is “Cost Search Bottom”

This can be calculated by the following quotient:


$$\frac{length(L_2)}{length(L_1)}$$





# Why?

If we think we are jumping



Then cost of searching each of the bottom segments = 2


Thus the ratio is a “decent” approximation to the worst case search

$$\frac{\text{length}(L_2)}{\text{length}(L_1)} = \frac{5}{3} = 1.66$$



# Why?

If we think we are jumping



Then cost of searching each of the bottom segments = 2

Thus the ratio is a “decent” approximation to the worst case search

$$\frac{\text{length}(L_2)}{\text{length}(L_1)} = \frac{5}{3} = 1.66$$



# Outline

## 1 Dictionaries

- Definitions
- Dictionary operations
- Dictionary implementation

## 2 Skip Lists

- Why Skip Lists?
- The Idea Behind All of It!!!
- **A Little of Optimization**
- Skip List Definition
- Skip list implementation
- Insertion for Skip Lists
- Deletion in Skip Lists
- Properties
- The Height of the Skip List
- Search and Insertion Times
- Applications
- Summary



Thus, we have...

Then, the cost for a search (when  $\text{length}(L_2) = n$ )

$$\text{Search Cost} = \text{length}(L_1) + \frac{\text{length}(L_2)}{\text{length}(L_1)} = \text{length}(L_1) + \frac{n}{\text{length}(L_1)} \quad (1)$$

Taking the derivative with respect to  $\text{length}(L_1)$  and making the result equal 0

$$\frac{d\text{Search Cost}}{d\text{length}(L_1)} = 1 - \frac{n}{\text{length}^2(L_1)} = 0$$



Thus, we have...

Then, the cost for a search (when  $\text{length}(L_2) = n$ )

$$\text{Search Cost} = \text{length}(L_1) + \frac{\text{length}(L_2)}{\text{length}(L_1)} = \text{length}(L_1) + \frac{n}{\text{length}(L_1)} \quad (1)$$

Taking the derivative with respect to  $\text{length}(L_1)$  and making the result equal 0

$$\frac{d\text{Search Cost}}{d\text{length}(L_1)} = 1 - \frac{n}{\text{length}^2(L_1)} = 0$$



# Final Cost

We have that the optimal length for  $L_1$

$$\text{length}(L_1) = \sqrt{n}$$

Plugging back in (Eq. 1)

$$\text{Search Cost} = \sqrt{n} + \frac{n}{\sqrt{n}} = \sqrt{n} + \sqrt{n} = 2 \times \sqrt{n}$$



# Final Cost

We have that the optimal length for  $L_1$

$$\text{length}(L_1) = \sqrt{n}$$


Plugging back in (Eq. 1)

$$\text{Search Cost} = \sqrt{n} + \frac{n}{\sqrt{n}} = \sqrt{n} + \sqrt{n} = 2 \times \sqrt{n}$$



# Data structure with a Square Root Relation

Something like this





Now

For a three layer link list data structure

We get a search cost of  $3 \times \sqrt[3]{n}$

In general for  $k$  layers, we have

$$k \times \sqrt[k]{n}$$

Thus, if we make  $k = \log_2 n$  we get

$$\begin{aligned}\text{Search Cost} &= \log_2 n \times \sqrt[\log_2 n]{n} \\ &= \log_2 n \times (n)^{1/\log_2 n} \\ &= \log_2 n \times (n)^{\log_n 2} \\ &= \log_2 n \times 2 \\ &= \Theta(\log_2 n)\end{aligned}$$

Now

For a three layer link list data structure

We get a search cost of  $3 \times \sqrt[3]{n}$

In general for  $k$  layers, we have

$$k \times \sqrt[k]{n}$$

Thus, if we make  $k = \log_2 n$  we get

$$\begin{aligned}\text{Search Cost} &= \log_2 n \times \sqrt[\log_2 n]{n} \\ &= \log_2 n \times (n)^{1/\log_2 n} \\ &= \log_2 n \times (n)^{\log_n 2} \\ &= \log_2 n \times 2 \\ &= \Theta(\log_2 n)\end{aligned}$$

Now

For a three layer link list data structure

We get a search cost of  $3 \times \sqrt[3]{n}$

In general for  $k$  layers, we have

$$k \times \sqrt[k]{n}$$

Thus, if we make  $k = \log_2 n$ , we get

$$\begin{aligned}\text{Search Cost} &= \log_2 n \times \sqrt[\log_2 n]{n} \\ &= \log_2 n \times (n)^{1/\log_2 n} \\ &= \log_2 n \times (n)^{\log_n 2} \\ &= \log_2 n \times 2 \\ &= \Theta(\log_2 n)\end{aligned}$$

Thus


## Something Notable

We get the advantages of the binary search trees with a simpler architecture!!!



Thus


## Binary Search Trees




New Architecture

Thus

## Binary Search Trees



## New Architecture



# Problem!!!

If we decided to have a deterministic algorithm

- We need to decide how to do
  - ▶ Insertion
  - ▶ Deletions

We can simplify them

- By using probabilities



# Problem!!!

## If we decided to have a deterministic algorithm

- We need to decide how to do
  - ▶ Insertion
  - ▶ Deletions

## We can simplify them

- By using probabilities





Thus

We are ready to give a

## Definition for Skip List



# Outline

## 1 Dictionaries

- Definitions
- Dictionary operations
- Dictionary implementation

## 2 Skip Lists

- Why Skip Lists?
- The Idea Behind All of It!!!
- A Little of Optimization
- **Skip List Definition**
- Skip list implementation
- Insertion for Skip Lists
- Deletion in Skip Lists
- Properties
- The Height of the Skip List
- Search and Insertion Times
- Applications
- Summary



# A Little Bit of History

## Skip List

They were invented by William Worthington "Bill" Pugh Jr.!!!



# A Little Bit of History

## Skip List

They were invented by William Worthington "Bill" Pugh Jr.!!!

## How is him?

- He is is an American computer scientist who invented the skip list and the Omega test for deciding Presburger arithmetic.
- He was the co-author of the static code analysis tool FindBugs.
- He was highly influential in the development of the current memory model of the Java language together with his PhD student Jeremy Manson.



# A Little Bit of History

## Skip List

They were invented by William Worthington "Bill" Pugh Jr.!!!

## How is him?

- He is is an American computer scientist who invented the skip list and the Omega test for deciding Presburger arithmetic.
- He was the co-author of the static code analysis tool FindBugs.
- He was highly influential in the development of the current memory model of the Java language together with his PhD student Jeremy Manson.



# A Little Bit of History

## Skip List

They were invented by William Worthington "Bill" Pugh Jr.!!!

## How is him?

- He is is an American computer scientist who invented the skip list and the Omega test for deciding Presburger arithmetic.
- He was the co-author of the static code analysis tool FindBugs.
- He was highly influential in the development of the current memory model of the Java language together with his PhD student Jeremy Manson.



# Skip List Definition

## Definition

A skip list for a set  $S$  of distinct (key,element) items is a series of lists  $S_0, S_1, \dots, S_h$  such that:

- Each list  $S_i$  contains the special keys  $+\infty$  and  $-\infty$
- List  $S_0$  contains the keys of  $S$  in nondecreasing order
- Each list is a subsequence of the previous one
  - ▶  $S_0 \supseteq S_1 \supseteq S_2 \supseteq \dots \supseteq S_h$
- List  $S_h$  contains only the two special keys



# Skip List Definition

## Definition

A skip list for a set  $S$  of distinct (key,element) items is a series of lists  $S_0, S_1, \dots, S_h$  such that:

- Each list  $S_i$  contains the special keys  $+\infty$  and  $-\infty$
- List  $S_0$  contains the keys of  $S$  in nondecreasing order
- Each list is a subsequence of the previous one
  - ▶  $S_0 \supseteq S_1 \supseteq S_2 \supseteq \dots \supseteq S_h$
- List  $S_h$  contains only the two special keys





# Skip List Definition

## Definition

A skip list for a set  $S$  of distinct (key,element) items is a series of lists  $S_0, S_1, \dots, S_h$  such that:

- Each list  $S_i$  contains the special keys  $+\infty$  and  $-\infty$
- List  $S_0$  contains the keys of  $S$  in nondecreasing order
- Each list is a subsequence of the previous one
  - ▶  $S_0 \supseteq S_1 \supseteq S_2 \supseteq \dots \supseteq S_h$
- List  $S_h$  contains only the two special keys



# Skip List Definition

## Definition

A skip list for a set  $S$  of distinct (key,element) items is a series of lists  $S_0, S_1, \dots, S_h$  such that:

- Each list  $S_i$  contains the special keys  $+\infty$  and  $-\infty$
- List  $S_0$  contains the keys of  $S$  in nondecreasing order
- Each list is a subsequence of the previous one

$$\rightarrow S_0 \supseteq S_1 \supseteq S_2 \supseteq \dots \supseteq S_h$$

- List  $S_h$  contains only the two special keys



# Skip List Definition

## Definition

A skip list for a set  $S$  of distinct (key,element) items is a series of lists  $S_0, S_1, \dots, S_h$  such that:

- Each list  $S_i$  contains the special keys  $+\infty$  and  $-\infty$
- List  $S_0$  contains the keys of  $S$  in nondecreasing order
- Each list is a subsequence of the previous one
  - ▶  $S_0 \supseteq S_1 \supseteq S_2 \supseteq \dots \supseteq S_h$

• List  $S_h$  contains only the two special keys



# Skip List Definition

## Definition


A skip list for a set  $S$  of distinct (key,element) items is a series of lists  $S_0, S_1, \dots, S_h$  such that:

- Each list  $S_i$  contains the special keys  $+\infty$  and  $-\infty$
- List  $S_0$  contains the keys of  $S$  in nondecreasing order
- Each list is a subsequence of the previous one
  - ▶  $S_0 \supseteq S_1 \supseteq S_2 \supseteq \dots \supseteq S_h$
- List  $S_h$  contains only the two special keys



# Skip List Definition

## Example



# Skip list search

We search for a key  $x$  in a skip list as follows

- We start at the first position of the top list.
- At the current position  $p$ , we compare  $x$  with  $y == p.next.key$ 
  - ▶  $x == y$ : we return  $p.next.element$
  - ▶  $x > y$ : we scan forward
  - ▶  $x < y$ : we “drop down”
- If we try to drop down past the bottom list, we return *null*.



# Skip list search

We search for a key  $x$  in a skip list as follows

- We start at the first position of the top list.
- At the current position  $p$ , we compare  $x$  with  $y == p.next.key$ 
  - ▶  $x == y$ : we return  $p.next.element$
  - ▶  $x > y$ : we scan forward
  - ▶  $x < y$ : we “drop down”
- If we try to drop down past the bottom list, we return *null*.



# Skip list search

We search for a key  $x$  in a skip list as follows

- We start at the first position of the top list.
- At the current position  $p$ , we compare  $x$  with  $y == p.next.key$ 
  - ▶  $x == y$ : we return  $p.next.element$
  - ▶  $x > y$ : we scan forward
  - ▶  $x < y$ : we “drop down”
- If we try to drop down past the bottom list, we return *null*.





# Skip list search

We search for a key  $x$  in a skip list as follows

- We start at the first position of the top list.
- At the current position  $p$ , we compare  $x$  with  $y == p.next.key$ 
  - ▶  $x == y$ : we return  $p.next.element$
  - ▶  $x > y$ : we scan forward
  - ▶  $x < y$ : we “drop down”
- If we try to drop down past the bottom list, we return *null*.



# Skip list search

We search for a key  $x$  in a skip list as follows

- We start at the first position of the top list.
- At the current position  $p$ , we compare  $x$  with  $y == p.next.key$ 
  - ▶  $x == y$ : we return  $p.next.element$
  - ▶  $x > y$ : we scan forward
  - ▶  $x < y$ : we “drop down”
- If we try to drop down past the bottom list, we return *null*.



# Skip list search


We search for a key  $x$  in a skip list as follows

- We start at the first position of the top list.
- At the current position  $p$ , we compare  $x$  with  $y == p.next.key$ 
  - ▶  $x == y$ : we return  $p.next.element$
  - ▶  $x > y$ : we scan forward
  - ▶  $x < y$ : we “drop down”
- If we try to drop down past the bottom list, we return *null*.




## Example search for 78

$x < p.next.key$ : "drop down"




## Example search for 78

$x > p.next.key$ : "scan forward"




## Example search for 78

$x < p.next.key$ : "drop down"




## Example search for 78

$x > p.next.key$ : "scan forward"



## Example search for 78


$x > p.next.key$ : "scan forward"






## Example search for 78

$x < p.next.key$ : "drop down"



## Example search for 78

$x == y$ : we return  $p.next.element$



# Outline

## 1 Dictionaries

- Definitions
- Dictionary operations
- Dictionary implementation

## 2 Skip Lists

- Why Skip Lists?
- The Idea Behind All of It!!!
- A Little of Optimization
- Skip List Definition
- **Skip list implementation**
- Insertion for Skip Lists
- Deletion in Skip Lists
- Properties
- The Height of the Skip List
- Search and Insertion Times
- Applications
- Summary



# How do we implement this data structure?

## We can implement a skip list with quad-nodes

A quad-node stores:

- Entry Value
- Link to the previous node
- Link to the next node
- Link to the above node
- Link to the below node

Also we define special keys PLUS\_INF and MINUS\_INF, and we modify the key comparator to handle them.



# How do we implement this data structure?

## We can implement a skip list with quad-nodes

A quad-node stores:

- Entry Value
- Link to the previous node
- Link to the next node
- Link to the above node
- Link to the below node

Also we define special keys PLUS\_INF and MINUS\_INF, and we modify the key comparator to handle them.



# How do we implement this data structure?

## We can implement a skip list with quad-nodes

A quad-node stores:

- Entry Value
- Link to the previous node
- Link to the next node
- Link to the above node
- Link to the below node

Also we define special keys PLUS\_INF and MINUS\_INF, and we modify the key comparator to handle them.



# How do we implement this data structure?

## We can implement a skip list with quad-nodes

A quad-node stores:

- Entry Value
- Link to the previous node
- Link to the next node
- Link to the above node
- Link to the below node

Also we define special keys PLUS\_INF and MINUS\_INF, and we modify the key comparator to handle them.



# How do we implement this data structure?

## We can implement a skip list with quad-nodes

A quad-node stores:

- Entry Value
- Link to the previous node
- Link to the next node
- Link to the above node
- Link to the below node

Also we define special keys PLUS\_INF and MINUS\_INF, and we modify the key comparator to handle them.





# How do we implement this data structure?

## We can implement a skip list with quad-nodes

A quad-node stores:

- Entry Value
- Link to the previous node
- Link to the next node
- Link to the above node
- Link to the below node

Also we define special keys `PLUS_INF` and `MINUS_INF`, and we modify the key comparator to handle them.



# How do we implement this data structure?

## We can implement a skip list with quad-nodes

A quad-node stores:


- Entry Value
- Link to the previous node
- Link to the next node
- Link to the above node
- Link to the below node

Also we define special keys PLUS\_INF and MINUS\_INF, and we modify the key comparator to handle them.



# Example

## Quad-Node Example



# Skip lists uses Randomization

## Use of randomization

We use a randomized algorithm to insert items into a skip list.

## Running time

We analyze the expected running time of a randomized algorithm under the following assumptions:

- The coins are unbiased.
- The coin tosses are independent.

# Skip lists uses Randomization

## Use of randomization

We use a randomized algorithm to insert items into a skip list.

## Running time

We analyze the expected running time of a randomized algorithm under the following assumptions:

- The coins are unbiased.
- The coin tosses are independent.

## Worst case running time

The worst case running time of a randomized algorithm is often large but has very low probability.

- e.g. It occurs when all the coin tosses give "heads."

# Skip lists uses Randomization

## Use of randomization

We use a randomized algorithm to insert items into a skip list.

## Running time

We analyze the expected running time of a randomized algorithm under the following assumptions:

- The coins are unbiased.
- The coin tosses are independent.

## Worst case running time

The worst case running time of a randomized algorithm is often large but has very low probability.

- e.g. It occurs when all the coin tosses give "heads."

# Skip lists uses Randomization

## Use of randomization

We use a randomized algorithm to insert items into a skip list.

## Running time

We analyze the expected running time of a randomized algorithm under the following assumptions:

- The coins are unbiased.
- The coin tosses are independent.

## Worst case running time

The worst case running time of a randomized algorithm is often large but has very low probability.

- e.g. It occurs when all the coin tosses give "heads."

# Skip lists uses Randomization

## Use of randomization

We use a randomized algorithm to insert items into a skip list.

## Running time

We analyze the expected running time of a randomized algorithm under the following assumptions:

- The coins are unbiased.
- The coin tosses are independent.

## Worst case running time

The worst case running time of a randomized algorithm is often large but has very low probability.

• e.g. It occurs when all the coin tosses give "heads."



# Skip lists uses Randomization

## Use of randomization

We use a randomized algorithm to insert items into a skip list.

## Running time

We analyze the expected running time of a randomized algorithm under the following assumptions:

- The coins are unbiased.
- The coin tosses are independent.

## Worst case running time

The worst case running time of a randomized algorithm is often large but has very low probability.

- e.g. It occurs when all the coin tosses give “**heads.**”

# Outline

## 1 Dictionaries

- Definitions
- Dictionary operations
- Dictionary implementation

## 2 Skip Lists

- Why Skip Lists?
- The Idea Behind All of It!!!
- A Little of Optimization
- Skip List Definition
- Skip list implementation
- **Insertion for Skip Lists**
- Deletion in Skip Lists
- Properties
- The Height of the Skip List
- Search and Insertion Times
- Applications
- Summary



# Insertion

## To insert

To insert an entry  $(key, object)$  into a skip list, we use a randomized algorithm:

- We repeatedly toss a coin until we get tails:
  - We denote with  $i$  the number of times the coin came up heads.



# Insertion

## To insert

To insert an entry  $(key, object)$  into a skip list, we use a randomized algorithm:

- We repeatedly toss a coin until we get tails:

► We denote with  $i$  the number of times the coin came up heads.



# Insertion

## To insert

To insert an entry  $(key, object)$  into a skip list, we use a randomized algorithm:

- We repeatedly toss a coin until we get tails:
  - ▶ We denote with  $i$  the number of times the coin came up heads.



# We have two cases

If  $i \geq h$ , we add to the skip list new lists  $S_{h+1}, \dots, S_{i+1}$

- Each containing only the two special keys.
- We search for  $x$  in the skip list and find the positions  $p_0, p_1, \dots, p_i$  of the items with largest key less than  $x$  in each lists  $S_0, S_1, \dots, S_i$ .
- For  $j \leftarrow 0, \dots, i$ , we insert item  $(key, object)$  into list  $S_j$  after position  $p_j$ .



# We have two cases

If  $i \geq h$ , we add to the skip list new lists  $S_{h+1}, \dots, S_{i+1}$

- Each containing only the two special keys.
- We search for  $x$  in the skip list and find the positions  $p_0, p_1, \dots, p_i$  of the items with largest key less than  $x$  in each lists  $S_0, S_1, \dots, S_i$ .
- For  $j \leftarrow 0, \dots, i$ , we insert item  $(key, object)$  into list  $S_j$  after position  $p_j$ .

If  $i < h$ , we do not need new lists

- We search for  $x$  in the skip list and find the positions  $p_0, p_1, \dots, p_{i-1}$  of the items with largest key less than  $x$  in each lists  $S_0, S_1, \dots, S_{i-1}$ .
- For  $j \leftarrow 0, \dots, i-1$ , we insert item  $(key, object)$  into list  $S_j$  after position  $p_j$ .



# We have two cases

If  $i \geq h$ , we add to the skip list new lists  $S_{h+1}, \dots, S_{i+1}$

- Each containing only the two special keys.
- We search for  $x$  in the skip list and find the positions  $p_0, p_1, \dots, p_i$  of the items with largest key less than  $x$  in each lists  $S_0, S_1, \dots, S_i$ .
- For  $j \leftarrow 0, \dots, i$ , we insert item  $(key, object)$  into list  $S_j$  after position  $p_j$ .

If  $i < h$ , we do not need new lists

- We search for  $x$  in the skip list and find the positions  $p_0, p_1, \dots, p_{i-1}$  of the items with largest key less than  $x$  in each lists  $S_0, S_1, \dots, S_{i-1}$ .
- For  $j \leftarrow 0, \dots, i-1$ , we insert item  $(key, object)$  into list  $S_j$  after position  $p_j$ .





## We have two cases

If  $i \geq h$ , we add to the skip list new lists  $S_{h+1}, \dots, S_{i+1}$

- Each containing only the two special keys.
- We search for  $x$  in the skip list and find the positions  $p_0, p_1, \dots, p_i$  of the items with largest key less than  $x$  in each lists  $S_0, S_1, \dots, S_i$ .
- For  $j \leftarrow 0, \dots, i$ , we insert item  $(key, object)$  into list  $S_j$  after position  $p_j$ .

If  $i < h$ , we do not insert new lists

- We search for  $x$  in the skip list and find the positions  $p_0, p_1, \dots, p_{i-1}$  of the items with largest key less than  $x$  in each lists  $S_0, S_1, \dots, S_{i-1}$ .
- For  $j \leftarrow 0, \dots, i-1$ , we insert item  $(key, object)$  into list  $S_j$  after position  $p_j$ .



# We have two cases

If  $i \geq h$ , we add to the skip list new lists  $S_{h+1}, \dots, S_{i+1}$

- Each containing only the two special keys.
- We search for  $x$  in the skip list and find the positions  $p_0, p_1, \dots, p_i$  of the items with largest key less than  $x$  in each lists  $S_0, S_1, \dots, S_i$ .
- For  $j \leftarrow 0, \dots, i$ , we insert item  $(key, object)$  into list  $S_j$  after position  $p_j$ .

If  $i < h$ , we do not insert new lists

- We search for  $x$  in the skip list and find the positions  $p_0, p_1, \dots, p_{i-1}$  of the items with largest key less than  $x$  in each lists  $S_0, S_1, \dots, S_{i-1}$ .
- For  $j \leftarrow 0, \dots, i-1$ , we insert item  $(key, object)$  into list  $S_j$  after position  $p_j$ .



# We have two cases

If  $i \geq h$ , we add to the skip list new lists  $S_{h+1}, \dots, S_{i+1}$

- Each containing only the two special keys.
- We search for  $x$  in the skip list and find the positions  $p_0, p_1, \dots, p_i$  of the items with largest key less than  $x$  in each lists  $S_0, S_1, \dots, S_i$ .
- For  $j \leftarrow 0, \dots, i$ , we insert item  $(key, object)$  into list  $S_j$  after position  $p_j$ .


If  $i < h$ , we do not insert new lists

- We search for  $x$  in the skip list and find the positions  $p_0, p_1, \dots, p_{i-1}$  of the items with largest key less than  $x$  in each lists  $S_0, S_1, \dots, S_{i-1}$ .
- For  $j \leftarrow 0, \dots, i-1$ , we insert item  $(key, object)$  into list  $S_j$  after position  $p_j$ .




## Example: Insertion of 15 in the skip list

First, we use  $i = 2$  to insert  $S_3$  into the skip list



## Example: Insertion of 15 in the skip list


Clearly, you first search for the predecessor key!!!






## Example: Insertion of 15 in the skip list

Insert the necessary Quad-Nodes and necessary information



## Example: Insertion of 15 in the skip list


Insert the necessary Quad-Nodes and necessary information





## Example: Insertion of 15 in the skip list

Finally!!!



# Outline

## 1 Dictionaries

- Definitions
- Dictionary operations
- Dictionary implementation

## 2 Skip Lists

- Why Skip Lists?
- The Idea Behind All of It!!!
- A Little of Optimization
- Skip List Definition
- Skip list implementation
- Insertion for Skip Lists
- **Deletion in Skip Lists**
- Properties
- The Height of the Skip List
- Search and Insertion Times
- Applications
- Summary



# Deletion

To remove an entry with key  $x$  from a skip list, we proceed as follows

- We search for  $x$  in the skip list and find the positions  $p_0, p_1, \dots, p_i$  of the items with key  $x$ , where position  $p_j$  is in list  $S_j$ .
- We remove positions  $p_0, p_1, \dots, p_i$  from the lists  $S_0, S_1, \dots, S_i$ .
- We remove all but one list containing only the two special keys



# Deletion

To remove an entry with key  $x$  from a skip list, we proceed as follows

- We search for  $x$  in the skip list and find the positions  $p_0, p_1, \dots, p_i$  of the items with key  $x$ , where position  $p_j$  is in list  $S_j$ .
- We remove positions  $p_0, p_1, \dots, p_i$  from the lists  $S_0, S_1, \dots, S_i$ .

• We remove all but one list containing only the two special keys



# Deletion


To remove an entry with key  $x$  from a skip list, we proceed as follows

- We search for  $x$  in the skip list and find the positions  $p_0, p_1, \dots, p_i$  of the items with key  $x$ , where position  $p_j$  is in list  $S_j$ .
- We remove positions  $p_0, p_1, \dots, p_i$  from the lists  $S_0, S_1, \dots, S_i$ .
- We remove all but one list containing only the two special keys




## Example: Delete of 34 in the skip list

We search for 34 in the skip list and find the positions  $p_0, p_1, \dots, p_2$  of the items with key 34




## Example: Delete of 34 in the skip list

We search for 34 in the skip list and find the positions  $p_0, p_1, \dots, p_2$  of the items with key 34



## Example: Delete of 34 in the skip list


We start doing the deletion!!!






## Example: Delete of 34 in the skip list

### One Quad-Node after another




## Example: Delete of 34 in the skip list

### One Quad-Node after another




## Example: Delete of 34 in the skip list

### One Quad-Node after another



## Example: Delete of 34 in the skip list

### Remove One Level



# Outline

## 1 Dictionaries

- Definitions
- Dictionary operations
- Dictionary implementation

## 2 Skip Lists

- Why Skip Lists?
- The Idea Behind All of It!!!
- A Little of Optimization
- Skip List Definition
- Skip list implementation
- Insertion for Skip Lists
- Deletion in Skip Lists
- **Properties**
- The Height of the Skip List
- Search and Insertion Times
- Applications
- Summary



# Space usage

## Space usage

The space used by a skip list depends on the random bits used by each invocation of the insertion algorithm.



Space :  $O(n)$

## Theorem

The expected space usage of a skip list with  $n$  items is  $O(n)$ .

## Space : $O(n)$

### Theorem

The expected space usage of a skip list with  $n$  items is  $O(n)$ .

### Proof

We use the following two basic probabilistic facts:

- Fact 1: The probability of getting  $i$  consecutive heads when flipping a coin is  $\frac{1}{2^i}$ .
- Fact 2: If each of  $n$  entries is present in a set with probability  $p$ , the expected size of the set is  $np$ .
- How? Remember  $X = X_1 + X_2 + \dots + X_n$  where  $X_i$  is an indicator function for event  $A_i =$  the  $i$  element is present in the set. Thus:

$$E[X] = \underbrace{\sum_{i=1}^n E[X_i]}_{\text{Equivalence } E[X_i] \text{ and } Pr\{A_i\}} = \sum_{i=1}^n Pr\{A_i\} = \sum_{i=1}^n p = np$$

Equivalence  $E[X_i]$  and  $Pr\{A_i\}$



Space :  $O(n)$

## Theorem

The expected space usage of a skip list with  $n$  items is  $O(n)$ .

## Proof

We use the following two basic probabilistic facts:

① *Fact 1:* The probability of getting  $i$  consecutive heads when flipping a coin is  $\frac{1}{2^i}$ .

② *Fact 2:* If each of  $n$  entries is present in a set with probability  $p$ , the expected size of the set is  $np$ .

③ How? Remember  $X = X_1 + X_2 + \dots + X_n$  where  $X_i$  is an indicator function for event  $A_i =$  the  $i$  element is present in the set. Thus:

$$E[X] = \underbrace{\sum_{i=1}^n E[X_i]}_{\text{Equivalence } E[X_i] \text{ and } Pr\{A_i\}} = \sum_{i=1}^n Pr\{A_i\} = \sum_{i=1}^n p = np$$

Equivalence  $E[X_i]$  and  $Pr\{A_i\}$

## Space : $O(n)$

### Theorem

The expected space usage of a skip list with  $n$  items is  $O(n)$ .

### Proof

We use the following two basic probabilistic facts:

- ① *Fact 1:* The probability of getting  $i$  consecutive heads when flipping a coin is  $\frac{1}{2^i}$ .
- ② *Fact 2:* If each of  $n$  entries is present in a set with probability  $p$ , the expected size of the set is  $np$ .

⊙ How? Remember  $X = X_1 + X_2 + \dots + X_n$  where  $X_i$  is an indicator function for event  $A_i =$  the  $i$  element is present in the set. Thus:

$$E[X] = \underbrace{\sum_{i=1}^n E[X_i]}_{\text{Equivalence } E[X_i] \text{ and } Pr\{A_i\}} = \sum_{i=1}^n Pr\{A_i\} = \sum_{i=1}^n p = np$$

Equivalence  $E[X_i]$  and  $Pr\{A_i\}$

## Space : $O(n)$

### Theorem

The expected space usage of a skip list with  $n$  items is  $O(n)$ .

### Proof

We use the following two basic probabilistic facts:

- ① *Fact 1:* The probability of getting  $i$  consecutive heads when flipping a coin is  $\frac{1}{2^i}$ .
- ② *Fact 2:* If each of  $n$  entries is present in a set with probability  $p$ , the expected size of the set is  $np$ .
  - ① How? Remember  $X = X_1 + X_2 + \dots + X_n$  where  $X_i$  is an indicator function for event  $A_i =$  the  $i$  element is present in the set. Thus:

$$E[X] = \underbrace{\sum_{i=1}^n E[X_i]}_{\text{Equivalence } E[X_i] \text{ and } Pr(A_i)} = \sum_{i=1}^n Pr\{A_i\} = \sum_{i=1}^n p = np$$

## Space : $O(n)$

### Theorem

The expected space usage of a skip list with  $n$  items is  $O(n)$ .

### Proof

We use the following two basic probabilistic facts:

- ① *Fact 1:* The probability of getting  $i$  consecutive heads when flipping a coin is  $\frac{1}{2^i}$ .
- ② *Fact 2:* If each of  $n$  entries is present in a set with probability  $p$ , the expected size of the set is  $np$ .

- ① How? Remember  $X = X_1 + X_2 + \dots + X_n$  where  $X_i$  is an indicator function for event  $A_i =$  the  $i$  element is present in the set. Thus:

$$E[X] = \underbrace{\sum_{i=1}^n E[X_i]}_{\text{Equivalence } E[X_A] \text{ and } Pr\{A\}} = \sum_{i=1}^n Pr\{A_i\} = \sum_{i=1}^n p = np$$

Equivalence  $E[X_A]$  and  $Pr\{A\}$

# Proof

Now consider a skip list with  $n$  entries

Using Fact 1, an element is inserted in list  $S_i$  with a probability of

$$P[x \in S_i] = \frac{1}{2^i}$$

Now by Fact 2

The expected size of list  $S_i$  is

$$E[|S_i|] = \frac{n}{2^i}$$



# Proof

Now consider a skip list with  $n$  entries

Using Fact 1, an element is inserted in list  $S_i$  with a probability of

$$P[x \in S_i] = \frac{1}{2^i}$$

Now by Fact 2

The expected size of list  $S_i$  is

$$E[|S_i|] = \frac{n}{2^i}$$



# Proof

The expected number of nodes used by the skip list with height  $h$

$$E[\text{Size Skip List}] = \sum_{i=0}^h \frac{n}{2^i} = n \sum_{i=0}^h \frac{1}{2^i}$$

**Here, we have a problem!!! What is the value of  $h$ ?**



# Height $h$

## First

The running time of the search and insertion algorithms is affected by the height  $h$  of the skip list.

## Second

We show that with high probability, a skip list with  $n$  items has height  $O(\log n)$ .





# Height $h$

## First

The running time of the search and insertion algorithms is affected by the height  $h$  of the skip list.

## Second

We show that with high probability, a skip list with  $n$  items has height  $O(\log n)$ .



For this, we have the following fact!!!

### We use the following Fact 3

We can view the level  $l(x_i) = \max \{j \mid \text{where } x_i \in S_j\}$  of the elements in the skip list as the following random variable

$$X_i = l(x_i)$$

for each element  $x_i$  in the skip list.



For this, we have the following fact!!!

### We use the following Fact 3

We can view the level  $l(x_i) = \max \{j \mid \text{where } x_i \in S_j\}$  of the elements in the skip list as the following random variable

$$X_i = l(x_i)$$

for each element  $x_i$  in the skip list.

### And this is a random variable!!!

- Remember the insertions!!! Using an unbiased coin!!
- Thus, all  $X_i$  have a geometric distribution.



For this, we have the following fact!!!

### We use the following Fact 3

We can view the level  $l(x_i) = \max \{j \mid \text{where } x_i \in S_j\}$  of the elements in the skip list as the following random variable

$$X_i = l(x_i)$$

for each element  $x_i$  in the skip list.


### And this is a random variable!!!

- Remember the insertions!!! Using an unbiased coin!!
- Thus, all  $X_i$  have a geometric distribution.



# Example for $l(x_i)$

We have



# BTW What is the geometric distribution?

$k$  failures where

$$k = \{1, 2, 3, \dots\}$$

Probability mass function

$$Pr(X = k) = (1 - p)^{k-1} p$$



## BTW What is the geometric distribution?

$k$  failures where

$$k = \{1, 2, 3, \dots\}$$


Probability mass function

$$Pr(X = k) = (1 - p)^{k-1} p$$



# Probability Mass Function

## For Different Probabilities





Then

We have the following inequality for the geometric variables

$$Pr[X_i > t] \leq (1 - p)^t \quad \forall i = 1, 2, \dots, n$$

- If we assume we have a fair coin  $p = \frac{1}{2}$

This is because

$$F(t) = P[X_i \leq t] = \sum_{i=1}^t (1-p)^{i-1} p$$



Then

We have the following inequality for the geometric variables

$$Pr[X_i > t] \leq (1 - p)^t \quad \forall i = 1, 2, \dots, n$$

- If we assume we have a fair coin  $p = \frac{1}{2}$

This is because

$$F(t) = P[X_i \leq t] = \sum_{i=1}^t (1 - p)^{i-1} p$$



Then, we have

Then, we have that

$$Pr[X_i > t] = \sum_{i=t+1}^{\infty} (1-p)^{i-1} p = 1$$

Thus, we have that

Then, we have

Then, we have that

$$Pr[X_i > t] = \sum_{i=t+1}^{\infty} (1-p)^{i-1} p = 1$$

Thus, we have that

$$\begin{aligned} \sum_{i=t+1}^{\infty} (1-p)^{i-1} p &= p \sum_{i=t+1}^{\infty} (1-p)^{i-1} \\ &= p \sum_{k=1, k=i-t}^{\infty} (1-p)^{k+t-1} \\ &= p(1-p)^t \sum_{k=1, k=i-t}^{\infty} (1-p)^{k-1} \\ &= (1-p)^t \frac{p}{1-p} \leq (1-t)^t \text{ Given the fair coin} \end{aligned}$$

Then, we have

Then, we have that

$$Pr[X_i > t] = \sum_{i=t+1}^{\infty} (1-p)^{i-1} p = 1$$

Thus, we have that

$$\begin{aligned} \sum_{i=t+1}^{\infty} (1-p)^{i-1} p &= p \sum_{i=t+1}^{\infty} (1-p)^{i-1} \\ &= p \sum_{k=1, k=i-t}^{\infty} (1-p)^{k+t-1} \\ &= p (1-p)^t \sum_{k=1, k=i-t}^{\infty} (1-p)^{k-1} \\ &= (1-p)^t \frac{p}{1-p} \leq (1-t)^t \text{ Given the fair coin} \end{aligned}$$

Then, we have

Then, we have that

$$Pr[X_i > t] = \sum_{i=t+1}^{\infty} (1-p)^{i-1} p = 1$$

Thus, we have that

$$\begin{aligned} \sum_{i=t+1}^{\infty} (1-p)^{i-1} p &= p \sum_{i=t+1}^{\infty} (1-p)^{i-1} \\ &= p \sum_{k=1, k=i-t}^{\infty} (1-p)^{k+t-1} \\ &= p (1-p)^t \sum_{k=1, k=i-t}^{\infty} (1-p)^{k-1} \\ &= (1-p)^t \frac{p}{1-p} \leq (1-t)^t \text{ Given the fair coin} \end{aligned}$$

Then, we have

Then, we have that

$$Pr[X_i > t] = \sum_{i=t+1}^{\infty} (1-p)^{i-1} p = 1$$

Thus, we have that

$$\begin{aligned} \sum_{i=t+1}^{\infty} (1-p)^{i-1} p &= p \sum_{i=t+1}^{\infty} (1-p)^{i-1} \\ &= p \sum_{k=1, k=i-t}^{\infty} (1-p)^{k+t-1} \\ &= p (1-p)^t \sum_{k=1, k=i-t}^{\infty} (1-p)^{k-1} \\ &= (1-p)^t \frac{p}{1-p} \leq (1-t)^t \quad \text{Given the fair coin} \end{aligned}$$

Then, we have

Using our original formula

$$\Pr [X_i > t] \leq (1 - t)^t$$





In this way, we have

Then, we have

$$Pr \left\{ \max_i X_i > t \right\} \leq n(1 - p)^t$$



# How?

We have that

$$\begin{aligned} Pr \left\{ \max_i X_i > t \right\} &= Pr \left\{ \max \{X_1, X_2, \dots, X_n\} > t \right\} \\ &= \sum_{i=1}^n Pr \left\{ X_i > t \text{ and } X_i = \max \{X_1, X_2, \dots, X_n\} \right\} \end{aligned}$$

How?

- That one of the elements becomes the maximum in height and a height greater than  $t$



## How?

We have that

$$\begin{aligned} Pr \left\{ \max_i X_i > t \right\} &= Pr \left\{ \max \{X_1, X_2, \dots, X_n\} > t \right\} \\ &= \sum_{i=1}^n Pr \{X_i > t \text{ and } X_i = \max \{X_1, X_2, \dots, X_n\}\} \end{aligned}$$

## How?

- That one of the elements becomes the maximum in height and a height greater than  $t$



# Why?

Because the height of an element depends on independent event

- Each toss coin until tails is independent of the others!!!



# Example

## When having two lists

$$\{\max(X_1, X_2) > t\} = \{X_1 > t \text{ and } X_1 > X_2 \text{ or exclusive } X_2 > t \text{ and } X_2 > X_1\}$$

- Yes, you need to remember that the max is a single element not both...



# Therefore

## Then

$$\begin{aligned} Pr \{X_1 > t \text{ and } X_1 > X_2 \text{ or exclusive } X_2 > t\} &= Pr \{X_1 > t \text{ and } X_1 > X_2\} + \dots \\ &\quad Pr \{X_2 > t \text{ and } X_2 > X_1\} \end{aligned}$$

Assuming exclusivity between phenomena  $X_1$ ,  $X_2$  and  $X_3$

$$\begin{aligned} Pr \{X_1 > t \text{ and } X_1 > X_2 \text{ or exclusive } X_2 > t\} &= P(X_1 > t) P(X_1 > X_2) + \dots \\ &\quad P(X_2 > t) P(X_2 > X_1) \\ &\leq P(X_1 > t) + P(X_2 > t) \end{aligned}$$



# Therefore

## Then

$$\begin{aligned} Pr \{X_1 > t \text{ and } X_1 > X_2 \text{ or exclusive } X_2 > t\} = & Pr \{X_1 > t \text{ and } X_1 > X_2\} + \dots \\ & Pr \{X_2 > t \text{ and } X_2 > X_1\} \end{aligned}$$

## Assuming exclusivity between phenomena $X_i > X_j$ and $X_i > t$

$$\begin{aligned} Pr \{X_1 > t \text{ and } X_1 > X_2 \text{ or exclusive } X_2 > t\} = & P(X_1 > t) P(X_1 > X_2) + \dots \\ & P(X_2 > t) P(X_2 > X_1) \\ \leq & P(X_1 > t) + P(X_2 > t) \end{aligned}$$



This gives us something

We have that

$$Pr \{X_i > t \text{ and } X_i = \max \{X_i\}_{i=1}^n\} = Pr \{X_i > t\} P \{X_i = \max \{X_i\}_{i=1}^n\}$$

Then, we can say that

$$Pr \{X_i > t \text{ and } X_i = \max \{X_i\}_{i=1}^n\} \leq Pr \{X_i > t\}$$





This gives us something

We have that

$$Pr \{X_i > t \text{ and } X_i = \max \{X_i\}_{i=1}^n\} = Pr \{X_i > t\} P \{X_i = \max \{X_i\}_{i=1}^n\}$$

Then, we can say that

$$Pr \{X_i > t \text{ and } X_i = \max \{X_i\}_{i=1}^n\} \leq Pr \{X_i > t\}$$



Finally, using this fact

We have when summing over all events  $X_i$



$$\sum_{i=1}^n \Pr \{X_i > t\} \leq \sum_{i=1}^n (1-p)^t = n (1-p)^t$$



# An Observation

## The $\max_i X_i$

It represents the list with the one entry apart from the special keys.



## Another One

**Also REMEMBER!!!**

We are talking about a fair coin, thus  $p = \frac{1}{2}$ .



# Outline

## 1 Dictionaries

- Definitions
- Dictionary operations
- Dictionary implementation

## 2 Skip Lists

- Why Skip Lists?
- The Idea Behind All of It!!!
- A Little of Optimization
- Skip List Definition
- Skip list implementation
- Insertion for Skip Lists
- Deletion in Skip Lists
- Properties
- **The Height of the Skip List**
- Search and Insertion Times
- Applications
- Summary



Height:  $3 \log_2 n$  with probability at least  $1 - \frac{1}{n^2}$

### Theorem

A skip list with  $n$  entries has height at most  $3 \log_2 n$  with probability at least  $1 - \frac{1}{n^2}$



# Proof

Consider a skip list with  $n$  entries

By Fact 3, the probability that list  $S_t$  has at least one item (The  $\max_i X_i > t$ ) is at most  $\frac{n}{2^t}$ .

$$P(|S_t| \geq 1) = P\left(\max_i X_i > t\right) \leq \frac{n}{2^t}.$$

By picking  $t = \log_2 n$

We have that the probability that  $S_{\log_2 n}$  has at least one entry is at most:

$$\frac{n}{2^{\log_2 n}} = \frac{n}{n} = 1.$$



# Proof

Consider a skip list with  $n$  entries

By Fact 3, the probability that list  $S_t$  has at least one item (The  $\max_i X_i > t$ ) is at most  $\frac{n}{2^t}$ .

$$P(|S_t| \geq 1) = P\left(\max_i X_i > t\right) \leq \frac{n}{2^t}.$$

By picking  $t = 3 \log n$

We have that the probability that  $S_{3 \log_2 n}$  has at least one entry is at most:

$$\frac{n}{2^{3 \log_2 n}} = \frac{n}{n^3} = \frac{1}{n^2}.$$





# Look at we want to model

## We want to model

- The height of the Skip List is at most  $t = 3 \log_2 n$
- Equivalent to the negation of having list  $S_{3 \log_2 n}$



# Look at we want to model

## We want to model

- The height of the Skip List is at most  $t = 3 \log_2 n$
- Equivalent to the negation of having list  $S_{3 \log_2 n}$

Then, the probability that the height  $h = 3 \log_2 n$  of the skip list is

$$P(\text{Skip List height } 3 \log_2 n) = 1 - \frac{1}{n^2}$$



# Look at we want to model

## We want to model

- The height of the Skip List is at most  $t = 3 \log_2 n$
- Equivalent to the negation of having list  $S_{3 \log_2 n}$

Then, the probability that the height  $h = 3 \log_2 n$  of the skip list is

$$P(\text{Skip List height } 3 \log_2 n) = 1 - \frac{1}{n^2}$$



# Finally

The expected number of nodes used by the skip list with height  $h$

- Given that  $h = 3 \log_2 n$

$$\sum_{i=0}^{3 \log_2 n} \frac{n}{2^i} = n \sum_{i=0}^{3 \log_2 n} \frac{1}{2^i}$$

Given the geometric sum

$$S_m = \sum_{k=0}^m r^k = \frac{1 - r^{m+1}}{1 - r}$$



# Finally

The expected number of nodes used by the skip list with height  $h$

- Given that  $h = 3 \log_2 n$

$$\sum_{i=0}^{3 \log_2 n} \frac{n}{2^i} = n \sum_{i=0}^{3 \log_2 n} \frac{1}{2^i}$$

Given the geometric sum

$$S_m = \sum_{k=0}^m r^k = \frac{1 - r^{m+1}}{1 - r}$$



# We have finally

## The Upper Bound on the number of nodes

$$\begin{aligned} n \sum_{i=0}^{3 \log_2 n} \frac{1}{2^i} &= n \left( \frac{1 - \left(\frac{1}{2}\right)^{3 \log_2 n + 1}}{1 - 1/2} \right) \\ &= n \left( \frac{1 - \frac{1}{2^{3 \log_2 n + 1}}}{1/2} \right) \\ &= n \left( \frac{1 - \frac{1}{(2^{\log_2 n})^3 2}}{1/2} \right) \\ &= n \left( \frac{1 - \frac{1}{2n^3}}{1/2} \right) = n \left( \frac{2 [2n^3 - 1]}{2n^3} \right) \end{aligned}$$

# We have finally

## The Upper Bound on the number of nodes

$$\begin{aligned}n \sum_{i=0}^{3 \log_2 n} \frac{1}{2^i} &= n \left( \frac{1 - \left(\frac{1}{2}\right)^{3 \log_2 n + 1}}{1 - 1/2} \right) \\&= n \left( \frac{1 - \frac{1}{2^{3 \log_2 n + 1}}}{1/2} \right) \\&= n \left( \frac{1 - \frac{1}{(2^{\log_2 n})^3 2}}{1/2} \right) \\&= n \left( \frac{1 - \frac{1}{2n^3}}{1/2} \right) = n \left( \frac{2 [2n^3 - 1]}{2n^3} \right)\end{aligned}$$

We have finally

## The Upper Bound on the number of nodes

$$\begin{aligned}n \sum_{i=0}^{3 \log_2 n} \frac{1}{2^i} &= n \left( \frac{1 - \left(\frac{1}{2}\right)^{3 \log_2 n + 1}}{1 - 1/2} \right) \\&= n \left( \frac{1 - \frac{1}{2^{3 \log_2 n + 1}}}{1/2} \right) \\&= n \left( \frac{1 - \frac{1}{(2^{\log_2 n})^3 2}}{1/2} \right) \\&= n \left( \frac{1 - \frac{1}{2n^3}}{1/2} \right) = n \left( \frac{2 [2n^3 - 1]}{2n^3} \right)\end{aligned}$$



# We have finally

## The Upper Bound on the number of nodes

$$\begin{aligned} n \sum_{i=0}^{3 \log_2 n} \frac{1}{2^i} &= n \left( \frac{1 - \left(\frac{1}{2}\right)^{3 \log_2 n + 1}}{1 - 1/2} \right) \\ &= n \left( \frac{1 - \frac{1}{2^{3 \log_2 n + 1}}}{1/2} \right) \\ &= n \left( \frac{1 - \frac{1}{(2^{\log_2 n})^3 2}}{1/2} \right) \\ &= n \left( \frac{1 - \frac{1}{2n^3}}{1/2} \right) = n \left( \frac{2[2n^3 - 1]}{2n^3} \right) \end{aligned}$$

# Finally

We have

$$\left( \frac{2n^3 - 1}{n^2} \right) = 2n - \frac{1}{n^2} \leq 2n$$

The Upper Bound with probability 1 –

$$2n - \frac{1}{n^2} \leq 2n = O(n)$$



# Finally

We have

$$\left( \frac{2n^3 - 1}{n^2} \right) = 2n - \frac{1}{n^2} \leq 2n$$

The Upper Bound with probability  $1 - \frac{1}{n^2}$

$$2n - \frac{1}{n^2} \leq 2n = O(n)$$



# Outline

## 1 Dictionaries

- Definitions
- Dictionary operations
- Dictionary implementation

## 2 Skip Lists

- Why Skip Lists?
- The Idea Behind All of It!!!
- A Little of Optimization
- Skip List Definition
- Skip list implementation
- Insertion for Skip Lists
- Deletion in Skip Lists
- Properties
- The Height of the Skip List
- **Search and Insertion Times**
- Applications
- Summary



# Search and Insertion Times

## Fact 4

**The expected number of coin tosses required in order to get tails is 2:**

$$\text{Given that } x \sim G\left(\frac{1}{2}\right) \implies E[x] = \frac{1}{p} = 2 \text{ (Fair Coin Assumption)}$$

We use this

To prove that a search in a skip list takes  $O(\log n)$  expected time.

- After all insertions require searches!!!



# Search and Insertion Times

## Fact 4

**The expected number of coin tosses required in order to get tails is 2:**

$$\text{Given that } x \sim G\left(\frac{1}{2}\right) \implies E[x] = \frac{1}{p} = 2 \text{ (Fair Coin Assumption)}$$

## We use this

To prove that a search in a skip list takes  $O(\log n)$  expected time.

- After all insertions require searches!!!



# Search and Insertions times

## Search time

The search time in skip list is proportional to

**the number of drop-down steps + the number of scan-forward steps**

### Drop-down steps

The drop-down steps are bounded by the height of the skip list and thus are  $O(\log_2 n)$  with high probability.

### Theorem

A search in a skip list takes  $O(\log_2 n)$  expected time.



# Search and Insertions times

## Search time

The search time in skip list is proportional to

**the number of drop-down steps + the number of scan-forward steps**

## Drop-down steps

The drop-down steps are bounded by the height of the skip list and thus are  $O(\log_2 n)$  with high probability.

## Theorem

A search in a skip list takes  $O(\log_2 n)$  expected time.





# Search and Insertions times

## Search time

The search time in skip list is proportional to

**the number of drop-down steps + the number of scan-forward steps**

## Drop-down steps

The drop-down steps are bounded by the height of the skip list and thus are  $O(\log_2 n)$  with high probability.

## Theorem

A search in a skip list takes  $O(\log_2 n)$  expected time.



# Proof

## First

- When we scan forward in a list, the destination key does not belong to a higher list.

A scan-forward step is associated with a former coin toss that gave tails

- By Fact 4, in each list the expected number of scan-forward steps is 2.



# Proof

## First

- When we scan forward in a list, the destination key does not belong to a higher list.

A scan-forward step is associated with a former coin toss that gave tails

- By Fact 4, in each list the expected number of scan-forward steps is 2.



# Why?

Given the list  $S_i$

- Then, the scan-forward intervals (Jumps between  $x_i$  and  $x_{i+1}$ ) to the right of  $S_i$  are

$$I_1 = [x_1, x_2], I_2 = [x_2, x_3] \dots I_k = [x_k, +\infty]$$

Then

These interval exist at level  $i$  if and only if all  $x_1, x_2, \dots, x_k$  belong to  $S_i$ .



# Why?

Given the list  $S_i$

- Then, the scan-forward intervals (Jumps between  $x_i$  and  $x_{i+1}$ ) to the right of  $S_i$  are

$$I_1 = [x_1, x_2], I_2 = [x_2, x_3] \dots I_k = [x_k, +\infty]$$

Then


These interval exist at level  $i$  if and only if all  $x_1, x_2, \dots, x_k$  belong to  $S_i$ .



We introduce the following concept based on these intervals

## Scan-forward siblings

These are element that you find in the search path before finding an element in the upper list.



# Now

Given that a search is being done,  $S_i$  contains  $l$  forward siblings

It must be the case that given  $x_1, \dots, x_l$  scan-forward siblings, we have that

$$x_1, \dots, x_l \notin S_{i+1}$$

and  $x_{l+1} \in S_{i+1}$



# Thus

We have

Since each element of  $S_i$  is independently chosen to be in  $S_{i+1}$  with probability  $p = \frac{1}{2}$ .

We have

The number of scan-forward siblings is bounded by a geometric random variable  $X_i$  with parameter  $p = \frac{1}{2}$ .

- Imagine the fact that you have multiple fails... then  $x_1, \dots, x_i \notin S_{i+1}$  is modeled by  $X_i$

Thus, we have that

The expected number of scan-forward siblings is bounded by 2!!!

$$\text{Expected \# Scan-Fordward Siblings at } i \leq \underbrace{E[X_i]}_{\text{Mean}} = \frac{1}{1/2} = 2$$



# Thus

We have

Since each element of  $S_i$  is independently chosen to be in  $S_{i+1}$  with probability  $p = \frac{1}{2}$ .

We have

The number of scan-forward siblings is bounded by a geometric random variable  $X_i$  with parameter  $p = \frac{1}{2}$ .

- Imagine the fact that you have multiple fails... then  $x_1, \dots, x_l \notin S_{i+1}$  is modeled by  $X_i$

Thus, we have that

The expected number of scan-forward siblings is bounded by 2!!!

$$\text{Expected \# Scan-Fordward Siblings at } i \leq \underbrace{E[X_i]}_{\text{Mean}} = \frac{1}{1/2} = 2$$

# Thus

## We have

Since each element of  $S_i$  is independently chosen to be in  $S_{i+1}$  with probability  $p = \frac{1}{2}$ .

## We have

The number of scan-forward siblings is bounded by a geometric random variable  $X_i$  with parameter  $p = \frac{1}{2}$ .

- Imagine the fact that you have multiple fails... then  $x_1, \dots, x_l \notin S_{i+1}$  is modeled by  $X_i$

## Thus, we have that

The expected number of scan-forward siblings is bounded by 2!!!

$$\text{Expected \# Scan-Fordward Siblings at } i \leq \underbrace{E[X_i]}_{\text{Mean}} = \frac{1}{1/2} = 2$$

Then

In the worst case scenario

A search is bounded by  $O(\log_2 n) + 2\log_2 n = O(\log_2 n)$

And given that a insertion is a (search) + (deletion bounded by the height)

Thus, an insertion is bounded by  $2\log_2 n + 3\log_2 n = O(\log_2 n)$



Then

In the worst case scenario

A search is bounded by  $O(\log_2 n) + 2\log_2 n = O(\log_2 n)$

An given that a insertion is a **(search) + (deletion bounded by the height)**

Thus, an insertion is bounded by  $2\log_2 n + 3\log_2 n = O(\log_2 n)$



# Outline

## 1 Dictionaries

- Definitions
- Dictionary operations
- Dictionary implementation

## 2 Skip Lists

- Why Skip Lists?
- The Idea Behind All of It!!!
- A Little of Optimization
- Skip List Definition
- Skip list implementation
- Insertion for Skip Lists
- Deletion in Skip Lists
- Properties
- The Height of the Skip List
- Search and Insertion Times
- **Applications**
- Summary



# Applications

## We have

- Cyrus IMAP servers offer a "skiplist" backend Data Base implementation.
- Lucene uses skip lists to search delta-encoded posting lists in logarithmic time.
- Redis, an ANSI-C open-source persistent key/value store for Posix systems, uses skip lists in its implementation of ordered sets.
- leveldb, a fast key-value storage library written at Google that provides an ordered mapping from string keys to string values.
- Skip lists are used for efficient statistical computations of running medians.



# Applications

## We have

- Cyrus IMAP servers offer a "skiplist" backend Data Base implementation.
- Lucene uses skip lists to search delta-encoded posting lists in logarithmic time.
- Redis, an ANSI-C open-source persistent key/value store for Posix systems, uses skip lists in its implementation of ordered sets.
- leveldb, a fast key-value storage library written at Google that provides an ordered mapping from string keys to string values.
- Skip lists are used for efficient statistical computations of running medians.



# Applications

## We have

- Cyrus IMAP servers offer a "skiplist" backend Data Base implementation.
- Lucene uses skip lists to search delta-encoded posting lists in logarithmic time.
- Redis, an ANSI-C open-source persistent key/value store for Posix systems, uses skip lists in its implementation of ordered sets.
- leveldb, a fast key-value storage library written at Google that provides an ordered mapping from string keys to string values.
- Skip lists are used for efficient statistical computations of running medians.





# Applications

## We have

- Cyrus IMAP servers offer a "skiplist" backend Data Base implementation.
- Lucene uses skip lists to search delta-encoded posting lists in logarithmic time.
- Redis, an ANSI-C open-source persistent key/value store for Posix systems, uses skip lists in its implementation of ordered sets.
- leveldb, a fast key-value storage library written at Google that provides an ordered mapping from string keys to string values.
- Skip lists are used for efficient statistical computations of running medians.



# Applications

## We have

- Cyrus IMAP servers offer a "skiplist" backend Data Base implementation.
- Lucene uses skip lists to search delta-encoded posting lists in logarithmic time.
- Redis, an ANSI-C open-source persistent key/value store for Posix systems, uses skip lists in its implementation of ordered sets.
- leveldb, a fast key-value storage library written at Google that provides an ordered mapping from string keys to string values.
- Skip lists are used for efficient statistical computations of running medians.



# Outline

## 1 Dictionaries

- Definitions
- Dictionary operations
- Dictionary implementation

## 2 Skip Lists

- Why Skip Lists?
- The Idea Behind All of It!!!
- A Little of Optimization
- Skip List Definition
- Skip list implementation
- Insertion for Skip Lists
- Deletion in Skip Lists
- Properties
- The Height of the Skip List
- Search and Insertion Times
- Applications
- **Summary**



# Summary

## Summary

- A skip list is a data structure for dictionaries that uses a randomized insertion algorithm.
- In a skip list with  $n$  entries:
  - ▶ The expected space used is  $O(n)$
  - ▶ The expected search, insertion and deletion time is  $O(\log n)$
- Skip list are fast and simple to implement in practice.



# Summary

## Summary

- A skip list is a data structure for dictionaries that uses a randomized insertion algorithm.
- In a skip list with  $n$  entries:
  - ▶ The expected space used is  $O(n)$
  - ▶ The expected search, insertion and deletion time is  $O(\log n)$
- Skip list are fast and simple to implement in practice.



# Summary

## Summary

- A skip list is a data structure for dictionaries that uses a randomized insertion algorithm.
- In a skip list with  $n$  entries:
  - ▶ The expected space used is  $O(n)$
  - ▶ The expected search, insertion and deletion time is  $O(\log n)$
- Skip list are fast and simple to implement in practice.



## Summary

- A skip list is a data structure for dictionaries that uses a randomized insertion algorithm.
- In a skip list with  $n$  entries:
  - ▶ The expected space used is  $O(n)$
  - ▶ The expected search, insertion and deletion time is  $O(\log n)$
- Skip list are fast and simple to implement in practice.



## Summary

- A skip list is a data structure for dictionaries that uses a randomized insertion algorithm.
- In a skip list with  $n$  entries:
  - ▶ The expected space used is  $O(n)$
  - ▶ The expected search, insertion and deletion time is  $O(\log n)$
- Skip list are fast and simple to implement in practice.





# Summary

## Summary

- A skip list is a data structure for dictionaries that uses a randomized insertion algorithm.
- In a skip list with  $n$  entries:
  - ▶ The expected space used is  $O(n)$
  - ▶ The expected search, insertion and deletion time is  $O(\log n)$
- Skip list are fast and simple to implement in practice.



# Thanks

## Questions?

