

# Introduction to Analysis of Algorithms

## CTypes and Python

Andres Mendez-Vazquez

September 5, 2020

# Outline

## 1 How to extend Python using C

- The Different Ways
- Using Cython
- Using CTypes
- The Python Part

# Outline

## 1 How to extend Python using C

- The Different Ways
  - Using Cython
  - Using CTypes
  - The Python Part

# We have different ways

## First one, the Python API

- A set of functions, macros and variables that provide access to most aspects of the Python run-time system.
  - ▶ The Python API is incorporated in a C source file by including the header "Python.h".

### Example

```
static PyObject *  
spam_system(PyObject *self, PyObject *args) {  
    const char *command;  
    int sts;  
    if (!PyArg_ParseTuple(args, "s", &command))  
        return NULL;  
    sts = system(command);  
    return PyLong_FromLong(sts);  
}
```

# We have different ways

## First one, the Python API

- A set of functions, macros and variables that provide access to most aspects of the Python run-time system.
  - ▶ The Python API is incorporated in a C source file by including the header "Python.h".

## Example

```
static PyObject *  
spam_system(PyObject *self, PyObject *args) {  
    const char *command;  
    int sts;  
    if (!PyArg_ParseTuple(args, "s", \&command))  
        return NULL;  
    sts = system(command);  
    return PyLong_FromLong(sts);  
}
```

# Problem

We have a series of macros included at the Python.h

- **PyObject** is an object structure that you use to define object types for Python.
- `PyArg_ParseTuple` parses the arguments you'll receive from your Python program into local variables.
- etc

# Problem

We have a series of macros included at the Python.h

- **PyObject** is an object structure that you use to define object types for Python.
- **PyArg\_ParseTuple** parses the arguments you'll receive from your Python program into local variables.

• etc

This can be used to build specific libraries totally transparent for Python

- However, this is fine for the final module after development....
  - ▶ In our case, we need something faster...

# Problem

We have a series of macros included at the Python.h

- **PyObject** is an object structure that you use to define object types for Python.
- **PyArg\_ParseTuple** parses the arguments you'll receive from your Python program into local variables.
- etc

This can be used to build specific libraries totally transparent for Python

- However, this is fine for the final module after development....
  - ▶ In our case, we need something faster...



# Problem

We have a series of macros included at the Python.h

- **PyObject** is an object structure that you use to define object types for Python.
- **PyArg\_ParseTuple** parses the arguments you'll receive from your Python program into local variables.
- etc

This can be used to build specific libraries totally transparent for Python

- However, this is fine for the final module after development....

» In our case, we need something faster...

# Problem

We have a series of macros included at the Python.h

- **PyObject** is an object structure that you use to define object types for Python.
- **PyArg\_ParseTuple** parses the arguments you'll receive from your Python program into local variables.
- etc

This can be used to build specific libraries totally transparent for Python

- However, this is fine for the final module after development....
  - ▶ In our case, we need something faster...

# Outline

## 1 How to extend Python using C

- The Different Ways
- **Using Cython**
- Using CTypes
- The Python Part

# Cython

## They say

- “Cython is an optimising static compiler for both the Python programming language and the extended Cython programming language (based on Pyrex). It makes writing C extensions for Python as easy as Python itself.”

# Cython

## They say

- “Cython is an optimising static compiler for both the Python programming language and the extended Cython programming language (based on Pyrex). It makes writing C extensions for Python as easy as Python itself.”

## However, it is not that simple

- Cython is heavily dependent of their implementation on a OS
- You have a steep curve of learning
- The footprint of the programs is too large
- Not everything is at the documentation...

# Cython

## They say

- “Cython is an optimising static compiler for both the Python programming language and the extended Cython programming language (based on Pyrex). It makes writing C extensions for Python as easy as Python itself.”

## However, it is not that simple

- Cython is heavily dependent of their implementation on a OS
- You have a steep curve of learning
  - The footprint of the programs is too large
  - Not everything is at the documentation...

We want something that allows to pass all the info from one env to another

- So, you only deal with the specific language problems

# Cython

## They say

- “Cython is an optimising static compiler for both the Python programming language and the extended Cython programming language (based on Pyrex). It makes writing C extensions for Python as easy as Python itself.”

## However, it is not that simple

- Cython is heavily dependent of their implementation on a OS
- You have a steep curve of learning
- The footprint of the programs is too large
- Not everything is at the documentation...

We want something that allows to pass all the info from one env to another

- So, you only deal with the specific language problems

# Cython

## They say

- “Cython is an optimising static compiler for both the Python programming language and the extended Cython programming language (based on Pyrex). It makes writing C extensions for Python as easy as Python itself.”

## However, it is not that simple

- Cython is heavily dependent of their implementation on a OS
- You have a steep curve of learning
- The footprint of the programs is too large
- Not everything is at the documentation....

We want something that allows to pass all the info from one env to another

- So, you only deal with the specific language problems



# Cython

## They say

- “Cython is an optimising static compiler for both the Python programming language and the extended Cython programming language (based on Pyrex). It makes writing C extensions for Python as easy as Python itself.”

## However, it is not that simple

- Cython is heavily dependent of their implementation on a OS
- You have a steep curve of learning
- The footprint of the programs is too large
- Not everything is at the documentation....

## We want something that allows to pass all the info from one env to another

- So, you only deal with the specific language problems

# Outline

## 1 How to extend Python using C

- The Different Ways
- Using Cython
- Using CTypes
- The Python Part

# Our Choice

## CTypes

- ctypes is a foreign function library for Python.
- It provides C compatible data types, and allows calling functions in DLLs or shared libraries.
- It can be used to wrap these libraries in pure Python.

# Our Choice

## CTypes

- ctypes is a foreign function library for Python.
- It provides C compatible data types, and allows calling functions in DLLs or shared libraries.
- It can be used to wrap these libraries in pure Python.

## Something Notable

- ctypes exports the cdll, and on Windows windll and oledll objects, for loading dynamic link libraries.

# Our Choice

## CTypes

- ctypes is a foreign function library for Python.
- It provides C compatible data types, and allows calling functions in DLLs or shared libraries.
- It can be used to wrap these libraries in pure Python.

## Something Notable

- ctypes exports the cdll, and on Windows windll and oledll objects, for loading dynamic link libraries.

# Our Choice

## CTypes

- ctypes is a foreign function library for Python.
- It provides C compatible data types, and allows calling functions in DLLs or shared libraries.
- It can be used to wrap these libraries in pure Python.

## Something Notable

- ctypes exports the cdll, and on Windows windll and oledll objects, for loading dynamic link libraries.

# Structure of the development

## First

- Generate your C function

```
cmult.c
```

```
#ifndef INSERTIONSORT_FILE
#define INSERTIONSORT_FILE
/*cmult.h*/
float cmult(int int_param, float float_param);
#endif
```

# Structure of the development

## First

- Generate your C function

## cmult.h

```
#ifndef INSERTIONSORT_FILE
#define INSERTIONSORT_FILE
    /*cmult.h*/
    float cmult(int int_param, float float_param);
#endif
```



# Finally

## cmult.c

```
// cmult.c
#include <stdio.h>
#include "cmult.h"
float cmult(int int_param, float float_param) {
    float return_value = int_param * float_param;
    printf(" In cmult : int: %d float %.1f returning %.1f\n", int_param,
float_param, return_value);
    return return_value;
}
```

As you can see

- It is pure C...

# Finally

## cmult.c

```
// cmult.c
#include <stdio.h>
#include "cmult.h"
float cmult(int int_param, float float_param) {
    float return_value = int_param * float_param;
    printf(" In cmult : int: %d float %.1f returning %.1f\n", int_param,
float_param, return_value);
    return return_value;
}
```

## As you can see

- It is pure C...

# How do we facilitate the compilation

For this, we can use invoke from python

- Invoke is a Python (2.7 and 3.4+) task execution tool & library,

Let us to take a look at

- task.py

# How do we facilitate the compilation

For this, we can use invoke from python

- Invoke is a Python (2.7 and 3.4+) task execution tool & library,

Let us to take a look at

- task.py

**-C**

- Compile or assemble the source files, but do not link

**-Wall**

- This enables all the warnings about constructions that some users consider questionable

**-Werror**

- Make all warnings into errors.

## -C

- Compile or assemble the source files, but do not link

## -Wall

- This enables all the warnings about constructions that some users consider questionable

## -Werror

- Make all warnings into errors.

## -C

- Compile or assemble the source files, but do not link

## -Wall

- This enables all the warnings about constructions that some users consider questionable

## -Werror

- Make all warnings into errors.

# Then

**-fpic**

- Generate position-independent code (PIC) suitable for use in a shared library, if supported for the target machine

• Include the API extensions, in this case, `/usr/include/python3.8`



# Then

**-fpic**

- Generate position-independent code (PIC) suitable for use in a shared library, if supported for the target machine

**-I**

- Include the API extensions, in this case, `/usr/include/python3.8`

# Linking the objects being generated

```
"gcc -shared -o libcmult.so cmult.o"
```

- Linkage with the libraries is done here...

## shared

- Produce a shared object which can then be linked with other objects to form an executable.

## o

- Place the primary output in file file.
  - ▶ In this case so and o
    - ★ A dynamic .so library can be loaded and unloaded at runtime and you have a better flexibility

# Linking the objects being generated

```
"gcc -shared -o libcmult.so cmult.o"
```

- Linkage with the libraries is done here...

**-shared**

- Produce a shared object which can then be linked with other objects to form an executable.

- Place the primary output in file file.
  - ▶ In this case so and o
  - ★ A dynamic .so library can be loaded and unloaded at runtime and you have a better flexibility

# Linking the objects being generated

```
"gcc -shared -o libcmult.so cmult.o"
```

- Linkage with the libraries is done here...

**-shared**

- Produce a shared object which can then be linked with other objects to form an executable.

**-O**

- Place the primary output in file file.
  - ▶ In this case so and o
    - ★ A dynamic .so library can be loaded and unloaded at runtime and you have a better flexibility

# Outline

## 1 How to extend Python using C

- The Different Ways
- Using Cython
- Using CTypes
- The Python Part

## We have to load this libraries

pathlib can be used

- `pathlib.Path().absolute() / "libcmult.so"`

Then, `ctypes` can be used for this

- `c_lib = ctypes.CDLL(libname)`

Then

- Some extra setup needs to be done

## We have to load this libraries

pathlib can be used

- `pathlib.Path().absolute() / "libcmult.so"`

Then, using ctypes can be used for this

- `c_lib = ctypes.CDLL(libname)`

Then

- Some extra setup needs to be done

## We have to load this libraries

pathlib can be used

- `pathlib.Path().absolute() / "libcmult.so"`

Then, using ctypes can be used for this

- `c_lib = ctypes.CDLL(libname)`

Then

- Some extra setup needs to be done



# Moving Python Objects to C

First the output needs to be setup even the void one

- `c_lib.cmult.restype = ctypes.c_float`

The arguments also need to be converted

- `answer = c_lib.cmult(x, ctypes.c_float(y))`

# Moving Python Objects to C

First the output needs to be setup even the void one

- `c_lib.cmult.restype = ctypes.c_float`

The arguments also need to be converted

- `answer = c_lib.cmult(x, ctypes.c_float(y))`

# Now

We need to have more complex examples

- So we can look at the more interesting problems