

Analysis of Algorithms

Complexity and Sorting

Andres Mendez-Vazquez

September 9, 2020

Outline

1 Algorithmic Complexity Analysis

- Introduction
- Asymptotic Bounds
- Correctness of Algorithms
- Exercises



Outline

1 Algorithmic Complexity Analysis

- Introduction
- Asymptotic Bounds
- Correctness of Algorithms
- Exercises



Algorithm efficiency

When measuring an algorithm efficiency we must consider:

- Speed.
- Memory usage.
- Scalability.



Algorithm efficiency

When measuring an algorithm efficiency we must consider:

- Speed.
- Memory usage.
- Scalability.

Measuring speed

- Speed is measured in terms of the number of operations relative to the size of the input.



Algorithm efficiency

When measuring an algorithm efficiency we must consider:

- Speed.
- Memory usage.
- Scalability.

Measuring speed

- Speed is measured in terms of the number of operations relative to the size of the input.



Algorithm efficiency

When measuring an algorithm efficiency we must consider:

- Speed.
- Memory usage.
- Scalability.

Measuring speed!

- Speed is measured in terms of the number of operations relative to the size of the input.



Asymptotic bounds

Intuition

An asymptotic bound is a curve that represents the limit of a function.



Asymptotic bounds

Intuition

An asymptotic bound is a curve that represents the limit of a function.

For the purpose of analyzing the speed of an algorithm, three typical asymptotic bounds are used.

1 Big O (Upper bound)

2 Big Ω (Lower bound)

3 Big Θ (Expected bound)



Asymptotic bounds

Intuition

An asymptotic bound is a curve that represents the limit of a function.

For the purpose of analyzing the speed of an algorithm, three typical asymptotic bounds are used.

① Big O (Upper bound)

② Big Ω (Lower bound)

③ Big Θ (Expected bound)



Asymptotic bounds

Intuition

An asymptotic bound is a curve that represents the limit of a function.

For the purpose of analyzing the speed of an algorithm, three typical asymptotic bounds are used.

- 1 Big O (Upper bound)
- 2 Big Ω (Lower bound)
- 3 Big Θ (Expected bound)



Outline

1 Algorithmic Complexity Analysis


- Introduction
- **Asymptotic Bounds**
- Correctness of Algorithms
- Exercises



Big O (Upper bound)

Intuition

- Let $f(n)$ and $g(n)$ be two real valued functions, let's build intuition on the meaning of $f(n) \in O(g(n))$.




Definition

- $f(n) \in O(g(n))$ if there exists $c, n_0 > 0$ such that $f(n) \leq c \cdot g(n)$ for all $n \geq n_0$.

Big O (Upper bound)

Intuition

- Let $f(n)$ and $g(n)$ be two real valued functions, let's build intuition on the meaning of $f(n) \in O(g(n))$.




Definition

- $f(n) \in O(g(n))$ if there exists $c, n_0 > 0$ such that $f(n) \leq c \cdot g(n)$ for all $n \geq n_0$.

Big Ω (Lower bound)

Intuition

- Let $f(n)$ and $g(n)$ be two real valued functions, let's build intuition on the meaning of $f(n) \in \Omega(g(n))$.




Definition

- $f(n) \in \Omega(g(n))$ if there exists $c, n_0 > 0$ such that $f(n) \geq c \cdot g(n)$ for all $n \geq n_0$.

Big Ω (Lower bound)

Intuition

- Let $f(n)$ and $g(n)$ be two real valued functions, let's build intuition on the meaning of $f(n) \in \Omega(g(n))$.




Definition

- $f(n) \in \Omega(g(n))$ if there exists $c, n_0 > 0$ such that $f(n) \geq c \cdot g(n)$ for all $n \geq n_0$.

Big Θ (Expected bound)

Intuition

- Let $f(n)$ and $g(n)$ be two real valued functions, let's build intuition on the meaning of $f(n) \in \Theta(g(n))$.




Definition

- $f(n) \in O(g(n))$ if there exists $c, n_0 > 0$ such that $f(n) \leq c \cdot g(n)$ for all $n \geq n_0$.

Big Θ (Expected bound)

Intuition

- Let $f(n)$ and $g(n)$ be two real valued functions, let's build intuition on the meaning of $f(n) \in \Theta(g(n))$.



Definition

- $f(n) \in O(g(n))$ if there exists $c, n_0 > 0$ such that $f(n) \leq c \cdot g(n)$ for all $n \geq n_0$.

Outline

1 Algorithmic Complexity Analysis

- Introduction
- Asymptotic Bounds
- **Correctness of Algorithms**
- Exercises



Correctness of an algorithm

Loop invariant and loop conditional

- A loop invariant is a condition that is necessarily true immediately before and immediately after each iteration of a loop.
- A loop conditional is a statements that controls the termination of the loop.
- Both loop invariant and loop conditional must be different conditions.

Correctness of an algorithm

Loop invariant and loop conditional

- A loop invariant is a condition that is necessarily true immediately before and immediately after each iteration of a loop.
- A loop conditional is a statements that controls the termination of the loop.
- Both loop invariant and loop conditional must be different conditions.

Example

- To prove an algorithm is correct we must find a loop conditional that ensures the algorithm terminates.
- The loop invariant must be true:
 - ▶ Before the loop starts
 - ▶ Before each iteration of the loop
 - ▶ After the loop terminates

Correctness of an algorithm

Loop invariant and loop conditional

- A loop invariant is a condition that is necessarily true immediately before and immediately after each iteration of a loop.
- A loop conditional is a statements that controls the termination of the loop.
- Both loop invariant and loop conditional must be different conditions.

Example

- To prove an algorithm is correct we must find a loop conditional that ensures the algorithm terminates.
- The loop invariant must be true:
 - ▶ Before the loop starts
 - ▶ Before each iteration of the loop
 - ▶ After the loop terminates

Correctness of an algorithm

Loop invariant and loop conditional

- A loop invariant is a condition that is necessarily true immediately before and immediately after each iteration of a loop.
- A loop conditional is a statements that controls the termination of the loop.
- Both loop invariant and loop conditional must be different conditions.

Facts!

- To prove an algorithm is correct we must find a loop conditional that ensures the algorithm terminates.
- The loop invariant must be true:
 - ▶ Before the loop starts
 - ▶ Before each iteration of the loop
 - ▶ After the loop terminates

Correctness of an algorithm

Loop invariant and loop conditional

- A loop invariant is a condition that is necessarily true immediately before and immediately after each iteration of a loop.
- A loop conditional is a statements that controls the termination of the loop.
- Both loop invariant and loop conditional must be different conditions.

Facts!

- To prove an algorithm is correct we must find a loop conditional that ensures the algorithm terminates.
- The loop invariant must be true:
 - ▶ Before the loop starts
 - ▶ Before each iteration of the loop
 - ▶ After the loop terminates

Correctness of an algorithm

Loop invariant and loop conditional

- A loop invariant is a condition that is necessarily true immediately before and immediately after each iteration of a loop.
- A loop conditional is a statements that controls the termination of the loop.
- Both loop invariant and loop conditional must be different conditions.

Facts!

- To prove an algorithm is correct we must find a loop conditional that ensures the algorithm terminates.
- The loop invariant must be true:
 - ▶ Before the loop starts
 - ▶ Before each iteration of the loop
 - ▶ After the loop terminates

Correctness of an algorithm

Loop invariant and loop conditional

- A loop invariant is a condition that is necessarily true immediately before and immediately after each iteration of a loop.
- A loop conditional is a statements that controls the termination of the loop.
- Both loop invariant and loop conditional must be different conditions.

Facts!

- To prove an algorithm is correct we must find a loop conditional that ensures the algorithm terminates.
- The loop invariant must be true:
 - ▶ Before the loop starts
 - ▶ Before each iteration of the loop
 - ▶ After the loop terminates

Correctness of an algorithm

Loop invariant and loop conditional

- A loop invariant is a condition that is necessarily true immediately before and immediately after each iteration of a loop.
- A loop conditional is a statements that controls the termination of the loop.
- Both loop invariant and loop conditional must be different conditions.

Facts!

- To prove an algorithm is correct we must find a loop conditional that ensures the algorithm terminates.
- The loop invariant must be true:
 - ▶ Before the loop starts
 - ▶ Before each iteration of the loop
 - ▶ After the loop terminates

Outline

1 Algorithmic Complexity Analysis

- Introduction
- Asymptotic Bounds
- Correctness of Algorithms
- Exercises



Well, now you know the basics. Time to work!

From Dasgupta's Algorithms book, exercise 0.1

Using the definition in each of the following situations indicate whether $f = O(g)$, or $f = \Omega(g)$, or both (in which case $f = \Theta(g)$).

① $f(n) = n - 100$, $g(n) = n - 200$

② $f(n) = n2^n$, $g(n) = 3^n$



Well, now you know the basics. Time to work!

From Dasgupta's Algorithms book, exercise 0.1

Using the definition in each of the following situations indicate whether $f = O(g)$, or $f = \Omega(g)$, or both (in which case $f = \Theta(g)$).

① $f(n) = n - 100$, $g(n) = n - 200$

② $f(n) = n2^n$, $g(n) = 3^n$



Well, now you know the basics. Time to work!

From Dasgupta's Algorithms book, exercise 0.1

Using the definition in each of the following situations indicate whether $f = O(g)$, or $f = \Omega(g)$, or both (in which case $f = \Theta(g)$).

① $f(n) = n - 100$, $g(n) = n - 200$

② $f(n) = n2^n$, $g(n) = 3^n$



Exercise

Let's try this one!

Show that $\sum_{k=1}^n \frac{1}{k^2}$ is bounded by a constant. (help me here!).



Exercise

From Cormen's book exercise 2.3-4

We can express insertion sort as a recursive procedure as follows. In order to sort $A[1 \dots n]$, we recursively sort $A[1 \dots n - 1]$ and then insert $A[n]$ into the sorted array. Write a recurrence for the running time of this recursive version of insertion sort.



Exercise

From Cormen's book exercise 3.1-7

Prove that $o(g(n)) \cap \omega(g(n))$ is the empty set.



Exercise

From Cormen's book exercise 3.2-8

Show that $k \ln k = \Theta(n)$ implies that $k = \Theta\left(\frac{n}{\ln n}\right)$.



Exercise

From Cormen's book exercise 4.3-1, 4.3-6

① Show that the solution of $T(n) = T(\lceil \frac{n}{2} \rceil) + 1$ is $O(\lg n)$.

② Show that the solution of $T(n) = 2T(\lfloor \frac{n}{2} \rfloor) + 1$ is $\Omega(n \lg n)$.



Exercise

From Cormen's book exercise 4.3-1, 4.3-6

- 1 Show that the solution of $T(n) = T(\lceil \frac{n}{2} \rceil) + 1$ is $O(\lg n)$.
- 2 Show that the solution of $T(n) = 2T(\lfloor \frac{n}{2} \rfloor) + 1$ is $\Omega(n \lg n)$.



Exercise

From Cormen's book exercise 2.1-3

Consider the searching problem:

Input: A sequence of n numbers $A = \langle a_1, a_2, \dots, a_n \rangle$ and a value v .

Output: An index i such that $v = A[i]$ or the special value NIL if v does not appear in A .

Write pseudocode for linear search, which scans through the sequence, looking for v . Using a loop invariant, prove that your algorithm is correct. Make sure that your loop invariant fulfills the three necessary properties.

