

Analysis of Algorithms

Divide and Conquer

Andres Mendez-Vazquez

January 10, 2018

Outline

1 Divide and Conquer: The Holy Grail!!

- Introduction
- Split problems into smaller ones

2 Divide and Conquer

- Not only that, we can define functions recursively
- Classic Application: Divide and Conquer
- Using Recursion to Calculate Complexities

3 Using Induction to prove Algorithm Correctness

- Relation Between Recursion and Induction
- Now, Structural Induction!!!
- Example of the Use of Structural Induction for Proving Loop Correctness
 - The Structure of the Inductive Proof for a Loop
 - Insertion Sort Proof

4 Asymptotic Notation

- Big Notation
- Relation with step count
- The Terrible Reality
- The Little Bounds
- Interpreting the Notation
- Properties

5 Method to Solve Recursions

- Substitution Method
- The Recursion-Tree Method
- The Master Method



Outline

1 Divide and Conquer: The Holy Grail!!

- Introduction
 - Split problems into smaller ones

2 Divide and Conquer

- Not only that, we can define functions recursively
- Classic Application: Divide and Conquer
- Using Recursion to Calculate Complexities

3 Using Induction to prove Algorithm Correctness

- Relation Between Recursion and Induction
- Now, Structural Induction!!!
- Example of the Use of Structural Induction for Proving Loop Correctness
 - The Structure of the Inductive Proof for a Loop
 - Insertion Sort Proof

4 Asymptotic Notation

- Big Notation
- Relation with step count
- The Terrible Reality
- The Little Bounds
- Interpreting the Notation
- Properties

5 Method to Solve Recursions

- Substitution Method
- The Recursion-Tree Method
- The Master Method



Divide an Conquer

Divide et impera

A classic technique based on the multi-based recursion.



Divide an Conquer

Divide et impera

A classic technique based on the multi-based recursion.

Thus, we have

That Divide and Conquer works by recursively breaking down the problem into subproblems and solving those subproblems recursively.

• Until you reach a base case!!!



Cinvestav

Divide an Conquer

Divide et impera

A classic technique based on the multi-based recursion.

Thus, we have

That Divide and Conquer works by recursively breaking down the problem into subproblems and solving those subproblems recursively.

- Until you reach a base case!!!

Remark

Given the fact of the following equivalence:

$$\textit{Recursion} \equiv \textit{Iteration}$$



Cinvestav

Divide an Conquer

Divide et impera

A classic technique based on the multi-based recursion.

Thus, we have

That Divide and Conquer works by recursively breaking down the problem into subproblems and solving those subproblems recursively.

- Until you reach a base case!!!

Remark

Given the fact of the following equivalence:

$$\textit{Recursion} \equiv \textit{Iteration} \quad (1)$$



Cinvestav

Outline

1 Divide and Conquer: The Holy Grail!!

- Introduction
- Split problems into smaller ones

2 Divide and Conquer

- Not only that, we can define functions recursively
- Classic Application: Divide and Conquer
- Using Recursion to Calculate Complexities

3 Using Induction to prove Algorithm Correctness

- Relation Between Recursion and Induction
- Now, Structural Induction!!!
- Example of the Use of Structural Induction for Proving Loop Correctness
 - The Structure of the Inductive Proof for a Loop
 - Insertion Sort Proof

4 Asymptotic Notation

- Big Notation
- Relation with step count
- The Terrible Reality
- The Little Bounds
- Interpreting the Notation
- Properties

5 Method to Solve Recursions

- Substitution Method
- The Recursion-Tree Method
- The Master Method



Gauss and the Beginning

Carl Friedrich Gauss (1777–1855)

He devised a way to multiply two imaginary numbers as

$$(a + bi)(c + di) = ac + (ad + bc)i - bd \quad (2)$$

By realizing that

$$bc + ad = (a + b)(c + d) - ac - bd \quad (3)$$

Thus minimizing the number of multiplications from four to three.

Finally,

We can represent binary numbers like 1001 as $1000 + 01 = 2^3 \times 10 + 01$



Cinvestav

Gauss and the Beginning

Carl Friedrich Gauss (1777–1855)

He devised a way to multiply two imaginary numbers as

$$(a + bi)(c + di) = ac + (ad + bc)i - bd \quad (2)$$

By realizing that

$$bc + ad = (a + b)(c + d) - ac - bd \quad (3)$$

Thus minimizing the number of multiplications from four to three.

Example

We can represent binary numbers like 1001 as $1000 + 01 = 2^3 \times 10 + 01$



Cinvestav

Gauss and the Beginning

Carl Friedrich Gauss (1777–1855)

He devised a way to multiply two imaginary numbers as

$$(a + bi)(c + di) = ac + (ad + bc)i - bd \quad (2)$$

By realizing that

$$bc + ad = (a + b)(c + d) - ac - bd \quad (3)$$

Thus minimizing the number of multiplications from four to three.

Actually

We can represent binary numbers like 1001 as $1000 + 01 = 2^2 \times 10 + 01$



Cinvestav

Thus

We can represent numbers x, y as

- $x = x_L \circ x_R = 2^{n/2}x_L + x_R$

- $y = y_L \circ y_R = 2^{n/2}y_L + y_R$

Thus

We can represent numbers x, y as

- $x = x_L \circ x_R = 2^{n/2}x_L + x_R$
- $y = y_L \circ y_R = 2^{n/2}y_L + y_R$

Thus, the multiplication can be found by using

$$xy = (2^{n/2}x_L + x_R)(2^{n/2}y_L + y_R) = 2^n x_L y_L + 2^{n/2}(x_L y_R + x_R y_L) + x_R y_R \quad (4)$$

Thus

We can represent numbers x, y as

- $x = x_L \circ x_R = 2^{n/2}x_L + x_R$
- $y = y_L \circ y_R = 2^{n/2}y_L + y_R$

Thus, the multiplication can be found by using

$$xy = (2^{n/2}x_L + x_R)(2^{n/2}y_L + y_R) = 2^n x_L y_L + 2^{n/2}(x_L y_R + x_R y_L) + x_R y_R \quad (4)$$

However,

if we use the Gauss's trick, we only need $x_L y_L$, $x_R y_R$, $(x_L + x_R)(y_L + y_R)$ to calculate the multiplication:

- $x_L y_R + x_R y_L = (x_L + x_R)(y_L + y_R) - x_L y_L - x_R y_R$

Thus

We can represent numbers x, y as

- $x = x_L \circ x_R = 2^{n/2}x_L + x_R$
- $y = y_L \circ y_R = 2^{n/2}y_L + y_R$

Thus, the multiplication can be found by using

$$xy = (2^{n/2}x_L + x_R)(2^{n/2}y_L + y_R) = 2^n x_L y_L + 2^{n/2}(x_L y_R + x_R y_L) + x_R y_R \quad (4)$$

However

if we use the Gauss's trick, we only need $x_L y_L$, $x_R y_R$, $(x_L + x_R)(y_L + y_R)$ to calculate the multiplication:

$$\bullet x_L y_R + x_R y_L = (x_L + x_R)(y_L + y_R) - x_L y_L - x_R y_R$$

Thus

We can represent numbers x, y as

- $x = x_L \circ x_R = 2^{n/2}x_L + x_R$
- $y = y_L \circ y_R = 2^{n/2}y_L + y_R$

Thus, the multiplication can be found by using

$$xy = (2^{n/2}x_L + x_R)(2^{n/2}y_L + y_R) = 2^n x_L y_L + 2^{n/2}(x_L y_R + x_R y_L) + x_R y_R \quad (4)$$

However

if we use the Gauss's trick, we only need $x_L y_L$, $x_R y_R$, $(x_L + x_R)(y_L + y_R)$ to calculate the multiplication:

- $x_L y_R + x_R y_L = (x_L + x_R)(y_L + y_R) - x_L y_L - x_R y_R$

Now, You have this...

We have that

xy can be calculated by using the two parts, Left and Right.

Then

Thus, each x_{LL} , x_{LYR} , x_{RYL} and x_{RR} can be calculated in a similar way

Recursion

This is know as a Recursive Procedure!!!



Cinvestav

Now, You have this...

We have that

xy can be calculated by using the two parts, Left and Right.

Then

Thus, each x_Lx_L , x_Ly_R , x_Ry_L and x_Ry_R can be calculated in a similar way

Recursion

This is know as a Recursive Procedure!!!



Cinvestav

Now, You have this...

We have that

xy can be calculated by using the two parts, Left and Right.

Then

Thus, each x_Lx_L , x_Ly_R , x_Ry_L and x_Ry_R can be calculated in a similar way

Recursion

This is know as a Recursive Procedure!!!



Cinvestav

Complexities

Old Multiplication

$$T(n) = 4T\left(\frac{n}{2}\right) + \text{Some Work} \quad (5)$$

Complexities

Old Multiplication

$$T(n) = 4T\left(\frac{n}{2}\right) + \text{Some Work} \quad (5)$$

New Multiplication

$$T(n) = 3T\left(\frac{n}{2}\right) + \text{Some Work} \quad (6)$$

Complexities

Old Multiplication

$$T(n) = 4T\left(\frac{n}{2}\right) + \text{Some Work} \quad (5)$$

New Multiplication

$$T(n) = 3T\left(\frac{n}{2}\right) + \text{Some Work} \quad (6)$$

We will prove that

- For old style multiplications $O(n^2)$.

• For new style multiplications $O(n^{\log_2 3})$

Complexities

Old Multiplication

$$T(n) = 4T\left(\frac{n}{2}\right) + \text{Some Work} \quad (5)$$

New Multiplication

$$T(n) = 3T(n) + \text{Some Work} \quad (6)$$

We will prove that

- For old style multiplications $O(n^2)$.
- For new style multiplications $O(n^{\log_2 3})$

Epitaph

We can do divide and conquer

In a really unclever way!!!



Epitaph

We can do divide and conquer

In a really unclever way!!!

Or we can go and design something better

Thus, improving speedup!!!



Epitaph

We can do divide and conquer

In a really unclever way!!!

Or we can go and design something better

Thus, improving speedup!!!

The difference between

- A great design...
- Or a crappy job...



Cinvestav

Epitaph

We can do divide and conquer

In a really unclever way!!!

Or we can go and design something better

Thus, improving speedup!!!

The difference between

- A great design...
- Or a crappy job...



Cinvestav

Recursion is the base of Divide and Conquer

This is the natural way we do many things

We always attack smaller versions first of the large one!!!

Stephen Cole Kleene

- He defined the basics about the use of recursion.



Cinvestav


Recursion is the base of Divide and Conquer

This is the natural way we do many things

We always attack smaller versions first of the large one!!!

Stephen Cole Kleene

- He defined the basics about the use of recursion.



Kleene and Company

Some facts about him

- Stephen Cole Kleene (January 5, 1909 – January 25, 1994) was an American mathematician.
- One of the students of Alonzo Church!!!
 - ▶ Church is best known for the lambda calculus, Church-Turing thesis and proving the undecidability of the use of an algorithm to say Yes(Valid) or No(No Valid) to a first order logic statement on a FOL System (Proposed by David Hilbert).

Kleene and Company

Some facts about him

- Stephen Cole Kleene (January 5, 1909 – January 25, 1994) was an American mathematician.
- One of the students of Alonzo Church!!!
 - ▶ Church is best known for the lambda calculus, Church-Turing thesis and proving the undecidability of the use of an algorithm to say Yes(Valid) or No(No Valid) to a first order logic statement on a FOL System (Proposed by David Hilbert).

Recursion Theory

- Kleene, along with Alan Turing, Emil Post, and others, is best known as a founder of the branch of mathematical logic known as recursion theory.
- This theory subsequently helped to provide the foundations of theoretical computer science.

Kleene and Company

Some facts about him

- Stephen Cole Kleene (January 5, 1909 – January 25, 1994) was an American mathematician.
- One of the students of Alonzo Church!!!
 - ▶ Church is best known for the lambda calculus, Church–Turing thesis and proving the undecidability of the use of an algorithm to say Yes(Valid) or No(No Valid) to a first order logic statement on a FOL System (Proposed by David Hilbert).

Recursion Theory

- Kleene, along with Alan Turing, Emil Post, and others, is best known as a founder of the branch of mathematical logic known as recursion theory.
- This theory subsequently helped to provide the foundations of theoretical computer science.

Kleene and Company

Some facts about him

- Stephen Cole Kleene (January 5, 1909 – January 25, 1994) was an American mathematician.
- One of the students of Alonzo Church!!!
 - ▶ Church is best known for the lambda calculus, Church–Turing thesis and proving the undecidability of the use of an algorithm to say Yes(Valid) or No(No Valid) to a first order logic statement on a FOL System (Proposed by David Hilbert).

Recursion Theory

- Kleene, along with Alan Turing, Emil Post, and others, is best known as a founder of the branch of mathematical logic known as recursion theory.
- This theory subsequently helped to provide the foundations of theoretical computer science.

Kleene and Company

Some facts about him

- Stephen Cole Kleene (January 5, 1909 – January 25, 1994) was an American mathematician.
- One of the students of Alonzo Church!!!
 - ▶ Church is best known for the lambda calculus, Church–Turing thesis and proving the undecidability of the use of an algorithm to say Yes(Valid) or No(No Valid) to a first order logic statement on a FOL System (Proposed by David Hilbert).

Recursion Theory

- Kleene, along with Alan Turing, Emil Post, and others, is best known as a founder of the branch of mathematical logic known as recursion theory.
- This theory subsequently helped to provide the foundations of theoretical computer science.

Recursion

Something Notable

- Sometimes it is difficult to define an object explicitly.
 - It may be easy to define this object in smaller version of itself.
 - This process is called recursion!!!

Recursion

Something Notable

- Sometimes it is difficult to define an object explicitly.
- It may be easy to define this object in smaller version of itself.
- This process is called recursion!!!

Thus

We can use recursion to define sequences, functions, and sets.

Recursion

Something Notable

- Sometimes it is difficult to define an object explicitly.
- It may be easy to define this object in smaller version of itself.
- **This process is called recursion!!!**

Thus

We can use recursion to define sequences, functions, and sets.

Example

- $a_n = 2^n$ for $n = 0, 1, 2, \dots \implies 1, 2, 4, 8, 16, 32, \dots$
- Thus, the sequence can be defined in a recursive way:

$$a_{n+1} = 2 \times a_n$$

(7)

Recursion

Something Notable

- Sometimes it is difficult to define an object explicitly.
- It may be easy to define this object in smaller version of itself.
- **This process is called recursion!!!**

Thus

We can use recursion to define sequences, functions, and sets.

Example

- $a_n = 2^n$ for $n = 0, 1, 2, \dots \implies 1, 2, 4, 8, 16, 32, \dots$
- Thus, the sequence can be defined in a recursive way:

$$a_{n+1} = 2 \times a_n$$

Recursion

Something Notable

- Sometimes it is difficult to define an object explicitly.
- It may be easy to define this object in smaller version of itself.
- **This process is called recursion!!!**

Thus

We can use recursion to define sequences, functions, and sets.

Example

- $a_n = 2^n$ for $n = 0, 1, 2, \dots \implies 1, 2, 4, 8, 16, 32, \dots$

• Thus, the sequence can be defined in a recursive way:

$$a_{n+1} = 2 \times a_n$$

Recursion

Something Notable

- Sometimes it is difficult to define an object explicitly.
- It may be easy to define this object in smaller version of itself.
- **This process is called recursion!!!**

Thus

We can use recursion to define sequences, functions, and sets.

Example

- $a_n = 2^n$ for $n = 0, 1, 2, \dots \implies 1, 2, 4, 8, 16, 32, \dots$
- Thus, the sequence can be defined in a recursive way:

$$a_{n+1} = 2 \times a_n$$

Recursion

Something Notable

- Sometimes it is difficult to define an object explicitly.
- It may be easy to define this object in smaller version of itself.
- **This process is called recursion!!!**

Thus

We can use recursion to define sequences, functions, and sets.

Example

- $a_n = 2^n$ for $n = 0, 1, 2, \dots \implies 1, 2, 4, 8, 16, 32, \dots$
- Thus, the sequence can be defined in a recursive way:

$$a_{n+1} = 2 \times a_n \quad (7)$$

Outline

- 1 Divide and Conquer: The Holy Grail!!
 - Introduction
 - Split problems into smaller ones
- 2 Divide and Conquer
 - **Not only that, we can define functions recursively**
 - Classic Application: Divide and Conquer
 - Using Recursion to Calculate Complexities
- 3 Using Induction to prove Algorithm Correctness
 - Relation Between Recursion and Induction
 - Now, Structural Induction!!!
 - Example of the Use of Structural Induction for Proving Loop Correctness
 - The Structure of the Inductive Proof for a Loop
 - Insertion Sort Proof
- 4 Asymptotic Notation
 - Big Notation
 - Relation with step count
 - The Terrible Reality
 - The Little Bounds
 - Interpreting the Notation
 - Properties
- 5 Method to Solve Recursions
 - Substitution Method
 - The Recursion-Tree Method
 - The Master Method



Recursively Defined Functions

First

Assume T is a function with the set of nonnegative integers as its domain.



Recursively Defined Functions

First

Assume T is a function with the set of nonnegative integers as its domain.

Second

We use two steps to define T :

Basis step:

Specify the value of $T(0)$.

Recursive step:

Give a rule for $T(x)$ using $T(y)$ where $0 \leq y < x$.



Cinvestav

Recursively Defined Functions

First

Assume T is a function with the set of nonnegative integers as its domain.

Second

We use two steps to define T :

Basis step:

Specify the value of $T(0)$.

Recursive step:

Give a rule for $T(x)$ using $T(y)$ where $0 \leq y < x$.

Third

Such a definition is called a recursive or inductive definition.



Cinvestav

Recursively Defined Functions

First

Assume T is a function with the set of nonnegative integers as its domain.

Second

We use two steps to define T :

Basis step:

Specify the value of $T(0)$.

Recursive step:

Give a rule for $T(x)$ using $T(y)$ where $0 \leq y < x$.

Third

Such a definition is called a recursive or inductive definition.



Cinvestav

Recursively Defined Functions

First

Assume T is a function with the set of nonnegative integers as its domain.

Second

We use two steps to define T :

Basis step:

Specify the value of $T(0)$.

Recursive step:

Give a rule for $T(x)$ using $T(y)$ where $0 \leq y < x$.

Third

Such a definition is called a recursive or inductive definition.



Cinvestav

Recursively Defined Functions

First

Assume T is a function with the set of nonnegative integers as its domain.

Second

We use two steps to define T :

Basis step:

Specify the value of $T(0)$.

Recursive step:

Give a rule for $T(x)$ using $T(y)$ where $0 \leq y < x$.

Third

Such a definition is called a recursive or inductive definition.



Cinvestav

Recursively Defined Functions

First

Assume T is a function with the set of nonnegative integers as its domain.

Second

We use two steps to define T :

Basis step:

Specify the value of $T(0)$.

Recursive step:

Give a rule for $T(x)$ using $T(y)$ where $0 \leq y < x$.

Thus

Such a definition is called a recursive or inductive definition.



Cinvestav

Example

Can you give me the following?

Give an inductive definition of the factorial function $T(n) = n!$.

Base case

Which is the base case?

Recursive case

What is the recursive case?



Cinvestav

Example

Can you give me the following?

Give an inductive definition of the factorial function $T(n) = n!$.

Base case

Which is the base case?

Recursive case

What is the recursive case?



Cinvestav

Example

Can you give me the following?

Give an inductive definition of the factorial function $T(n) = n!$.

Base case

Which is the base case?

Recursive case

What is the recursive case?



Cinvestav

We can go further...

Recursively Defined Sets and Structures

- Assume S is a set.
- We can use two steps to define the elements of S .



We can go further...

Recursively Defined Sets and Structures

- Assume S is a set.
- We can use two steps to define the elements of S .

Basis Step

Specify an initial collection of elements.



Cinvestav

We can go further...

Recursively Defined Sets and Structures

- Assume S is a set.
- We can use two steps to define the elements of S .

Basis Step

Specify an initial collection of elements.

Recursive Step

Give a rule for forming new elements from those already known to be in S .



Cinvestav

We can go further...

Recursively Defined Sets and Structures

- Assume S is a set.
- We can use two steps to define the elements of S .

Basis Step

Specify an initial collection of elements.

Recursive Step

Give a rule for forming new elements from those already known to be in S .



Cinvestav

Example

Consider

Consider $S \subseteq \mathbb{Z}$ defined by...

Base Step

$3 \in S$

Inductive Step

If $x \in S$ and $y \in S$, then $x + y \in S$.



Example

Consider

Consider $S \subseteq \mathbb{Z}$ defined by...

Basis Step

$3 \in S$

Inductive Step

If $x \in S$ and $y \in S$, then $x + y \in S$.



Cinvestav

Example

Consider

Consider $S \subseteq \mathbb{Z}$ defined by...

Basis Step

$3 \in S$

Recursive Step

If $x \in S$ and $y \in S$, then $x + y \in S$.



Cinvestav

Example

Elements

- $3 \in S$
- $3 + 3 = 6 \in S$
- $6 + 3 = 9 \in S$
- $6 + 6 = 12 \in S$
- ...



Outline

1 Divide and Conquer: The Holy Grail!!

- Introduction
- Split problems into smaller ones

2 Divide and Conquer

- Not only that, we can define functions recursively
- **Classic Application: Divide and Conquer**
- Using Recursion to Calculate Complexities

3 Using Induction to prove Algorithm Correctness

- Relation Between Recursion and Induction
- Now, Structural Induction!!!
- Example of the Use of Structural Induction for Proving Loop Correctness
 - The Structure of the Inductive Proof for a Loop
 - Insertion Sort Proof

4 Asymptotic Notation

- Big Notation
- Relation with step count
- The Terrible Reality
- The Little Bounds
- Interpreting the Notation
- Properties

5 Method to Solve Recursions

- Substitution Method
- The Recursion-Tree Method
- The Master Method



Divide and Conquer

Divide

Split problem into a number of subproblems.

Conquer

Solve each subproblem recursively.

Combine

The solution of the problems into the solution of the original problem.



Divide and Conquer

Divide

Split problem into a number of subproblems.

Conquer

Solve each subproblem recursively.

Combine

The solution of the problems into the solution of the original problem.



Cinvestav

Divide and Conquer

Divide

Split problem into a number of subproblems.

Conquer

Solve each subproblem recursively.

Combine

The solution of the problems into the solution of the original problem.



Cinvestav

Time Complexities

Definition

- Given an input as a string where the problem is being encoded using an alphabet Σ ,
 - ▶ The **time complexity** quantifies the amount of time taken by an algorithm to run as a function on the length of such string.



The Divide and Conquer of Merge Sort

Merge-Sort(A, p, r)

- 1 if $p < r$ then
- 2 $q \leftarrow \left\lfloor \frac{p+r}{2} \right\rfloor$
- 3 Merge-Sort(A, p, q)
- 4 Merge-Sort($A, q + 1, r$)
- 5 MERGE(A, p, q, r)

Explanation

Divide part into the conquer!!!



Cinvestav

The Divide and Conquer of Merge Sort

Merge-Sort(A, p, r)

- ① if $p < r$ then
- ② $q \leftarrow \left\lfloor \frac{p+r}{2} \right\rfloor$
- ③ Merge-Sort(A, p, q)
- ④ Merge-Sort($A, q + 1, r$)
- ⑤ MERGE(A, p, q, r)

Explanation

The combine part!!!



Cinvestav

Merge Sort

- Merge(A, p, q, r)
 - 1 $n_1 \leftarrow q - p + 1, n_2 \leftarrow r - p$
 - 2 let $L[1, 2, \dots, n_1 + 1]$ and $R[1, 2, \dots, n_2 + 1]$ be new arrays.
 - 3 for $i \leftarrow 1$ to n_1
 - 4 $L[i] \leftarrow A[p + i - 1]$
 - 5 for $j \leftarrow 1$ to n_2
 - 6 $R[j] \leftarrow A[q + j]$
 - 7 $L[n_1 + 1] \leftarrow \infty$
 - 8 $R[n_2 + 1] \leftarrow \infty$
 - 9 $i \leftarrow 1, j \leftarrow 1$
 - 10 for $k \leftarrow p$ to r
 - 11 if $L[i] \leq R[j]$ then
 - 12 $A[k] \leftarrow L[i]$
 - 13 $i \leftarrow i + 1$
 - 14 else
 - 15 $A[k] \leftarrow R[j]$
 - 16 $j \leftarrow j + 1$

Explanation

- Copy all to be merged lists into two containers.



Merge Sort


- Merge(A, p, q, r)
 - 1 $n_1 \leftarrow q - p + 1, n_2 \leftarrow r - p$
 - 2 let $L[1, 2, \dots, n_1 + 1]$ and $R[1, 2, \dots, n_2 + 1]$ be new arrays.
 - 3 for $i \leftarrow 1$ to n_1
 - 4 $L[i] \leftarrow A[p + i - 1]$
 - 5 for $j \leftarrow 1$ to n_2
 - 6 $R[j] \leftarrow A[q + j]$
 - 7 $L[n_1 + 1] \leftarrow \infty$
 - 8 $R[n_2 + 1] \leftarrow \infty$
 - 9 $i \leftarrow 1, j \leftarrow 1$
 - 10 for $k \leftarrow p$ to r
 - 11 if $L[i] \leq R[j]$ then
 - 12 $A[k] \leftarrow L[i]$
 - 13 $i \leftarrow i + 1$
 - 14 else
 - 15 $A[k] \leftarrow R[j]$
 - 16 $j \leftarrow j + 1$

Explanation

- Merging part.



The Merge Sort Recursion Cost Function



Outline

1 Divide and Conquer: The Holy Grail!!

- Introduction
- Split problems into smaller ones

2 Divide and Conquer

- Not only that, we can define functions recursively
- Classic Application: Divide and Conquer
- **Using Recursion to Calculate Complexities**

3 Using Induction to prove Algorithm Correctness

- Relation Between Recursion and Induction
- Now, Structural Induction!!!
- Example of the Use of Structural Induction for Proving Loop Correctness
 - The Structure of the Inductive Proof for a Loop
 - Insertion Sort Proof

4 Asymptotic Notation

- Big Notation
- Relation with step count
- The Terrible Reality
- The Little Bounds
- Interpreting the Notation
- Properties

5 Method to Solve Recursions

- Substitution Method
- The Recursion-Tree Method
- The Master Method



Recursive Functions

Using Church-Turing Thesis

Every computable function from natural numbers to natural numbers is recursive and computable.

YES!!

We can use recursive functions to represent the TOTAL number of steps carried when computing an ALGORITHM



Cinvestav

Recursive Functions

Using Church-Turing Thesis

Every computable function from natural numbers to natural numbers is recursive and computable.

YES!!!

We can use recursive functions to represent the TOTAL number of steps carried when computing an ALGORITHM



Cinvestav

Thus, we have

Each Step for ONE Merging takes...

A certain constant time c !!!

Thus, if we merge n elements

Total time at level 1 of recursion:

$$cn \quad (8)$$

In addition:

We have that the recursion split each work by

$$\frac{1}{2^i}, \text{ for } i = 1, \dots, \log n \quad (9)$$



Cinvestav

Thus, we have

Each Step for ONE Merging takes...

A certain constant time c !!

Thus, if we merge n elements

Total time at level 1 of recursion:

$$cn \quad (8)$$

In addition:

We have that the recursion split each work by

$$\frac{1}{2^i}, \text{ for } i = 1, \dots, \log n \quad (9)$$



Cinvestav

Thus, we have

Each Step for ONE Merging takes...

A certain constant time c !!

Thus, if we merge n elements

Total time at level 1 of recursion:

$$cn \quad (8)$$

In addition...

We have that the recursion split each work by

$$\frac{1}{2^i}, \text{ for } i = 1, \dots, \log n \quad (9)$$



Cinvestav

Thus, we have the following Recursion

Base Case $n = 1$

$$T(n) = c \quad (10)$$

Where c stands for a constant in the number of time units or assembly instructions per line!!!

Recursive Step $n > 1$

$$T(n) = 2T\left(\frac{n}{2}\right) + cn \quad (11)$$

Finally

$$T(n) = \begin{cases} c & \text{if } n = 1 \\ 2T\left(\frac{n}{2}\right) + cn & \text{if } n > 1 \end{cases} \quad (12)$$

Thus, we have the following Recursion

Base Case $n = 1$

$$T(n) = c \quad (10)$$

Where c stands for a constant in the number of time units or assembly instructions per line!!!

Recursive Step $n > 1$

$$2T\left(\frac{n}{2}\right) + cn \quad (11)$$

Finally

$$T(n) = \begin{cases} c & \text{if } n = 1 \\ 2T\left(\frac{n}{2}\right) + cn & \text{if } n > 1 \end{cases} \quad (12)$$

Thus, we have the following Recursion

Base Case $n = 1$

$$T(n) = c \quad (10)$$

Where c stands for a constant in the number of time units or assembly instructions per line!!!

Recursive Step $n > 1$

$$2T\left(\frac{n}{2}\right) + cn \quad (11)$$

Finally

$$T(n) = \begin{cases} c & \text{if } n = 1 \\ 2T\left(\frac{n}{2}\right) + cn & \text{if } n > 1 \end{cases} \quad (12)$$

Outline

- 1 Divide and Conquer: The Holy Grail!!
 - Introduction
 - Split problems into smaller ones
- 2 Divide and Conquer
 - Not only that, we can define functions recursively
 - Classic Application: Divide and Conquer
 - Using Recursion to Calculate Complexities
- 3 Using Induction to prove Algorithm Correctness
 - **Relation Between Recursion and Induction**
 - Now, Structural Induction!!!
 - Example of the Use of Structural Induction for Proving Loop Correctness
 - The Structure of the Inductive Proof for a Loop
 - Insertion Sort Proof
- 4 Asymptotic Notation
 - Big Notation
 - Relation with step count
 - The Terrible Reality
 - The Little Bounds
 - Interpreting the Notation
 - Properties
- 5 Method to Solve Recursions
 - Substitution Method
 - The Recursion-Tree Method
 - The Master Method



Recursion and Induction

Something Notable

When a sequence is defined recursively, mathematical induction can be used to prove results about the sequence.



Cinvestav

For Example

We want

To show that the set S is the set A of all positive integers that are multiples of 3.

First step

Show that if $\forall k \geq 1$ $P(k)$ is true, then $P(k+1)$ is true

We define first the inductive hypothesis

$P(k) : 3k \in S$ is true



Cinvestav

For Example

We want

To show that the set S is the set A of all positive integers that are multiples of 3.

First $A \subseteq S$

Show that if $\forall k \geq 1$ $P(k)$ is true, then $P(k+1)$ is true

We define first the inductive hypothesis

$P(k) : 3k \in S$ is true



Cinvestav

For Example

We want

To show that the set S is the set A of all positive integers that are multiples of 3.

First $A \subseteq S$

Show that if $\forall k \geq 1$ $P(k)$ is true, then $P(k+1)$ is true

We define, first, the inductive hypothesis

$P(k) : 3k \in S$ is true



Cinvestav

Thus

We know the following by definition

$$3 \in S$$



Cinvestav

Thus

We know the following by definition

$$3 \in S$$

We need to prove that for any k

$$P(k+1) : 3(k+1) = 3k+3 \in S$$



Cinvestav

Thus

We know the following by definition

$$3 \in S$$

We need to prove that for any k

$$P(k+1) : 3(k+1) = 3k+3 \in S$$

We have using the recursive definition

We know that $3k \in S$ and $3 \in S$ is true, therefore by definition

$$3k+3 = 3(k+1) \in S$$



Cinvestav

Thus

We know the following by definition

$$3 \in S$$

We need to prove that for any k

$$P(k+1) : 3(k+1) = 3k+3 \in S$$

We have using the recursive definition

We know that $3k \in S$ and $3 \in S$ is true, therefore by definition

$$3k+3 = 3(k+1) \in S$$



Cinvestav

Finally

- We have that for $x \in A$ with $x = 3k$ for $k \geq 1$, then by the previous proof $3k \in S!!!$
- Then, $A \subseteq S!!!$



Finally

- We have that for $x \in A$ with $x = 3k$ for $k \geq 1$, then by the previous proof $3k \in S$!!!
- Then, $A \subseteq S$!!!

Now show that $S \subseteq A$

Or $\forall x, x \in S$ then $x \in A$



Now

Finally

- We have that for $x \in A$ with $x = 3k$ for $k \geq 1$, then by the previous proof $3k \in S$!!!
- Then, $A \subseteq S$!!!

Now, show that $S \subseteq A$

Or $\forall x, x \in S$ then $x \in A$

Given the definition

- Basis Step: $3 \in S$
- Recursive Step: $x \in S, y \in S \Rightarrow x + y \in S$



Cinvestav

Now

Finally

- We have that for $x \in A$ with $x = 3k$ for $k \geq 1$, then by the previous proof $3k \in S$!!!
- Then, $A \subseteq S$!!!

Now, show that $S \subseteq A$

Or $\forall x, x \in S$ then $x \in A$

Given the definition

- Basis Step: $3 \in S$
- Recursive Step: $x \in S, y \in S \Rightarrow x + y \in S$



Cinvestav

Finally

- We have that for $x \in A$ with $x = 3k$ for $k \geq 1$, then by the previous proof $3k \in S!!!$
- Then, $A \subseteq S!!!$

Now, show that $S \subseteq A$

Or $\forall x, x \in S$ then $x \in A$

Given the definition

- Basis Step: $3 \in S$
- Recursive Step: $x \in S, y \in S \Rightarrow x + y \in S$



Then

First, $3 \in S$

It is clear that $3 \in A$



Then

First, $3 \in S$

It is clear that $3 \in A$

Now, given $x \in S$ and $y \in S$

- if $x \in A$ and $y \in A$

- Then, x and y are multiples of 3



Then

First, $3 \in S$

It is clear that $3 \in A$

Now, given $x \in S$ and $y \in S$

- if $x \in A$ and $y \in A$
- Then, x and y are multiples of 3

Therefore

- $x + y$ is a multiple of 3 with $x + y \in S$ by definition, and also $x + y \in A$
- Therefore, $S \subseteq A$



Then

First, $3 \in S$

It is clear that $3 \in A$

Now, given $x \in S$ and $y \in S$

- if $x \in A$ and $y \in A$
- Then, x and y are multiples of 3

Therefore

- $x + y$ is a multiple of 3 with $x + y \in S$ by definition, and also $x + y \in A$
- Therefore, $S \subset A$



Cinvestav

Then

First, $3 \in S$

It is clear that $3 \in A$

Now, given $x \in S$ and $y \in S$

- if $x \in A$ and $y \in A$
- Then, x and y are multiples of 3

Therefore

- $x + y$ is a multiple of 3 with $x + y \in S$ by definition, and also $x + y \in A$
- Therefore, $S \subseteq A$



Cinvestav

Outline

- 1 Divide and Conquer: The Holy Grail!!
 - Introduction
 - Split problems into smaller ones
- 2 Divide and Conquer
 - Not only that, we can define functions recursively
 - Classic Application: Divide and Conquer
 - Using Recursion to Calculate Complexities
- 3 Using Induction to prove Algorithm Correctness
 - Relation Between Recursion and Induction
 - **Now, Structural Induction!!!**
 - Example of the Use of Structural Induction for Proving Loop Correctness
 - The Structure of the Inductive Proof for a Loop
 - Insertion Sort Proof
- 4 Asymptotic Notation
 - Big Notation
 - Relation with step count
 - The Terrible Reality
 - The Little Bounds
 - Interpreting the Notation
 - Properties
- 5 Method to Solve Recursions
 - Substitution Method
 - The Recursion-Tree Method
 - The Master Method



Structural induction

Something Notable

Instead of mathematical induction to prove a result about a recursively defined sets, we can use a more convenient form of induction known as structural induction.



Structural induction

Something Notable

Instead of mathematical induction to prove a result about a recursively defined sets, we can use a more convenient form of induction known as structural induction.

First

- Assume we have a recursive definition for a set S .
- Given $n \in S$, we must show that $P(n)$ is true using structural induction.



Cinvestav

Structural induction

Something Notable

Instead of mathematical induction to prove a result about a recursively defined sets, we can use a more convenient form of induction known as structural induction.

First

- Assume we have a recursive definition for a set S .
- Given $n \in S$, we must show that $P(n)$ is true using structural induction.



Cinvestav

Definition of Structural induction

Basis Step

- Assume j is an element specified in the base step of the definition.
- Show that $\forall j, P(j)$ is true.



Definition of Structural induction

Basis Step

- Assume j is an element specified in the base step of the definition.
- Show that $\forall j, P(j)$ is true.

Recursive step

- Let x be a new element constructed in the recursive step of the definition.
- Assume k_1, k_2, \dots, k_m are elements used to construct an element x in the recursive step of the definition.
- Show that
$$\forall k_1, k_2, \dots, k_m ((P(k_1) \wedge P(k_2) \wedge \dots \wedge P(k_m)) \rightarrow P(x)).$$



Definition of Structural induction

Basis Step

- Assume j is an element specified in the base step of the definition.
- Show that $\forall j, P(j)$ is true.

Recursive step

- Let x be a new element constructed in the recursive step of the definition.
- Assume k_1, k_2, \dots, k_m are elements used to construct an element x in the recursive step of the definition.
- Show that
$$\forall k_1, k_2, \dots, k_m ((P(k_1) \wedge P(k_2) \wedge \dots \wedge P(k_m)) \rightarrow P(x)).$$



Definition of Structural induction

Basis Step

- Assume j is an element specified in the base step of the definition.
- Show that $\forall j, P(j)$ is true.

Recursive step

- Let x be a new element constructed in the recursive step of the definition.
- Assume k_1, k_2, \dots, k_m are elements used to construct an element x in the recursive step of the definition.
- Show that
$$\forall k_1, k_2, \dots, k_m ((P(k_1) \wedge P(k_2) \wedge \dots \wedge P(k_m)) \rightarrow P(x)).$$



Definition of Structural induction

Basis Step

- Assume j is an element specified in the base step of the definition.
- Show that $\forall j, P(j)$ is true.

Recursive step

- Let x be a new element constructed in the recursive step of the definition.
- Assume k_1, k_2, \dots, k_m are elements used to construct an element x in the recursive step of the definition.
- Show that
$$\forall k_1, k_2, \dots, k_m ((P(k_1) \wedge P(k_2) \wedge \dots \wedge P(k_m)) \rightarrow P(x)).$$



Therefore

We can use structural induction

To prove the correctness of a loop in an algorithm!!!



Cinvestav

Therefore

We can use structural induction

To prove the correctness of a loop in an algorithm!!!

Yes!!! In a loop we have an iteration

- That goes from 1 to n .

• And it has a property P that needs to be maintained!!!



Cinvestav

Therefore

We can use structural induction

To prove the correctness of a loop in an algorithm!!!

Yes!!! In a loop we have an iteration

- That goes from 1 to n .
- And it has a property P that needs to be maintained!!!

Thus, the new element to be constructed

It can be our array to be sorted!!!



Cinvestav

Therefore

We can use structural induction

To prove the correctness of a loop in an algorithm!!!

Yes!!! In a loop we have an iteration

- That goes from 1 to n .
- And it has a property P that needs to be maintained!!!

Thus, the new element to be constructed

It can be our array to be sorted!!!



Cinvestav

Outline

- 1 Divide and Conquer: The Holy Grail!!
 - Introduction
 - Split problems into smaller ones
- 2 Divide and Conquer
 - Not only that, we can define functions recursively
 - Classic Application: Divide and Conquer
 - Using Recursion to Calculate Complexities
- 3 Using Induction to prove Algorithm Correctness
 - Relation Between Recursion and Induction
 - Now, Structural Induction!!!
 - **Example of the Use of Structural Induction for Proving Loop Correctness**
 - The Structure of the Inductive Proof for a Loop
 - Insertion Sort Proof
- 4 Asymptotic Notation
 - Big Notation
 - Relation with step count
 - The Terrible Reality
 - The Little Bounds
 - Interpreting the Notation
 - Properties
- 5 Method to Solve Recursions
 - Substitution Method
 - The Recursion-Tree Method
 - The Master Method



Again Insertion Sort - Proving the Sorting Property

Data: Unsorted Sequence A

Result: Sort Sequence A

Insertion Sort(A)

for $j \leftarrow 2$ **to** $\text{length}(A)$ **do**

$\text{key} \leftarrow A[j];$

 // Insert $A[j]$ Insert $A[j]$ into the sorted sequence
 $A[1, \dots, j - 1]$

$i \leftarrow j - 1;$

while $i > 0$ *and* $A[i] > \text{key}$ **do**

$A[i + 1] \leftarrow A[i];$

$i \leftarrow i - 1;$

end

$A[i + 1] \leftarrow \text{key}$

end



Outline

- 1 Divide and Conquer: The Holy Grail!!
 - Introduction
 - Split problems into smaller ones
- 2 Divide and Conquer
 - Not only that, we can define functions recursively
 - Classic Application: Divide and Conquer
 - Using Recursion to Calculate Complexities
- 3 Using Induction to prove Algorithm Correctness
 - Relation Between Recursion and Induction
 - Now, Structural Induction!!!
 - Example of the Use of Structural Induction for Proving Loop Correctness
 - The Structure of the Inductive Proof for a Loop
 - Insertion Sort Proof
- 4 Asymptotic Notation
 - Big Notation
 - Relation with step count
 - The Terrible Reality
 - The Little Bounds
 - Interpreting the Notation
 - Properties
- 5 Method to Solve Recursions
 - Substitution Method
 - The Recursion-Tree Method
 - The Master Method



The Structure of the Inductive Proof for a Loop

You have an initial input n

- Input of n elements.

• Always be sure about your input!!!



The Structure of the Inductive Proof for a Loop

You have an initial input n

- Input of n elements.
- Always be sure about your input!!!

Then, we have the following steps:

- Initialization - Before the loop.
- Maintenance - In the loop.
- Termination - At the end of the loop.



The Structure of the Inductive Proof for a Loop

You have an initial input n

- Input of n elements.
- Always be sure about your input!!!

Then, we have the following steps

- 1 Initialization - Before the loop.
- 2 Maintenance - In the loop.
- 3 Termination - At the end of the loop.



The Structure of the Inductive Proof for a Loop

You have an initial input n

- Input of n elements.
- Always be sure about your input!!!

Then, we have the following steps

- 1 Initialization - Before the loop.
- 2 Maintenance - In the loop.
- 3 Termination - At the end of the loop.



Cinvestav

The Structure of the Inductive Proof for a Loop

You have an initial input n

- Input of n elements.
- Always be sure about your input!!!

Then, we have the following steps

- 1 Initialization - Before the loop.
- 2 Maintenance - In the loop.
- 3 Termination - At the end of the loop.



Initialization

We have the following before the loop

- That the condition is true for one element!!!

► For example, in insertion sort $A[1]$ is an already sorted array.



Cinvestav

Initialization

We have the following before the loop

- That the condition is true for one element!!!
 - ▶ For example, in insertion sort $A[1]$ is an already sorted array.



Cinvestav

First, we must be able to prove that

- The property holds before entering into the loop.

► That the array $A[1 \dots j - 1]$ is sorted!!!



Maintenance

First, we must be able to prove that

- The property holds before entering into the loop.
 - ▶ That the array $A[1 \dots j - 1]$ is sorted!!!

Then, we need to prove that

The insertion sort maintains the sorted property during the loop.



Cinvestav

Maintenance

First, we must be able to prove that

- The property holds before entering into the loop.
 - ▶ That the array $A[1 \dots j - 1]$ is sorted!!!

Then, we need to prove that

The insertion sort maintains the sorted property during the loop.



Cinvestav

Termination

We need

- To prove that the property is TRUE for n elements.
 - ▶ At the end of the algorithm $A[1, \dots, n]$ is a sorted



Outline

- 1 Divide and Conquer: The Holy Grail!!
 - Introduction
 - Split problems into smaller ones
- 2 Divide and Conquer
 - Not only that, we can define functions recursively
 - Classic Application: Divide and Conquer
 - Using Recursion to Calculate Complexities
- 3 Using Induction to prove Algorithm Correctness
 - Relation Between Recursion and Induction
 - Now, Structural Induction!!!
 - **Example of the Use of Structural Induction for Proving Loop Correctness**
 - The Structure of the Inductive Proof for a Loop
 - **Insertion Sort Proof**
- 4 Asymptotic Notation
 - Big Notation
 - Relation with step count
 - The Terrible Reality
 - The Little Bounds
 - Interpreting the Notation
 - Properties
- 5 Method to Solve Recursions
 - Substitution Method
 - The Recursion-Tree Method
 - The Master Method



For example, Insertion Sort (Thanks to Luis Rodriguez Oracle Master 2012)

First, we define the following sets with sorted elements

- $Less = \langle x_1, \dots, x_k | x_i < key, i = 1, \dots, k \rangle$
- $Greater = \langle x_1, \dots, x_m | x_j > key, j = 1, \dots, m \rangle$
- $I =$ elements still not compared to the key

For example, Insertion Sort (Thanks to Luis Rodriguez Oracle Master 2012)

First, we define the following sets with sorted elements

- $Less = \langle x_1, \dots, x_k | x_i < key, i = 1, \dots, k \rangle$
- $Greater = \langle x_1, \dots, x_m | x_j > key, j = 1, \dots, m \rangle$
- $I =$ elements still not compared to the key

Initialization

We have $A[1..1]$ with only one element \Rightarrow it is sorted

For example, Insertion Sort (Thanks to Luis Rodriguez Oracle Master 2012)

First, we define the following sets with sorted elements

- $Less = \langle x_1, \dots, x_k | x_i < key, i = 1, \dots, k \rangle$
- $Greater = \langle x_1, \dots, x_m | x_j > key, j = 1, \dots, m \rangle$
- I = elements still not compared to the key

Initialization

We have $A[1..1]$ with only one element \Rightarrow it is sorted

Maintenance

Before we enter to the inner while loop, we have

- $A[1..j-1]$ an already sorted array
- $Less = \emptyset$
- $Greater = \emptyset$
- $I = A[1..j-1]$.

For example, Insertion Sort (Thanks to Luis Rodriguez Oracle Master 2012)

First, we define the following sets with sorted elements

- $Less = \langle x_1, \dots, x_k | x_i < key, i = 1, \dots, k \rangle$
- $Greater = \langle x_1, \dots, x_m | x_j > key, j = 1, \dots, m \rangle$
- I = elements still not compared to the key

Initialization

We have $A[1..1]$ with only one element \Rightarrow it is sorted

Maintenance

Before we enter to the inner while loop, we have

- $A[1..j-1]$ an already sorted array
- $Less = \emptyset$
- $Greater = \emptyset$
- $I = A[1..j-1]$.

For example, Insertion Sort (Thanks to Luis Rodriguez Oracle Master 2012)

First, we define the following sets with sorted elements

- $Less = \langle x_1, \dots, x_k | x_i < key, i = 1, \dots, k \rangle$
- $Greater = \langle x_1, \dots, x_m | x_j > key, j = 1, \dots, m \rangle$
- I = elements still not compared to the key

Initialization

We have $A[1..1]$ with only one element \Rightarrow it is sorted

Maintenance

Before we enter to the inner while loop, we have

- $A[1..j-1]$ an already sorted array
- $Less = \emptyset$
- $Greater = \emptyset$
- $I = A[1..j-1]$.

For example, Insertion Sort (Thanks to Luis Rodriguez Oracle Master 2012)

First, we define the following sets with sorted elements

- $Less = \langle x_1, \dots, x_k | x_i < key, i = 1, \dots, k \rangle$
- $Greater = \langle x_1, \dots, x_m | x_j > key, j = 1, \dots, m \rangle$
- I = elements still not compared to the key

Initialization

We have $A[1..1]$ with only one element \Rightarrow it is sorted

Maintenance

Before we enter to the inner while loop, we have

- 1 $A[1..j-1]$ an already **sorted array**

• $Less = \emptyset$

• $Greater = \emptyset$

• $I = A[1..j-1]$

For example, Insertion Sort (Thanks to Luis Rodriguez Oracle Master 2012)

First, we define the following sets with sorted elements

- $Less = \langle x_1, \dots, x_k | x_i < key, i = 1, \dots, k \rangle$
- $Greater = \langle x_1, \dots, x_m | x_j > key, j = 1, \dots, m \rangle$
- I = elements still not compared to the key

Initialization

We have $A[1..1]$ with only one element \Rightarrow it is sorted

Maintenance

Before we enter to the inner while loop, we have

- 1 $A[1..j-1]$ an already **sorted array**
- 2 $Less = \emptyset$
- 3 $Greater = \emptyset$
- 4 $I = A[1..j-1]$

For example, Insertion Sort (Thanks to Luis Rodriguez Oracle Master 2012)

First, we define the following sets with sorted elements

- $Less = \langle x_1, \dots, x_k | x_i < key, i = 1, \dots, k \rangle$
- $Greater = \langle x_1, \dots, x_m | x_j > key, j = 1, \dots, m \rangle$
- I = elements still not compared to the key

Initialization

We have $A[1..1]$ with only one element \Rightarrow it is sorted

Maintenance

Before we enter to the inner while loop, we have

- 1 $A[1..j-1]$ an already **sorted array**
- 2 $Less = \emptyset$
- 3 $Greater = \emptyset$

• $I = A[1..j-1]$

For example, Insertion Sort (Thanks to Luis Rodriguez Oracle Master 2012)

First, we define the following sets with sorted elements

- $Less = \langle x_1, \dots, x_k | x_i < key, i = 1, \dots, k \rangle$
- $Greater = \langle x_1, \dots, x_m | x_j > key, j = 1, \dots, m \rangle$
- I = elements still not compared to the key

Initialization

We have $A[1..1]$ with only one element \Rightarrow it is sorted

Maintenance

Before we enter to the inner while loop, we have

- ① $A[1..j-1]$ an already **sorted array**
- ② $Less = \emptyset$
- ③ $Greater = \emptyset$
- ④ $I = A[1..j-1]$.

Then

Case I

You never enter in the inner loop, thus $A[j - 1] < key \Rightarrow$
 $Less = A[1..j - 1]$, thus $A[1..j]$ is a sorted array.



Then

Case I

You never enter in the inner loop, thus $A[j - 1] < key \Rightarrow$
 $Less = A[1..j - 1]$, thus $A[1..j]$ is a sorted array.

Case II

① You entered the inner while loop.

② Thus at each iteration we have the following structure

$$A[1..j] = \boxed{I} \mid \boxed{A[i]} \mid \boxed{Greater}$$

► where $Greater = \langle A[i], A[i + 1], \dots, A[j - 1] \rangle$.

Note: I and $Greater$ are sorted such that $A[1..j]$ is sorted by itself
at this moment in the inner loop



Cinvestav

Then

Case I

You never enter in the inner loop, thus $A[j - 1] < key \Rightarrow$
 $Less = A[1..j - 1]$, thus $A[1..j]$ is a sorted array.

Case II

- 1 You entered the inner while loop.
- 2 Thus at each iteration we have the following structure

$$A[1..j] = \boxed{I \mid A[i] \mid Greater}$$

• where $Greater = (A[i], A[i + 1], \dots, A[j - 1])$.

Note: I and $Greater$ are sorted such that $A[1..j]$ is sorted by itself
at this moment in the inner loop



Cinvestav

Then

Case I

You never enter in the inner loop, thus $A[j - 1] < key \Rightarrow$
 $Less = A[1..j - 1]$, thus $A[1..j]$ is a sorted array.

Case II

- 1 You entered the inner while loop.
- 2 Thus at each iteration we have the following structure

$$A[1..j] = \boxed{I \mid A[i] \mid Greater}$$

► where $Greater = \langle A[i], A[i + 1], \dots, A[j - 1] \rangle$.

Note: I and $Greater$ are sorted such that $A[1..j]$ is sorted by itself
at this moment in the inner loop



Cinvestav

Then

Case I

You never enter in the inner loop, thus $A[j - 1] < key \Rightarrow$
 $Less = A[1..j - 1]$, thus $A[1..j]$ is a sorted array.

Case II

- 1 You entered the inner while loop.
- 2 Thus at each iteration we have the following structure

$$A[1..j] = \boxed{I \mid A[i] \mid Greater}$$

► where $Greater = \langle A[i], A[i + 1], \dots, A[j - 1] \rangle$.

Note: I and $Greater$ are sorted such that $A[1..j]$ is sorted by itself at this moment in the inner loop



Cinvestav

Thus, we get out of the inner loop once $I = \emptyset$.

- ① We have that $A[1..j] = \boxed{\text{Less} \mid A[i+1] \mid \text{Greater}}$, where $A[i+2] == A[i+1]$.

- ② Thus, $A[1..j]$ is sorted before inserting the key into the position $A[i+1]$.
- ③ Then, because elements of $A[1..j]$ are sorted,
 - ④ We have that after inserting the key at position $i+1$ in $A[1..j]$ the array is still sorted after iteration j .



Thus, we get out of the inner loop once $I = \emptyset$.

- 1 We have that $A[1...j] = \boxed{\text{Less} \mid A[i+1] \mid \text{Greater}}$, where $A[i+2] == A[i+1]$.
- 2 Thus, $A[1...j]$ is sorted before inserting the key into the position $A[i+1]$.
- 3 Then, because elements of $A[1...j]$ are sorted,
 - 4 We have that after inserting the key at position $i+1$ in $A[1...j]$ the array is still sorted after iteration j .



Thus, we get out of the inner loop once $I = \emptyset$.

- 1 We have that $A[1...j] = \boxed{\text{Less} \mid A[i+1] \mid \text{Greater}}$, where $A[i+2] == A[i+1]$.
- 2 Thus, $A[1...j]$ is sorted before inserting the key into the position $A[i+1]$.
- 3 Then, because elements of $A[1...j]$ are sorted,

• We have that after inserting the key at position $i+1$ in $A[1...j]$ the array is still sorted after iteration j .



Thus, we get out of the inner loop once $I = \emptyset$.

- ① We have that $A[1...j] = \boxed{\text{Less} \mid A[i+1] \mid \text{Greater}}$, where $A[i+2] == A[i+1]$.
- ② Thus, $A[1...j]$ is sorted before inserting the key into the position $A[i+1]$.
- ③ Then, because elements of $A[1...j]$ are sorted,
 - ① We have that after inserting the key at position $i+1$ in $A[1...j]$ **the array is still sorted after iteration j .**



Finally, Termination

Termination

- Once $j > \text{length}(A)$, we get out of the outer loop and $j = n + 1$.
- Then, using the maintenance procedure we have that the sub-array $A[1..n]$ is sorted as we wanted.



Finally, Termination

Termination

- Once $j > \text{length}(A)$, we get out of the outer loop and $j = n + 1$.
- Then, using the maintenance procedure we have that the sub-array $A[1...n]$ is sorted as we wanted.



Actually

This is known as
Loop Invariance!!!

Actually

This is known as
Loop Invariance!!!

Why is this important? Recursion \equiv Iteration

- How?

- ▶ A computational system that can compute every Turing Computable function is called Turing complete (or Turing powerful).

Why is this important? The entire class of algorithms that can be implemented

Actually

This is known as
Loop Invariance!!!

Why is this important? Recursion \equiv Iteration

- How?
 - ▶ A computational system that can compute every Turing Computable function is called Turing complete (or Turing powerful).

Properties

A Turing-complete system is called Turing equivalent if every function it can compute is also Turing Computable.

- It computes precisely the same class of functions as do Turing machines.

Actually

This is known as
Loop Invariance!!!

Why is this important? Recursion \equiv Iteration

- How?
 - ▶ A computational system that can compute every Turing Computable function is called Turing complete (or Turing powerful).

Properties

A Turing-complete system is called Turing equivalent if every function it can compute is also Turing Computable.

- It computes precisely the same class of functions as do Turing machines.

Actually

This is known as
Loop Invariance!!!

Why is this important? Recursion \equiv Iteration

- How?
 - ▶ A computational system that can compute every Turing Computable function is called Turing complete (or Turing powerful).

Properties

A Turing-complete system is called Turing equivalent if every function it can compute is also Turing Computable.

- It computes precisely the same class of functions as do Turing machines.

Recursion \equiv Iteration

Then

Since you can build a Turing complete language using strictly iterative structures and a Turing complete language using only recursive structures, then the two are therefore equivalent.



Recursion \equiv Iteration

Then

Since you can build a Turing complete language using strictly iterative structures and a Turing complete language using only recursive structures, then the two are therefore equivalent.

Proof From Lambda Calculus

- Assume languages IT (with Iterative constructs only) and REC (with Recursive constructs only).
- Simulate a universal Turing machine using IT, then simulate a universal Turing machine using REC.
- The existence of the simulator programs guarantees that both IT and REC can calculate all the computable functions.



Cinvestav

Recursion \equiv Iteration

Then

Since you can build a Turing complete language using strictly iterative structures and a Turing complete language using only recursive structures, then the two are therefore equivalent.

Proof From Lambda Calculus

- Assume languages IT (with Iterative constructs only) and REC (with Recursive constructs only).
- Simulate a universal Turing machine using IT, then simulate a universal Turing machine using REC.
- The existence of the simulator programs guarantees that both IT and REC can calculate all the computable functions.



Cinvestav

Recursion \equiv Iteration

Then

Since you can build a Turing complete language using strictly iterative structures and a Turing complete language using only recursive structures, then the two are therefore equivalent.

Proof From Lambda Calculus

- Assume languages IT (with Iterative constructs only) and REC (with Recursive constructs only).
- Simulate a universal Turing machine using IT, then simulate a universal Turing machine using REC.
- The existence of the simulator programs guarantees that both IT and REC can calculate all the computable functions.



Cinvestav

Nevertheless

Important

- We use **RECURSIVE** procedures, when we begin to solve new problems so we can understand them.

• Then, we move everything to **ITERATIVE** procedures for speed!!!



Cinvestav

Nevertheless

Important

- We use **RECURSIVE** procedures, when we begin to solve new problems so we can understand them.
- Then, we move everything to **ITERATIVE** procedures for speed!!!



Cinvestav

Outline

- 1 Divide and Conquer: The Holy Grail!!
 - Introduction
 - Split problems into smaller ones
- 2 Divide and Conquer
 - Not only that, we can define functions recursively
 - Classic Application: Divide and Conquer
 - Using Recursion to Calculate Complexities
- 3 Using Induction to prove Algorithm Correctness
 - Relation Between Recursion and Induction
 - Now, Structural Induction!!!
 - Example of the Use of Structural Induction for Proving Loop Correctness
 - The Structure of the Inductive Proof for a Loop
 - Insertion Sort Proof
- 4 Asymptotic Notation
 - **Big Notation**
 - Relation with step count
 - The Terrible Reality
 - The Little Bounds
 - Interpreting the Notation
 - Properties
- 5 Method to Solve Recursions
 - Substitution Method
 - The Recursion-Tree Method
 - The Master Method



Introduction

Let's go back to first principles

- We can look at our problem of complexities as bounding functions for approximation.

Can we do better?

Asymptotic Approximation... We will see a little bit more as the course goes...



Cinvestav

Introduction

Let's go back to first principles

- We can look at our problem of complexities as bounding functions for approximation.

Can we do better?

Asymptotic Approximation... We will see a little bit more as the course goes...



Cinvestav

Big O

Definition (Big O - Upper Bound)

For a given function $g(n)$:

$$O(g(n)) = \{f(n) \mid \text{There exists } c > 0 \text{ and } n_0 > 0 \\ \text{s.t. } 0 \leq f(n) \leq cg(n) \forall n \geq n_0\}$$

Example



Cinvestav


Big O

Definition (Big O - Upper Bound)

For a given function $g(n)$:

$$O(g(n)) = \{f(n) \mid \text{There exists } c > 0 \text{ and } n_0 > 0 \\ \text{s.t. } 0 \leq f(n) \leq cg(n) \forall n \geq n_0\}$$

Example



Big Ω

Definition (Big Ω - Lower Bound)

For a given function $g(n)$:

$$\Omega(g(n)) = \{f(n) \mid \text{There exists } c > 0 \text{ and } n_0 > 0 \\ \text{s.t. } 0 \leq cg(n) \leq f(n) \forall n \geq n_0\}$$

Example



Cinvestav


Big Ω

Definition (Big Ω - Lower Bound)

For a given function $g(n)$:

$$\Omega(g(n)) = \{f(n) \mid \text{There exists } c > 0 \text{ and } n_0 > 0 \\ \text{s.t. } 0 \leq cg(n) \leq f(n) \forall n \geq n_0\}$$

Example



Big Θ

Definition (Big Θ - Tight Bound)

For a given function $g(n)$:

$$\Theta(g(n)) = \{f(n) \mid \text{There exists } c_1 > 0, c_2 > 0 \text{ and } n_0 > 0 \\ \text{s.t. } 0 \leq c_1 g(n) \leq f(n) \leq c_2 g(n) \forall n \geq n_0\}$$

Example



Cinvestav


Big Θ

Definition (Big Θ - Tight Bound)

For a given function $g(n)$:

$$\Theta(g(n)) = \{f(n) \mid \text{There exists } c_1 > 0, c_2 > 0 \text{ and } n_0 > 0 \\ \text{s.t. } 0 \leq c_1 g(n) \leq f(n) \leq c_2 g(n) \forall n \geq n_0\}$$

Example



Outline

- 1 Divide and Conquer: The Holy Grail!!
 - Introduction
 - Split problems into smaller ones
- 2 Divide and Conquer
 - Not only that, we can define functions recursively
 - Classic Application: Divide and Conquer
 - Using Recursion to Calculate Complexities
- 3 Using Induction to prove Algorithm Correctness
 - Relation Between Recursion and Induction
 - Now, Structural Induction!!!
 - Example of the Use of Structural Induction for Proving Loop Correctness
 - The Structure of the Inductive Proof for a Loop
 - Insertion Sort Proof
- 4 Asymptotic Notation
 - Big Notation
 - **Relation with step count**
 - The Terrible Reality
 - The Little Bounds
 - Interpreting the Notation
 - Properties
- 5 Method to Solve Recursions
 - Substitution Method
 - The Recursion-Tree Method
 - The Master Method



Can we relate this with practical examples?

You could say

This is too theoretical!

However, this is not the case!!

Look at this java code...



Cinvestav

Can we relate this with practical examples?

You could say

This is too theoretical!

However, this is not the case!!

Look at this java code...



Example: Step count of Insertion Sort in Java

Counting when $A.length = n$

<i>// Sort A assume is full</i>	
<code>public int [] InsertionSort(int [] A){</code>	Step
<i>// Initial Variables</i>	0
<code>int B[] = new int[A.length];</code>	1
<code>int size = 1;</code>	1
<code>int i, j, t;</code>	1
<i>// Initialize the Array B</i>	0
<code>B[0]=A[0];</code>	1
<code>for(i = 1; i < A.length; i++){</code>	n
<code> t = A[i];</code>	n-1
<code> for(j=size-1;</code>	
<code> j>=0&& t<B[j]; j--)</code>	i+1
<code> {</code>	
<code> <i>//shift to the right</i></code>	0
<code> B[j+1]=B[j];}</code>	i
<code> B[j+1]=t;</code>	n-1
<code> size++;</code>	n-1
<code> }</code>	
<code>return B;</code>	1
<code>}</code>	

The Result

Step count for body of for loop is

$$6 + 3(n - 1) + n + \sum_{i=1}^{n-1} (i + 1) + \sum_{j=1}^{n-1} (i) \quad (13)$$

The summation

They have the quadratic terms n^2 .

Complexity

Insertion sort complexity is $O(n^2)$



Cinvestav

The Result

Step count for body of for loop is

$$6 + 3(n - 1) + n + \sum_{i=1}^{n-1} (i + 1) + \sum_{j=1}^{n-1} (i) \quad (13)$$

The summation

They have the quadratic terms n^2 .

Complexity

Insertion sort complexity is $O(n^2)$



Cinvestav

The Result

Step count for body of for loop is

$$6 + 3(n - 1) + n + \sum_{i=1}^{n-1} (i + 1) + \sum_{j=1}^{n-1} (i) \quad (13)$$

The summation

They have the quadratic terms n^2 .

Complexity

Insertion sort complexity is $O(n^2)$



Cinvestav

What does this means for insertion sort?

We have

$$6 + 3(n-1) + n + \sum_{i=1}^{n-1} (i+1) + \sum_{j=1}^{n-1} (i) = \dots$$

$$3 + 4n + \frac{n(n-1)}{2} + n - 1 + \frac{n(n-1)}{2} = \dots$$

$$2 + 5n + n(n-1) = \dots$$

$$n^2 + 4n + 2 \leq n^2 + 4n^2 + 2n^2$$

What does this means for insertion sort?

We have

$$6 + 3(n-1) + n + \sum_{i=1}^{n-1} (i+1) + \sum_{j=1}^{n-1} (i) = \dots$$

$$3 + 4n + \frac{n(n-1)}{2} + n - 1 + \frac{n(n-1)}{2} = \dots$$

$$2 + 5n + n(n-1) = \dots$$

$$n^2 + 4n + 2 \leq n^2 + 4n^2 + 2n^2$$

Thus

$$n^2 + 4n + 2 \leq 7n^2 \quad (14)$$

With $T_{\text{insertion}}(n) = n^2 + 4n + 2$ describing the number of steps for insertion when we have n numbers.

What does this means for insertion sort?

We have

$$6 + 3(n-1) + n + \sum_{i=1}^{n-1} (i+1) + \sum_{j=1}^{n-1} (i) = \dots$$

$$3 + 4n + \frac{n(n-1)}{2} + n - 1 + \frac{n(n-1)}{2} = \dots$$

$$2 + 5n + n(n-1) = \dots$$

$$n^2 + 4n + 2 \leq n^2 + 4n^2 + 2n^2$$

Thus

$$n^2 + 4n + 2 \leq 7n^2$$

(14)

With $T_{\text{insertion}}(n) = n^2 + 4n + 2$ describing the number of steps for insertion when we have n numbers.

What does this means for insertion sort?

We have

$$6 + 3(n-1) + n + \sum_{i=1}^{n-1} (i+1) + \sum_{j=1}^{n-1} (i) = \dots$$

$$3 + 4n + \frac{n(n-1)}{2} + n - 1 + \frac{n(n-1)}{2} = \dots$$

$$2 + 5n + n(n-1) = \dots$$

$$n^2 + 4n + 2 \leq n^2 + 4n^2 + 2n^2$$

Thus

$$n^2 + 4n + 2 \leq 7n^2 \quad (14)$$

With $T_{\text{insertion}}(n) = n^2 + 4n + 2$ describing the number of steps for insertion when we have n numbers.

What does this means for insertion sort?

We have

$$6 + 3(n-1) + n + \sum_{i=1}^{n-1} (i+1) + \sum_{j=1}^{n-1} (i) = \dots$$

$$3 + 4n + \frac{n(n-1)}{2} + n - 1 + \frac{n(n-1)}{2} = \dots$$

$$2 + 5n + n(n-1) = \dots$$

$$n^2 + 4n + 2 \leq n^2 + 4n^2 + 2n^2$$

Thus

$$n^2 + 4n + 2 \leq 7n^2 \quad (14)$$

With $T_{\text{insertion}}(n) = n^2 + 4n + 2$ describing the number of steps for insertion when we have n numbers.

Actually

For $n_0 = 2$

$$2^2 + 4 \times 2 + 2 = 14 < 7 \times 2^2 = 28 \quad (15)$$

Graphically




Cinvestav

Actually

For $n_0 = 2$

$$2^2 + 4 \times 2 + 2 = 14 < 7 \times 2^2 = 28 \quad (15)$$

Graphically



Meaning

First

Time or number of operations does not exceed cn^2 for a constant c on any input of size n (n suitably large).

Questions

- Is $O(n^2)$ too much time?
- Is the algorithm practical?



Meaning

First

Time or number of operations does not exceed cn^2 for a constant c on any input of size n (n suitably large).

Questions

- Is $O(n^2)$ too much time?
- Is the algorithm practical?



Outline

- 1 Divide and Conquer: The Holy Grail!!
 - Introduction
 - Split problems into smaller ones
- 2 Divide and Conquer
 - Not only that, we can define functions recursively
 - Classic Application: Divide and Conquer
 - Using Recursion to Calculate Complexities
- 3 Using Induction to prove Algorithm Correctness
 - Relation Between Recursion and Induction
 - Now, Structural Induction!!!
 - Example of the Use of Structural Induction for Proving Loop Correctness
 - The Structure of the Inductive Proof for a Loop
 - Insertion Sort Proof
- 4 Asymptotic Notation
 - Big Notation
 - Relation with step count
 - **The Terrible Reality**
 - The Little Bounds
 - Interpreting the Notation
 - Properties
- 5 Method to Solve Recursions
 - Substitution Method
 - The Recursion-Tree Method
 - The Master Method



Then

We have the following

n	n	$n \log n$	n^2	n^3	n^4
1000	1 micros	10 micros	1 milis	1 second	17 minutes
10,000	10 micros	130 micros	100 milis	17 minutes	116 days
10^6	1 milis	20 milis	17 minutes	32 years	3×10^7 years

It is much worse



Cinvestav

Then

We have the following

n	n	$n \log n$	n^2	n^3	n^4
1000	1 micros	10 micros	1 milis	1 second	17 minutes
10,000	10 micros	130 micros	100 milis	17 minutes	116 days
10^6	1 milis	20 milis	17 minutes	32 years	3×10^7 years

It is much worse

n	n^{10}	2^n
1000	3.2×10^{13} years	3.2×10^{283} years
10,000	???	???
10^6	?????	?????

The Reign of the Non Polynomial Algorithms

Outline

- 1 Divide and Conquer: The Holy Grail!!
 - Introduction
 - Split problems into smaller ones
- 2 Divide and Conquer
 - Not only that, we can define functions recursively
 - Classic Application: Divide and Conquer
 - Using Recursion to Calculate Complexities
- 3 Using Induction to prove Algorithm Correctness
 - Relation Between Recursion and Induction
 - Now, Structural Induction!!!
 - Example of the Use of Structural Induction for Proving Loop Correctness
 - The Structure of the Inductive Proof for a Loop
 - Insertion Sort Proof
- 4 Asymptotic Notation
 - Big Notation
 - Relation with step count
 - The Terrible Reality
 - **The Little Bounds**
 - Interpreting the Notation
 - Properties
- 5 Method to Solve Recursions
 - Substitution Method
 - The Recursion-Tree Method
 - The Master Method



Little o Bound

Definition

For a given function $g(n)$:

$$o(g(n)) = \{f(n) \mid \text{For any } c > 0 \text{ there exists } n_0 > 0 \\ \text{s.t. } 0 \leq f(n) < cg(n) \ \forall n \geq n_0\}$$

Observations

It is not tight.

- For example, We have that $2n = o(n^2)$, but $2n^2 \neq o(n^2)$.



Little o Bound

Definition

For a given function $g(n)$:

$$o(g(n)) = \{f(n) \mid \text{For any } c > 0 \text{ there exists } n_0 > 0 \\ \text{s.t. } 0 \leq f(n) < cg(n) \ \forall n \geq n_0\}$$

Observations

It is not tight.

- For example, We have that $2n = o(n^2)$, but $2n^2 \neq o(n^2)$.



Cinvestav

Little o Bound

Not only that

Under the definition, we have for any $f(n) \in o(g(n))$

$$\lim_{n \rightarrow \infty} \frac{f(n)}{g(n)} = 0$$



Little ω Bound

Definition

For a given function $g(n)$:

$$\omega(g(n)) = \{f(n) \mid \text{For any } c > 0 \text{ there exists } n_0 > 0 \text{ s.t.} \\ 0 \leq cg(n) < f(n) \ \forall n \geq n_0\}$$

Observations

It is not tight.

- For example, $\frac{n^2}{2} = \omega(n)$, but $\frac{n^2}{2} \neq \omega(n^2)$.



Little ω Bound

Definition

For a given function $g(n)$:

$$\omega(g(n)) = \{f(n) \mid \text{For any } c > 0 \text{ there exists } n_0 > 0 \text{ s.t.} \\ 0 \leq cg(n) < f(n) \ \forall n \geq n_0\}$$

Observations

It is not tight.

- For example, $\frac{n^2}{2} = \omega(n)$, but $\frac{n^2}{2} \neq \omega(n^2)$.



Little ω Bound

Not only that

Under the definition, we have for any $f(n) \in \omega(g(n))$

$$\lim_{n \rightarrow \infty} \frac{f(n)}{g(n)} = \infty$$



Cinvestav

Outline

- 1 Divide and Conquer: The Holy Grail!!
 - Introduction
 - Split problems into smaller ones
- 2 Divide and Conquer
 - Not only that, we can define functions recursively
 - Classic Application: Divide and Conquer
 - Using Recursion to Calculate Complexities
- 3 Using Induction to prove Algorithm Correctness
 - Relation Between Recursion and Induction
 - Now, Structural Induction!!!
 - Example of the Use of Structural Induction for Proving Loop Correctness
 - The Structure of the Inductive Proof for a Loop
 - Insertion Sort Proof
- 4 Asymptotic Notation
 - Big Notation
 - Relation with step count
 - The Terrible Reality
 - The Little Bounds
 - **Interpreting the Notation**
 - Properties
- 5 Method to Solve Recursions
 - Substitution Method
 - The Recursion-Tree Method
 - The Master Method



Interpretation

How do you interpret $f(n) = O(n^2)$?

It means that $f(n)$ belongs to $O(n^2)$



Interpretation

How do you interpret $f(n) = O(n^2)$?

It means that $f(n)$ belongs to $O(n^2)$

How do you interpret $2n^2 + 3n + 1 = 2n^2 + \Theta(n)$?

$\exists f(n) \in \Theta(n)$ such that:

$$\begin{aligned} 2n^2 + 3n + 1 &= 2n^2 + f(n) \\ &= 2n^2 + \Theta(n) \end{aligned}$$



Interpretation

How do you interpret $f(n) = O(n^2)$?

It means that $f(n)$ belongs to $O(n^2)$

How do you interpret $2n^2 + 3n + 1 = 2n^2 + \Theta(n)$?

$\exists f(n) \in \Theta(n)$ such that:

$$\begin{aligned} 2n^2 + 3n + 1 &= 2n^2 + f(n) \\ &= 2n^2 + \Theta(n) \end{aligned}$$



Interpretation

How do you interpret $f(n) = O(n^2)$?

It means that $f(n)$ belongs to $O(n^2)$

How do you interpret $2n^2 + 3n + 1 = 2n^2 + \Theta(n)$?

$\exists f(n) \in \Theta(n)$ such that:

$$\begin{aligned} 2n^2 + 3n + 1 &= 2n^2 + f(n) \\ &= 2n^2 + \Theta(n) \end{aligned}$$



Outline

- 1 Divide and Conquer: The Holy Grail!!
 - Introduction
 - Split problems into smaller ones
- 2 Divide and Conquer
 - Not only that, we can define functions recursively
 - Classic Application: Divide and Conquer
 - Using Recursion to Calculate Complexities
- 3 Using Induction to prove Algorithm Correctness
 - Relation Between Recursion and Induction
 - Now, Structural Induction!!!
 - Example of the Use of Structural Induction for Proving Loop Correctness
 - The Structure of the Inductive Proof for a Loop
 - Insertion Sort Proof
- 4 Asymptotic Notation
 - Big Notation
 - Relation with step count
 - The Terrible Reality
 - The Little Bounds
 - Interpreting the Notation
 - Properties
- 5 Method to Solve Recursions
 - Substitution Method
 - The Recursion-Tree Method
 - The Master Method



Properties

Equivalence

For any two functions $f(n)$ and $g(n)$, we have that $f(n) = \Theta(g(n))$ if and only if $f(n) = O(g(n))$ and $f(n) = \Omega(g(n))$.

Transitivity

$f(n) = \Theta(g(n))$ and $g(n) = \Theta(h(n))$ then $f(n) = \Theta(h(n))$

Reflexivity

$f(n) = \Theta(f(n))$

Symmetry

$f(n) = \Theta(g(n)) \iff g(n) = \Theta(f(n))$

Transpose Symmetry

$f(n) = O(g(n)) \iff g(n) = \Omega(f(n))$

Properties

Equivalence

For any two functions $f(n)$ and $g(n)$, we have that $f(n) = \Theta(g(n))$ if and only if $f(n) = O(g(n))$ and $f(n) = \Omega(g(n))$.

Transitivity

$f(n) = \Theta(g(n))$ and $g(n) = \Theta(h(n))$ then $f(n) = \Theta(h(n))$

Self-Inv

$$f(n) = \Theta(f(n))$$

Symmetry

$$f(n) = \Theta(g(n)) \iff g(n) = \Theta(f(n))$$

Transpose Symmetry

$$f(n) = O(g(n)) \iff g(n) = \Omega(f(n))$$

Properties

Equivalence

For any two functions $f(n)$ and $g(n)$, we have that $f(n) = \Theta(g(n))$ if and only if $f(n) = O(g(n))$ and $f(n) = \Omega(g(n))$.

Transitivity

$f(n) = \Theta(g(n))$ and $g(n) = \Theta(h(n))$ then $f(n) = \Theta(h(n))$

Reflexivity

$f(n) = \Theta(f(n))$

Symmetry

$f(n) = \Theta(g(n)) \iff g(n) = \Theta(f(n))$

Transpose Symmetry

$f(n) = O(g(n)) \iff g(n) = \Omega(f(n))$

Properties

Equivalence

For any two functions $f(n)$ and $g(n)$, we have that $f(n) = \Theta(g(n))$ if and only if $f(n) = O(g(n))$ and $f(n) = \Omega(g(n))$.

Transitivity

$f(n) = \Theta(g(n))$ and $g(n) = \Theta(h(n))$ then $f(n) = \Theta(h(n))$

Reflexivity

$f(n) = \Theta(f(n))$

Symmetry

$f(n) = \Theta(g(n)) \iff g(n) = \Theta(f(n))$

Transposed Symmetry

$f(n) = O(g(n)) \iff g(n) = \Omega(f(n))$

Properties

Equivalence

For any two functions $f(n)$ and $g(n)$, we have that $f(n) = \Theta(g(n))$ if and only if $f(n) = O(g(n))$ and $f(n) = \Omega(g(n))$.

Transitivity

$f(n) = \Theta(g(n))$ and $g(n) = \Theta(h(n))$ then $f(n) = \Theta(h(n))$

Reflexivity

$f(n) = \Theta(f(n))$

Symmetry

$f(n) = \Theta(g(n)) \iff g(n) = \Theta(f(n))$

Transpose Symmetry

$f(n) = O(g(n)) \iff g(n) = \Omega(f(n))$

Ok, we have the basics...

Now...

What do we do?



Cinvestav

Ok, we have the basics...

Now...

What do we do?

We will look at methods to solve recursions!!!

① Substitution Method

② Recursion-Tree Method

③ Master Method



Cinvestav

Ok, we have the basics...

Now...

What do we do?

We will look at methods to solve recursions!!!

- 1 Substitution Method
- 2 Recursion-Tree Method

3 Master Method



Cinvestav

Ok, we have the basics...

Now...

What do we do?

We will look at methods to solve recursions!!!

- 1 Substitution Method
- 2 Recursion-Tree Method
- 3 Master Method



Cinvestav

Outline

- 1 Divide and Conquer: The Holy Grail!!
 - Introduction
 - Split problems into smaller ones
- 2 Divide and Conquer
 - Not only that, we can define functions recursively
 - Classic Application: Divide and Conquer
 - Using Recursion to Calculate Complexities
- 3 Using Induction to prove Algorithm Correctness
 - Relation Between Recursion and Induction
 - Now, Structural Induction!!!
 - Example of the Use of Structural Induction for Proving Loop Correctness
 - The Structure of the Inductive Proof for a Loop
 - Insertion Sort Proof
- 4 Asymptotic Notation
 - Big Notation
 - Relation with step count
 - The Terrible Reality
 - The Little Bounds
 - Interpreting the Notation
 - Properties
- 5 Method to Solve Recursions
 - **Substitution Method**
 - The Recursion-Tree Method
 - The Master Method



The Substitution Method

The Steps in the Method

- Guess the form of the solution.
- Use mathematical induction to find the constants and show that the solution works.



The Substitution Method

The Steps in the Method

- Guess the form of the solution.
- Use mathematical induction to find the constants and show that the solution works.



Cinvestav

Example

Solve the following recurrence

$$T(n) = 2T\left(\left\lfloor \frac{n}{2} \right\rfloor\right) + n \quad (16)$$

I decide to do the following GUESS

Guess that $T(n) = O(n \log n)$!!!

For this

We assume that the bound holds for $\lfloor \frac{n}{2} \rfloor < n$ (Remember Inductive Hypothesis!!!).



Cinvestav

Example

Solve the following recurrence

$$T(n) = 2T\left(\left\lfloor \frac{n}{2} \right\rfloor\right) + n \quad (16)$$

I decide to do the following GUESS

Guess that $T(n) = O(n \log n)!!!$

For this

We assume that the bound holds for $\lfloor \frac{n}{2} \rfloor < n$ (Remember Inductive Hypothesis!!!).



Cinvestav

Example

Solve the following recurrence

$$T(n) = 2T\left(\left\lfloor \frac{n}{2} \right\rfloor\right) + n \quad (16)$$

I decide to do the following GUESS

Guess that $T(n) = O(n \log n)$!!!

For this

We assume that the bound holds for $\lfloor \frac{n}{2} \rfloor < n$ (Remember Inductive Hypothesis!!!).



Cinvestav

Therefore

We have that the following inequality holds

$$T\left(\left\lfloor \frac{n}{2} \right\rfloor\right) \leq c \left\lfloor \frac{n}{2} \right\rfloor \log_2 \left(\left\lfloor \frac{n}{2} \right\rfloor\right) \quad (17)$$

Thus, we have that



Cinvestav

Therefore

We have that the following inequality holds

$$T\left(\left\lfloor \frac{n}{2} \right\rfloor\right) \leq c \left\lfloor \frac{n}{2} \right\rfloor \log_2 \left(\left\lfloor \frac{n}{2} \right\rfloor\right) \quad (17)$$

Thus, we have that

$$\begin{aligned} T(n) &= 2T\left(\left\lfloor \frac{n}{2} \right\rfloor\right) + n \\ &\leq 2c \left\lfloor \frac{n}{2} \right\rfloor \log_2 \left(\left\lfloor \frac{n}{2} \right\rfloor\right) + n \end{aligned}$$



Cinvestav

Therefore

We have that the following inequality holds

$$T\left(\left\lfloor \frac{n}{2} \right\rfloor\right) \leq c \left\lfloor \frac{n}{2} \right\rfloor \log_2 \left(\left\lfloor \frac{n}{2} \right\rfloor\right) \quad (17)$$

Thus, we have that

$$\begin{aligned} T(n) &= 2T\left(\left\lfloor \frac{n}{2} \right\rfloor\right) + n \\ &\leq 2c \left\lfloor \frac{n}{2} \right\rfloor \log_2 \left(\left\lfloor \frac{n}{2} \right\rfloor\right) + n \end{aligned}$$



Cinvestav

Thus

We have that

$$T(n) \leq 2c \left\lfloor \frac{n}{2} \right\rfloor \log_2 \left(\left\lfloor \frac{n}{2} \right\rfloor \right) + n$$

$$\leq 2c \times \frac{n}{2} \times \log_2 \left(\frac{n}{2} \right) + n$$

$$= cn \log_2 \left(\frac{n}{2} \right) + n$$

Thus

We have that

$$\begin{aligned}T(n) &\leq 2c \left\lfloor \frac{n}{2} \right\rfloor \log_2 \left(\left\lfloor \frac{n}{2} \right\rfloor \right) + n \\&\leq 2c \times \frac{n}{2} \times \log_2 \left(\frac{n}{2} \right) + n \\&= cn \log_2 \left(\frac{n}{2} \right) + n\end{aligned}$$

Remember the following

$$\begin{aligned}\log_2 \left(\frac{n}{2} \right) &= \log_2 n - \log_2 2 \\&= \log_2 n - 1\end{aligned}$$

Thus

We have that

$$\begin{aligned}T(n) &\leq 2c \left\lfloor \frac{n}{2} \right\rfloor \log_2 \left(\left\lfloor \frac{n}{2} \right\rfloor \right) + n \\&\leq 2c \times \frac{n}{2} \times \log_2 \left(\frac{n}{2} \right) + n \\&= cn \log_2 \left(\frac{n}{2} \right) + n\end{aligned}$$

Remember the following

$$\begin{aligned}\log_2 \left(\frac{n}{2} \right) &= \log_2 n - \log_2 2 \\&= \log_2 n - 1\end{aligned}$$

Thus

We have that

$$\begin{aligned}T(n) &\leq 2c \left\lfloor \frac{n}{2} \right\rfloor \log_2 \left(\left\lfloor \frac{n}{2} \right\rfloor \right) + n \\&\leq 2c \times \frac{n}{2} \times \log_2 \left(\frac{n}{2} \right) + n \\&= cn \log_2 \left(\frac{n}{2} \right) + n\end{aligned}$$

Remember the following

$$\begin{aligned}\log_2 \left(\frac{n}{2} \right) &= \log_2 n - \log_2 2 \\&= \log_2 n - 1\end{aligned}$$

Thus

We have that

$$\begin{aligned}T(n) &\leq 2c \left\lfloor \frac{n}{2} \right\rfloor \log_2 \left(\left\lfloor \frac{n}{2} \right\rfloor \right) + n \\&\leq 2c \times \frac{n}{2} \times \log_2 \left(\frac{n}{2} \right) + n \\&= cn \log_2 \left(\frac{n}{2} \right) + n\end{aligned}$$

Remember the following

$$\begin{aligned}\log_2 \left(\frac{n}{2} \right) &= \log_2 n - \log_2 2 \\&= \log_2 n - 1\end{aligned}$$

Finally, we have

We have

$$T(n) \leq cn \log_2 n - cn + n$$

Now, we need to have that

Finally, we have

We have

$$T(n) \leq cn \log_2 n - cn + n$$

Now, we need to have that

$$-cn + n \leq 0$$

$$n \leq cn$$

$$1 \leq n$$

Finally, we have

We have

$$T(n) \leq cn \log_2 n - cn + n$$

Now, we need to have that

$$-cn + n \leq 0$$

$$n \leq cn$$

$$1 \leq c$$

Then, as long as $c \geq 1$, we have that

$$T(n) \leq cn \log_2 n - cn + n$$

$$\leq cn \log_2 n$$

Finally, we have

We have

$$T(n) \leq cn \log_2 n - cn + n$$

Now, we need to have that

$$-cn + n \leq 0$$

$$n \leq cn$$

$$1 \leq c$$

Then, as long $c \geq 1$, we have that

$$\begin{aligned} T(n) &\leq cn \log_2 n - cn + n \\ &\leq cn \log_2 n \end{aligned}$$

Finally, we have

We have

$$T(n) \leq cn \log_2 n - cn + n$$

Now, we need to have that

$$-cn + n \leq 0$$

$$n \leq cn$$

$$1 \leq c$$

Then, as long $c \geq 1$, we have that

$$T(n) \leq cn \log_2 n - cn + n$$

$$\leq cn \log_2 n$$

Finally, we have

We have

$$T(n) \leq cn \log_2 n - cn + n$$

Now, we need to have that

$$-cn + n \leq 0$$

$$n \leq cn$$

$$1 \leq c$$

Then, as long $c \geq 1$, we have that

$$\begin{aligned} T(n) &\leq cn \log_2 n - cn + n \\ &\leq cn \log_2 n \end{aligned}$$

Subtleties

What about ?

$$T(n) = T\left(\left\lfloor \frac{n}{2} \right\rfloor\right) + T\left(\left\lceil \frac{n}{2} \right\rceil\right) + 1$$

Here, we have a problem

Look at the Board!!!



Cinvestav

Outline

- 1 Divide and Conquer: The Holy Grail!!
 - Introduction
 - Split problems into smaller ones
- 2 Divide and Conquer
 - Not only that, we can define functions recursively
 - Classic Application: Divide and Conquer
 - Using Recursion to Calculate Complexities
- 3 Using Induction to prove Algorithm Correctness
 - Relation Between Recursion and Induction
 - Now, Structural Induction!!!
 - Example of the Use of Structural Induction for Proving Loop Correctness
 - The Structure of the Inductive Proof for a Loop
 - Insertion Sort Proof
- 4 Asymptotic Notation
 - Big Notation
 - Relation with step count
 - The Terrible Reality
 - The Little Bounds
 - Interpreting the Notation
 - Properties
- 5 Method to Solve Recursions
 - Substitution Method
 - **The Recursion-Tree Method**
 - The Master Method



The Recursion-Tree Method

Surprise

- Sometimes is hard to do a good guess.

• For example $T(n) = 3T\left(\frac{n}{4}\right) + cn^2$



The Recursion-Tree Method


Surprise

- Sometimes is hard to do a good guess.
- For example $T(n) = 3T\left(\frac{n}{4}\right) + cn^2$



The Recursion-Tree Method

Therefore, we draw the recursion tree



Using the previous expansion, we count!!!

Counting Again!!!

- A subproblem for a node at depth i is $n/4^i$, then once

$$n/4^i = 1 \Rightarrow i = \log_4 n \quad (18)$$

- At each level $i = 0, 1, 2, \dots, \log_4 n - 1$ the cost of each node is

$$c \left(\frac{n}{4^i} \right)^2 \quad (19)$$

- At each level $i = 0, 1, 2, \dots, \log_4 n - 1$ the total cost of the work is

$$3^i c \left(\frac{n}{4^i} \right)^2 = \left(\frac{3}{16} \right)^i cn^2 \quad (20)$$

- At depth $\log_4 n$, we have this many nodes

$$3^{\log_4 n} = n^{\log_4 3} \quad (21)$$

Using the previous expansion, we count!!!

Counting Again!!!

- A subproblem for a node at depth i is $n/4^i$, then once

$$n/4^i = 1 \Rightarrow i = \log_4 n \quad (18)$$

- At each level $i = 0, 1, 2, \dots, \log_4 n - 1$ the cost of each node is

$$c \left(\frac{n}{4^i} \right)^2 \quad (19)$$

- At each level $i = 0, 1, 2, \dots, \log_4 n - 1$ the total cost of the work is

$$3^i c \left(\frac{n}{4^i} \right)^2 = \left(\frac{3}{16} \right)^i cn^2 \quad (20)$$

- At depth $\log_4 n$, we have this many nodes

$$3^{\log_4 n} = n^{\log_4 3} \quad (21)$$

Using the previous expansion, we count!!!

Counting Again!!!

- A subproblem for a node at depth i is $n/4^i$, then once

$$n/4^i = 1 \Rightarrow i = \log_4 n \quad (18)$$

- At each level $i = 0, 1, 2, \dots, \log_4 n - 1$ the cost of each node is

$$c \left(\frac{n}{4^i} \right)^2 \quad (19)$$

- At each level $i = 0, 1, 2, \dots, \log_4 n - 1$ the total cost of the work is

$$3^i c \left(\frac{n}{4^i} \right)^2 = \left(\frac{3}{16} \right)^i cn^2 \quad (20)$$

- At depth $\log_4 n$, we have this many nodes

$$3^{\log_4 n} = n^{\log_4 3} \quad (21)$$

Using the previous expansion, we count!!!

Counting Again!!!

- A subproblem for a node at depth i is $n/4^i$, then once

$$n/4^i = 1 \Rightarrow i = \log_4 n \quad (18)$$

- At each level $i = 0, 1, 2, \dots, \log_4 n - 1$ the cost of each node is

$$c \left(\frac{n}{4^i} \right)^2 \quad (19)$$

- At each level $i = 0, 1, 2, \dots, \log_4 n - 1$ the total cost of the work is

$$3^i c \left(\frac{n}{4^i} \right)^2 = \left(\frac{3}{16} \right)^i cn^2 \quad (20)$$

- At depth $\log_4 n$, we have this many nodes

$$3^{\log_4 n} = n^{\log_4 3} \quad (21)$$

Now, we add all this counts!!!

Then, we have that

$$T(n) = \sum_{i=0}^{\log_4 n - 1} \left(\frac{3}{16}\right)^i cn^2 + n^{\log_4 3}$$

$$< \sum_{i=0}^{\infty} \left(\frac{3}{16}\right)^i cn^2 + n^{\log_4 3}$$

$$= \frac{1}{1 - (3/16)} cn^2 + n^{\log_4 3}$$

$$= O(n^2)$$



Now, we add all this counts!!!

Then, we have that

$$\begin{aligned} T(n) &= \sum_{i=0}^{\log_4 n - 1} \left(\frac{3}{16}\right)^i cn^2 + n^{\log_4 3} \\ &< \sum_{i=0}^{\infty} \left(\frac{3}{16}\right)^i cn^2 + n^{\log_4 3} \\ &= \frac{1}{1 - (3/16)} cn^2 + n^{\log_4 3} \\ &= O(n^2) \end{aligned}$$



Now, we add all this counts!!!

Then, we have that

$$\begin{aligned}T(n) &= \sum_{i=0}^{\log_4 n - 1} \left(\frac{3}{16}\right)^i cn^2 + n^{\log_4 3} \\&< \sum_{i=0}^{\infty} \left(\frac{3}{16}\right)^i cn^2 + n^{\log_4 3} \\&= \frac{1}{1 - (3/16)} cn^2 + n^{\log_4 3} \\&= O(n^2)\end{aligned}$$



Now, we add all this counts!!!

Then, we have that

$$\begin{aligned}T(n) &= \sum_{i=0}^{\log_4 n - 1} \left(\frac{3}{16}\right)^i cn^2 + n^{\log_4 3} \\&< \sum_{i=0}^{\infty} \left(\frac{3}{16}\right)^i cn^2 + n^{\log_4 3} \\&= \frac{1}{1 - (3/16)} cn^2 + n^{\log_4 3} \\&= O(n^2)\end{aligned}$$



Outline

- 1 Divide and Conquer: The Holy Grail!!
 - Introduction
 - Split problems into smaller ones
- 2 Divide and Conquer
 - Not only that, we can define functions recursively
 - Classic Application: Divide and Conquer
 - Using Recursion to Calculate Complexities
- 3 Using Induction to prove Algorithm Correctness
 - Relation Between Recursion and Induction
 - Now, Structural Induction!!!
 - Example of the Use of Structural Induction for Proving Loop Correctness
 - The Structure of the Inductive Proof for a Loop
 - Insertion Sort Proof
- 4 Asymptotic Notation
 - Big Notation
 - Relation with step count
 - The Terrible Reality
 - The Little Bounds
 - Interpreting the Notation
 - Properties
- 5 Method to Solve Recursions
 - Substitution Method
 - The Recursion-Tree Method
 - The Master Method



The Master Theorem

Theorem - Cookbook for solving $T(n) = aT\left(\frac{n}{b}\right) + f(n)$

Let $a \geq 1$ and $b > 1$ be constants, let $f(n)$ be a function, and let $T(n)$ be defined on the non-negative integers by the recurrence

$$T(n) = aT\left(\frac{n}{b}\right) + f(n) \quad (22)$$

where we interpret $\frac{n}{b}$ as $\lfloor \frac{n}{b} \rfloor$ or $\lceil \frac{n}{b} \rceil$. Then $T(n)$ can be bounded asymptotically as follows:

- If $f(n) = O(n^{\log_b a - \epsilon})$ for some constant $\epsilon > 0$. Then $T(n) = \Theta(n^{\log_b a})$.
- If $f(n) = \Theta(n^{\log_b a})$, then $T(n) = \Theta(n^{\log_b a} \lg n)$.
- If $f(n) = \Omega(n^{\log_b a + \epsilon})$ for some constant $\epsilon > 0$ and if $af\left(\frac{n}{b}\right) \leq cf(n)$ for some $c < 1$ and all sufficiently large n , then $T(n) = \Theta(f(n))$.



The Master Theorem

Theorem - Cookbook for solving $T(n) = aT\left(\frac{n}{b}\right) + f(n)$

Let $a \geq 1$ and $b > 1$ be constants, let $f(n)$ be a function, and let $T(n)$ be defined on the non-negative integers by the recurrence

$$T(n) = aT\left(\frac{n}{b}\right) + f(n) \quad (22)$$

where we interpret $\frac{n}{b}$ as $\lfloor \frac{n}{b} \rfloor$ or $\lceil \frac{n}{b} \rceil$. Then $T(n)$ can be bounded asymptotically as follows:

- If $f(n) = O(n^{\log_b a - \epsilon})$ for some constant $\epsilon > 0$, then $T(n) = \Theta(n^{\log_b a})$.
- If $f(n) = \Theta(n^{\log_b a})$, then $T(n) = \Theta(n^{\log_b a} \lg n)$.
- If $f(n) = \Omega(n^{\log_b a + \epsilon})$ for some constant $\epsilon > 0$ and if $af\left(\frac{n}{b}\right) \leq cf(n)$ for some $c < 1$ and all sufficiently large n , then $T(n) = \Theta(f(n))$.



The Master Theorem

Theorem - Cookbook for solving $T(n) = aT\left(\frac{n}{b}\right) + f(n)$

Let $a \geq 1$ and $b > 1$ be constants, let $f(n)$ be a function, and let $T(n)$ be defined on the non-negative integers by the recurrence

$$T(n) = aT\left(\frac{n}{b}\right) + f(n) \quad (22)$$

where we interpret $\frac{n}{b}$ as $\lfloor \frac{n}{b} \rfloor$ or $\lceil \frac{n}{b} \rceil$. Then $T(n)$ can be bounded asymptotically as follows:

- 1 If $f(n) = O(n^{\log_b a - \epsilon})$ for some constant $\epsilon > 0$. Then $T(n) = \Theta(n^{\log_b a})$.
- 2 If $f(n) = \Theta(n^{\log_b a})$, then $T(n) = \Theta(n^{\log_b a} \lg n)$.
- 3 If $f(n) = \Omega(n^{\log_b a + \epsilon})$ for some constant $\epsilon > 0$ and if $af\left(\frac{n}{b}\right) \leq cf(n)$ for some $c < 1$ and all sufficiently large n , then $T(n) = \Theta(f(n))$.



The Master Theorem

Theorem - Cookbook for solving $T(n) = aT\left(\frac{n}{b}\right) + f(n)$

Let $a \geq 1$ and $b > 1$ be constants, let $f(n)$ be a function, and let $T(n)$ be defined on the non-negative integers by the recurrence

$$T(n) = aT\left(\frac{n}{b}\right) + f(n) \quad (22)$$

where we interpret $\frac{n}{b}$ as $\lfloor \frac{n}{b} \rfloor$ or $\lceil \frac{n}{b} \rceil$. Then $T(n)$ can be bounded asymptotically as follows:

- 1 If $f(n) = O(n^{\log_b a - \epsilon})$ for some constant $\epsilon > 0$. Then $T(n) = \Theta(n^{\log_b a})$.
- 2 If $f(n) = \Theta(n^{\log_b a})$, then $T(n) = \Theta(n^{\log_b a} \lg n)$.

3 If $f(n) = \Omega(n^{\log_b a + \epsilon})$ for some constant $\epsilon > 0$ and if $a f\left(\frac{n}{b}\right) \leq c f(n)$ for some $c < 1$ and all sufficiently large n , then $T(n) = \Theta(f(n))$.



The Master Theorem

Theorem - Cookbook for solving $T(n) = aT\left(\frac{n}{b}\right) + f(n)$

Let $a \geq 1$ and $b > 1$ be constants, let $f(n)$ be a function, and let $T(n)$ be defined on the non-negative integers by the recurrence

$$T(n) = aT\left(\frac{n}{b}\right) + f(n) \quad (22)$$

where we interpret $\frac{n}{b}$ as $\lfloor \frac{n}{b} \rfloor$ or $\lceil \frac{n}{b} \rceil$. Then $T(n)$ can be bounded asymptotically as follows:

- 1 If $f(n) = O(n^{\log_b a - \epsilon})$ for some constant $\epsilon > 0$. Then $T(n) = \Theta(n^{\log_b a})$.
- 2 If $f(n) = \Theta(n^{\log_b a})$, then $T(n) = \Theta(n^{\log_b a} \lg n)$.
- 3 If $f(n) = \Omega(n^{\log_b a + \epsilon})$ for some constant $\epsilon > 0$ and if $af\left(\frac{n}{b}\right) \leq cf(n)$ for some $c < 1$ and all sufficiently large n , then $T(n) = \Theta(f(n))$.



We will prove a simplified version

Simplified Master Method

If $T(n) = aT(\lceil \frac{n}{b} \rceil) + O(n^d)$ for some constants $a > 0$, $b > 1$, and $d \geq 0$ then

$$T(n) = \begin{cases} O(n^d) & \text{if } d > \log_b a \\ O(n^d \log n) & \text{if } d = \log_b a \\ O(n^{\log_b a}) & \text{if } d < \log_b a \end{cases}$$

Proof at the Board

Look at this



Cinvestav

Using the Master Theorem

Consider the following recursion

$$T(n) = 9T\left(\frac{n}{3}\right) + n$$

We have that

$$a = 9, b = 3 \text{ and } f(n) = n$$

Thus

$$n^{\log_3 9} = \Theta(n^2) \text{ and } f(n) = O(n^{\log_3 9 - \epsilon}) \text{ with } \epsilon = 1$$

Then, we use then the case 1 of the Master Theorem

$$T(n) = O(n^2) \quad (23)$$

Using the Master Theorem

Consider the following recursion

$$T(n) = 9T\left(\frac{n}{3}\right) + n$$

We have that

$$a = 9, b = 3 \text{ and } f(n) = n$$

Thus

$$n^{\log_3 9} = \Theta(n^2) \text{ and } f(n) = O(n^{\log_3 9 - \epsilon}) \text{ with } \epsilon = 1$$

Then, we use then the case 1 of the Master Theorem

$$T(n) = O(n^2) \quad (23)$$

Using the Master Theorem

Consider the following recursion

$$T(n) = 9T\left(\frac{n}{3}\right) + n$$

We have that

$$a = 9, b = 3 \text{ and } f(n) = n$$

Thus

$$n^{\log_3 9} = \Theta(n^2) \text{ and } f(n) = O(n^{\log_3 9 - \epsilon}) \text{ with } \epsilon = 1$$

Then, we use then the case 1 of the Master Theorem

$$T(n) = O(n^2) \quad (23)$$

Using the Master Theorem

Consider the following recursion

$$T(n) = 9T\left(\frac{n}{3}\right) + n$$

We have that

$$a = 9, b = 3 \text{ and } f(n) = n$$

Thus

$$n^{\log_3 9} = \Theta(n^2) \text{ and } f(n) = O(n^{\log_3 9 - \epsilon}) \text{ with } \epsilon = 1$$

Then, we use then the case 1 of the Master Theorem

$$T(n) = O(n^2) \quad (23)$$