

3-11-2024

Training Day – 32

Topic:* Bar Charts and Histograms in Matplotlib

- Created bar charts and histograms to visualize data distributions.
- Example: Plotted a histogram for a dataset of random integers.

Topic: Bar Charts and Histograms in Matplotlib

- Visualizing categorical and continuous data distributions.
- Example:

```
data = [5, 7, 8, 6, 7]
plt.bar(range(len(data)), data)
plt.hist(data, bins=3)
plt.show()
```

- In "barplot" some attributes are practiced to visualize the given data are as follows-

- > color: It help. to change the colour of bars in graph.
- > width: It is used to change the broadness of bars in the graph.
- > xlabel: It used for naming of the X-axis of the bar graph.
- > ylabel: It used for naming of the Y-axis of the bar graph.
- > barh: This attribute change the direction of bars, i.e. Vertical to Horizontal.



- As same like "bar graph" attributes are same in "histogram".

- In " piechart" some attributes are used to help in the visualization of given data are -

- > explode: It help to point out the selected portion of the pie-chart by exploding the part from the whole chart according to given explode value.
- > autopct: It represent the data in percentage automatically and it's value is-
"autopct='%1.2f%%' ".

- In box plot there are some concepts which are important to understand for making visualization easier and identifying outliers easily.

1. IQR: It stand for "inter quartile range", which define as the difference of "third quartile(q3) and first quartile (q0)".
2. Outliers are those value which comes after the last quartile to affect our mean, as well as below the first quartile.
3. Our whole data is divided in four part i.e. 25%, 50%, 75%, 100%, and these percentile values refers to our quartile(q1,q2,q3,q4).
4. The value of lower_limit is extracted by applying formula of $\text{lower_limit} = q1 - 1.5 * (\text{IQR})$.
The value of upper_limit is extracted by applying formula of $\text{upper_limit} = q3 + 1.5 * (\text{IQR})$.



Topic:* Scatter Plots in Matplotlib

- Plotted relationships between two variables.
- Example: Visualized correlation between "Age" and "Height" columns.

Topic: Scatter Plots in Matplotlib

- Example:


```
x = [1, 2, 3]
y = [2, 4, 1]
plt.scatter(x, y)
plt.title("Scatter Plot")
plt.show()
```

visualization easier and identifying outliers easily.

1. IQR: It stand for "inter quartile range", which define as the difference of "third quartile(q3) and first quartile (q0)".
2. Outliers are those value which comes after the last quartile to affect our mean, as well as below the first quartile.
3. Our whole data is divided in four part i.e. 25%, 50%, 75%, 100%, and these percentile values refers to our quartile(q1,q2,q3,q4).
4. The value of lower_limit is extracted by applying formula of $\text{lower_limit} = q1 - 1.5 * (\text{IQR})$.
The value of upper_limit is extracted by applying formula of $\text{upper_limit} = q3 + 1.5 * (\text{IQR})$.

```
pr=['c','java','perl','php']
stud=[200,30,60,40]
plt.subplot(1,3,2)
plt.scatter(pr,stud,color='green');
plt.xlabel('programming language',color='Red')
plt.ylabel('number of students',color='Red');
plt.title('Scatterplot');

pr=['c','java','perl','php']
stud=[200,30,60,40]
plt.subplot(1,3,3)
plt.bar(pr,stud,color='green',width=0.5);
plt.xlabel('programming language',color='Red')
plt.ylabel('number of students',color='Red');
plt.title('Barplot');
```



```
df=sns.load_dataset('tips')  
df
```

	total_bill	tip	sex	smoker	day	time	size
0	16.99	1.01	Female	No	Sun	Dinner	2

1:45

1x



5-11-2024

Training Day – 34

Topic: * Stacked Charts with Legends in Matplotlib

- Created stacked area charts and added legends and titles.
- Example: Visualized cumulative sales over time for different products.

Stacked bar plots represent different groups on the highest of 1 another. The peak of the bar depends on the resulting height of the mixture of the results of the groups. It goes from rock bottom to the worth rather than going from zero to value.

Topic: Stacked Charts with Legends in Matplotlib

- Example:

```
x = [1, 2, 3]
y1 = [2, 3, 4]
y2 = [3, 4, 5]
plt.stackplot(x, y1, y2, labels=["Group 1", "Group 2"])
plt.legend()
plt.show()
```


visualization easier and identifying outliers easily.

1. IQR: It stand for "inter quartile range", which define as the difference of "third quartile(q3) and first quartile (q0)".
2. Outliers are those value which comes after the last quartile to affect our mean, as well as below the first quartile.
3. Our whole data is divided in four part i.e. 25%, 50%, 75%, 100%, and these percentile values refers to our quartile(q1,q2,q3,q4).
4. The value of lower_limit is extracted by applying formula of $\text{lower_limit} = q1 - 1.5 * (\text{IQR})$.
The value of upper_limit is extracted by applying formula of $\text{upper_limit} = q3 + 1.5 * (\text{IQR})$.

EXAMPLE

```
# importing package
import matplotlib.pyplot as plt
# create data
x = ['A', 'B', 'C', 'D']
y1 = [10, 20, 10, 30]
y2 = [20, 25, 15, 25]
# plot bars in stack manner
plt.bar(x, y1, color='r')
```

```
plt.bar(x, y2, bottom=y1, color='b')  
plt.show()
```



6-11-2024

Training Day – 30

Topic: Pandas Groupby Operations

- Grouped data by specific columns and applied aggregation functions.
- Example: Grouped by "Category" column and calculated sums for each group. we will use the *groupby()* function to perform various operations on grouped data.

```
[9]
...

[35]
df.groupby(['Type 1'])['Attack'].max().sort_values(ascending=False)
```

Type 1	Attack
Psychic	190
Bug	185
Dragon	180
Ground	180
Ghost	165
Rock	165
Normal	160
Fire	160
Water	155
Dark	150
Steel	150
Fighting	145
Grass	132
Fairy	131
Ice	130
Electric	123
Flying	115
Poison	106

Name: Attack, dtype: int64

```
[51]
df.groupby(['Type 1'])['Attack'].agg(['sum', 'min', 'max', 'count', 'mean']).sort_values(by='max', ascending=False).head(1)
```

```
[55]
df['Name'].nunique()
```

800

```
[57]
df.groupby(['Name'])['Attack'].sum()
```

Name	Attack
Abomasnow	92
AbomasnowMega Abomasnow	132
Abra	20
Absol	130
AbsolMega Absol	150
...	...
Zoroark	105
Zorua	65
Zubat	45
Zweilous	85
Zygardese% Forme	100

Name: Attack, Length: 800, dtype: int64

09-11-2024

Training Day – 31


Topic:* Introduction to Matplotlib

- Learned to create simple line plots.
- Example: Plotted $y = x^2$ for x in range 0 to 10.

Matplotlib is a powerful and versatile open-source plotting library for Python, designed to help users visualize data in a variety of formats. Developed by John D. Hunter in 2003, it enables users to graphically represent data, facilitating easier analysis and understanding. **If you want to convert your boring data into interactive plots and graphs, Matplotlib is the tool for you.**

```
1 import matplotlib.pyplot as plt
2
3 x = [0, 1, 2, 3, 4]
4 y = [0, 1, 4, 9, 16]
5
6 plt.plot(x, y)
7 plt.show()
```

it:



- **Import Matplotlib:** Start by importing matplotlib.pyplot as plt.
- **Create Data:** Prepare your data in the form of lists or arrays.
- **Plot Data:** Use plt.plot() to create the plot.
- **Customize Plot:** Add titles, labels, and other elements using methods like plt.title(), plt.xlabel(), and plt.ylabel().
- **Display Plot:** Use plt.show() to display the plot.