

#### **EXP.NO: 4.1**

**AIM:** Write a c++ program to illustrate the use of function templates

#### **PROGRAM:**

```
#include <iostream>

using namespace std;

template <typename T>
void bubbleSort(T a[], int n) {
    T temp;
    for (int i = 0; i < n - 1; i++) {
        for (int j = 0; j < n - 1 - i; j++) {
            if (a[j] > a[j + 1]) {
                temp = a[j];
                a[j] = a[j + 1];
                a[j + 1] = temp;
            }
        }
    }
}

template <typename T>
void print(T a[], int n) {
    for (int i = 0; i < n; i++) {
        cout << a[i] << " ";
    }
    cout << endl;
}

int main() {
    int a[5] = {12, 97, 34, 56, 3};
    char c[5] = {'s', 'e', 'a', 'm', 'h'};
```

```
float f[5] = {2.5, 14.7, 98.2, 33.5, 58.4};
```

```
cout << "Original int array: ";
```

```
print(a, 5);
```

```
bubbleSort(a, 5);
```

```
cout << "Sorted int array: ";
```

```
print(a, 5);
```

```
cout << "\nOriginal char array: ";
```

```
print(c, 5);
```

```
bubbleSort(c, 5);
```

```
cout << "Sorted char array: ";
```

```
print(c, 5);
```

```
cout << "\nOriginal float array: ";
```

```
print(f, 5);
```

```
bubbleSort(f, 5);
```

```
cout << "Sorted float array: ";
```

```
print(f, 5);
```

```
return 0;
```

```
}
```

### Output:

```
/Users/yaswanthkakarla/CLionProjects/untitled5/cmake-build-debug/untitled5
Original int array: 12 97 34 56 3
Sorted int array: 3 12 34 56 97

Original char array: s e a m h
Sorted char array: a e h m s

Original float array: 2.5 14.7 98.2 33.5 58.4
Sorted float array: 2.5 14.7 33.5 58.4 98.2

Process finished with exit code 0
```

**EXP.NO: 4.2**

**AIM: :** Write a c++ program to implement template class

**PROGRAM:**

```
#include<iostream>

using namespace std;

template <class T>

class Sample
{
    private:
        T n;

    public:
        void get()
        {
            cout << "Enter n value:";

            cin >> n;
        }

        void show()
        {
            cout << "n= " << n << endl;
        }
};

int main()
{
    Sample<int> s1;

    s1.get();

    s1.show();

    Sample<char> s2;

    s2.get();

    s2.show();
}
```

```
    Sample<float> s3;  
  
    s3.get();  
  
    s3.show();  
  
    return 0;  
}
```

### Output:

```
/Users/yaswanthkakarla/CLionProjects/untitled5/cmake-build-debug/untitled5  
Enter n value: 10  
n = 10  
Enter n value: y  
n = y  
Enter n value: 171  
n = 171  
  
Process finished with exit code 0
```

**EXP.NO: 4.3**

**AIM:** Write a c++ program to implement class templates with multiple parameters

**PROGRAM:**

```
#include<iostream>

using namespace std;

template <class T1, class T2>

class Sample
{
    private:
        T1 x;
        T2 y;
    public:
        void get()
        {
            cin >> x >> y;
        }
        void show()
        {
            cout << "x= " << x << endl;
            cout << "y= " << y << endl;
        }
};

int main()
{
    Sample<int, float> s1;

    cout << "Enter int , float value:";
    s1.get();
    s1.show();
}
```

```
Sample<char, int> s2;

cout << "Enter char , int value:";

s2.get();

s2.show();

Sample<float, char> s3;

cout << "Enter float, char value:";

s3.get();

s3.show();

return 0;

}
```

### Output:

```
/Users/yaswanthkakarla/CLionProjects/untitled5/cmake-build-debug/untitled5
Enter int and float value: 10 10.55
x = 10
y = 10.55
Enter char and int value: y 171
x = y
y = 171
Enter float and char value: 10.55 y
x = 10.55
y = y

Process finished with exit code 0
|
```