

Grants

A grant is an individual free round allocation issued to a specific player from an offer.

Endpoints

Method	Path	Description
POST	/grants	Issue grant to player
POST	/grants/batch	Issue grants to multiple players
GET	/grants/{grantId}	Get grant details
GET	/grants	List grants (paginated, filterable)
DELETE	/grants/{grantId}	Cancel grant

Issue Grant

POST /grants

Request Fields

Name	Type	Mandatory	Description
grant_id	String	Yes	Unique ID (idempotency key, max 64 chars)
offer_id	String	Yes	Offer to issue from
player_id	String	Yes	Player identifier

currency	String	Yes	ISO 4217 currency code
activation_date	String	No	ISO 8601; when the grant becomes usable. Null = immediately
expiry_date	String	Conditional	ISO 8601. See rules below
rounds	Integer	No	Per-grant amount override for fixed-bet offers. See "Per-grant amount override" below.
free_round_balance	Number	No	Per-grant amount override for bet-range offers. See "Per-grant amount override" below.

expiry_date rules.

- **Grants under a campaign** (`offer.campaign_id` is set): `expiry_date` is optional. If omitted, the grant inherits `campaign.end_date`. If provided, it must be **within** the campaign window (`<= campaign.end_date`, inclusive) – an expiry past the campaign end is rejected with error code `1024` (`GRANT_EXPIRY_AFTER_CAMPAIGN_END`). The resolved value is snapshotted at issue time; later changes to the campaign window do not retroactively affect already-issued grants.
- **Standalone grants** (`offer.campaign_id` is null): `expiry_date` is **required**. Omitting it is rejected with error code `1025` (`GRANT_EXPIRY_REQUIRED`).

Per-grant amount override (optional, additive)

Operators that want to award **different amounts to different players from the same offer template** can specify the awarded amount on the grant request. The two override fields are mutually exclusive and type-matched to the offer's mode:

Offer mode	Override field	Resolved balance
<code>fixed_bet</code>	<code>rounds</code> (Integer)	<code>rounds × offer.bet</code>

bet_range	free_round_balance (Number)	the override value
-----------	-----------------------------	--------------------

Existing integrations are unaffected. Operators that omit both fields continue to inherit the offer's default `free_round_balance` exactly as before. No request body shape changes; both new fields are optional.

Examples

Fixed-bet offer template, three players with different round counts in one batch:

```
POST /grants/batch
{
  "offer_id": "crash-promo-template",
  "expiry_date": "2026-06-01T00:00:00Z",
  "grants": [
    {"grant_id": "g-1", "player_id": "alice", "currency": "USD",
    "rounds": 5},
    {"grant_id": "g-2", "player_id": "bob", "currency": "USD",
    "rounds": 10},
    {"grant_id": "g-3", "player_id": "carol", "currency": "USD",
    "rounds": 25},
    {"grant_id": "g-4", "player_id": "dave", "currency": "USD"}
  ]
}
```

`dave` has no override and inherits the offer's default. Mixing inheritance and override in the same batch is allowed.

Bet-range offer template, single grant with explicit balance:

```
POST /grants
{
  "grant_id": "g-vip-bob",
  "offer_id": "crash-vip-range",
  "player_id": "bob",
  "currency": "USD",
  "free_round_balance": 25.00,
  "expiry_date": "2026-06-01T00:00:00Z"
}
```

Response echo

When an override is supplied, the grant response and `GET /grants/{id}` include the operator's input verbatim under `awarded_rounds` and `awarded_free_round_balance` so retries and audits can confirm what was applied. Both fields are `null` when no override was given. Values are read from persisted columns — never recomputed.

```
{
  "result_code": 0,
  "data": {
    "grant_id": "g-1",
    "free_round_balance": 5.00,          // resolved, what player
    actually got
    "awarded_rounds": 5,                // echo of operator's override
    input
    "awarded_free_round_balance": null,  // null on fixed-bet grants
    "balance_remaining": 5.00,
    ...
  }
}
```

Idempotency

A retried `POST /grants` with the same `grant_id` returns the **original grant unchanged** – including the originally-resolved `free_round_balance` and the originally-echoed override fields. Subsequent calls with different `rounds` or `free_round_balance` are **not** applied; the first call wins. The override fields don't change idempotent retry behavior.

Validation rules

Condition	Error code	Name
<code>rounds</code> set on a <code>bet_range</code> offer (or <code>free_round_balance</code> set on a <code>fixed_bet</code> offer)	1028	GRANT_AMO UNT_FIELD _MISMATCH
Both <code>rounds</code> and <code>free_round_balance</code> set on the same request	1028	GRANT_AMO UNT_FIELD _MISMATCH
<code>rounds <= 0</code> or <code>free_round_balance <= 0</code>	1027	GRANT_INV ALID_AMOU NT
Resolved balance below the offer's minimum playable bet	1029	GRANT_BAL ANCE_BELO W_MIN_BET

Example

Request:

```
POST /grants
{
  "grant_id": "grant-abc-123",
  "offer_id": "crash-promo-1",
  "player_id": "player-456",
  "currency": "USD",
  "expiry_date": "2026-04-10T00:00:00Z"
}
```

**Response:**

```
{
  "result_code": 0,
  "data": {
    "grant_id": "grant-abc-123",
    "offer_id": "crash-promo-1",
    "campaign_id": "spring-promo-2026",
    "player_id": "player-456",
    "currency": "USD",
    "status": "PENDING",
    "free_round_balance": 5.00,
    "balance_used": 0,
    "balance_remaining": 5.00,
    "rounds_played": 0,
    "activation_date": null,
    "expiry_date": "2026-04-10T00:00:00Z",
    "created_at": "2026-04-01T04:21:59.247Z"
  }
}
```



Duplicate detection (idempotent create & cancel)

POST /grants (issue) and DELETE /grants/{grantId} (cancel) are idempotent, and their responses mark whether the call was a first-time operation or an idempotent replay. The response is always `result_code: 0`; two fields inside the `data` object carry the distinction:

Field	Type	Meaning
<code>duplicate</code>	Boolean	<code>true</code> when the call was an idempotent replay – the grant already existed, or was already cancelled – and nothing new was created or changed. <code>false</code> on a first-time operation.

<code>duplicate</code>	String	<code>"ALREADY_EXISTS"</code> – a <code>grant_id</code> that already exists was re-issued. <code>"ALREADY_CANCELLED"</code> – a grant that was already <code>CANCELLED</code> was cancelled again. <code>null</code> when <code>duplicate</code> is <code>false</code> .
<code>_reason</code>	(nullable)	

`duplicate: true` is also returned when two creates of the same `grant_id` arrive **concurrently** – exactly one is the fresh issue, the rest report `ALREADY_EXISTS`. In every duplicate case the original grant is returned unchanged and no second grant is created.

Use these fields to recognise a replay – for example to surface an "already created / already cancelled" outcome to your own upstream – without diffing the grant body. They are additive and optional: integrations that ignore them are unaffected.

These two fields describe an **operation outcome**, not grant state; on `GET /grants/{grantId}` and list responses they are `null`.

Duplicate create response:

```
{
  "result_code": 0,
  "data": {
    "grant_id": "grant-abc-123",
    "status": "PENDING",
    "duplicate": true,
    "duplicate_reason": "ALREADY_EXISTS"
  }
}
```

On a first-time issue or cancel, `duplicate` is `false` and `duplicate_reason` is `null`.

Not treated as duplicates: cancelling a **non-existent** grant remains an error, and cancelling a grant that has already **started / completed / expired** still returns `1014 / 1015` (see the Cancel Grant table) – those are distinct non-cancellable states, not idempotent replays.

Grant Lifecycle

Status	Description	Terminal?
PENDING	Issued but not yet activated	No
ACTIVE	Activated, available for play	No

IN_PROGRESS	Bound to a game session, player is playing	No
EXHAUSTED	Free round balance no longer covers another bet, but the player's last freeround bet is still in flight (cashable / cancellable). Treat as still "currently active" for the player.	No – revertible to IN_PROGRESS on cancel of the exhausting bet
COMPLETED	All free round bets settled; grant is truly done	Yes
CANCELLED	Cancelled via <code>DELETE /grants/{grantId}</code> while the grant was still <code>PENDING</code> or <code>ACTIVE</code>	Yes
EXPIRED	Expired past the expiry date	Yes

Status Transitions

```
PENDING → ACTIVE → IN_PROGRESS → EXHAUSTED → COMPLETED (terminal)
                                     ↓
                                     (revertible to IN_PROGRESS on cancel
                                     of the bet that exhausted the balance)
{ACTIVE | IN_PROGRESS | EXHAUSTED} → EXPIRED | CANCELLED (terminal)
```

Working with EXHAUSTED

- Where you check "is this grant currently active for this player", include `EXHAUSTED` alongside `ACTIVE` and `IN_PROGRESS`.
- Where you check `status == 'COMPLETED'` to mean "freeround is done", continue using `COMPLETED` only – it is the truly-terminal natural-completion state.
- `EXHAUSTED → COMPLETED` is the natural settlement transition; `EXHAUSTED → IN_PROGRESS` is the revert when the exhausting bet is cancelled during the betting window. Both happen server-side without integration changes.

Get Grant

```
GET /grants/{grantId}
```

Returns full grant details including balance tracking and lifecycle timestamps.

Response Fields

Name	Type	Description
grant_id	String	Grant identifier
offer_id	String	Source offer
campaign_id	String	Source campaign (nullable)
player_id	String	Player identifier
currency	String	Currency code
status	String	Current status
free_round_balance	Number	Resolved awarded balance for this player. Equals the offer's default unless an override was supplied at issue.
balance_used	Number	Amount spent so far
balance_remaining	Number	Remaining balance
rounds_played	Integer	Number of rounds completed
bet_mode	String	<code>FIXED_BET</code> or <code>BET_RANGE</code> — the offer's bet shape, snapshotted on the grant. Useful for rendering grant history with the right detail (fixed per-round bet vs player-chosen range).
min_cashout_coeff	Number (nullable)	Minimum cashout coefficient that applied to bets under this grant (Crash games only; null otherwise).

		Snapshoted at issue time from the offer.
awarded_rounds	Integer (nullable)	Echo of the <code>rounds</code> override the operator supplied at issue (fixed-bet offers). Null when no override was given.
awarded_free_round_balance	Number (nullable)	Echo of the <code>free_round_balance</code> override the operator supplied at issue (bet-range offers). Null when no override was given.
activation_date	String	When the grant was activated
expiry_date	String	When the grant expires
created_at	String	Creation timestamp
activated_at	String	Activation timestamp
completed_at	String	Completion timestamp
cancelled_at	String	Cancellation timestamp
total_win	Number (nullable)	Terminal-state snapshot of the player's freeround winnings under this grant – sum of CASHED_OUT bet payouts. Null on non-terminal grants (<code>PENDING</code> / <code>ACTIVE</code> / <code>IN_PROGRESS</code> / <code>EXHAUSTED</code>). Populated once at terminal with the value frozen at the moment of transition; never updated thereafter. By status: <code>COMPLETED</code> → final snapshot value; <code>CANCELLED</code> → <code>0.00</code> (cancel is only legal pre-play, so no winnings are possible); <code>EXPIRED</code> → final snapshot value (same semantic as <code>COMPLETED</code>).

For live winnings during play, derive from `FREEBET_WIN` wires (`PER_ROUND`); AGGREGATED grants emit only one grant-level WIN at terminal — see [bonus/aggregated-settlement.md](#).

List Grants

GET `/grants`

Query Parameters

Name	Type	Description
player_id	String	Filter by player
offer_id	String	Filter by offer
status	String	Filter by status
page	Integer	Page number (default: 1)
page_size	Integer	Items per page (default: 20)

Example

GET `/grants?player_id=player-456&status=ACTIVE&page=1&page_size=10`



Cancel Grant

DELETE `/grants/{grantId}`

Cancels a grant. Only allowed before the player starts playing (status must be `PENDING` or `ACTIVE`). Once the player has placed any freeround bet, the grant must reach a

terminal status on its own (`COMPLETED` , `EXPIRED` , or natural `CANCELLED`) – operator-driven cancellation is no longer accepted.

Current Status	Result
PENDING	CANCELLED
ACTIVE	CANCELLED
IN_PROGRESS	Rejected (<code>1014 GRANT_ALREADY_STARTED</code>)
EXHAUSTED	Rejected (<code>1014 GRANT_ALREADY_STARTED</code>) – player has used the grant; cancellation would create a reconciliation gap with already-cashed-out internal play
COMPLETED	Rejected (<code>1015 GRANT_ALREADY_COMPLETED</code>)
EXPIRED	Rejected (<code>1015 GRANT_ALREADY_EXPIRED</code>)
CANCELLED	Idempotent – returns the existing <code>CANCELLED</code> grant, flagged <code>duplicate: true / duplicate_reason: "ALREADY_CANCELLED"</code> (see Duplicate detection)

Example

```
DELETE /grants/grant-abc-123
```



Response:

```
{
  "result_code": 0,
  "data": {
    "grant_id": "grant-abc-123",
    "status": "CANCELLED",
    "cancelled_at": "2026-04-01T04:24:03.913Z"
  }
}
```

