

Bonus API (Free Rounds)

The Bonus API allows operators to create promotional free round campaigns, configure offers, and issue grants to players. Players receive free rounds that let them play without using their own balance.

Environment	Base URL
Production	<code>https://bonus.playcore.live/v1</code>
Staging	<code>https://bonus.playcore.dev/v1</code>

Authentication

All requests require two headers:

Header	Description
<code>X-API-Key</code>	Operator-level API key
<code>X-Operator-Id</code>	Operator identifier (all resources are scoped to this operator)

Requests without valid headers return:

```
{
  "result_code": 1007,
  "message": "Missing required header: X-API-Key"
}
```



Concepts

Campaign (Optional)

A campaign is an **optional** tracking identifier for grouping free round activity. It is not

required to create or issue free rounds.

The primary use case is **GGR negotiation between provider and operator**. A game provider can create a campaign and share the `campaign_id` with the operator. The operator then issues free rounds under that campaign. All grants under the campaign are tracked separately — enabling both parties to agree on how those free rounds count toward GGR calculations.

For example, as part of a promotional agreement, a provider and operator may agree that free rounds issued under a specific campaign are excluded from GGR, counted at a reduced rate, or attributed to a marketing budget. The campaign provides the shared reference for this tracking.

Campaigns can also be used independently by the operator for their own reporting and grouping — for example, to track a seasonal promotion or segment free round spend by marketing initiative.

Campaigns have a start/end date, optional grant limits, and a status lifecycle:

DRAFT → ACTIVE → PAUSED → ENDED
↘ ENDED



Offer

An offer defines the free round configuration. There are two modes:

Mode	Description	Operator configures	Player chooses bet?
fixed_bet	Fixed per-round bet amount	<code>rounds + bet</code> (balance computed automatically)	No
bet_range	Player-selectable bet within bounds	<code>free_round_balance + min_bet + max_bet</code>	Yes, within range

Bet Mode

Each offer has a `bet_mode` that determines how the bet cost is handled:

Mode	Description	Win	Status
------	-------------	-----	--------

calculation			
ZERO_BET	Operator funds the bet. Player's wallet is not touched at placement. Full win is credited at settlement.	walletCre dit = nominalWi n	Supported
BET_FROM_WIN	Operator funds the bet (player's wallet still untouched at placement). The bet stake is deducted from any nominal win at settlement, clamped at zero.	walletCre dit = max(0, nominalWi n - stake)	Supported

Both modes use the same wallet wire fields (`bet_type=FREEBET` , `win_type=FREEBET_WIN`); only the win amount differs. Zero-net `BET_FROM_WIN` settlements (e.g. cashout exactly at unit multiplier) still send `FREEBET_WIN`, `amount=0` — zero is the settlement amount, not absence of settlement.

Both `bet_mode` values are supported with both `settlement_mode` values. Each round's settled amount uses the standard `BET_FROM_WIN` netting; for `AGGREGATED` grants the operator-visible WIN amount is the sum of those netted per-round values. See [bonus/aggregated-settlement.md](#) for the full `AGGREGATED` wire shape.

Grant

A grant is an individual free round allocation issued to a specific player from an offer. Grants track balance, rounds played, and lifecycle:

```
PENDING → ACTIVE → IN_PROGRESS → EXHAUSTED → COMPLETED (terminal)
                                     ↓
                                     (revertible to IN_PROGRESS on cancel
                                     of the bet that exhausted the balance)
{ACTIVE | IN_PROGRESS | EXHAUSTED} → EXPIRED | CANCELLED (terminal)
```

`EXHAUSTED` means the free round balance no longer covers another bet, but the player's last freeround bet is still in flight (cashable / cancellable) — treat it as still "currently active" for the player. The grant only becomes truly done at `COMPLETED`. See [Grants → Grant Lifecycle](#) for the full status reference.

Endpoints

Endpoint	Method	Description
Discovery	GET	Check game bonus support
Campaigns	CRUD	Manage campaigns
Offers	CRUD	Create and manage offers
Grants	CRUD	Issue, list, and cancel grants

Response Model

All responses return HTTP 200 with `result_code` in the body (same model as the Wallet API):

```
{
  "result_code": 0,
  "data": { ... }
}
```



Non-zero `result_code` indicates a business error:

```
{
  "result_code": 2001,
  "message": "Offer not found",
  "error": {
    "code": "OFFER_NOT_FOUND",
    "message": "Offer not found: xyz"
  }
}
```



Idempotency

All creation endpoints are idempotent on caller-provided IDs (`campaign_id`, `offer_id`, `grant_id`). Duplicate calls return the original response without side effects.

Error Codes

Code	Name	Description
------	------	-------------

0	SUCCESS	Operation completed
1007	AUTH_ERROR	Missing or invalid authentication
1001	CAMPAIGN_NOT_FOUND	Campaign does not exist
1003	CAMPAIGN_NOT_ACTIVE	Campaign must be ACTIVE
1004	CAMPAIGN_HAS_OFFERS	Cannot delete campaign with offers
2001	OFFER_NOT_FOUND	Offer does not exist
2002	OFFER_ALREADY_EXISTS	Duplicate offer ID (idempotent)
2003	OFFER_HAS_GRANTS	Cannot delete offer with grants
3001	GRANT_NOT_FOUND	Grant does not exist
3003	GRANT_ALREADY_STARTED	Cannot cancel grant after play started
1027	GRANT_INVALID_AMOUNT	Per-grant override <code>rounds</code> or <code>free_round_balance</code> is zero or negative
1028	GRANT_AMOUNT_FIELD_MISMATCH	Wrong override field for the offer's mode, or both override fields set together
1029	GRANT_BALANCE_BELOW_MIN_BET	Resolved per-grant balance is below the offer's minimum playable bet