

Game Launch

Overview

The Game Launch API provides an HTTP endpoint to obtain a ready-to-use launch URL for a specific game.

The returned `launch_url` can be used directly in the lobby (redirect or iframe) and requires no additional parameters from the Operator side.

The Integration Service is responsible for building the operator-specific launch URL and for rotating launch domains if needed.

Endpoint

POST `/seamless/launch/url`

Request Fields

Name	Type	Mandatory	Description
user_id	String	Yes	Player identifier in the Operator system.
currency	String	Yes	Currency code in ISO 4217 format (e.g. <code>EUR</code> , <code>USD</code> , <code>GEL</code>).
game_id	String	Yes	Unique game identifier.
mode	String	Yes	Game mode. Allowed values: <code>real</code> , <code>demo</code> . Currently informational/reserved — recorded on the session and passed to the game client, but does not change wallet behavior; <code>player/info</code> is called for every

			launch regardless of <code>mode</code> .
lang	String	Yes	Game UI language in ISO 639-1 format (e.g. <code>en</code> , <code>ka</code>).
platform	String	Yes	Target platform. Allowed values: <code>desktop</code> , <code>mobile</code> .
ip	String	Yes	Player's IPv4 or IPv6 address. Used for operator-side security and geo checks.
exit_url	String	No	Absolute URL the player is redirected to when exiting the game. When provided, a close button appears in the game header allowing the player to leave. When omitted, no exit button is rendered.
error_url	String	No	Absolute URL the player is redirected to on a critical game error. When provided, the error overlay includes a close button redirecting the player to this URL. When omitted, the game attempts to close the tab/window.
session_id	String	No	Operator-defined session identifier. If provided, this value will be used as <code>session_id</code> in all subsequent wallet callbacks. The same value is also sent on the <code>player/info</code> request made during launch. If omitted or blank, the platform generates a canonical session ID and uses it everywhere.
extra_params	Object (flat	No	Flat key-value map of operator-

key-value)

specific or game-specific parameters. All values must be JSON primitives (string, number, boolean). Appended to the final launch URL as query parameters.

Response Fields

Name	Type	Mandatory	Description
result_code	int	Yes	Result code. 0 indicates success.
launch_url	String	Yes	Fully constructed game URL ready for browser redirect or iframe embedding. No additional query parameters are required.
session_id	String	Yes	Canonical session identifier for this game session. This exact value will appear in the <code>session_id</code> field of all subsequent wallet callbacks (<code>balance</code> , <code>bet</code> , <code>win</code> , <code>rollback</code>), and on the <code>player/info</code> request made during launch.

URL Parameter Behavior

Parameter	UI Effect	When Visible
<code>exit_url</code>	Close button in the game header	During gameplay
<code>error_url</code>	Close button on the error overlay	On critical errors

**Recommendation**

Always provide both `exit_url` and `error_url` to ensure players are never stranded in the game or on an error screen.

Extra Parameters

The `extra_params` field accepts a flat key-value map that is appended to the final launch URL as query parameters. The game client reads these parameters at startup to override default settings.

Supported Keys

Key	Type	Default	Description
<code>sound</code>	Boolean	<code>true</code>	Enable or disable game sound effects on launch.
<code>music</code>	Boolean	<code>true</code>	Enable or disable background music on launch.
<code>animation</code>	Boolean	<code>true</code>	Enable or disable UI animations on launch.

All three settings default to `true` if not specified. Players can still toggle these settings at runtime via the in-game settings panel.

Example usage:

```
"extra_params": {  
  "sound": false,  
  "music": false,  
  "animation": true  
}
```



**Note**

Operators may also pass arbitrary custom parameters (e.g. `"fullscreen": true`). Only the keys listed above have built-in game client behavior.

Example

Request:

```
POST /seamless/launch/url
{
  "user_id": "1234",
  "game_id": "king_move",
  "mode": "real",
  "currency": "EUR",
  "lang": "en",
  "platform": "desktop",
  "ip": "127.0.0.1",
  "exit_url": "https://operator.com/lobby",
  "error_url": "https://operator.com/error",
  "session_id": "f47ac10b-58cc-4372-a567-0e02b2c3d479",
  "extra_params": {
    "sound": false,
    "music": false,
    "animation": true
  }
}
```

**Response:**

```
{
  "result_code": 0,
  "session_id": "f47ac10b-58cc-4372-a567-0e02b2c3d479",
  "launch_url": "https://games.optimo-rgs.com/optimo-play/launch?token=ab12cd34&game_id=king_move&lang=en&mode=real"
}
```

