

Bet

Used when player places a bet.

Endpoint

POST /seamless/bet

Request Fields

Name	Type	Mandatory	Description
timestamp	Number	Yes	Unix epoch timestamp in milliseconds indicating when the bet was recorded on the RGS side. Used as the authoritative date/time for reporting and reconciliation.
bet_type	String	Yes	Type of bet. Possible values: BET (standard real-money bet), FREEBET (free-bet bonus), and other provider-specific types.
user_id	String	Yes	Player identifier in the Operator system.
amount	Number	Yes	Bet amount in the specified currency. When building the signature string, this value must be normalized to the currency's precision scale (e.g. 1.00 for USD). See Amount Precision .
currency	String	Yes	Currency code in ISO 4217 format.

game_id	String	Yes	Unique game identifier.
session_id	String	Yes	Active game session identifier.
transaction_id	String	Yes	Unique transaction identifier (unique per operator + game).
round_id	String	Yes	Unique game round identifier.
gift_id	String	No	Gift/bonus campaign identifier. When present, related campaign details (e.g. total spins, remaining spins) are included in <code>attributes</code> .
attributes	Object	No	Key-value map of additional game-specific metadata. Excluded from signature calculation.

Response Fields

Name	Type	Mandatory	Description
result_code	int	Yes	Result code. <code>0</code> indicates success.
message	String	No	Descriptive error message. Present only when <code>result_code</code> is non-zero.
balance	number	On success	Player's balance after the bet, in the requested currency. Required when <code>result_code</code> is <code>0</code> ; optional on error.
currency	String	On success	Currency of the returned

			balance. Must match the request currency. Required when <code>result_code</code> is 0; optional on error.
transaction_id	String	No	Operator-assigned transaction identifier, used for reconciliation.

Rules

- If `amount` exceeds the player's available balance, the Operator **must reject** the bet with `result_code: 1012` (Insufficient balance). The player's balance must not change.
- If the `round_id` has already been closed (`round_finished = 1` was received earlier), the Operator **must reject** the bet with `result_code: 1008` (Invalid round).
- If the player has reached a responsible gaming limit (loss, wager, or time), the Operator **must reject** the bet with the corresponding code: `1013` (loss limit), `1014` (wager limit), `1015` (time limit), or `1016` (general limit).
- All bet calls are idempotent by `transaction_id`. If a bet with the same `transaction_id` was already processed, return the original response. GameHub may retry the same `transaction_id` up to 16 times over ~45 hours on a non-2xx response; see [GameHub Retry Policy](#).
- To **reject** a bet, return **HTTP 200 with non-zero `result_code`**. Returning HTTP 4xx is treated as retryable, not as a definitive rejection.

Freeround bets

A bet placed under a free-rounds campaign is identified by **three correlated fields**:

Field	Value	Meaning
<code>bet_type</code>	<code>FREEBET</code>	This is a freeround placement, not a real-money bet.
<code>amount</code>	<code>0.00</code>	Wallet is NOT debited. The player's balance must not change.

<code>gift_id</code>	<code><grantId></code>	Identifier of the specific grant that funds this bet. Same value travels on the corresponding <code>FREEBET_WIN</code> and rollback for the same bet – operators can join the three records on <code>gift_id</code> to reconstruct the per-grant lifecycle.
----------------------	------------------------------	---

In addition, the `attributes` map carries one extra freeround-specific entry:

Attribute	Type	Description
<code>configure dBet</code>	String (decimal, currency-precision formatted)	The actual bet amount the player chose for this round, in the bet's currency. For fixed-amount offers this is just the fixed value; for range offers (where the campaign configures a min/max range and the player picks within it) this is the value the player actually selected.

Why `configuredBet` is sent even though `amount` is `0.00`: the wallet-level `amount` represents the **balance impact** (zero for freerounds, by definition), while `configuredBet` represents the **stake the player placed** for the purposes of game logic, RTP accounting, and reporting. The two are deliberately separate so freeround player activity can be recorded for internal RTP / KPI dashboards without ever debiting the wallet.

Additional rules specific to `FREEBET`:

- Acknowledge with `result_code: 0`, balance unchanged. The wallet isn't charged.
- Insufficient-balance rejection (`1012`) does **not** apply – the wallet isn't charged.
- Responsible-gaming limits (codes `1013` / `1014` / `1015` / `1016`) **may still apply** at your discretion. Compare against `configuredBet`, not `amount`.
- Store `gift_id` on the bet record so the matching `FREEBET_WIN` and any later rollback can be joined back to the original placement.
- An **aggregated** freeround BET (identified by `round_id = aggregated:<grantId>`) is sent when the player first uses the grant and may arrive **after the game session has ended** – the `session_id` may no longer be active. The Operator **must not** reject it due to an expired or inactive session. (Per-round freeround bets are live player actions and are unaffected by this rule.)

Example

Request:

```
POST /seamless/bet
{
  "timestamp": 1730379235000,
  "bet_type": "BET",
  "user_id": "1234",
  "amount": 1.00,
  "currency": "USD",
  "game_id": "king_move",
  "session_id": "f47ac10b-58cc-4372-a567-0e02b2c3d479",
  "transaction_id": "B112233",
  "round_id": "SBR001",
  "attributes": {
    "test1": "test value1",
    "test2": "test value2"
  }
}
```

**Response:**

```
{
  "result_code": 0,
  "balance": 56.12,
  "currency": "USD",
  "transaction_id": "B112233"
}
```

