

Rollback

Used to refund a failed or invalid bet.

Rollback Rules

Scenario	Response	GGR impact
Bet exists, no win, round open	<code>result_code: 0</code> — refund bet amount	Exclude bet from GGR (canceled)
<code>parent_transaction_id</code> not found	<code>result_code: 1011</code> (Bet not found)	Nothing to exclude
Bet already has a corresponding win	<code>result_code: 1017</code> (Bet already settled)	Bet stays in GGR
Round already closed (<code>round_finished = 1</code>)	<code>result_code: 1017</code> (Bet already settled)	Bet stays in GGR

Idempotency: Subsequent calls with the same `transaction_id` must return the same response. No additional refunds are made. GameHub may retry the same `transaction_id` up to 16 times over ~45 hours on a non-2xx response; see [GameHub Retry Policy](#).



Additional Notes

- Rollback may arrive **after the game session has ended** — the `session_id` may no longer be active. The Operator must not reject a rollback due to an expired or inactive session.
- To **reject** a rollback, return **HTTP 200 with non-zero `result_code`** (typically `1011` or `1017`). Returning HTTP 4xx is treated as retryable, not as a definitive rejection.

Freeround rollbacks

A rollback of a freeround bet (e.g. user cancelled the bet before the round started, or wallet-side compensation flow) is identified by **two correlated fields**:

Field	Value	Meaning
<code>gift_id</code>	<code><grantId></code>	Echoes the value sent on the originating <code>FREEBET</code> placement.
<code>parent_transaction_id</code>	<code><betId>-bet</code>	Points at the original <code>FREEBET</code> bet. The bet record on the operator side already carries <code>attributes.configuredBet</code> (the player's chosen stake) — look it up via this link when you need the stake value.

Per the request-fields table above, rollback requests carry **no amount field at all**, and `attributes` on a freeround rollback is empty. The stake the player placed is recoverable from the parent bet record; the campaign-side bookkeeping (one round returned to the grant's remaining-rounds counter) is internal to the platform and not reflected on the wire.

Additional rules specific to freeround rollbacks:

- Acknowledge with `result_code: 0`, balance unchanged (the original `FREEBET` was never charged).
- The rejection rules in the table above still apply: if the matching `FREEBET_WIN` was already credited, return `result_code: 1017` (Bet already settled).
- Use `gift_id` to update the campaign-side audit trail (e.g. mark the round as cancelled rather than settled).

Endpoint

`POST /seamless/rollback`

Request Fields

Name	Type	Mandatory	Description
------	------	-----------	-------------

timestamp	Number	Yes	Unix epoch timestamp in milliseconds indicating when the rollback was recorded on the RGS side. Used as the authoritative date/time for reporting and reconciliation.
user_id	String	Yes	Player identifier in the Operator system.
game_id	String	Yes	Unique game identifier.
session_id	String	Yes	Game session identifier. Note: the session may no longer be active at the time of rollback. The Operator must not reject a rollback due to an expired or inactive session.
transaction_id	String	Yes	Unique rollback transaction identifier.
parent_transaction_id	String	Yes	The <code>transaction_id</code> of the original bet to reverse.
round_id	String	Yes	Game round identifier.
gift_id	String	No	Gift/bonus campaign identifier. When present, related campaign details are included in <code>attributes</code> .
attributes	Object	No	Key-value map of additional game-specific

metadata. Excluded from signature calculation.

Response Fields

Name	Type	Mandatory	Description
result_code	int	Yes	Result code. <code>0</code> = success (bet refunded), <code>1011</code> = bet not found, <code>1017</code> = bet already settled.
message	String	No	Descriptive error message. Present only when <code>result_code</code> is non-zero.
balance	number	On success	Player's balance after the rollback. Required when <code>result_code</code> is <code>0</code> ; optional on error.
currency	String	On success	Currency of the returned balance. Must match the request currency. Required when <code>result_code</code> is <code>0</code> ; optional on error.
transaction_id	String	No	Operator-assigned transaction identifier, used for reconciliation.

Example

Request:

```
POST /seamless/rollback
{
  "timestamp": 1730379235000,
  "user_id": "1234",
  "game_id": "king_move",
  "session_id": "f47ac10b-58cc-4372-a567-0e02b2c3d479",
```



```
"transaction_id": "R112234",  
"parent_transaction_id": "B112233",  
"round_id": "SBR001"  
}
```

Response (bet refunded):

```
{  
  "result_code": 0,  
  "balance": 57.12,  
  "currency": "USD",  
  "transaction_id": "R112234"  
}
```

**Response (bet not found):**

```
{  
  "result_code": 1011,  
  "message": "Bet not found"  
}
```

**Response (bet already has a win or round closed):**

```
{  
  "result_code": 1017,  
  "message": "Bet already settled"  
}
```

