

Win

Used when player wins.

Endpoint

POST /seamless/win

Request Fields

Name	Type	Mandatory	Description
timestamp	Number	Yes	Unix epoch timestamp in milliseconds indicating when the win was recorded on the RGS side. Used as the authoritative date/time for reporting and reconciliation.
win_type	String	Yes	Type of win. Possible values: WIN (standard win), FREEBET_WIN (free-bet bonus win), JACKPOT (jackpot payout), CLOSE_ROUND (explicit round closure signal), and other provider-specific types.
user_id	String	Yes	Player identifier in the Operator system.
amount	Number	Yes	Win amount in the specified currency. When

			building the signature string, this value must be normalized to the currency's precision scale (e.g. <code>1.00</code> for USD). See Amount Precision .
currency	String	Yes	Currency code in ISO 4217 format.
game_id	String	Yes	Unique game identifier.
session_id	String	Yes	Game session identifier. Note: the session may no longer be active at the time of win (e.g. due to late settlement, retries, or reconciliation). The Operator must not reject a win due to an expired or inactive session.
transaction_id	String	Yes	Unique transaction identifier (unique per operator + game).
parent_transaction_id	String	No	The <code>transaction_id</code> of the originating bet. Sent when <code>win_type</code> is <code>WIN</code> or <code>FREEBET_WIN</code> ; <code>null</code> otherwise (e.g. for <code>JACKPOT</code> , <code>CLOSE_ROUND</code>).
round_id	String	Yes	Unique game round identifier. The Operator must reject the request if the round has already been closed.
round_finished	int	Yes	Indicates whether this is

			the final action in the round. <code>1</code> = round is now closed — no further bet, win, or rollback requests with this <code>round_id</code> are permitted. <code>0</code> = round remains open.
gift_id	String	No	Gift/bonus campaign identifier. When present, related campaign details are included in <code>attributes</code> .
attributes	Object	No	Key-value map of additional game-specific metadata. Excluded from signature calculation.

Response Fields

Name	Type	Mandatory	Description
result_code	int	Yes	Result code. <code>0</code> indicates success.
message	String	No	Descriptive error message. Present only when <code>result_code</code> is non-zero.
balance	number	On success	Player's balance after the win, in the requested currency. Required when <code>result_code</code> is <code>0</code> ; optional on error.
currency	String	On success	Currency of the returned balance. Must match the request currency. Required when <code>result_code</code> is <code>0</code> ; optional on

error.			
transaction_id	String	No	Operator-assigned transaction identifier, used for reconciliation.

Rules

- When `win_type` is `WIN` or `FREEBET_WIN`, the `parent_transaction_id` references the originating bet. If the referenced bet does **not** exist in the Operator's system (i.e. the `parent_transaction_id` cannot be found), the Operator **must not** credit the win amount. Return `result_code: 1011` (Bet not found).
- A bet can only have **one** corresponding win. If a win arrives with a different `transaction_id` but references a `parent_transaction_id` that already has a recorded win, the Operator **should reject** with `result_code: 1011` (Bet not found). The bet is considered settled by the first win.

Note — defense in depth. The aggregator already derives every Win `transaction_id` deterministically from the originating bet's `transaction_id` (one win per bet produces one fixed txid), so retries always reuse the same value and are caught by the standard `transaction_id` idempotency check (see the last bullet in this section). This parent-reference guard is therefore a **nice-to-have** safety net rather than strictly required. Implementing it protects the Operator's ledger against any caller that regenerates txids on retry and makes double-settlement physically impossible regardless of provider behaviour.

- When `win_type` is `JACKPOT`, `parent_transaction_id` is `null` — no bet lookup is required.
- When `win_type` is `CLOSE_ROUND`, `parent_transaction_id` is `null` — no bet lookup is required. This is an explicit round closure signal: `amount` is `0` and `round_finished` is `1`. It is used to close rounds that were not closed by a prior win. This is not sent for every user — only for users whose round was not already closed (e.g. a player who placed bets but cancelled them all before the game started). The Operator should acknowledge with `result_code: 0` and current balance.
- When `win_type` is `FREEBET_WIN` and the originating offer's `bet_mode = BET_FROM_WIN`, the `amount` is **already netted** of the bet stake by the platform: `amount = max(0, nominalWin - stake)`. Operators **should not** apply any additional deduction. A zero-amount `FREEBET_WIN` is a real settlement (the bet's outcome was a win whose net to the player is zero) — acknowledge with `result_code: 0` and current balance, same as any non-zero `FREEBET_WIN`.

Worked example: stake `1.00`, multiplier `5x`, nominal `5.00`, `BET_FROM_WIN` net = `5.00 - 1.00 = 4.00` — operator receives `amount: 4.00`. At unit multiplier (1.0x): nominal `1.00`, net = `0.00` — operator receives `amount: 0.00` and still

acknowledges. ZERO_BET freerounds receive the full nominal (no deduction). The wire fields `bet_type=FREEBET` and `win_type=FREEBET_WIN` are identical for both modes; only the `amount` differs. - If the `round_id` has already been closed (`round_finished = 1` was received earlier), the Operator **must reject** the request with `result_code: 1008` (Invalid round). - Win may arrive **after the game session has ended** – the `session_id` may no longer be active (e.g. due to late settlement, aggregator retries, or reconciliation). The Operator **must not** reject a win due to an expired or inactive session. - All win calls are idempotent by `transaction_id`. If a win with the same `transaction_id` was already processed, return the original response. GameHub may retry the same `transaction_id` up to 16 times over ~45 hours on a non-2xx response; see [GameHub Retry Policy](#). - To **reject** a win, return **HTTP 200 with non-zero result_code**. Returning HTTP 4xx is treated as retryable, not as a definitive rejection.

Freeround wins

A win settling a freeround bet is identified by **three correlated fields**:

Field	Value	Meaning
<code>win_type</code>	<code>FREEBET_WIN</code>	This is the settlement of a freeround bet, not a real-money win.
<code>gift_id</code>	<code><grantId></code>	Echoes the value sent on the originating bet's <code>gift_id</code> . Operators can join the bet and win records on this field.
<code>parent_transaction_id</code>	<code><betId>-bet</code>	The <code>transaction_id</code> of the originating <code>FREEBET</code> bet – same correlation key as for normal <code>WIN</code> .

The `amount` semantics for freeround wins are spelled out in the `BET_FROM_WIN` rule above. In short:

- **ZERO_BET** mode (the default freeround mode): operator receives the full nominal win amount.
- **BET_FROM_WIN** mode: operator receives `max(0, nominalWin - stake)` – the platform has already netted the bet stake. A zero-amount `FREEBET_WIN` is a real

settlement, not a skip, and must be acknowledged with `result_code: 0`.

The `attributes` map on a `FREEBET_WIN` is typically empty – the freeround-specific metadata that travels on the bet (e.g. `configuredBet`) is captured at placement time and isn't re-sent on the win.

Additional rules specific to `FREEBET_WIN`:

- Acknowledge with `result_code: 0` and credit `amount` to the player's balance.
- The originating bet was sent with `amount: 0.00` (no wallet debit). The `FREEBET_WIN` is the **first** point in the freeround lifecycle where the balance moves.
- A `FREEBET_WIN` with `amount: 0.00` is a valid settlement (loss outcome on a freeround, or a zero-net `BET_FROM_WIN` cashout). Acknowledge it – do not reject.

Example

Request:

```
POST /seamless/win
{
  "timestamp": 1730379235000,
  "win_type": "WIN",
  "user_id": "1234",
  "amount": 1.00,
  "currency": "USD",
  "game_id": "king_move",
  "session_id": "f47ac10b-58cc-4372-a567-0e02b2c3d479",
  "transaction_id": "W112234",
  "parent_transaction_id": "B112233",
  "round_id": "SBR001",
  "round_finished": 1,
  "attributes": {
    "test1": "test value1",
    "test2": "test value2"
  }
}
```

Response:

```
{
  "result_code": 0,
  "balance": 61.12,
  "currency": "USD",
  "transaction_id": "W112234"
}
```

Example: Close Round

Request:

```
POST /seamless/win
{
  "timestamp": 1730379240000,
  "win_type": "CLOSE_ROUND",
  "user_id": "1234",
  "amount": 0.00,
  "currency": "USD",
  "game_id": "king_move",
  "session_id": "f47ac10b-58cc-4372-a567-0e02b2c3d479",
  "transaction_id": "close-round-SBR001-1234",
  "round_id": "SBR001",
  "round_finished": 1
}
```

`CLOSE_ROUND` is not mandatory and is not sent for every player. It is only sent when a player's round was not already closed by a regular win. `parent_transaction_id` is absent — no bet lookup is required.