

Photon Voice

v2.4.1

Generated by Doxygen 1.8.10

Thu Feb 21 2019 17:48:01

Contents

1	Photon Voice Doxygen Readme	1
2	Namespace Documentation	3
2.1	Photon Namespace Reference	3
2.2	Photon.Voice Namespace Reference	3
2.2.1	Enumeration Type Documentation	6
2.2.1.1	Codec	6
2.3	Photon.Voice.IOS Namespace Reference	6
2.4	Photon.Voice.PUN Namespace Reference	6
2.5	Photon.Voice.Unity Namespace Reference	6
2.6	Photon.Voice.Unity.UtilityScripts Namespace Reference	7
2.7	POpusCodec Namespace Reference	7
2.8	POpusCodec.Enums Namespace Reference	8
2.8.1	Enumeration Type Documentation	8
2.8.1.1	Bandwidth	8
2.8.1.2	Channels	8
2.8.1.3	Delay	8
2.8.1.4	OpusApplicationType	9
2.8.1.5	SignalHint	9
3	Class Documentation	11
3.1	SpeexProcessor.AECLatencyResultType Struct Reference	11
3.2	AudioClipWrapper Class Reference	11
3.3	AudioDesc Class Reference	11
3.4	AudioInEnumerator Class Reference	12
3.5	AudioOutCapture Class Reference	12
3.6	AudioSessionParameters Struct Reference	12
3.7	AudioSessionParametersPresets Class Reference	13
3.7.1	Member Data Documentation	13
3.7.1.1	Game	13
3.7.1.2	VoIP	13
3.8	AudioStreamPlayer Class Reference	13

3.9	AudioUtil Class Reference	13
3.9.1	Detailed Description	15
3.9.2	Member Function Documentation	15
3.9.2.1	Convert(float[] src, short[] dst, int dstCount)	15
3.9.2.2	Convert(short[] src, float[] dst, int dstCount)	15
3.9.2.3	ForceToStereo< T >(T[] src, T[] dst, int srcChannels)	15
3.9.2.4	Resample< T >(T[] src, T[] dst, int dstCount, int channels)	15
3.9.2.5	ResampleAndConvert(short[] src, float[] dst, int dstCount, int channels)	15
3.9.2.6	ResampleAndConvert(float[] src, short[] dst, int dstCount, int channels)	17
3.10	BufferReaderPushAdapter< T > Class Template Reference	17
3.10.1	Detailed Description	17
3.10.2	Constructor & Destructor Documentation	17
3.10.2.1	BufferReaderPushAdapter(LocalVoice localVoice, IDataReader< T > reader)	17
3.10.3	Member Function Documentation	18
3.10.3.1	Service(LocalVoice localVoice)	18
3.11	BufferReaderPushAdapterAsyncPool< T > Class Template Reference	18
3.11.1	Detailed Description	18
3.11.2	Constructor & Destructor Documentation	18
3.11.2.1	BufferReaderPushAdapterAsyncPool(LocalVoice localVoice, IDataReader< T > reader)	18
3.11.3	Member Function Documentation	18
3.11.3.1	Service(LocalVoice localVoice)	19
3.12	BufferReaderPushAdapterAsyncPoolCopy< T > Class Template Reference	20
3.12.1	Detailed Description	20
3.12.2	Constructor & Destructor Documentation	20
3.12.2.1	BufferReaderPushAdapterAsyncPoolCopy(LocalVoice localVoice, IDataReader< T > reader)	20
3.12.3	Member Function Documentation	20
3.12.3.1	Service(LocalVoice localVoice)	20
3.13	BufferReaderPushAdapterAsyncPoolFloatToShort Class Reference	21
3.13.1	Detailed Description	21
3.13.2	Constructor & Destructor Documentation	21
3.13.2.1	BufferReaderPushAdapterAsyncPoolFloatToShort(Voice.LocalVoice localVoice, Voice.IDataReader< float > reader)	21
3.13.3	Member Function Documentation	21
3.13.3.1	Service(Voice.LocalVoice localVoice)	21
3.14	BufferReaderPushAdapterBase< T > Class Template Reference	21
3.14.1	Detailed Description	22
3.14.2	Constructor & Destructor Documentation	22
3.14.2.1	BufferReaderPushAdapterBase(IDataReader< T > reader)	22
3.14.3	Member Function Documentation	22

3.14.3.1	Dispose()	22
3.14.3.2	Service(LocalVoice localVoice)	22
3.15	WebRTCAudioLib.ConfigParam Struct Reference	23
3.16	ConnectAndJoin Class Reference	23
3.17	OpusCodec.Decoder Class Reference	23
3.17.1	Member Function Documentation	24
3.17.1.1	DecodeToByte(byte[] buf)	24
3.17.1.2	DecodeToFloat(byte[] buf)	24
3.17.1.3	DecodeToShort(byte[] buf)	24
3.17.1.4	Open(VoiceInfo i)	25
3.18	OpusCodec.Encoder< T > Class Template Reference	25
3.18.1	Member Function Documentation	25
3.18.1.1	EncodeAndGetOutput(T[] buf)	25
3.19	OpusCodec.EncoderFactory Class Reference	26
3.20	OpusCodec.EncoderFloat Class Reference	26
3.21	OpusCodec.EncoderShort Class Reference	26
3.22	FactoryPrimitiveArrayPool< T > Class Template Reference	26
3.22.1	Detailed Description	27
3.23	FactoryReusableArray< T > Class Template Reference	27
3.23.1	Detailed Description	27
3.24	Framer< T > Class Template Reference	27
3.24.1	Detailed Description	28
3.24.2	Constructor & Destructor Documentation	28
3.24.2.1	Framer(int frameSize)	28
3.24.3	Member Function Documentation	28
3.24.3.1	Count(int bufLen)	28
3.24.3.2	Frame(T[] buf)	28
3.25	IAudioDesc Interface Reference	28
3.25.1	Detailed Description	29
3.25.2	Property Documentation	29
3.25.2.1	Channels	29
3.25.2.2	Error	29
3.25.2.3	SamplingRate	29
3.26	IAudioOut Interface Reference	29
3.27	IAudioPusher< T > Interface Template Reference	29
3.27.1	Detailed Description	30
3.27.2	Member Function Documentation	30
3.27.2.1	SetCallback(Action< T[]> callback, ObjectFactory< T[], int > bufferFactory)	30
3.28	IAudioReader< T > Interface Template Reference	30
3.28.1	Detailed Description	30

3.29	IDataReader< T > Interface Template Reference	30
3.29.1	Detailed Description	30
3.29.2	Member Function Documentation	31
3.29.2.1	Read(T[] buffer)	31
3.30	IDecoder Interface Reference	31
3.30.1	Detailed Description	31
3.30.2	Member Function Documentation	31
3.30.2.1	Open(VoiceInfo info)	31
3.30.3	Property Documentation	31
3.30.3.1	Error	31
3.31	IDecoderDirect Interface Reference	32
3.31.1	Detailed Description	32
3.31.2	Member Function Documentation	32
3.31.2.1	DecodeToByte(byte[] buf)	32
3.31.2.2	DecodeToFloat(byte[] buf)	32
3.31.2.3	DecodeToShort(byte[] buf)	33
3.32	IDecoderQueued Interface Reference	33
3.32.1	Detailed Description	33
3.32.2	Member Function Documentation	33
3.32.2.1	Decode(byte[] buf)	33
3.33	IDecoderQueuedOutputImageNative Interface Reference	33
3.34	IEncoder Interface Reference	34
3.34.1	Detailed Description	34
3.34.2	Property Documentation	34
3.34.2.1	Error	34
3.35	IEncoderDataFlow< T > Interface Template Reference	34
3.35.1	Detailed Description	34
3.36	IEncoderDataFlowDirect< T > Interface Template Reference	34
3.36.1	Detailed Description	35
3.36.2	Member Function Documentation	35
3.36.2.1	EncodeAndGetOutput(T[] buf)	35
3.37	IEncoderNativeImageDirect Interface Reference	35
3.38	IEncoderQueued Interface Reference	35
3.38.1	Detailed Description	36
3.38.2	Member Function Documentation	36
3.38.2.1	GetOutput()	36
3.39	AudioUtil.ILevelMeter Interface Reference	36
3.39.1	Detailed Description	36
3.39.2	Member Function Documentation	36
3.39.2.1	ResetAccumAvgPeakAmp()	36

3.39.3	Property Documentation	37
3.39.3.1	AccumAvgPeakAmp	37
3.39.3.2	CurrentAvgAmp	37
3.39.3.3	CurrentPeakAmp	37
3.40	ILocalVoiceAudio Interface Reference	37
3.40.1	Detailed Description	37
3.40.2	Member Function Documentation	37
3.40.2.1	VoiceDetectorCalibrate(int durationMs)	37
3.40.3	Property Documentation	38
3.40.3.1	LevelMeter	38
3.40.3.2	VoiceDetector	38
3.40.3.3	VoiceDetectorCalibrating	38
3.41	ILoggable Interface Reference	38
3.42	ILogger Interface Reference	38
3.43	ImageBufferInfo Class Reference	38
3.44	ImageBufferNative Class Reference	39
3.45	ImageBufferNativeAlloc Class Reference	39
3.46	ImageBufferNativeGCHandleSinglePlane Class Reference	39
3.47	ImageBufferNativePool< T > Class Template Reference	40
3.48	IOSAudioForceToSpeaker Class Reference	40
3.49	IProcessor< T > Interface Template Reference	40
3.49.1	Detailed Description	40
3.49.2	Member Function Documentation	40
3.49.2.1	Process(T[] buf)	40
3.50	IServiceable Interface Reference	41
3.50.1	Detailed Description	41
3.50.2	Member Function Documentation	41
3.50.2.1	Service(LocalVoice localVoice)	41
3.51	ISyncAudioOut Interface Reference	41
3.52	AudioUtil.IVoiceDetector Interface Reference	42
3.52.1	Detailed Description	42
3.52.2	Property Documentation	42
3.52.2.1	ActivityDelayMs	42
3.52.2.2	Detected	42
3.52.2.3	DetectedTime	42
3.52.2.4	On	42
3.52.2.5	Threshold	42
3.52.3	Event Documentation	43
3.52.3.1	OnDetected	43
3.53	IVoiceTransport Interface Reference	43

3.54	AudioUtil.LevelMeter< T > Class Template Reference	43
3.54.1	Detailed Description	44
3.54.2	Member Function Documentation	44
3.54.2.1	Process(T[] buf)	44
3.54.2.2	ResetAccumAvgPeakAmp()	44
3.55	AudioUtil.LevelMeterDummy Class Reference	44
3.55.1	Detailed Description	44
3.55.2	Member Function Documentation	45
3.55.2.1	ResetAccumAvgPeakAmp()	45
3.56	AudioUtil.LevelMeterFloat Class Reference	45
3.56.1	Detailed Description	45
3.56.2	Constructor & Destructor Documentation	45
3.56.2.1	LevelMeterFloat(int samplingRate, int numChannels)	45
3.57	AudioUtil.LevelMeterShort Class Reference	45
3.57.1	Detailed Description	46
3.57.2	Constructor & Destructor Documentation	46
3.57.2.1	LevelMeterShort(int samplingRate, int numChannels)	46
3.58	LoadBalancingFrontend Class Reference	46
3.59	LoadBalancingTransport Class Reference	46
3.59.1	Detailed Description	47
3.59.2	Constructor & Destructor Documentation	47
3.59.2.1	LoadBalancingTransport(ConnectionProtocol connectionProtocol=Connection↔ Protocol.Udp)	47
3.59.3	Member Function Documentation	47
3.59.3.1	Dispose()	47
3.59.3.2	SendDebugEchoVoicesInfo(int channelId)	48
3.59.3.3	Service()	49
3.59.4	Property Documentation	49
3.59.4.1	GlobalInterestGroup	49
3.59.4.2	VoiceClient	49
3.60	LocalVoice Class Reference	49
3.60.1	Detailed Description	50
3.60.2	Member Function Documentation	50
3.60.2.1	RemoveSelf()	50
3.60.3	Property Documentation	50
3.60.3.1	DebugEchoMode	50
3.60.3.2	Encrypt	50
3.60.3.3	FramesSent	51
3.60.3.4	FramesSentBytes	51
3.60.3.5	Info	51

3.60.3.6	InterestGroup	51
3.60.3.7	IsCurrentlyTransmitting	51
3.60.3.8	LocalUserServiceable	51
3.60.3.9	Reliable	51
3.60.3.10	TransmitEnabled	51
3.61	LocalVoiceAudio< T > Class Template Reference	51
3.61.1	Detailed Description	52
3.61.2	Member Function Documentation	52
3.61.2.1	Create(VoiceClient voiceClient, byte voiceId, IEncoder encoder, VoiceInfo voiceInfo, int channelId)	52
3.61.2.2	VoiceDetectorCalibrate(int durationMs)	52
3.61.3	Property Documentation	53
3.61.3.1	VoiceDetectorCalibrating	53
3.62	LocalVoiceAudioDummy Class Reference	53
3.62.1	Detailed Description	53
3.62.2	Member Function Documentation	53
3.62.2.1	VoiceDetectorCalibrate(int durationMs)	53
3.62.3	Member Data Documentation	54
3.62.3.1	Dummy	54
3.63	LocalVoiceAudioFloat Class Reference	54
3.63.1	Detailed Description	54
3.64	LocalVoiceAudioShort Class Reference	54
3.64.1	Detailed Description	54
3.65	LocalVoiceFramed< T > Class Template Reference	54
3.65.1	Detailed Description	55
3.65.2	Member Function Documentation	55
3.65.2.1	AddPostProcessor(params IProcessor< T >[] processors)	55
3.65.2.2	AddPreProcessor(params IProcessor< T >[] processors)	55
3.65.2.3	ClearProcessors()	56
3.65.2.4	Dispose()	56
3.65.2.5	PushData(T[] buf)	56
3.65.2.6	PushDataAsync(T[] buf)	56
3.65.3	Property Documentation	56
3.65.3.1	PushDataAsyncReady	56
3.66	LocalVoiceFramedBase Class Reference	56
3.66.1	Detailed Description	56
3.66.2	Property Documentation	57
3.66.2.1	FrameSize	57
3.67	Logger Class Reference	57
3.68	MicWrapper Class Reference	57

3.69	ObjectFactory< TType, TInfo > Interface Template Reference	57
3.69.1	Detailed Description	58
3.70	ObjectPool< TType, TInfo > Class Template Reference	58
3.70.1	Detailed Description	59
3.70.2	Constructor & Destructor Documentation	59
3.70.2.1	ObjectPool(int capacity, string name)	59
3.70.2.2	ObjectPool(int capacity, string name, TInfo info)	59
3.70.3	Member Function Documentation	59
3.70.3.1	AcquireOrCreate()	59
3.70.3.2	AcquireOrCreate(TInfo info)	59
3.70.3.3	Dispose()	59
3.70.3.4	Init(TInfo info)	60
3.70.3.5	Release(TType obj, TInfo objInfo)	60
3.70.3.6	Release(TType obj)	60
3.70.4	Property Documentation	60
3.70.4.1	Info	60
3.71	OpusCodec Class Reference	60
3.72	OpusDecoder Class Reference	60
3.73	OpusEncoder Class Reference	61
3.73.1	Property Documentation	61
3.73.1.1	EncoderDelay	61
3.74	OpusException Class Reference	62
3.75	WebRTCAudioLib.Param Struct Reference	62
3.76	PhotonVoiceCreatedParams Class Reference	62
3.77	Recorder.PhotonVoiceCreatedParams Class Reference	62
3.78	PhotonVoiceLagSimulationGui Class Reference	63
3.79	PhotonVoiceNetwork Class Reference	63
3.79.1	Detailed Description	64
3.79.2	Member Function Documentation	64
3.79.2.1	ConnectAndJoinRoom()	64
3.79.2.2	Disconnect()	64
3.79.3	Member Data Documentation	64
3.79.3.1	AutoConnectAndJoin	64
3.79.3.2	AutoCreateSpeakerIfNotFound	64
3.79.3.3	AutoLeaveAndDisconnect	64
3.79.3.4	VoiceRoomNameSuffix	64
3.79.4	Property Documentation	64
3.79.4.1	Instance	64
3.80	PhotonVoiceStatsGui Class Reference	65
3.80.1	Detailed Description	65

3.81 PhotonVoiceView Class Reference	65
3.81.1 Detailed Description	66
3.81.2 Member Data Documentation	66
3.81.2.1 AutoCreateRecorderIfNotFound	66
3.81.2.2 SetupDebugSpeaker	66
3.81.2.3 UsePrimaryRecorder	66
3.81.3 Property Documentation	66
3.81.3.1 IsRecorder	66
3.81.3.2 IsRecording	66
3.81.3.3 IsSetup	66
3.81.3.4 IsSpeaker	66
3.81.3.5 IsSpeaking	66
3.81.3.6 RecorderInUse	66
3.81.3.7 SpeakerInUse	67
3.82 PrimitiveArrayPool< T > Class Template Reference	67
3.82.1 Detailed Description	67
3.83 Recorder Class Reference	67
3.83.1 Detailed Description	69
3.83.2 Member Function Documentation	69
3.83.2.1 Init(VoiceClient voiceClient, object customObj=null)	69
3.83.2.2 ReInit()	69
3.83.2.3 VoiceDetectorCalibrate(int durationMs)	69
3.83.3 Property Documentation	70
3.83.3.1 AudioClip	70
3.83.3.2 AudioGroup	70
3.83.3.3 Bitrate	70
3.83.3.4 DebugEchoMode	70
3.83.3.5 Encrypt	70
3.83.3.6 FrameDuration	70
3.83.3.7 InputFactory	70
3.83.3.8 InterestGroup	70
3.83.3.9 IsCurrentlyTransmitting	70
3.83.3.10 IsInitialized	70
3.83.3.11 LevelMeter	71
3.83.3.12 LoopAudioClip	71
3.83.3.13 MicrophoneType	71
3.83.3.14 PhotonMicrophoneDeviceld	71
3.83.3.15 PhotonMicrophoneEnumerator	71
3.83.3.16 ReliableMode	71
3.83.3.17 RequiresInit	71

3.83.3.18 SamplingRate	71
3.83.3.19 SourceType	71
3.83.3.20 TransmitEnabled	71
3.83.3.21 TypeConvert	71
3.83.3.22 UnityMicrophoneDevice	71
3.83.3.23 UserData	72
3.83.3.24 VoiceDetection	72
3.83.3.25 VoiceDetectionDelayMs	72
3.83.3.26 VoiceDetectionThreshold	72
3.83.3.27 VoiceDetector	72
3.83.3.28 VoiceDetectorCalibrating	72
3.84 RemoteVoiceInfo Class Reference	72
3.84.1 Detailed Description	72
3.84.2 Property Documentation	72
3.84.2.1 ChannelId	72
3.84.2.2 Info	73
3.84.2.3 PlayerId	73
3.84.2.4 VoiceId	73
3.85 RemoteVoiceLink Class Reference	73
3.86 RemoteVoiceOptions Struct Reference	73
3.86.1 Detailed Description	74
3.86.2 Property Documentation	74
3.86.2.1 Decoder	74
3.86.2.2 OnDecodedFrameByteAction	74
3.86.2.3 OnDecodedFrameFloatAction	74
3.86.2.4 OnDecodedFrameShortAction	74
3.86.2.5 OnRemoteVoiceRemoveAction	74
3.87 AudioUtil.Resampler< T > Class Template Reference	74
3.87.1 Detailed Description	74
3.87.2 Constructor & Destructor Documentation	75
3.87.2.1 Resampler(int dstSize, int channels)	75
3.87.3 Member Function Documentation	75
3.87.3.1 Process(T[] buf)	75
3.88 Speaker Class Reference	75
3.88.1 Detailed Description	76
3.88.2 Property Documentation	76
3.88.2.1 Actor	76
3.88.2.2 IsLinked	76
3.88.2.3 IsPlaying	76
3.88.2.4 Lag	76

3.88.2.5 OnRemoteVoiceRemoveAction	76
3.89 SpeexLib Class Reference	76
3.89.1 Member Data Documentation	78
3.89.1.1 SPEEX_ECHO_GET_FRAME_SIZE	78
3.89.1.2 SPEEX_ECHO_GET_IMPULSE_RESPONSE	78
3.89.1.3 SPEEX_ECHO_GET_IMPULSE_RESPONSE_SIZE	78
3.89.1.4 SPEEX_ECHO_GET_SAMPLING_RATE	78
3.89.1.5 SPEEX_ECHO_SET_SAMPLING_RATE	78
3.89.1.6 SPEEX_PREPROCESS_GET_AGC	78
3.89.1.7 SPEEX_PREPROCESS_GET_AGC_DECREMENT	78
3.89.1.8 SPEEX_PREPROCESS_GET_AGC_GAIN	78
3.89.1.9 SPEEX_PREPROCESS_GET_AGC_INCREMENT	78
3.89.1.10 SPEEX_PREPROCESS_GET_AGC_LEVEL	78
3.89.1.11 SPEEX_PREPROCESS_GET_AGC_LOUDNESS	78
3.89.1.12 SPEEX_PREPROCESS_GET_AGC_MAX_GAIN	78
3.89.1.13 SPEEX_PREPROCESS_GET_AGC_TARGET	79
3.89.1.14 SPEEX_PREPROCESS_GET_DENOISE	79
3.89.1.15 SPEEX_PREPROCESS_GET_DEREVERB	79
3.89.1.16 SPEEX_PREPROCESS_GET_DEREVERB_DECAY	79
3.89.1.17 SPEEX_PREPROCESS_GET_DEREVERB_LEVEL	79
3.89.1.18 SPEEX_PREPROCESS_GET_ECHO_STATE	79
3.89.1.19 SPEEX_PREPROCESS_GET_ECHO_SUPPRESS	79
3.89.1.20 SPEEX_PREPROCESS_GET_ECHO_SUPPRESS_ACTIVE	79
3.89.1.21 SPEEX_PREPROCESS_GET_NOISE_PSD	79
3.89.1.22 SPEEX_PREPROCESS_GET_NOISE_PSD_SIZE	79
3.89.1.23 SPEEX_PREPROCESS_GET_NOISE_SUPPRESS	79
3.89.1.24 SPEEX_PREPROCESS_GET_PROB	79
3.89.1.25 SPEEX_PREPROCESS_GET_PROB_CONTINUE	80
3.89.1.26 SPEEX_PREPROCESS_GET_PROB_START	80
3.89.1.27 SPEEX_PREPROCESS_GET_PSD	80
3.89.1.28 SPEEX_PREPROCESS_GET_PSD_SIZE	80
3.89.1.29 SPEEX_PREPROCESS_GET_VAD	80
3.89.1.30 SPEEX_PREPROCESS_SET_AGC	80
3.89.1.31 SPEEX_PREPROCESS_SET_AGC_DECREMENT	80
3.89.1.32 SPEEX_PREPROCESS_SET_AGC_INCREMENT	80
3.89.1.33 SPEEX_PREPROCESS_SET_AGC_LEVEL	80
3.89.1.34 SPEEX_PREPROCESS_SET_AGC_MAX_GAIN	80
3.89.1.35 SPEEX_PREPROCESS_SET_AGC_TARGET	80
3.89.1.36 SPEEX_PREPROCESS_SET_DENOISE	80
3.89.1.37 SPEEX_PREPROCESS_SET_DEREVERB	81

3.89.1.38 SPEEX_PREPROCESS_SET_DEREVERB_DECAY	81
3.89.1.39 SPEEX_PREPROCESS_SET_DEREVERB_LEVEL	81
3.89.1.40 SPEEX_PREPROCESS_SET_ECHO_STATE	81
3.89.1.41 SPEEX_PREPROCESS_SET_ECHO_SUPPRESS	81
3.89.1.42 SPEEX_PREPROCESS_SET_ECHO_SUPPRESS_ACTIVE	81
3.89.1.43 SPEEX_PREPROCESS_SET_NOISE_SUPPRESS	81
3.89.1.44 SPEEX_PREPROCESS_SET_PROB_CONTINUE	81
3.89.1.45 SPEEX_PREPROCESS_SET_PROB_START	81
3.89.1.46 SPEEX_PREPROCESS_SET_VAD	81
3.90 SpeexProcessor Class Reference	81
3.91 TestTone Class Reference	82
3.92 AudioUtil.ToneAudioPusher< T > Class Template Reference	82
3.92.1 Detailed Description	83
3.92.2 Constructor & Destructor Documentation	83
3.92.2.1 ToneAudioPusher(int frequency=440, int bufSizeMs=100, int sampling↵ Rate=441000, int channels=2)	83
3.92.3 Member Function Documentation	83
3.92.3.1 SetCallback(Action< T[]> callback, ObjectFactory< T[], int > bufferFactory) . .	83
3.93 AudioUtil.ToneAudioReader< T > Class Template Reference	83
3.93.1 Detailed Description	84
3.93.2 Constructor & Destructor Documentation	84
3.93.2.1 ToneAudioReader(Func< double > clockSec=null, double frequency=440, int samplingRate=441000, int channels=2)	84
3.93.3 Member Function Documentation	84
3.93.3.1 Read(T[] buf)	84
3.93.4 Property Documentation	84
3.93.4.1 Channels	84
3.93.4.2 Error	84
3.93.4.3 SamplingRate	84
3.94 ToneAudioReader Class Reference	84
3.95 UnityAndroidAudioInAEC Class Reference	85
3.96 UnityAudioOut Class Reference	85
3.97 UnsupportedCodecException Class Reference	86
3.97.1 Detailed Description	86
3.97.2 Constructor & Destructor Documentation	86
3.97.2.1 UnsupportedCodecException(string info, Codec codec, ILogger logger)	86
3.98 UnsupportedSampleTypeException Class Reference	86
3.98.1 Detailed Description	86
3.98.2 Constructor & Destructor Documentation	86
3.98.2.1 UnsupportedSampleTypeException(Type t)	86

3.99 OpusCodec.Util Class Reference	87
3.100VoiceClient Class Reference	87
3.100.1 Detailed Description	88
3.100.2 Member Function Documentation	88
3.100.2.1 CreateLocalVoice(VoiceInfo voiceInfo, int channelId=ChannelAuto, IEncoder encoder=null)	88
3.100.2.2 CreateLocalVoiceAudio< T >(VoiceInfo voiceInfo, int channelId=ChannelAuto, IEncoder encoder=null)	88
3.100.2.3 CreateLocalVoiceAudioFromSource(Voice.VoiceInfo voiceInfo, Voice.IAudioDesc source, bool forceShort=false, int channelId=ChannelAuto, IEncoder encoder=null)	89
3.100.2.4 CreateLocalVoiceFramed< T >(VoiceInfo voiceInfo, int frameSize, int channelId=ChannelAuto, IEncoderDataFlow< T > encoder=null)	89
3.100.2.5 LocalVoicesInChannel(int channelId)	90
3.100.2.6 RemoteVoiceInfoDelegate(int channelId, int playerId, byte voiceId, VoiceInfo voiceInfo, ref RemoteVoiceOptions options)	90
3.100.2.7 RemoveLocalVoice(LocalVoice voice)	90
3.100.2.8 Service()	90
3.100.3 Property Documentation	90
3.100.3.1 DebugLostPercent	90
3.100.3.2 FramesLost	90
3.100.3.3 FramesReceived	90
3.100.3.4 FramesSent	90
3.100.3.5 FramesSentBytes	91
3.100.3.6 LocalVoices	91
3.100.3.7 OnRemoteVoiceInfoAction	91
3.100.3.8 RemoteVoiceInfos	91
3.100.3.9 RoundTripTime	91
3.100.3.10RoundTripTimeVariance	91
3.100.3.11SuppressInfoDuplicateWarning	91
3.101VoiceComponent Class Reference	91
3.102VoiceConnection Class Reference	92
3.102.1 Detailed Description	93
3.102.2 Member Function Documentation	93
3.102.2.1 ConnectUsingSettings(AppSettings overwriteSettings=null)	93
3.102.3 Member Data Documentation	93
3.102.3.1 PrimaryRecorder	93
3.102.3.2 Settings	93
3.102.3.3 SpeakerFactory	93
3.102.4 Property Documentation	93
3.102.4.1 ClientState	93
3.102.4.2 FramesLostPercent	94

3.102.4.3 FramesLostPerSecond	94
3.102.4.4 FramesReceivedPerSecond	94
3.102.4.5 Logger	94
3.102.4.6 LogLevel	94
3.102.4.7 SpeakerPrefab	94
3.102.4.8 VoiceClient	94
3.102.5 Event Documentation	94
3.102.5.1 RemoteVoiceAdded	94
3.102.5.2 SpeakerLinked	94
3.103AudioUtil.VoiceDetector< T > Class Template Reference	94
3.103.1 Detailed Description	95
3.103.2 Member Function Documentation	95
3.103.2.1 Process(T[] buf)	95
3.103.3 Property Documentation	95
3.103.3.1 ActivityDelayMs	95
3.103.3.2 Detected	96
3.103.3.3 DetectedTime	96
3.103.3.4 On	96
3.103.3.5 Threshold	96
3.103.4 Event Documentation	96
3.103.4.1 OnDetected	96
3.104AudioUtil.VoiceDetectorCalibration< T > Class Template Reference	96
3.104.1 Detailed Description	97
3.104.2 Constructor & Destructor Documentation	97
3.104.2.1 VoiceDetectorCalibration(IVoiceDetector voiceDetector, ILevelMeter levelMeter, int samplingRate, int channels)	97
3.104.3 Member Function Documentation	97
3.104.3.1 Calibrate(int durationMs)	97
3.104.3.2 Process(T[] buf)	97
3.105AudioUtil.VoiceDetectorDummy Class Reference	97
3.105.1 Detailed Description	98
3.106AudioUtil.VoiceDetectorFloat Class Reference	98
3.106.1 Detailed Description	98
3.106.2 Constructor & Destructor Documentation	98
3.106.2.1 VoiceDetectorFloat(int samplingRate, int numChannels)	98
3.107AudioUtil.VoiceDetectorShort Class Reference	98
3.107.1 Detailed Description	99
3.107.2 Constructor & Destructor Documentation	99
3.107.2.1 VoiceDetectorShort(int samplingRate, int numChannels)	99
3.108VoiceEventCode Class Reference	99

3.108.1 Detailed Description	99
3.108.2 Member Function Documentation	100
3.108.2.1 GetCode(int channelId)	100
3.108.2.2 TryGetChannelID(byte evCode, int maxChannels, out byte channelId)	101
3.108.3 Member Data Documentation	101
3.108.3.1 Code0	101
3.109 VoiceInfo Struct Reference	101
3.109.1 Detailed Description	102
3.109.2 Member Function Documentation	102
3.109.2.1 CreateAudioOpus(OPusCodec.Enums.SamplingRate samplingRate, int sourceSamplingRate, int channels, OpusCodec.FrameDuration frameDuration←Us, int bitrate, object userdata=null)	102
3.109.3 Property Documentation	102
3.109.3.1 Bitrate	102
3.109.3.2 Channels	102
3.109.3.3 FrameDurationSamples	103
3.109.3.4 FrameDurationUs	103
3.109.3.5 FrameSize	103
3.109.3.6 Height	103
3.109.3.7 SamplingRate	103
3.109.3.8 SourceSamplingRate	103
3.109.3.9 UserData	103
3.109.3.10 Width	103
3.110 AudioUtil.VoiceLevelDetectCalibrate< T > Class Template Reference	103
3.110.1 Detailed Description	104
3.110.2 Constructor & Destructor Documentation	104
3.110.2.1 VoiceLevelDetectCalibrate(int samplingRate, int channels)	104
3.110.3 Member Function Documentation	104
3.110.3.1 Calibrate(int durationMs)	104
3.110.3.2 Process(T[] buf)	104
3.110.4 Property Documentation	104
3.110.4.1 LevelMeter	104
3.110.4.2 VoiceDetector	105
3.111 VoiceLogger Class Reference	105
3.112 WebRtcAudioDsp Class Reference	105
3.113 WebRTCAudioLib Class Reference	105
3.114 WebRTCAudioProcessor Class Reference	106

Chapter 1

Photon Voice Doxygen Readme

Offline Docs

Manual Generation

To manually generate doxygen offline files:

```
"doxygen .\Docs\doxygen\voice-doxxygen-offline.config"
```

Automatic Generation

Simply run "Docs\generate_offline.bat". Open the file and edit DOXYGEN_PATH accordingly. Also you need a LaTeX distribution installed and some packages/dependencies.

This script will also copy the offline files to their respective locations and then clean up.

Files

HTML

It is not possible to disable HTML files generation. So those are just ignored or cleaned up after generation.

CHM

"PhotonVoice-Documentation.chm" should be copied

to "Assets\Photon\PhotonVoice-Documentation.chm"

from "Docs\TempOutputDocs\VOICE_OFFLINE_HTML\PhotonVoice-Documentation.chm".

PDF

"PhotonVoice-Documentation.pdf" should be copied

to "Assets\Photon\PhotonVoice-Documentation.pdf"

from "Docs\TempOutputDocs\latex\refman.pdf".

Online Docs

To manually generate doxygen online files:

```
"doxygen .\Docs\doxygen\voice-doxxygen-online.config"
```


Chapter 2

Namespace Documentation

2.1 Photon Namespace Reference

Namespaces

- namespace [Voice](#)

2.2 Photon.Voice Namespace Reference

Namespaces

- namespace [IOS](#)
- namespace [PUN](#)
- namespace [Unity](#)

Classes

- class [AudioDesc](#)
- class [AudioInEnumerator](#)
- class [AudioStreamPlayer](#)
- class [AudioUtil](#)

Collection of Audio Utility functions and classes.

- class [BufferReaderPushAdapter](#)

Simple [BufferReaderPushAdapterBase](#) implementation using a single buffer, using synchronous [LocalVoice.PushData](#).

- class [BufferReaderPushAdapterAsyncPool](#)

[BufferReaderPushAdapter](#) implementation using asynchronous [LocalVoice.PushDataAsync](#).

- class [BufferReaderPushAdapterAsyncPoolCopy](#)

[BufferReaderPushAdapter](#) implementation using asynchronous [LocalVoice.PushDataAsync](#) and data copy.

- class [BufferReaderPushAdapterAsyncPoolFloatToShort](#)

[BufferReaderPushAdapter](#) implementation using asynchronous [LocalVoice.PushDataAsync](#), converting float samples to short.

- class [BufferReaderPushAdapterBase](#)

Adapter base class to move data by reading from [IDataReader.Read](#) and pushing to [LocalVoice](#).

- class [FactoryPrimitiveArrayPool](#)

[PrimitiveArrayPool<T>](#) as wrapped in object factory interface.

- class [FactoryReusableArray](#)

Array factory returnig the same array instance as long as it requested with the same array length. If length changes, new array instance created.

- class [Framer](#)
Utility class to re-frame audio packets.
- interface [IAudioDesc](#)
Audio Source interface.
- interface [IAudioOut](#)
- interface [IAudioPusher](#)
Audio Pusher interface.
- interface [IAudioReader](#)
Audio Reader interface.
- interface [IDataReader](#)
Interface for pulling data, in case this is more appropriate than pushing it.
- interface [IDecoder](#)
Generic media decoder interface.
- interface [IDecoderDirect](#)
Interface for a media decoder that synchronously decodes data.
- interface [IDecoderQueued](#)
Interface for a media decoder that feeds its data output into a separate method or callback asynchronously, or does not produce output at all.
- interface [IDecoderQueuedOutputImageNative](#)
- interface [IEncoder](#)
Generic media encoder interface.
- interface [IEncoderDataFlow](#)
Interface for a generic media encoder data flow.
- interface [IEncoderDataFlowDirect](#)
Interface for an encoder data flow that synchronously encodes data.
- interface [IEncoderNativeImageDirect](#)
- interface [IEncoderQueued](#)
Interface for an encoder data flow that returns compressed data independently (produces output on its own) or asynchronously (usually from a queue).
- interface [ILocalVoiceAudio](#)
Interface for an outgoing audio stream.
- interface [ILogger](#)
- class [ImageBufferInfo](#)
- class [ImageBufferNative](#)
- class [ImageBufferNativeAlloc](#)
- class [ImageBufferNativeGCHandleSinglePlane](#)
- class [ImageBufferNativePool](#)
- interface [IProcessor](#)
Audio Processor interface.
- interface [IServiceable](#)
Interface for classes that want their [Service\(\)](#) function to be called regularly in the context of a [LocalVoice](#).
- interface [ISyncAudioOut](#)
- interface [IVoiceTransport](#)
- class [LoadBalancingFrontend](#)
- class [LoadBalancingTransport](#)
Extends [LoadBalancingClient](#) with audio streaming functionality.
- class [LocalVoice](#)
Represents outgoing data stream.
- class [LocalVoiceAudio](#)
Outgoing audio stream.

- class [LocalVoiceAudioDummy](#)
Dummy [LocalVoiceAudio](#)
- class [LocalVoiceAudioFloat](#)
Specialization of [LocalVoiceAudio](#) for float audio
- class [LocalVoiceAudioShort](#)
Specialization of [LocalVoiceAudio](#) for short audio
- class [LocalVoiceFramed](#)
Typed re-framing [LocalVoice](#)
- class [LocalVoiceFramedBase](#)
Typed re-framing [LocalVoice](#)
- interface [ObjectFactory](#)
Uniform interface to [ObjectPool](#)<TType, TInfo> and single reusable object.
- class [ObjectPool](#)
Generic Pool to re-use objects of a certain type (TType) that optionally match a certain property or set of properties (TInfo).
- class [OpusCodec](#)
- class [PrimitiveArrayPool](#)
Pool of Arrays with components of type T, with [ObjectPool](#) info being the array's size.
- class **RemoteVoice**
- class [RemoteVoiceInfo](#)
Information about a remote voice (incoming stream).
- struct [RemoteVoiceOptions](#)
Event Actions and other options for a remote voice (incoming stream).
- class [SpeexLib](#)
- class [SpeexProcessor](#)
- class [UnsupportedCodecException](#)
Exception thrown if an unsupported codec is encountered.
- class [UnsupportedSampleTypeException](#)
Exception thrown if an unsupported audio sample type is encountered.
- class [VoiceClient](#)
Base class for [Voice](#) clients implamantations
- class **VoiceCodec**
- class [VoiceEventCode](#)
PhotonVoice communication uses a single type of event, but differentiates transmission Channels by encoding a channelId into [VoiceEventCode](#).
- struct [VoiceInfo](#)
Describes stream properties.
- class [WebRTCAudioLib](#)
- class [WebRTCAudioProcessor](#)

Enumerations

- enum **EventSubcode** : byte
- enum **EventParam** : byte
- enum [Codec](#)
Enum for Media Codecs supported by PhotonVoice.
- enum **ImageFormat**
- enum **Rotation**
- enum **Flip**

Functions

- delegate void **OnImageOutputNative** (IntPtr buf, int width, int height, int stride)

2.2.1 Enumeration Type Documentation

2.2.1.1 enum Codec [strong]

Enum for Media Codecs supported by PhotonVoice.

Transmitted in [VoiceInfo](#). Do not change the values of this Enum!

Enumerator

AudioOpus OPUS audio

2.3 Photon.Voice.IOS Namespace Reference

Classes

- struct [AudioSessionParameters](#)
- class [AudioSessionParametersPresets](#)

Enumerations

- enum **AudioSessionCategory**
- enum **AudioSessionMode**
- enum **AudioSessionCategoryOption**

2.4 Photon.Voice.PUN Namespace Reference

Classes

- class [PhotonVoiceNetwork](#)

This class can be used to automatically sync client states between [PUN](#) and [Voice](#). It also sets a custom [PUN Speaker](#) factory to find the [Speaker](#) component for a character's voice. For this to work attach a [PhotonVoiceView](#) next to the [PhotonView](#) of your player's prefab.

- class [PhotonVoiceView](#)

Component that should be attached to a networked [PUN](#) prefab that has [PhotonView](#). It will bind remote [Recorder](#) with local [Speaker](#) of the same networked prefab. This component makes automatic voice stream routing easy for players' characters/avatars.

2.5 Photon.Voice.Unity Namespace Reference

Namespaces

- namespace [UtilityScripts](#)

Classes

- class [AudioClipWrapper](#)
- class [AudioOutCapture](#)
- interface [ILoggable](#)
- class [IOSAudioForceToSpeaker](#)
- class [Logger](#)
- class [MicWrapper](#)
- class [PhotonVoiceCreatedParams](#)
- class [Recorder](#)

Component representing outgoing audio stream in scene.

- class [RemoteVoiceLink](#)
- class [Speaker](#)

Component representing remote audio stream in local scene.

- class [UnityAndroidAudioInAEC](#)
- class [UnityAudioOut](#)
- class [VoiceComponent](#)
- class [VoiceConnection](#)

Component that represents a client voice connection to [Photon](#) Servers.

- class [VoiceLogger](#)
- class [WebRtcAudioDsp](#)

2.6 Photon.Voice.Unity.UtilityScripts Namespace Reference

Classes

- class [ConnectAndJoin](#)
- class [PhotonVoiceLagSimulationGui](#)
- class [PhotonVoiceStatsGui](#)

Basic GUI to show traffic and health statistics of the connection to [Photon](#), toggled by shift+tab.

- class [TestTone](#)
- class [ToneAudioReader](#)

2.7 POpusCodec Namespace Reference

Namespaces

- namespace [Enums](#)

Classes

- class [OpusDecoder](#)
- class [OpusEncoder](#)
- class [OpusException](#)
- class **Wrapper**

2.8 POpusCodec.Enums Namespace Reference

Enumerations

- enum [Bandwidth](#) : int
- enum [Channels](#) : int
- enum **Complexity** : int
- enum [Delay](#)

Using a duration of less than 10 ms will prevent the encoder from using the LPC or hybrid modes.

- enum **ForceChannels** : int
- enum [OpusApplicationType](#) : int
- enum **OpusStatusCode** : int
- enum **SamplingRate** : int
- enum [SignalHint](#) : int

2.8.1 Enumeration Type Documentation

2.8.1.1 enum **Bandwidth** : int `[strong]`

Enumerator

- Narrowband** Up to 4Khz
- Mediumband** Up to 6Khz
- Wideband** Up to 8Khz
- SuperWideband** Up to 12Khz
- Fullband** Up to 20Khz (High Definition)

2.8.1.2 enum **Channels** : int `[strong]`

Enumerator

- Mono** 1 Channel
- Stereo** 2 Channels

2.8.1.3 enum **Delay** `[strong]`

Using a duration of less than 10 ms will prevent the encoder from using the LPC or hybrid modes.

Enumerator

- Delay2dot5ms** 2.5ms
- Delay5ms** 5ms
- Delay10ms** 10ms
- Delay20ms** 20ms
- Delay40ms** 40ms
- Delay60ms** 60ms

2.8.1.4 enum OpusApplicationType : int [strong]

Enumerator

Voip Gives best quality at a given bitrate for voice signals. It enhances the input signal by high-pass filtering and emphasizing formants and harmonics. Optionally it includes in-band forward error correction to protect against packet loss. Use this mode for typical VoIP applications. Because of the enhancement, even at high bitrates the output may sound different from the input.

Audio Gives best quality at a given bitrate for most non-voice signals like music. Use this mode for music and mixed (music/voice) content, broadcast, and applications requiring less than 15 ms of coding delay.

RestrictedLowDelay Configures low-delay mode that disables the speech-optimized mode in exchange for slightly reduced delay.

2.8.1.5 enum SignalHint : int [strong]

Enumerator

Auto (default)

Voice Bias thresholds towards choosing LPC or Hybrid modes

Music Bias thresholds towards choosing MDCT modes.

Chapter 3

Class Documentation

3.1 SpeexProcessor.AECLatencyResultType Struct Reference

Public Attributes

- int **LatencyMs**
- int **LatencyDelayedMs**
- bool **PlayDetected**
- bool **PlayDelayedDetected**
- bool **RecDetected**

3.2 AudioClipWrapper Class Reference

Inherits [IAudioReader< T >](#).

Public Member Functions

- **AudioClipWrapper** (AudioClip audioClip)
- bool **Read** (float[] buffer)
- void **Dispose** ()

Properties

- bool **Loop** [get, set]
- int **SamplingRate** [get]
- int **Channels** [get]
- string **Error** [get]

3.3 AudioDesc Class Reference

Inherits [IAudioDesc](#).

Public Member Functions

- **AudioDesc** (int samplingRate, int channels, string error)
- void **Dispose** ()

Properties

- int **SamplingRate** [get]
- int **Channels** [get]
- string **Error** [get]

3.4 AudioInEnumerator Class Reference

Inherits IDisposable.

Public Member Functions

- **AudioInEnumerator** (Voice.ILogger logger)
- void **Refresh** ()
- string **NameAtIndex** (int i)
- int **IDAtIndex** (int i)
- bool **IDIsValid** (int id)
- void **Dispose** ()

Public Attributes

- readonly bool **IsSupported** = false

Properties

- string **Error** [get]
- int **Count** [get]

3.5 AudioOutCapture Class Reference

Inherits MonoBehaviour.

Events

- Action< float[], int > **OnAudioFrame**

3.6 AudioSessionParameters Struct Reference

Public Member Functions

- int **CategoryOptionsToInt** ()
- override string **ToString** ()

Public Attributes

- AudioSessionCategory **Category**
- AudioSessionMode **Mode**
- AudioSessionCategoryOption[] **CategoryOptions**

3.7 AudioSessionParametersPresets Class Reference

Static Public Attributes

- static [AudioSessionParameters](#) **Game**
- static [AudioSessionParameters](#) **VoIP**

3.7.1 Member Data Documentation

3.7.1.1 AudioSessionParameters Game [static]

Initial value:

```
= new AudioSessionParameters()
{
    Category = AudioSessionCategory.PlayAndRecord,
    Mode = AudioSessionMode.Default,
    CategoryOptions = new AudioSessionCategoryOption[] { AudioSessionCategoryOption.
DefaultToSpeaker, AudioSessionCategoryOption.AllowBluetooth }
}
```

3.7.1.2 AudioSessionParameters VoIP [static]

Initial value:

```
= new AudioSessionParameters()
{
    Category = AudioSessionCategory.PlayAndRecord,
    Mode = AudioSessionMode.VoiceChat,

    CategoryOptions = new AudioSessionCategoryOption[] { AudioSessionCategoryOption.AllowBluetooth
}
}
```

3.8 AudioStreamPlayer Class Reference

Inherits [IAudioOut](#).

Public Member Functions

- **AudioStreamPlayer** ([Photon.Voice.ILogger](#) logger, [Photon.Voice.ISyncAudioOut](#) audioOut, string logPrefix, bool debugInfo)
- void **Start** (int frequency, int channels, int frameSamples, int playDelayMs)
- void **Service** ()
- void **Push** (float[] frame)
- void **Stop** ()

Properties

- int **Lag** [get]
- bool **IsPlaying** [get]

3.9 AudioUtil Class Reference

Collection of Audio Utility functions and classes.

Classes

- interface [ILevelMeter](#)
Audio Level Metering interface.
- interface [IVoiceDetector](#)
Voice Activity Detector interface.
- class [LevelMeter](#)
Audio Level Meter.
- class [LevelMeterDummy](#)
Dummy Audio Level Meter that doesn't actually do anything.
- class [LevelMeterFloat](#)
LevelMeter specialization for float audio.
- class [LevelMeterShort](#)
LevelMeter specialization for short audio.
- class [Resampler](#)
Sample-rate conversion Audio Processor.
- class [ToneAudioPusher](#)
IAudioPusher that provides a constant tone signal.
- class [ToneAudioReader](#)
IAudioReader that provides a constant tone signal.
- class [VoiceDetector](#)
Simple voice activity detector triggered by signal level.
- class [VoiceDetectorCalibration](#)
Calibration Utility for Voice Detector
- class [VoiceDetectorDummy](#)
Dummy VoiceDetector that doesn't actually do anything.
- class [VoiceDetectorFloat](#)
VoiceDetector specialization for float audio.
- class [VoiceDetectorShort](#)
VoiceDetector specialization for float audio.
- class [VoiceLevelDetectCalibrate](#)
Utility Audio Processor Voice Detection Calibration.

Static Public Member Functions

- static void [Resample< T >](#) (T[] src, T[] dst, int dstCount, int channels)
Resample audio data so that the complete src buffer fits into dstCount samples in the dst buffer.
- static void [ResampleAndConvert](#) (short[] src, float[] dst, int dstCount, int channels)
Resample audio data so that the complete src buffer fits into dstCount samples in the dst buffer, and convert short to float samples along the way.
- static void [ResampleAndConvert](#) (float[] src, short[] dst, int dstCount, int channels)
Resample audio data so that the complete src buffer fits into dstCount samples in the dst buffer, and convert float to short samples along the way.
- static void [Convert](#) (float[] src, short[] dst, int dstCount)
Convert audio buffer from float to short samples.
- static void [Convert](#) (short[] src, float[] dst, int dstCount)
Convert audio buffer from short to float samples.
- static void [ForceToStereo< T >](#) (T[] src, T[] dst, int srcChannels)
Convert audio buffer with arbitrary number of channels to stereo.

3.9.1 Detailed Description

Collection of Audio Utility functions and classes.

3.9.2 Member Function Documentation

3.9.2.1 static void Convert (float[] *src*, short[] *dst*, int *dstCount*) [static]

Convert audio buffer from float to short samples.

Parameters

<i>src</i>	Source buffer.
<i>dst</i>	Destination buffer.
<i>dstCount</i>	Size of destination buffer (in total samples), source buffer must be of same length or longer.

3.9.2.2 static void Convert (short[] *src*, float[] *dst*, int *dstCount*) [static]

Convert audio buffer from short to float samples.

Parameters

<i>src</i>	Source buffer.
<i>dst</i>	Destination buffer.
<i>dstCount</i>	Size of destination buffer (in total samples), source buffer must be of same length or longer.

3.9.2.3 static void ForceToStereo< T > (T[] *src*, T[] *dst*, int *srcChannels*) [static]

Convert audio buffer with arbitrary number of channels to stereo.

For mono sources (*srcChannels*==1), the signal will be copied to both Left and Right stereo channels. For all others, the first two available channels will be used, any other channels will be discarded.

Parameters

<i>src</i>	Source buffer.
<i>dst</i>	Destination buffer.
<i>srcChannels</i>	Number of (interleaved) channels in <i>src</i> .

3.9.2.4 static void Resample< T > (T[] *src*, T[] *dst*, int *dstCount*, int *channels*) [static]

Resample audio data so that the complete *src* buffer fits into *dstCount* samples in the *dst* buffer.

This implements a primitive nearest-neighbor resampling algorithm for an arbitrary number of channels.

Parameters

<i>src</i>	Source buffer.
<i>dst</i>	Destination buffer.
<i>dstCount</i>	Target size of destination buffer (in samples per channel).
<i>channels</i>	Number of channels in the signal (1=mono, 2=stereo). Must be > 0.

3.9.2.5 static void ResampleAndConvert (short[] *src*, float[] *dst*, int *dstCount*, int *channels*) [static]

Resample audio data so that the complete *src* buffer fits into *dstCount* samples in the *dst* buffer, and convert short to float samples along the way.

This implements a primitive nearest-neighbor resampling algorithm for an arbitrary number of channels.

Parameters

<i>src</i>	Source buffer.
<i>dst</i>	Destination buffer.
<i>dstCount</i>	Target size of destination buffer (in samples per channel).
<i>channels</i>	Number of channels in the signal (1=mono, 2=stereo). Must be > 0.

3.9.2.6 static void ResampleAndConvert (float[] *src*, short[] *dst*, int *dstCount*, int *channels*) [static]

Resample audio data so that the complete *src* buffer fits into *dstCount* samples in the *dst* buffer, and convert float to short samples along the way.

This implements a primitive nearest-neighbor resampling algorithm for an arbitrary number of channels.

Parameters

<i>src</i>	Source buffer.
<i>dst</i>	Destination buffer.
<i>dstCount</i>	Target size of destination buffer (in samples per channel).
<i>channels</i>	Number of channels in the signal (1=mono, 2=stereo). Must be > 0.

3.10 BufferReaderPushAdapter< T > Class Template Reference

Simple [BufferReaderPushAdapterBase](#) implementation using a single buffer, using synchronous LocalVoice.Push↔Data

Inherits [BufferReaderPushAdapterBase< T >](#).

Public Member Functions

- [BufferReaderPushAdapter](#) (LocalVoice localVoice, IDataReader< T > reader)
Create a new BufferReaderPushAdapter instance
- override void [Service](#) (LocalVoice localVoice)
Do the actual data read/push.

Protected Attributes

- T[] **buffer**

3.10.1 Detailed Description

Simple [BufferReaderPushAdapterBase](#) implementation using a single buffer, using synchronous LocalVoice.Push↔Data

3.10.2 Constructor & Destructor Documentation

3.10.2.1 [BufferReaderPushAdapter](#) (LocalVoice localVoice, IDataReader< T > reader)

Create a new [BufferReaderPushAdapter](#) instance

Parameters

<i>localVoice</i>	LocalVoice instance to push data to.
<i>reader</i>	DataReader to read from.

3.10.3 Member Function Documentation

3.10.3.1 override void Service ([LocalVoice](#) *localVoice*) [virtual]

Do the actual data read/push.

Parameters

<i>localVoice</i>	LocalVoice instance to push data to.
-------------------	--

Implements [BufferedReaderPushAdapterBase< T >](#).

3.11 [BufferedReaderPushAdapterAsyncPool< T >](#) Class Template Reference

[BufferedReaderPushAdapter](#) implementation using asynchronous [LocalVoice.PushDataAsync](#).

Inherits [BufferedReaderPushAdapterBase< T >](#).

Public Member Functions

- [BufferedReaderPushAdapterAsyncPool](#) ([LocalVoice](#) *localVoice*, [IDataReader](#)< T > *reader*)
Create a new [BufferedReaderPushAdapter](#) instance
- override void [Service](#) ([LocalVoice](#) *localVoice*)
Do the actual data read/push.

Additional Inherited Members

3.11.1 Detailed Description

[BufferedReaderPushAdapter](#) implementation using asynchronous [LocalVoice.PushDataAsync](#).

Acquires a buffer from pool before each Read, releases buffer after last Read (brings Acquire/Release overhead).

Expects *localVoice* to be a [LocalVoiceFramed<T>](#) of same T.

3.11.2 Constructor & Destructor Documentation

3.11.2.1 [BufferedReaderPushAdapterAsyncPool](#) ([LocalVoice](#) *localVoice*, [IDataReader](#)< T > *reader*)

Create a new [BufferedReaderPushAdapter](#) instance

Parameters

<i>localVoice</i>	LocalVoice instance to push data to.
<i>reader</i>	DataReader to read from.

3.11.3 Member Function Documentation

3.11.3.1 override void Service (LocalVoice *localVoice*) [virtual]

Do the actual data read/push.

Parameters

<i>localVoice</i>	LocalVoice instance to push data to. Must be a LocalVoiceFramed<T> of same T.
-------------------	---

Implements [BufferReaderPushAdapterBase< T >](#).

3.12 BufferReaderPushAdapterAsyncPoolCopy< T > Class Template Reference

[BufferReaderPushAdapter](#) implementation using asynchronous [LocalVoice.PushDataAsync](#) and data copy.

Inherits [BufferReaderPushAdapterBase< T >](#).

Public Member Functions

- [BufferReaderPushAdapterAsyncPoolCopy](#) ([LocalVoice](#) localVoice, [IDataReader< T >](#) reader)
Create a new [BufferReaderPushAdapter](#) instance
- override void [Service](#) ([LocalVoice](#) localVoice)
Do the actual data read/push.

Protected Attributes

- **T[] buffer**

3.12.1 Detailed Description

[BufferReaderPushAdapter](#) implementation using asynchronous [LocalVoice.PushDataAsync](#) and data copy.

Reads data to preallocated buffer, copies it to buffer from pool before pushing. Compared with , this avoids one pool Acquire/Release cycle at the cost of a buffer copy. Expects localVoice to be a [LocalVoiceFramed<T>](#) of same T.

3.12.2 Constructor & Destructor Documentation

3.12.2.1 BufferReaderPushAdapterAsyncPoolCopy (LocalVoice localVoice, IDataReader< T > reader)

Create a new [BufferReaderPushAdapter](#) instance

Parameters

<i>localVoice</i>	LocalVoice instance to push data to.
<i>reader</i>	IDataReader to read from.

3.12.3 Member Function Documentation

3.12.3.1 override void Service (LocalVoice localVoice) [virtual]

Do the actual data read/push.

Parameters

<i>localVoice</i>	LocalVoice instance to push data to. Must be a LocalVoiceFramed<T> of same T.
-------------------	---

Implements [BufferReaderPushAdapterBase< T >](#).

3.13 [BufferReaderPushAdapterAsyncPoolFloatToShort](#) Class Reference

[BufferReaderPushAdapter](#) implementation using asynchronous [LocalVoice.PushDataAsync](#), converting float samples to short.

Inherits [BufferReaderPushAdapterBase< T >](#).

Public Member Functions

- [BufferReaderPushAdapterAsyncPoolFloatToShort](#) ([Voice.LocalVoice](#) localVoice, [Voice.IDataReader< float >](#) reader)
Create a new [BufferReaderPushAdapter](#) instance
- override void [Service](#) ([Voice.LocalVoice](#) localVoice)
Do the actual data read/push.

Additional Inherited Members

3.13.1 Detailed Description

[BufferReaderPushAdapter](#) implementation using asynchronous [LocalVoice.PushDataAsync](#), converting float samples to short.

This adapter works exactly like [BufferReaderPushAdapterAsyncPool](#), but it converts float samples to short. Acquires a buffer from pool before each Read, releases buffer after last Read.

Expects localVoice to be a [LocalVoiceFramed<T>](#) of same T.

3.13.2 Constructor & Destructor Documentation

3.13.2.1 [BufferReaderPushAdapterAsyncPoolFloatToShort](#) ([Voice.LocalVoice](#) localVoice, [Voice.IDataReader< float >](#) reader)

Create a new [BufferReaderPushAdapter](#) instance

Parameters

<i>localVoice</i>	LocalVoice instance to push data to.
<i>reader</i>	IDataReader to read from.

3.13.3 Member Function Documentation

3.13.3.1 override void [Service](#) ([Voice.LocalVoice](#) localVoice)

Do the actual data read/push.

Parameters

<i>localVoice</i>	LocalVoice instance to push data to. Must be a LocalVoiceFramed<T> of same T.
-------------------	---

3.14 [BufferReaderPushAdapterBase< T >](#) Class Template Reference

Adapter base class to move data by reading from [IDataReader.Read](#) and pushing to [LocalVoice](#).

Inherits [IServiceable](#).

Inherited by [BufferReaderPushAdapter< T >](#), [BufferReaderPushAdapterAsyncPool< T >](#), [BufferReaderPushAdapterAsyncPoolCopy< T >](#), and [BufferReaderPushAdapterAsyncPoolFloatToShort](#).

Public Member Functions

- abstract void [Service](#) ([LocalVoice](#) localVoice)
Do the actual data read/push.
- [BufferReaderPushAdapterBase](#) ([IDataReader](#)< T > reader)
Create a new [BufferReaderPushAdapterBase](#) instance
- void [Dispose](#) ()
Release resources associated with this instance.

Protected Attributes

- [IDataReader](#)< T > **reader**

3.14.1 Detailed Description

Adapter base class to move data by reading from [IDataReader.Read](#) and pushing to [LocalVoice](#).
Use this with a [LocalVoice](#) of same T type.

3.14.2 Constructor & Destructor Documentation

3.14.2.1 [BufferReaderPushAdapterBase](#) ([IDataReader](#)< T > *reader*)

Create a new [BufferReaderPushAdapterBase](#) instance

Parameters

<i>reader</i>	IDataReader to read from.
---------------	---

3.14.3 Member Function Documentation

3.14.3.1 void [Dispose](#) ()

Release resources associated with this instance.

3.14.3.2 abstract void [Service](#) ([LocalVoice](#) *localVoice*) [pure virtual]

Do the actual data read/push.

Parameters

<i>localVoice</i>	LocalVoice instance to push data to.
-------------------	--

Implements [IServiceable](#).

Implemented in [BufferReaderPushAdapterAsyncPoolCopy< T >](#), [BufferReaderPushAdapterAsyncPool< T >](#), and [BufferReaderPushAdapter< T >](#).

3.15 WebRTCAudioLib.ConfigParam Struct Reference

Public Attributes

- const int **AEC_DELAY_AGNOSTIC** = 12
- const int **AEC_EXTENDED_FILTER** = 13
- const int **AGC_EXPERIMENTAL** = 53
- const int **AGC_EXPERIMENTAL_STARTUP_MIN_VOLUME** = 54
- const int **AGC_EXPERIMENTAL_CLIP_LEVEL_MIN** = 55

3.16 ConnectAndJoin Class Reference

Inherits MonoBehaviour, IConnectionCallbacks, and IMatchmakingCallbacks.

Public Member Functions

- void **ConnectNow** ()
- void **OnCreatedRoom** ()
- void **OnCreateRoomFailed** (short returnCode, string message)
- void **OnFriendListUpdate** (List< FriendInfo > friendList)
- void **OnJoinedRoom** ()
- void **OnJoinRandomFailed** (short returnCode, string message)
- void **OnJoinRoomFailed** (short returnCode, string message)
- void **OnLeftRoom** ()
- void **OnConnected** ()
- void **OnConnectedToMaster** ()
- void **OnDisconnected** (DisconnectCause cause)
- void **OnRegionListReceived** (RegionHandler regionHandler)
- void **OnCustomAuthenticationResponse** (Dictionary< string, object > data)
- void **OnCustomAuthenticationFailed** (string debugMessage)

Public Attributes

- bool **RandomRoom** = true
- string **RoomName**

Properties

- bool **IsConnected** [get]

3.17 OpusCodec.Decoder Class Reference

Inherits [IDecoderDirect](#).

Public Member Functions

- **Decoder** ([ILogger](#) logger)
- void **Open** ([VoiceInfo](#) i)
Open (initialize) the decoder.
- byte[] **DecodeToByte** (byte[] buf)
Decode the given raw data buffer.
- float[] **DecodeToFloat** (byte[] buf)
Decode the given raw data buffer to floating point audio.
- short[] **DecodeToShort** (byte[] buf)
Decode the given raw data buffer to 'short' (16-bit) audio.
- void **Dispose** ()

Properties

- string **Error** [[get](#)]

3.17.1 Member Function Documentation

3.17.1.1 byte[] DecodeToByte (byte[] buf)

Decode the given raw data buffer.

Parameters

<i>buf</i>	Buffer of encoded (compressed) data.
------------	--------------------------------------

Returns

Buffer of decoded (uncompressed) data.

Implements [IDecoderDirect](#).

3.17.1.2 float[] DecodeToFloat (byte[] buf)

Decode the given raw data buffer to floating point audio.

Only sensible for audio data.

Parameters

<i>buf</i>	Buffer of encoded (compressed) data.
------------	--------------------------------------

Returns

Buffer of decoded (uncompressed) data.

Implements [IDecoderDirect](#).

3.17.1.3 short[] DecodeToShort (byte[] buf)

Decode the given raw data buffer to 'short' (16-bit) audio.

Only sensible for audio data.

Parameters

<i>buf</i>	Buffer of encoded (compressed) data.
------------	--------------------------------------

Returns

Buffer of decoded (uncompressed) data.

Implements [IDecoderDirect](#).

3.17.1.4 void Open (VoicelInfo info)

Open (initialize) the decoder.

Parameters

<i>info</i>	Properties of the data stream to decode.
-------------	--

Implements [IDecoder](#).

3.18 OpusCodec.Encoder< T > Class Template Reference

Inherits [IEncoderDataFlowDirect< T >](#).

Inherited by [OpusCodec.EncoderFloat](#), and [OpusCodec.EncoderShort](#).

Public Member Functions

- void **Dispose** ()
- abstract ArraySegment< byte > [EncodeAndGetOutput](#) (T[] buf)
Encode the given uncompressed media data.

Protected Member Functions

- **Encoder** (VoicelInfo i, [ILogger](#) logger)

Protected Attributes

- [OpusEncoder](#) **encoder**
- bool **disposed**

Properties

- string **Error** [get]

3.18.1 Member Function Documentation

3.18.1.1 abstract ArraySegment<byte> EncodeAndGetOutput (T[] buf) [pure virtual]

Encode the given uncompressed media data.

Parameters

<i>buf</i>	Array containing raw (uncompressed) data (e.g. audio samples).
------------	--

Returns

Encoded (compressed) data.

Implements [IEncoderDataFlowDirect< T >](#).

3.19 OpusCodec.EncoderFactory Class Reference

Static Public Member Functions

- static [IEncoder](#) **Create**< T > ([VoiceInfo](#) i, [ILogger](#) logger)

3.20 OpusCodec.EncoderFloat Class Reference

Inherits [OpusCodec.Encoder< T >](#).

Public Member Functions

- override [ArraySegment< byte >](#) **EncodeAndGetOutput** ([float\[\]](#) buf)

Additional Inherited Members

3.21 OpusCodec.EncoderShort Class Reference

Inherits [OpusCodec.Encoder< T >](#).

Public Member Functions

- override [ArraySegment< byte >](#) **EncodeAndGetOutput** ([short\[\]](#) buf)

Additional Inherited Members

3.22 FactoryPrimitiveArrayPool< T > Class Template Reference

[PrimitiveArrayPool<T>](#) as wrapped in object factory interface.

Inherits [ObjectFactory< TType, TInfo >](#).

Public Member Functions

- **FactoryPrimitiveArrayPool** (int capacity, string name)
- **FactoryPrimitiveArrayPool** (int capacity, string name, int info)
- [T\[\]](#) **New** ()
- [T\[\]](#) **New** (int size)
- void **Free** ([T\[\]](#) obj)
- void **Free** ([T\[\]](#) obj, int info)
- void **Dispose** ()

Properties

- int **Info** [get]

3.22.1 Detailed Description

PrimitiveArrayPool<T> as wrapped in object factory interface.

Template Parameters

<i>T</i>	Array element type.
----------	---------------------

3.23 FactoryReusableArray< T > Class Template Reference

Array factory returnig the same array instance as long as it requested with the same array length. If length changes, new array instance created.

Inherits [ObjectFactory< TType, TInfo >](#).

Public Member Functions

- **FactoryReusableArray** (int size)
- **T[] New** ()
- **T[] New** (int size)
- void **Free** (T[] obj)
- void **Free** (T[] obj, int info)
- void **Dispose** ()

Properties

- int **Info** [get]

3.23.1 Detailed Description

Array factory returnig the same array instance as long as it requested with the same array length. If length changes, new array instance created.

Template Parameters

<i>T</i>	Array element type.
----------	---------------------

3.24 Framer< T > Class Template Reference

Utility class to re-frame audio packets.

Public Member Functions

- [Framer](#) (int frameSize)
Create new [Framer](#) instance.
- int [Count](#) (int bufLen)
Get the number of frames available after adding bufLen samples.

- `IEnumerable< T[] > Frame (T[] buf)`
Append arbitrary-sized buffer and return available full frames.

3.24.1 Detailed Description

Utility class to re-frame audio packets.

3.24.2 Constructor & Destructor Documentation

3.24.2.1 `Framer (int frameSize)`

Create new `Framer` instance.

3.24.3 Member Function Documentation

3.24.3.1 `int Count (int bufLen)`

Get the number of frames available after adding `bufLen` samples.

Parameters

<code>bufLen</code>	Number of samples that would be added.
---------------------	--

Returns

Number of full frames available when adding `bufLen` samples.

3.24.3.2 `IEnumerable<T[] > Frame (T[] buf)`

Append arbitrary-sized buffer and return available full frames.

Parameters

<code>buf</code>	Array of samples to add.
------------------	--------------------------

Returns

Enumerator of full frames (might be none).

3.25 IAudioDesc Interface Reference

Audio Source interface.

Inherits `IDisposable`.

Inherited by `AudioDesc`, `IAudioPusher< T >`, and `IAudioReader< T >`.

Properties

- `int SamplingRate [get]`
Sampling rate of the audio signal (in Hz).
- `int Channels [get]`
Number of channels in the audio signal.
- `string Error [get]`
If not null, audio object is in invalid state.

3.25.1 Detailed Description

Audio Source interface.

3.25.2 Property Documentation

3.25.2.1 `int Channels` `[get]`

Number of channels in the audio signal.

3.25.2.2 `string Error` `[get]`

If not null, audio object is in invalid state.

3.25.2.3 `int SamplingRate` `[get]`

Sampling rate of the audio signal (in Hz).

3.26 IAudioOut Interface Reference

Inherited by [AudioStreamPlayer](#), and [ISyncAudioOut](#).

Public Member Functions

- void **Start** (int frequency, int channels, int frameSamplesPerChannel, int playDelayMs)
- void **Stop** ()
- void **Push** (float[] frame)
- void **Service** ()

Properties

- bool **IsPlaying** `[get]`
- int **Lag** `[get]`

3.27 IAudioPusher< T > Interface Template Reference

Audio Pusher interface.

Inherits [IAudioDesc](#).

Inherited by [AudioUtil.ToneAudioPusher< T >](#), and [UnityAndroidAudioInAEC](#).

Public Member Functions

- void [SetCallback](#) (Action< T[]> callback, [ObjectFactory](#)< T[], int > bufferFactory)
Set the callback function used for pushing data.

Additional Inherited Members

3.27.1 Detailed Description

Audio Pusher interface.

Opposed to an [IAudioReader](#) (which will deliver audio data when it is "pulled"), an [IAudioPusher](#) will push its audio data whenever it is ready,

3.27.2 Member Function Documentation

3.27.2.1 void SetCallback (Action< T[] > *callback*, ObjectFactory< T[], int > *bufferFactory*)

Set the callback function used for pushing data.

Parameters

<i>callback</i>	Callback function to use.
<i>localVoice</i>	Outgoing audio stream, for context.

Implemented in [AudioUtil.ToneAudioPusher< T >](#).

3.28 IAudioReader< T > Interface Template Reference

Audio Reader interface.

Inherits [IDataReader< T >](#), and [IAudioDesc](#).

Inherited by [AudioUtil.ToneAudioReader< T >](#), [AudioClipWrapper](#), [MicWrapper](#), and [ToneAudioReader](#).

Additional Inherited Members

3.28.1 Detailed Description

Audio Reader interface.

Opposed to an [IAudioPusher](#) (which will push its audio data whenever it is ready), an [IAudioReader](#) will deliver audio data when it is "pulled" (it's Read function is called).

3.29 IDataReader< T > Interface Template Reference

Interface for pulling data, in case this is more appropriate than pushing it.

Inherits IDisposable.

Inherited by [IAudioReader< T >](#).

Public Member Functions

- bool [Read](#) (T[] buffer)

Fill full given frame buffer with source uncompressed data or return false if not enough such data.

3.29.1 Detailed Description

Interface for pulling data, in case this is more appropriate than pushing it.

3.29.2 Member Function Documentation

3.29.2.1 bool Read (T[] *buffer*)

Fill full given frame buffer with source uncompressed data or return false if not enough such data.

Parameters

<i>buffer</i>	Buffer to fill.
---------------	-----------------

Returns

True if buffer was filled successfully, false otherwise.

Implemented in [AudioUtil.ToneAudioReader< T >](#).

3.30 IDecoder Interface Reference

Generic media decoder interface.

Inherits IDisposable.

Inherited by [IDecoderDirect](#), and [IDecoderQueued](#).

Public Member Functions

- void [Open](#) ([VoiceInfo](#) info)
Open (initialize) the decoder.

Properties

- string [Error](#) [get]
If not null, the object is in invalid state.

3.30.1 Detailed Description

Generic media decoder interface.

3.30.2 Member Function Documentation

3.30.2.1 void Open ([VoiceInfo](#) info)

Open (initialize) the decoder.

Parameters

<i>info</i>	Properties of the data stream to decode.
-------------	--

Implemented in [OpusCodec.Decoder](#).

3.30.3 Property Documentation

3.30.3.1 string Error [get]

If not null, the object is in invalid state.

3.31 IDecoderDirect Interface Reference

Interface for a media decoder that synchronously decodes data.

Inherits [IDecoder](#).

Inherited by [OpusCodec.Decoder](#).

Public Member Functions

- `byte[] DecodeToByte (byte[] buf)`
Decode the given raw data buffer.
- `float[] DecodeToFloat (byte[] buf)`
Decode the given raw data buffer to floating point audio.
- `short[] DecodeToShort (byte[] buf)`
Decode the given raw data buffer to 'short' (16-bit) audio.

Additional Inherited Members

3.31.1 Detailed Description

Interface for a media decoder that synchronously decodes data.

3.31.2 Member Function Documentation

3.31.2.1 `byte[] DecodeToByte (byte[] buf)`

Decode the given raw data buffer.

Parameters

<i>buf</i>	Buffer of encoded (compressed) data.
------------	--------------------------------------

Returns

Buffer of decoded (uncompressed) data.

Implemented in [OpusCodec.Decoder](#).

3.31.2.2 `float[] DecodeToFloat (byte[] buf)`

Decode the given raw data buffer to floating point audio.

Only sensible for audio data.

Parameters

<i>buf</i>	Buffer of encoded (compressed) data.
------------	--------------------------------------

Returns

Buffer of decoded (uncompressed) data.

Implemented in [OpusCodec.Decoder](#).

3.31.2.3 short [] DecodeToShort (byte[] buf)

Decode the given raw data buffer to 'short' (16-bit) audio.

Only sensible for audio data.

Parameters

<i>buf</i>	Buffer of encoded (compressed) data.
------------	--------------------------------------

Returns

Buffer of decoded (uncompressed) data.

Implemented in [OpusCodec.Decoder](#).

3.32 IDecoderQueued Interface Reference

Interface for a media decoder that feeds its data output into a separate method or callback asynchronously, or does not produce output at all.

Inherits [IDecoder](#).

Inherited by [IDecoderQueuedOutputImageNative](#).

Public Member Functions

- void [Decode](#) (byte[] buf)
Decode the given raw data buffer.

Additional Inherited Members

3.32.1 Detailed Description

Interface for a media decoder that feeds its data output into a separate method or callback asynchronously, or does not produce output at all.

3.32.2 Member Function Documentation

3.32.2.1 void Decode (byte[] buf)

Decode the given raw data buffer.

This function will be called also for every missing frame, with buf = null.

Parameters

<i>buf</i>	Buffer of encoded (compressed) data.
------------	--------------------------------------

3.33 IDecoderQueuedOutputImageNative Interface Reference

Inherits [IDecoderQueued](#).

Properties

- ImageFormat **OutputImageFormat** [get, set]
- Flip **OutputImageFlip** [get, set]
- Func< int, int, IntPtr > **OutputImageBufferGetter** [get, set]
- OnImageOutputNative **OnOutputImage** [get, set]

Additional Inherited Members

3.34 IEncoder Interface Reference

Generic media encoder interface.

Inherits IDisposable.

Inherited by [IEncoderDataFlow< T >](#), [IEncoderNativeImageDirect](#), and [IEncoderQueued](#).

Properties

- string [Error](#) [get]
If not null, the object is in invalid state.

3.34.1 Detailed Description

Generic media encoder interface.

3.34.2 Property Documentation

3.34.2.1 string Error [get]

If not null, the object is in invalid state.

3.35 IEncoderDataFlow< T > Interface Template Reference

Interface for a generic media encoder data flow.

Inherits [IEncoder](#).

Inherited by [IEncoderDataFlowDirect< T >](#).

Additional Inherited Members

3.35.1 Detailed Description

Interface for a generic media encoder data flow.

3.36 IEncoderDataFlowDirect< T > Interface Template Reference

Interface for an encoder data flow that synchronously encodes data.

Inherits [IEncoderDataFlow< T >](#).

Inherited by [OpusCodec.Encoder< T >](#).

Public Member Functions

- `ArraySegment< byte > EncodeAndGetOutput (T[] buf)`
Encode the given uncompressed media data.

Additional Inherited Members

3.36.1 Detailed Description

Interface for an encoder data flow that synchronously encodes data.

3.36.2 Member Function Documentation

3.36.2.1 `ArraySegment<byte> EncodeAndGetOutput (T[] buf)`

Encode the given uncompressed media data.

Parameters

<i>buf</i>	Array containing raw (uncompressed) data (e.g. audio samples).
------------	--

Returns

Encoded (compressed) data.

Implemented in [OpusCodec.Encoder< T >](#).

3.37 IEncoderNativeImageDirect Interface Reference

Inherits [IEncoder](#).

Public Member Functions

- `IEnumerable< ArraySegment< byte > > EncodeAndGetOutput (IntPtr[] buf, int width, int height, int[] stride, ImageFormat imageFormat, Rotation rotation, Flip flip)`

Additional Inherited Members

3.38 IEncoderQueued Interface Reference

Interface for an encoder data flow that returns compressed data independently (produces output on its own) or asynchronously (usually from a queue).

Inherits [IEncoder](#).

Public Member Functions

- `IEnumerable< ArraySegment< byte > > GetOutput ()`
Get an Enumerable of buffers containing encoded (compressed) data.

Additional Inherited Members

3.38.1 Detailed Description

Interface for an encoder data flow that returns compressed data independently (produces output on its own) or asynchronously (usually from a queue).

3.38.2 Member Function Documentation

3.38.2.1 `IEnumerable<ArraySegment<byte>> GetOutput ()`

Get an Enumerable of buffers containing encoded (compressed) data.

Returns

Encoded (compressed) data.

3.39 AudioUtil.ILevelMeter Interface Reference

Audio Level Metering interface.

Inherited by [AudioUtil.LevelMeter< T >](#), and [AudioUtil.LevelMeterDummy](#).

Public Member Functions

- void [ResetAccumAvgPeakAmp](#) ()
Reset [AccumAvgPeakAmp](#).

Properties

- float [CurrentAvgAmp](#) [get]
Average amplitude value over last half second.
- float [CurrentPeakAmp](#) [get]
Maximum amplitude value over last half second sec.
- float [AccumAvgPeakAmp](#) [get]
Average of CurrentPeakAmps since last reset.

3.39.1 Detailed Description

Audio Level Metering interface.

3.39.2 Member Function Documentation

3.39.2.1 `void ResetAccumAvgPeakAmp ()`

Reset [AccumAvgPeakAmp](#).

Implemented in [AudioUtil.LevelMeter< T >](#), and [AudioUtil.LevelMeterDummy](#).

3.39.3 Property Documentation

3.39.3.1 float AccumAvgPeakAmp [get]

Average of CurrentPeakAmps since last reset.

3.39.3.2 float CurrentAvgAmp [get]

Average amplitude value over last half second.

3.39.3.3 float CurrentPeakAmp [get]

Maximum amplitude value over last half second sec.

3.40 ILocalVoiceAudio Interface Reference

Interface for an outgoing audio stream.

Inherited by [LocalVoiceAudio< T >](#), and [LocalVoiceAudioDummy](#).

Public Member Functions

- void [VoiceDetectorCalibrate](#) (int durationMs)
Trigger voice detector calibration process.

Properties

- [AudioUtil.IVoiceDetector VoiceDetector](#) [get]
The VoiceDetector in use.
- [AudioUtil.ILevelMeter LevelMeter](#) [get]
The LevelMeter utility in use.
- bool [VoiceDetectorCalibrating](#) [get]
If true, voice detector calibration is in progress.

3.40.1 Detailed Description

Interface for an outgoing audio stream.

A [LocalVoice](#) always brings a LevelMeter and a VoiceDetector, which you can access using this interface.

3.40.2 Member Function Documentation

3.40.2.1 void VoiceDetectorCalibrate (int durationMs)

Trigger voice detector calibration process.

While calibrating, keep silence. [Voice](#) detector sets threshold based on measured background noise level.

Parameters

<i>durationMs</i>	Duration of calibration (in milliseconds).
-------------------	--

Implemented in [LocalVoiceAudioDummy](#), and [LocalVoiceAudio< T >](#).

3.40.3 Property Documentation

3.40.3.1 [AudioUtil.ILevelMeter](#) **LevelMeter** [get]

The LevelMeter utility in use.

3.40.3.2 [AudioUtil.IVoiceDetector](#) **VoiceDetector** [get]

The VoiceDetector in use.

Use it to enable or disable voice detector and set its parameters.

3.40.3.3 **bool** [VoiceDetectorCalibrating](#) [get]

If true, voice detector calibration is in progress.

3.41 ILoggable Interface Reference

Inherited by [VoiceComponent](#), and [VoiceConnection](#).

Properties

- DebugLevel **LogLevel** [get, set]
- [VoiceLogger](#) **Logger** [get]

3.42 ILogger Interface Reference

Inherited by [IVoiceTransport](#), [Logger](#), and [VoiceLogger](#).

Public Member Functions

- void **LogError** (string fmt, params object[] args)
- void **LogWarning** (string fmt, params object[] args)
- void **LogInfo** (string fmt, params object[] args)
- void **LogDebug** (string fmt, params object[] args)

3.43 ImageBufferInfo Class Reference

Public Member Functions

- **ImageBufferInfo** (int width, int height, int[] stride, ImageFormat format)

Properties

- int **Width** [get]
- int **Height** [get]
- int[] **Stride** [get]
- ImageFormat **Format** [get]
- Rotation **Rotation** [get, set]
- Flip **Flip** [get, set]

3.44 ImageBufferNative Class Reference

Inherited by [ImageBufferNativeAlloc](#), and [ImageBufferNativeGCHandleSinglePlane](#).

Public Member Functions

- **ImageBufferNative** ([ImageBufferInfo](#) info)
- virtual void **Release** ()
- virtual void **Dispose** ()

Properties

- [ImageBufferInfo](#) **Info** [get, protected set]
- IntPtr[] **Planes** [get, protected set]

3.45 ImageBufferNativeAlloc Class Reference

Inherits [ImageBufferNative](#), and [IDisposable](#).

Public Member Functions

- **ImageBufferNativeAlloc** ([ImageBufferNativePool](#)< [ImageBufferNativeAlloc](#) > pool, [ImageBufferInfo](#) info)
- override void **Release** ()
- override void **Dispose** ()

Additional Inherited Members

3.46 ImageBufferNativeGCHandleSinglePlane Class Reference

Inherits [ImageBufferNative](#), and [IDisposable](#).

Public Member Functions

- **ImageBufferNativeGCHandleSinglePlane** ([ImageBufferNativePool](#)< [ImageBufferNativeGCHandleSinglePlane](#) > pool, [ImageBufferInfo](#) info)
- void **PinPlane** (byte[] plane)
- override void **Release** ()
- override void **Dispose** ()

Additional Inherited Members

3.47 ImageBufferNativePool< T > Class Template Reference

Inherits [ObjectPool< TType, TInfo >](#).

Public Member Functions

- delegate T **Factory** ([ImageBufferNativePool< T >](#) pool, [ImageBufferInfo](#) info)
- **ImageBufferNativePool** (int capacity, Factory factory, string name)
- **ImageBufferNativePool** (int capacity, Factory factory, string name, [ImageBufferInfo](#) info)

Protected Member Functions

- override T **createObject** ([ImageBufferInfo](#) info)
- override void **destroyObject** (T obj)
- override bool **infosMatch** ([ImageBufferInfo](#) i0, [ImageBufferInfo](#) i1)

Additional Inherited Members

3.48 IOSAudioForceToSpeaker Class Reference

Inherits MonoBehaviour.

3.49 IProcessor< T > Interface Template Reference

Audio Processor interface.

Inherits IDisposable.

Inherited by [AudioUtil.LevelMeter< T >](#), [AudioUtil.Resampler< T >](#), [AudioUtil.VoiceDetector< T >](#), [AudioUtil.VoiceDetectorCalibration< T >](#), [AudioUtil.VoiceLevelDetectCalibrate< T >](#), [SpeexProcessor](#), and [WebRTCAudioProcessor](#).

Public Member Functions

- T[] **Process** (T[] buf)
Process a frame of audio data.

3.49.1 Detailed Description

Audio Processor interface.

3.49.2 Member Function Documentation

3.49.2.1 T[] Process (T[] buf)

Process a frame of audio data.

Parameters

<i>buf</i>	Buffer containing input audio data
------------	------------------------------------

Returns

Buffer containing output audio data

Implemented in [AudioUtil.VoiceLevelDetectCalibrate< T >](#), [AudioUtil.VoiceDetector< T >](#), [AudioUtil.VoiceDetectorCalibration< T >](#), [AudioUtil.LevelMeter< T >](#), and [AudioUtil.Resampler< T >](#).

3.50 IServiceable Interface Reference

Interface for classes that want their [Service\(\)](#) function to be called regularly in the context of a [LocalVoice](#).

Inherited by [BufferReaderPushAdapterBase< T >](#).

Public Member Functions

- void [Service](#) ([LocalVoice](#) localVoice)
Service function that should be called regularly.

3.50.1 Detailed Description

Interface for classes that want their [Service\(\)](#) function to be called regularly in the context of a [LocalVoice](#).

3.50.2 Member Function Documentation

3.50.2.1 void Service ([LocalVoice](#) localVoice)

Service function that should be called regularly.

Implemented in [BufferReaderPushAdapterAsyncPoolCopy< T >](#), [BufferReaderPushAdapterAsyncPool< T >](#), [BufferReaderPushAdapter< T >](#), and [BufferReaderPushAdapterBase< T >](#).

3.51 ISyncAudioOut Interface Reference

Inherits [IAudioOut](#).

Inherited by [UnityAudioOut](#).

Public Member Functions

- void **Pause** ()
- void **UnPause** ()

Properties

- int **PlaySamplePos** [get, set]

3.52 AudioUtil.IVoiceDetector Interface Reference

Voice Activity Detector interface.

Inherited by [AudioUtil.VoiceDetector< T >](#), and [AudioUtil.VoiceDetectorDummy](#).

Properties

- bool [On](#) [get, set]
If true, voice detection enabled.
- float [Threshold](#) [get, set]
Voice detected as soon as signal level exceeds threshold.
- bool [Detected](#) [get]
If true, voice detected.
- DateTime [DetectedTime](#) [get]
Last time when switched to detected state.
- int [ActivityDelayMs](#) [get, set]
Keep detected state during this time after signal level dropped below threshold.

Events

- Action [OnDetected](#)
Called when switched to detected state.

3.52.1 Detailed Description

Voice Activity Detector interface.

3.52.2 Property Documentation

3.52.2.1 int ActivityDelayMs [get], [set]

Keep detected state during this time after signal level dropped below threshold.

3.52.2.2 bool Detected [get]

If true, voice detected.

3.52.2.3 DateTime DetectedTime [get]

Last time when switched to detected state.

3.52.2.4 bool On [get], [set]

If true, voice detection enabled.

3.52.2.5 float Threshold [get], [set]

Voice detected as soon as signal level exceeds threshold.

3.52.3 Event Documentation

3.52.3.1 Action OnDetected

Called when switched to detected state.

3.53 IVoiceTransport Interface Reference

Inherits [ILogger](#).

Inherited by [LoadBalancingTransport](#).

Public Member Functions

- int **AssignChannel** ([VoiceInfo](#) v)
- bool **IsChannelJoined** (int channelId)
- void **SendVoicesInfo** (IEnumerable< [LocalVoice](#) > voices, int channelId, int targetPlayerId)
- void **SendVoiceRemove** ([LocalVoice](#) voice, int channelId, int targetPlayerId)
- void **SendFrame** (ArraySegment< byte > data, byte evNumber, byte voiceId, int channelId, [LocalVoice](#) localVoice)
- string **ChannelIdStr** (int channelId)
- string **PlayerIdStr** (int playerId)
- void **SetDebugEchoMode** ([LocalVoice](#) v)

3.54 AudioUtil.LevelMeter< T > Class Template Reference

Audio Level Meter.

Inherits [IProcessor< T >](#), and [AudioUtil.ILevelMeter](#).

Inherited by [AudioUtil.LevelMeterFloat](#), and [AudioUtil.LevelMeterShort](#).

Public Member Functions

- void [ResetAccumAvgPeakAmp](#) ()
Reset AccumAvgPeakAmp.
- abstract T[] [Process](#) (T[] buf)
Process a frame of audio data.
- void **Dispose** ()

Protected Attributes

- float **ampSum**
- float **ampPeak**
- int **bufferSize**
- float[] **prevValues**
- int **prevValuesHead**
- float **accumAvgPeakAmpSum**
- int **accumAvgPeakAmpCount**

Properties

- float **CurrentAvgAmp** [get]
- float **CurrentPeakAmp** [get, protected set]
- float **AccumAvgPeakAmp** [get]

3.54.1 Detailed Description

Audio Level Meter.

3.54.2 Member Function Documentation

3.54.2.1 `abstract T[] Process (T[] buf)` [pure virtual]

Process a frame of audio data.

Parameters

<i>buf</i>	Buffer containing input audio data
------------	------------------------------------

Returns

Buffer containing output audio data

Implements [IProcessor< T >](#).

3.54.2.2 `void ResetAccumAvgPeakAmp ()`

Reset AccumAvgPeakAmp.

Implements [AudioUtil.ILevelMeter](#).

3.55 AudioUtil.LevelMeterDummy Class Reference

Dummy Audio Level Meter that doesn't actually do anything.

Inherits [AudioUtil.ILevelMeter](#).

Public Member Functions

- void [ResetAccumAvgPeakAmp](#) ()
Reset AccumAvgPeakAmp.

Properties

- float **CurrentAvgAmp** [get]
- float **CurrentPeakAmp** [get]
- float **AccumAvgPeakAmp** [get]

3.55.1 Detailed Description

Dummy Audio Level Meter that doesn't actually do anything.

3.55.2 Member Function Documentation

3.55.2.1 void ResetAccumAvgPeakAmp ()

Reset AccumAvgPeakAmp.

Implements [AudioUtil.LevelMeter](#).

3.56 AudioUtil.LevelMeterFloat Class Reference

[LevelMeter](#) specialization for float audio.

Inherits [AudioUtil.LevelMeter< T >](#).

Public Member Functions

- [LevelMeterFloat](#) (int samplingRate, int numChannels)
Create new [LevelMeterFloat](#) instance.
- override float[] **Process** (float[] buf)

Additional Inherited Members

3.56.1 Detailed Description

[LevelMeter](#) specialization for float audio.

3.56.2 Constructor & Destructor Documentation

3.56.2.1 LevelMeterFloat (int *samplingRate*, int *numChannels*)

Create new [LevelMeterFloat](#) instance.

Parameters

<i>samplingRate</i>	Sampling rate of the audio signal (in Hz).
<i>numChannels</i>	Number of channels in the audio signal.

3.57 AudioUtil.LevelMeterShort Class Reference

[LevelMeter](#) specialization for short audio.

Inherits [AudioUtil.LevelMeter< T >](#).

Public Member Functions

- [LevelMeterShort](#) (int samplingRate, int numChannels)
Create new [LevelMeterShort](#) instance.
- override short[] **Process** (short[] buf)

Additional Inherited Members

3.57.1 Detailed Description

[LevelMeter](#) specialization for short audio.

3.57.2 Constructor & Destructor Documentation

3.57.2.1 LevelMeterShort (int *samplingRate*, int *numChannels*)

Create new [LevelMeterShort](#) instance.

Parameters

<i>samplingRate</i>	Sampling rate of the audio signal (in Hz).
<i>numChannels</i>	Number of channels in the audio signal.

3.58 LoadBalancingFrontend Class Reference

Inherits [LoadBalancingTransport](#).

Additional Inherited Members

3.59 LoadBalancingTransport Class Reference

Extends [LoadBalancingClient](#) with audio streaming functionality.

Inherits [LoadBalancingClient](#), [IVoiceTransport](#), and [IDisposable](#).

Inherited by [LoadBalancingFrontend](#).

Public Member Functions

- void **LogError** (string fmt, params object[] args)
- void **LogWarning** (string fmt, params object[] args)
- void **LogInfo** (string fmt, params object[] args)
- void **LogDebug** (string fmt, params object[] args)
- int **AssignChannel** ([VoiceInfo](#) v)
- bool **IsChannelJoined** (int channelId)
- void **SetDebugEchoMode** ([LocalVoice](#) v)
- [LoadBalancingTransport](#) (ConnectionProtocol connectionProtocol=ConnectionProtocol.Udp)
 - Initializes a new [LoadBalancingTransport](#).*
- new void **Service** ()
 - This method dispatches all available incoming commands and then sends this client's outgoing commands. Call this method regularly (2 to 20 times a second).*
- virtual bool **ChangeAudioGroups** (byte[] groupsToRemove, byte[] groupsToAdd)
- void **SendVoicesInfo** (IEnumerable< [LocalVoice](#) > voices, int channelId, int targetPlayerId)
- void **SendDebugEchoVoicesInfo** (int channelId)
 - Send VoicesInfo events to the local player for all voices that have DebugEcho enabled.*
- void **SendVoiceRemove** ([LocalVoice](#) voice, int channelId, int targetPlayerId)
- void **SendFrame** (ArraySegment< byte > data, byte evNumber, byte voiceId, int channelId, [LocalVoice](#) localVoice)

- string **ChannelIdStr** (int channelId)
- string **PlayerIdStr** (int playerId)
- void [Dispose](#) ()

Releases all resources used by the [LoadBalancingTransport](#) instance.

Protected Attributes

- [VoiceClient](#) **voiceClient**

Properties

- [VoiceClient](#) **VoiceClient** [get]

The [VoiceClient](#) implementation associated with this [LoadBalancingTransport](#).

- byte **GlobalAudioGroup** [get, set]
- byte [GlobalInterestGroup](#) [get, set]

Set global audio group for this client. This call sets InterestGroup for existing local voices and for created later to given value. Client set as listening to this group only until LoadBalancingPeer.OpChangeGroups() called. This method can be called any time.

3.59.1 Detailed Description

Extends LoadBalancingClient with audio streaming functionality.

Use your normal LoadBalancing workflow to join a [Voice](#) room. All standard LoadBalancing features are available.

To work with audio:

- Create outgoing audio streams with Client.CreateLocalVoice.
- Handle new incoming audio streams info with OnRemoteVoiceInfoAction .
- Handle incoming audio streams data with OnAudioFrameAction .
- Handle closing of incoming audio streams with .

3.59.2 Constructor & Destructor Documentation

3.59.2.1 LoadBalancingTransport (ConnectionProtocol *connectionProtocol* = ConnectionProtocol.Udp)

Initializes a new [LoadBalancingTransport](#).

Parameters

<i>connection↔ Protocol</i>	Connection protocol (UDP or TCP). ConnectionProtocol
---------------------------------	--

3.59.3 Member Function Documentation

3.59.3.1 void Dispose ()

Releases all resources used by the [LoadBalancingTransport](#) instance.

3.59.3.2 void SendDebugEchoVoicesInfo (int *channelId*)

Send VoicesInfo events to the local player for all voices that have DebugEcho enabled.

This function will call SendVoicesInfo for all local voices of our [VoiceClient](#) that have DebugEchoMode set to true, with the given channel ID, and the local Player's ActorNumber as target.

Parameters

<i>channelId</i>	Transport Channel ID
------------------	----------------------

3.59.3.3 new void Service ()

This method dispatches all available incoming commands and then sends this client's outgoing commands. Call this method regularly (2 to 20 times a second).

3.59.4 Property Documentation

3.59.4.1 byte GlobalInterestGroup [get], [set]

Set global audio group for this client. This call sets InterestGroup for existing local voices and for created later to given value. Client set as listening to this group only until LoadBalancingPeer.OpChangeGroups() called. This method can be called any time.

[LocalVoice.InterestGroup](#) LoadBalancingPeer.OpChangeGroups(byte[], byte[])

3.59.4.2 VoiceClient VoiceClient [get]

The [VoiceClient](#) implementation associated with this [LoadBalancingTransport](#).

3.60 LocalVoice Class Reference

Represents outgoing data stream.

Inherits IDisposable.

Inherited by [LocalVoiceAudioDummy](#), and [LocalVoiceFramedBase](#).

Public Member Functions

- virtual [IEncoder](#) **CreateDefaultEncoder** ([VoiceInfo](#) info)
- void [RemoveSelf](#) ()
Remove this voice from it's [VoiceClient](#) (using [VoiceClient.RemoveLocalVoice](#)
- virtual void **Dispose** ()

Public Attributes

- const int **DATA_POOL_CAPACITY** = 50

Protected Member Functions

- void **resetNoTransmitCnt** ()

Protected Attributes

- [IEncoder](#) **encoder**
- [VoiceClient](#) **voiceClient**
- volatile bool **disposed**
- object **disposeLock** = new object()

Properties

- byte **Group** [get, set]
- byte **InterestGroup** [get, set]

If InterestGroup != 0, voice's data is sent only to clients listening to this group (if supported by transport).
- **VoiceInfo Info** [get]

Returns Info structure assigned on local voice cration.
- bool **TransmitEnabled** [get, set]

If true, stream data broadcasted.
- bool **IsCurrentlyTransmitting** [get, protected set]

Returns true if stream broadcasts.
- int **FramesSent** [get]

Sent frames counter.
- int **FramesSentBytes** [get]

Sent frames bytes counter.
- bool **Reliable** [get, set]

Send data reliable.
- bool **Encrypt** [get, set]

Send data encrypted.
- **IServiceable LocalUserServiceable** [get, set]

Optional user object attached to [LocalVoice](#). its `Service()` will be called at each `VoiceClient.Service()` call.
- bool **DebugEchoMode** [get, set]

If true, outgoing stream routed back to client via server same way as for remote client's streams. Can be swithed any time. `OnRemoteVoiceInfoAction` and `OnRemoteVoiceRemoveAction` are triggered if required. This functionality availability depends on transport.

3.60.1 Detailed Description

Represents outgoing data stream.

3.60.2 Member Function Documentation

3.60.2.1 void RemoveSelf ()

Remove this voice from it's [VoiceClient](#) (using `VoiceClient.RemoveLocalVoice`

.

3.60.3 Property Documentation

3.60.3.1 bool DebugEchoMode [get], [set]

If true, outgoing stream routed back to client via server same way as for remote client's streams. Can be swithed any time. `OnRemoteVoiceInfoAction` and `OnRemoteVoiceRemoveAction` are triggered if required. This functionality availability depends on transport.

3.60.3.2 bool Encrypt [get], [set]

Send data encrypted.

3.60.3.3 int FramesSent [get]

Sent frames counter.

3.60.3.4 int FramesSentBytes [get]

Sent frames bytes counter.

3.60.3.5 VoiceInfo Info [get]

Returns Info structure assigned on local voice cration.

3.60.3.6 byte InterestGroup [get], [set]

If InterestGroup != 0, voice's data is sent only to clients listening to this group (if supported by transport).

3.60.3.7 bool IsCurrentlyTransmitting [get], [protected set]

Returns true if stream broadcasts.

3.60.3.8 IServiceable LocalUserServiceable [get], [set]

Optional user object attached to [LocalVoice](#). its Service() will be called at each [VoiceClient.Service\(\)](#) call.

3.60.3.9 bool Reliable [get], [set]

Send data reliable.

3.60.3.10 bool TransmitEnabled [get], [set]

If true, stream data broadcasted.

3.61 LocalVoiceAudio< T > Class Template Reference

Outgoing audio stream.

Inherits [LocalVoiceFramed< T >](#), and [ILocalVoiceAudio](#).

Inherited by [LocalVoiceAudioFloat](#), and [LocalVoiceAudioShort](#).

Public Member Functions

- override [IEncoder](#) **CreateDefaultEncoder** ([VoiceInfo](#) info)
- void [VoiceDetectorCalibrate](#) (int durationMs)
Trigger voice detector calibration process.

Static Public Member Functions

- static [LocalVoiceAudio< T >](#) **Create** ([VoiceClient](#) voiceClient, byte voiceId, [IEncoder](#) encoder, [VoiceInfo](#) voiceInfo, int channelId)
Create a new LocalVoiceAudio<T> instance.

Protected Member Functions

- void **initBuiltinProcessors** ()

Protected Attributes

- [AudioUtil.VoiceDetector](#)< T > **voiceDetector**
- [AudioUtil.VoiceDetectorCalibration](#)< T > **voiceDetectorCalibration**
- [AudioUtil.LevelMeter](#)< T > **levelMeter**
- int **channels**
- int **sourceSamplingRateHz**
- bool **resampleSource**

Properties

- virtual [AudioUtil.IVoiceDetector](#) **VoiceDetector** [get]
- virtual [AudioUtil.ILevelMeter](#) **LevelMeter** [get]
- bool [VoiceDetectorCalibrating](#) [get]

True if the VoiceDetector is currently calibrating.

Additional Inherited Members

3.61.1 Detailed Description

Outgoing audio stream.

3.61.2 Member Function Documentation

- 3.61.2.1 **static LocalVoiceAudio<T> Create (VoiceClient voiceClient, byte voiceId, IEncoder encoder, VoiceInfo voiceInfo, int channelId)** [static]

Create a new LocalVoiceAudio<T> instance.

Parameters

<i>voiceClient</i>	The VoiceClient to use for this outgoing stream.
<i>voiceId</i>	Numeric ID for this voice.
<i>encoder</i>	Encoder to use for this voice.
<i>channelId</i>	Voice transport channel ID to use for this voice.

Returns

The new LocalVoiceAudio<T> instance.

- 3.61.2.2 **void VoiceDetectorCalibrate (int durationMs)**

Trigger voice detector calibration process.

While calibrating, keep silence. [Voice](#) detector sets threshold basing on measured background noise level.

Parameters

<i>durationMs</i>	Duration of calibration in milliseconds.
-------------------	--

Implements [ILocalVoiceAudio](#).

3.61.3 Property Documentation

3.61.3.1 bool VoiceDetectorCalibrating [get]

True if the VoiceDetector is currently calibrating.

3.62 LocalVoiceAudioDummy Class Reference

Dummy [LocalVoiceAudio](#)

Inherits [LocalVoice](#), and [ILocalVoiceAudio](#).

Public Member Functions

- void [VoiceDetectorCalibrate](#) (int durationMs)
Trigger voice detector calibration process.

Static Public Attributes

- static [LocalVoiceAudioDummy Dummy](#) = new [LocalVoiceAudioDummy](#)()
A Dummy [LocalVoiceAudio](#) instance.

Properties

- [AudioUtil.IVoiceDetector](#) **VoiceDetector** [get]
- [AudioUtil.ILevelMeter](#) **LevelMeter** [get]
- bool **VoiceDetectorCalibrating** [get]

Additional Inherited Members

3.62.1 Detailed Description

Dummy [LocalVoiceAudio](#)

For testing, this [LocalVoiceAudio](#) implementation features a [AudioUtil.VoiceDetectorDummy](#) and a [AudioUtil.Level↔MeterDummy](#)

3.62.2 Member Function Documentation

3.62.2.1 void VoiceDetectorCalibrate (int durationMs)

Trigger voice detector calibration process.

While calibrating, keep silence. [Voice](#) detector sets threshold based on measured background noise level.

Parameters

<i>durationMs</i>	Duration of calibration (in milliseconds).
-------------------	--

Implements [ILocalVoiceAudio](#).

3.62.3 Member Data Documentation

3.62.3.1 `LocalVoiceAudioDummy Dummy = new LocalVoiceAudioDummy()` `[static]`

A Dummy [LocalVoiceAudio](#) instance.

3.63 LocalVoiceAudioFloat Class Reference

Specialization of [LocalVoiceAudio](#) for float audio

Inherits [LocalVoiceAudio< T >](#).

Additional Inherited Members

3.63.1 Detailed Description

Specialization of [LocalVoiceAudio](#) for float audio

3.64 LocalVoiceAudioShort Class Reference

Specialization of [LocalVoiceAudio](#) for short audio

Inherits [LocalVoiceAudio< T >](#).

Additional Inherited Members

3.64.1 Detailed Description

Specialization of [LocalVoiceAudio](#) for short audio

3.65 LocalVoiceFramed< T > Class Template Reference

Typed re-framing [LocalVoice](#)

Inherits [LocalVoiceFramedBase](#).

Inherited by [LocalVoiceAudio< T >](#).

Public Member Functions

- void [AddPostProcessor](#) (params [IProcessor< T >\[\]](#) processors)
Adds processors after any built-in processors and everything added with AddPreProcessor.
- void [AddPreProcessor](#) (params [IProcessor< T >\[\]](#) processors)
Adds processors before built-in processors and everything added with AddPostProcessor.
- void [ClearProcessors](#) ()

Clears all processors in pipeline including built-in resampling. User should add at least resampler processor after call.

- void [PushDataAsync](#) (T[] buf)

Asynchronously push data into this stream.

- void [PushData](#) (T[] buf)

Synchronously push data into this stream.

- override void [Dispose](#) ()

Releases resources used by the VoiceFramed instance. Buffers used for asynchronous push will be disposed in encoder thread's 'finally'.

Properties

- [FactoryPrimitiveArrayPool](#)< T > **BufferFactory** [get]
- bool [PushDataAsyncReady](#) [get]

Whether this [LocalVoiceFramed](#) has capacity for more data buffers to be pushed asynchronously.

Additional Inherited Members

3.65.1 Detailed Description

Typed re-framing [LocalVoice](#)

Consumes data in array buffers of arbitrary length. Repacks them in frames of constant length for further processing and encoding.

Parameters

<i>voiceInfo</i>	Outgoing stream parameters. Set applicable fields to read them by encoder and by receiving client when voice created.
<i>channelId</i>	Transport channel specific to transport. Set to VoiceClient.ChannelAuto to let transport automatically assign channel.
<i>encoder</i>	Encoder producing the stream.

Returns

Outgoing stream handler.

3.65.2 Member Function Documentation

3.65.2.1 void AddPostProcessor (params IProcessor< T >[] processors)

Adds processors after any built-in processors and everything added with AddPreProcessor.

Parameters

<i>processors</i>	
-------------------	--

3.65.2.2 void AddPreProcessor (params IProcessor< T >[] processors)

Adds processors before built-in processors and everything added with AddPostProcessor.

Parameters

<i>processors</i>	
-------------------	--

3.65.2.3 void ClearProcessors ()

Clears all processors in pipeline including built-in resampling. User should add at least resampler processor after call.

3.65.2.4 override void Dispose () [virtual]

Releases resources used by the VoiceFramed instance. Buffers used for asynchronous push will be disposed in encoder thread's 'finally'.

Reimplemented from [LocalVoice](#).

3.65.2.5 void PushData (T[] buf)

Synchronously push data into this stream.

3.65.2.6 void PushDataAsync (T[] buf)

Asynchronously push data into this stream.

3.65.3 Property Documentation

3.65.3.1 bool PushDataAsyncReady [get]

Whether this [LocalVoiceFramed](#) has capacity for more data buffers to be pushed asynchronously.

3.66 LocalVoiceFramedBase Class Reference

Typed re-framing [LocalVoice](#)

Inherits [LocalVoice](#).

Inherited by [LocalVoiceFramed< T >](#).

Properties

- int [FrameSize](#) [get]

Data flow will be repacked to frames of this size. May differ from input voiceInfo.FrameSize. Processors should resample in this case.

Additional Inherited Members

3.66.1 Detailed Description

Typed re-framing [LocalVoice](#)

Base class for typed re-framing [LocalVoice](#) implementation ([LocalVoiceFramedBase<T>](#))

3.66.2 Property Documentation

3.66.2.1 int FrameSize [get]

Data flow will be repacked to frames of this size. May differ from input voiceInfo.FrameSize. Processors should resample in this case.

3.67 Logger Class Reference

Inherits [ILogger](#).

Public Member Functions

- void **LogError** (string fmt, params object[] args)
- void **LogWarning** (string fmt, params object[] args)
- void **LogInfo** (string fmt, params object[] args)
- void **LogDebug** (string fmt, params object[] args)

3.68 MicWrapper Class Reference

Inherits [IAudioReader< T >](#).

Public Member Functions

- **MicWrapper** (string device, int suggestedFrequency, [Voice.ILogger](#) logger)
- void **Dispose** ()
- bool **Read** (float[] buffer)

Properties

- int **SamplingRate** [get]
- int **Channels** [get]
- string **Error** [get]

3.69 ObjectFactory< TType, TInfo > Interface Template Reference

Uniform interface to [ObjectPool<TType, TInfo>](#) and single reusable object.

Inherits [IDisposable](#).

Inherited by [FactoryPrimitiveArrayPool< T >](#), and [FactoryReusableArray< T >](#).

Public Member Functions

- TType **New** ()
- TType **New** (TInfo info)
- void **Free** (TType obj)
- void **Free** (TType obj, TInfo info)

Properties

- TInfo **Info** [get]

3.69.1 Detailed Description

Uniform interface to `ObjectPool<TType, TInfo>` and single reusable object.

Template Parameters

<i>TType</i>	Object type.
<i>TInfo</i>	Type of property used to check 2 objects identity (like integral length of array).

3.70 ObjectPool< TType, TInfo > Class Template Reference

Generic Pool to re-use objects of a certain type (TType) that optionally match a certain property or set of properties (TInfo).

Inherits IDisposable.

Inherited by [ImageBufferNativePool< T >](#), and [PrimitiveArrayPool< T >](#).

Public Member Functions

- [ObjectPool](#) (int capacity, string name)
Create a new [ObjectPool](#) instance. Does not call [Init\(\)](#).
- [ObjectPool](#) (int capacity, string name, TInfo info)
Create a new [ObjectPool](#) instance with the given info structure. Calls [Init\(\)](#).
- void [Init](#) (TInfo info)
(Re-)Initializes this [ObjectPool](#).
- TType [AcquireOrCreate](#) ()
Acquire an existing object, or create a new one if none are available.
- TType [AcquireOrCreate](#) (TInfo info)
Acquire an existing object (if info matches), or create a new one from the passed info.
- virtual bool [Release](#) (TType obj, TInfo objInfo)
Returns object to pool.
- virtual bool [Release](#) (TType obj)
Returns object to pool, or destroys it if the pool is full.
- void [Dispose](#) ()
Free resources associated with this [ObjectPool](#)

Protected Member Functions

- abstract TType **createObject** (TInfo info)
- abstract void **destroyObject** (TType obj)
- abstract bool **infosMatch** (TInfo i0, TInfo i1)

Protected Attributes

- int **capacity**
- TInfo **info**
- int **pos**
- string **name**

Properties

- TInfo [Info](#) [get]

The property (info) that objects in this Pool must match.

3.70.1 Detailed Description

Generic Pool to re-use objects of a certain type (TType) that optionally match a certain property or set of properties (TInfo).

Template Parameters

<i>TType</i>	Object type.
<i>TInfo</i>	Type of parameter used to check 2 objects identity (like integral length of array).

3.70.2 Constructor & Destructor Documentation

3.70.2.1 ObjectPool (int *capacity*, string *name*)

Create a new [ObjectPool](#) instance. Does not call [Init\(\)](#).

Parameters

<i>capacity</i>	Capacity (size) of the object pool.
<i>name</i>	Name of the object pool.

3.70.2.2 ObjectPool (int *capacity*, string *name*, TInfo *info*)

Create a new [ObjectPool](#) instance with the given info structure. Calls [Init\(\)](#).

Parameters

<i>capacity</i>	Capacity (size) of the object pool.
<i>name</i>	Name of the object pool.
<i>info</i>	Info about this Pool's objects.

3.70.3 Member Function Documentation

3.70.3.1 TType AcquireOrCreate ()

Acquire an existing object, or create a new one if none are available.

If it fails to get one from the pool, this will create from the info given in this pool's constructor.

3.70.3.2 TType AcquireOrCreate (TInfo *info*)

Acquire an existing object (if info matches), or create a new one from the passed info.

Parameters

<i>info</i>	Info structure to match, or create a new object with.
-------------	---

3.70.3.3 void Dispose ()

Free resources associated with this [ObjectPool](#)

3.70.3.4 void Init (TInfo *info*)

(Re-)Initializes this [ObjectPool](#).

If there are objects available in this Pool, they will be destroyed. Allocates (Capacity) new Objects.

Parameters

<i>info</i>	Info about this Pool's objects.
-------------	---------------------------------

3.70.3.5 virtual bool Release (TType *obj*, TInfo *objInfo*) [virtual]

Returns object to pool.

Parameters

<i>obj</i>	The object to return to the pool.
<i>objInfo</i>	The info structure about obj.

obj is returned to the pool only if *objInfo* matches this pool's info. Else, it is destroyed.

3.70.3.6 virtual bool Release (TType *obj*) [virtual]

Returns object to pool, or destroys it if the pool is full.

Parameters

<i>obj</i>	The object to return to the pool.
------------	-----------------------------------

3.70.4 Property Documentation**3.70.4.1 TInfo Info** [get]

The property (info) that objects in this Pool must match.

3.71 OpusCodec Class Reference**Classes**

- class [Decoder](#)
- class [Encoder](#)
- class [EncoderFactory](#)
- class [EncoderFloat](#)
- class [EncoderShort](#)
- class [Util](#)

Public Types

- enum **FrameDuration**

3.72 OpusDecoder Class Reference

Inherits [IDisposable](#).

Public Member Functions

- **OpusDecoder** (SamplingRate outputSamplingRateHz, [Channels](#) numChannels)
- float[] **DecodePacketFloat** (byte[] packetData)
- short[] **DecodePacketShort** (byte[] packetData)
- void **Dispose** ()

Properties

- string **Version** [get]
- [Bandwidth](#) **PreviousPacketBandwidth** [get]

3.73 OpusEncoder Class Reference

Inherits IDisposable.

Public Member Functions

- **OpusEncoder** (SamplingRate inputSamplingRateHz, [Channels](#) numChannels, int bitrate, [OpusApplicationType](#) applicationType, [Delay](#) encoderDelay)
- ArraySegment< byte > **Encode** (float[] pcmSamples)
- ArraySegment< byte > **Encode** (short[] pcmSamples)
- void **Dispose** ()

Public Attributes

- const int **BitrateMax** = -1

Properties

- SamplingRate **InputSamplingRate** [get]
- [Channels](#) **InputChannels** [get]
- string **Version** [get]
- [Delay](#) **EncoderDelay** [get, set]
Using a duration of less than 10 ms will prevent the encoder from using the LPC or hybrid modes.
- int **FrameSizePerChannel** [get]
- int **Bitrate** [get, set]
- [Bandwidth](#) **MaxBandwidth** [get, set]
- Complexity **Complexity** [get, set]
- int **ExpectedPacketLossPercentage** [get, set]
- [SignalHint](#) **SignalHint** [get, set]
- ForceChannels **ForceChannels** [get, set]
- bool **UseInbandFEC** [get, set]
- bool **UseUnconstrainedVBR** [get, set]
- bool **DtxEnabled** [get, set]

3.73.1 Property Documentation

3.73.1.1 Delay EncoderDelay [get], [set]

Using a duration of less than 10 ms will prevent the encoder from using the LPC or hybrid modes.

3.74 OpusException Class Reference

Inherits Exception.

Public Member Functions

- **OpusException** (OpusStatusCode statusCode, string message)

Properties

- OpusStatusCode **StatusCodes** [get]

3.75 WebRTCAudioLib.Param Struct Reference

Public Attributes

- const int **REVERSE_STREAM_DELAY_MS** = 1
- const int **AEC** = 10
- const int **AEC_SUPPRESSION_LEVEL** = 11
- const int **AECM** = 20
- const int **AECM_ROUTING_MODE** = 21
- const int **AECM_COMFORT_NOISE** = 22
- const int **HIGH_PASS_FILTER** = 31
- const int **NS** = 41
- const int **NS_LEVEL** = 42
- const int **AGC** = 51
- const int **AGC_MODE** = 52
- const int **AGC_COMPRESSION_GAIN** = 56
- const int **AGC_LIMITER** = 57
- const int **VAD** = 61
- const int **VAD_FRAME_SIZE_MS** = 62
- const int **VAD_LIKEHOOD** = 63

3.76 PhotonVoiceCreatedParams Class Reference

Properties

- [Voice.LocalVoice](#) **Voice** [get, set]
- [Voice.IAudioDesc](#) **AudioDesc** [get, set]

3.77 Recorder.PhotonVoiceCreatedParams Class Reference

Properties

- [LocalVoice](#) **Voice** [get, set]
- [IAudioDesc](#) **AudioDesc** [get, set]

3.78 PhotonVoiceLagSimulationGui Class Reference

Inherits MonoBehaviour.

Public Member Functions

- void **OnEnable** ()

3.79 PhotonVoiceNetwork Class Reference

This class can be used to automatically sync client states between [PUN](#) and [Voice](#). It also sets a custom [PUN](#) Speaker factory to find the Speaker component for a character's voice. For this to work attach a [PhotonVoiceView](#) next to the PhotonView of your player's prefab.

Inherits [VoiceConnection](#).

Public Member Functions

- bool [ConnectAndJoinRoom](#) ()
Connect voice client to [Photon](#) servers and join a [Voice](#) room
- void [Disconnect](#) ()
Disconnect voice client from all [Photon](#) servers

Public Attributes

- const string [VoiceRoomNameSuffix](#) = "_voice_"
Suffix for voice room names appended to [PUN](#) room names.
- bool [AutoConnectAndJoin](#) = true
Auto connect voice client and join a voice room when [PUN](#) client is joined to a [PUN](#) room
- bool [AutoLeaveAndDisconnect](#) = true
Auto disconnect voice client when [PUN](#) client is not joined to a [PUN](#) room
- bool [AutoCreateSpeakerIfNotFound](#) = true
Auto instantiate a GameObject and attach a Speaker component to link to a remote audio stream if no candidate could be found

Protected Member Functions

- override void **Awake** ()
- override void **OnApplicationQuit** ()
- override void **OnDestroy** ()
- override void **OnVoiceStateChanged** ([ClientState](#) fromState, [ClientState](#) toState)

Properties

- static [PhotonVoiceNetwork Instance](#) [get, set]
Singleton instance for [PhotonVoiceNetwork](#)

Additional Inherited Members

3.79.1 Detailed Description

This class can be used to automatically sync client states between [PUN](#) and [Voice](#). It also sets a custom [PUN](#) Speaker factory to find the Speaker component for a character's voice. For this to work attach a [PhotonVoiceView](#) next to the PhotonView of your player's prefab.

3.79.2 Member Function Documentation

3.79.2.1 `bool ConnectAndJoinRoom ()`

Connect voice client to [Photon](#) servers and join a [Voice](#) room

Returns

If true, connection command send from client

3.79.2.2 `void Disconnect ()`

Disconnect voice client from all [Photon](#) servers

3.79.3 Member Data Documentation

3.79.3.1 `bool AutoConnectAndJoin = true`

Auto connect voice client and join a voice room when [PUN](#) client is joined to a [PUN](#) room

3.79.3.2 `bool AutoCreateSpeakerIfNotFound = true`

Auto instantiate a GameObject and attach a Speaker component to link to a remote audio stream if no candidate could be found

3.79.3.3 `bool AutoLeaveAndDisconnect = true`

Auto disconnect voice client when [PUN](#) client is not joined to a [PUN](#) room

3.79.3.4 `const string VoiceRoomNameSuffix = "_voice_"`

Suffix for voice room names appended to [PUN](#) room names.

3.79.4 Property Documentation

3.79.4.1 `PhotonVoiceNetwork Instance` `[static], [get], [set]`

Singleton instance for [PhotonVoiceNetwork](#)

3.80 PhotonVoiceStatsGui Class Reference

Basic GUI to show traffic and health statistics of the connection to [Photon](#), toggled by shift+tab.

Inherits [MonoBehaviour](#).

3.80.1 Detailed Description

Basic GUI to show traffic and health statistics of the connection to [Photon](#), toggled by shift+tab.

The shown health values can help identify problems with connection losses or performance. Example: If the time delta between two consecutive `SendOutgoingCommands` calls is a second or more, chances rise for a disconnect being caused by this (because acknowledgments to the server need to be sent in due time).

3.81 PhotonVoiceView Class Reference

Component that should be attached to a networked [PUN](#) prefab that has [PhotonView](#). It will bind remote [Recorder](#) with local [Speaker](#) of the same networked prefab. This component makes automatic voice stream routing easy for players' characters/avatars.

Inherits [VoiceComponent](#).

Public Attributes

- bool [AutoCreateRecorderIfNotFound](#)
If true, a [Recorder](#) component will be added to the same [GameObject](#) if not found already.
- bool [UsePrimaryRecorder](#)
If true, [PhotonVoiceNetwork.PrimaryRecorder](#) will be used by this [PhotonVoiceView](#)
- bool [SetupDebugSpeaker](#)
If true, a [Speaker](#) component will be setup to be used for the [DebugEcho](#) mode

Protected Member Functions

- override void **Awake** ()

Properties

- [Recorder](#) [RecorderInUse](#) [get, set]
The [Recorder](#) component currently used by this [PhotonVoiceView](#)
- [Speaker](#) [SpeakerInUse](#) [get, set]
The [Speaker](#) component currently used by this [PhotonVoiceView](#)
- bool [IsSetup](#) [get, protected set]
If true, this [PhotonVoiceView](#) is setup and ready to be used
- bool [IsSpeaker](#) [get, protected set]
If true, this [PhotonVoiceView](#) has a [Speaker](#) setup for playback of received audio frames from remote audio source
- bool [IsSpeaking](#) [get]
If true, this [PhotonVoiceView](#) has a [Speaker](#) that is currently playing received audio frames from remote audio source
- bool [IsRecorder](#) [get, protected set]
If true, this [PhotonVoiceView](#) has a [Recorder](#) setup for transmission of audio stream from local audio source
- bool [IsRecording](#) [get]
If true, this [PhotonVoiceView](#) has a [Recorder](#) that is currently transmitting audio stream from local audio source

Additional Inherited Members

3.81.1 Detailed Description

Component that should be attached to a networked [PUN](#) prefab that has [PhotonView](#). It will bind remote Recorder with local Speaker of the same networked prefab. This component makes automatic voice stream routing easy for players' characters/avatars.

3.81.2 Member Data Documentation

3.81.2.1 `bool AutoCreateRecorderIfNotFound`

If true, a Recorder component will be added to the same GameObject if not found already.

3.81.2.2 `bool SetupDebugSpeaker`

If true, a Speaker component will be setup to be used for the DebugEcho mode

3.81.2.3 `bool UsePrimaryRecorder`

If true, [PhotonVoiceNetwork.PrimaryRecorder](#) will be used by this [PhotonVoiceView](#)

3.81.3 Property Documentation

3.81.3.1 `bool IsRecorder` `[get], [protected set]`

If true, this [PhotonVoiceView](#) has a Recorder setup for transmission of audio stream from local audio source

3.81.3.2 `bool IsRecording` `[get]`

If true, this [PhotonVoiceView](#) has a Recorder that is currently transmitting audio stream from local audio source

3.81.3.3 `bool IsSetup` `[get], [protected set]`

If true, this [PhotonVoiceView](#) is setup and ready to be used

3.81.3.4 `bool IsSpeaker` `[get], [protected set]`

If true, this [PhotonVoiceView](#) has a Speaker setup for playback of received audio frames from remote audio source

3.81.3.5 `bool IsSpeaking` `[get]`

If true, this [PhotonVoiceView](#) has a Speaker that is currently playing received audio frames from remote audio source

3.81.3.6 `Recorder RecorderInUse` `[get], [set]`

The Recorder component currently used by this [PhotonVoiceView](#)

3.81.3.7 Speaker SpeakerInUse [get], [set]

The Speaker component currently used by this [PhotonVoiceView](#)

3.82 PrimitiveArrayPool< T > Class Template Reference

Pool of Arrays with components of type T, with [ObjectPool](#) info being the array's size.

Inherits [ObjectPool< TType, TInfo >](#).

Public Member Functions

- **PrimitiveArrayPool** (int capacity, string name)
- **PrimitiveArrayPool** (int capacity, string name, int info)

Protected Member Functions

- override T[] **createObject** (int info)
- override void **destroyObject** (T[] obj)
- override bool **infosMatch** (int i0, int i1)

Additional Inherited Members**3.82.1 Detailed Description**

Pool of Arrays with components of type T, with [ObjectPool](#) info being the array's size.

Template Parameters

<i>T</i>	Array element type.
----------	---------------------

3.83 Recorder Class Reference

Component representing outgoing audio stream in scene.

Inherits [VoiceComponent](#).

Classes

- class [PhotonVoiceCreatedParams](#)

Public Types

- enum **InputSourceType**
- enum **MicType**
- enum **SampleTypeConv**

Public Member Functions

- void **Init** ([VoiceClient](#) voiceClient, object customObj=null)
Initializes the [Recorder](#) component to be able to transmit audio.
- void **Relnit** ()
Reinitializes the [Recorder](#) if something has changed that requires this.
- void **VoiceDetectorCalibrate** (int durationMs)
Trigger voice detector calibration process. While calibrating, keep silence. [Voice](#) detector sets threshold basing on measured background noise level.

Protected Member Functions

- virtual void **SendPhotonVoiceCreatedMessage** ()

Properties

- static [AudioInEnumerator PhotonMicrophoneEnumerator](#) [get]
Enumerator for the available microphone devices gathered by the [Photon](#) plugin.
- bool **IsInitialized** [get]
If true, this [Recorder](#) has been initialized and is ready to transmit to remote clients.
- bool **RequiresInit** [get]
Returns true if something has changed in the [Recorder](#) after initialization that won't take effect unless re initialized.
- bool **TransmitEnabled** [get, set]
If true, audio transmission is enabled.
- bool **Encrypt** [get, set]
If true, voice stream is sent encrypted.
- bool **DebugEchoMode** [get, set]
If true, outgoing stream routed back to client via server same way as for remote client's streams.
- bool **ReliableMode** [get, set]
If true, stream data sent in reliable mode.
- bool **VoiceDetection** [get, set]
If true, voice detection enabled.
- float **VoiceDetectionThreshold** [get, set]
[Voice](#) detection threshold (0..1, where 1 is full amplitude).
- int **VoiceDetectionDelayMs** [get, set]
Keep detected state during this time after signal level dropped below threshold. Default is 500ms
- object **UserData** [get, set]
Custom user object to be sent in the voice stream info event.
- Func< [IAudioDesc](#) > **InputFactory** [get, set]
Set the method returning new [Voice.IAudioDesc](#) instance to be assigned to a new voice created with Source set to Factory
- [AudioUtil.IVoiceDetector](#) **VoiceDetector** [get]
Returns voice activity detector for recorder's audio stream.
- string **UnityMicrophoneDevice** [get, set]
Set or get [Unity](#) microphone device used for streaming.
- int **PhotonMicrophoneDeviceId** [get, set]
Set or get photon microphone device used for streaming.
- byte **AudioGroup** [get, set]
Target interest group that will receive transmitted audio.
- byte **InterestGroup** [get, set]
Target interest group that will receive transmitted audio.

- bool [IsCurrentlyTransmitting](#) [get]
Returns true if audio stream broadcasts.
- [AudioUtil.ILevelMeter LevelMeter](#) [get]
Level meter utility.
- bool [VoiceDetectorCalibrating](#) [get]
If true, voice detector calibration is in progress.
- [ILocalVoiceAudio voiceAudio](#) [get]
- InputSourceType [SourceType](#) [get, set]
Audio data source.
- MicType [MicrophoneType](#) [get, set]
Which microphone API to use when the Source is set to Microphone.
- SampleTypeConv [TypeConvert](#) [get, set]
Force creation of 'short' pipeline and convert audio data to short for 'float' audio sources.
- AudioClip [AudioClip](#) [get, set]
Source audio clip.
- bool [LoopAudioClip](#) [get, set]
Loop playback for audio clip sources.
- POpusCodec.Enums.SamplingRate [SamplingRate](#) [get, set]
Outgoing audio stream sampling rate.
- OpusCodec.FrameDuration [FrameDuration](#) [get, set]
Outgoing audio stream encoder delay.
- int [Bitrate](#) [get, set]
Outgoing audio stream bitrate.

Additional Inherited Members

3.83.1 Detailed Description

Component representing outgoing audio stream in scene.

3.83.2 Member Function Documentation

3.83.2.1 void Init ([VoiceClient](#) *voiceClient*, object *customObj* = null)

Initializes the [Recorder](#) component to be able to transmit audio.

Parameters

<i>voiceClient</i>	The VoiceClient to be used with this Recorder .
<i>customObj</i>	Optional user data object to be transmitted with the voice stream info

3.83.2.2 void Relnit ()

Reinitializes the [Recorder](#) if something has changed that requires this.

3.83.2.3 void VoiceDetectorCalibrate (int *durationMs*)

Trigger voice detector calibration process. While calibrating, keep silence. [Voice](#) detector sets threshold basing on measured background noise level.

Parameters

<i>durationMs</i>	Duration of calibration in milliseconds.
-------------------	--

3.83.3 Property Documentation**3.83.3.1 AudioClip AudioClip** [get], [set]

Source audio clip.

3.83.3.2 byte AudioGroup [get], [set]

Target interest group that will receive transmitted audio.

If AudioGroup != 0, recorder's audio data is sent only to clients listening to this group.

3.83.3.3 int Bitrate [get], [set]

Outgoing audio stream bitrate.

3.83.3.4 bool DebugEchoMode [get], [set]

If true, outgoing stream routed back to client via server same way as for remote client's streams.

3.83.3.5 bool Encrypt [get], [set]

If true, voice stream is sent encrypted.

3.83.3.6 OpusCodec.FrameDuration FrameDuration [get], [set]

Outgoing audio stream encoder delay.

3.83.3.7 Func<IAudioDesc> InputFactory [get], [set]

Set the method returning new [Voice.IAudioDesc](#) instance to be assigned to a new voice created with Source set to Factory

3.83.3.8 byte InterestGroup [get], [set]

Target interest group that will receive transmitted audio.

If InterestGroup != 0, recorder's audio data is sent only to clients listening to this group.

3.83.3.9 bool IsCurrentlyTransmitting [get]

Returns true if audio stream broadcasts.

3.83.3.10 bool IsInitialized [get]

If true, this [Recorder](#) has been initialized and is ready to transmit to remote clients.

3.83.3.11 AudioUtil.ILevelMeter LevelMeter [get]

Level meter utility.

3.83.3.12 bool LoopAudioClip [get], [set]

Loop playback for audio clip sources.

3.83.3.13 MicType MicrophoneType [get], [set]

Which microphone API to use when the Source is set to Microphone.

3.83.3.14 int PhotonMicrophoneDeviceId [get], [set]

Set or get photon microphone device used for streaming.

3.83.3.15 AudiolnEnumerator PhotonMicrophoneEnumerator [static], [get]

Enumerator for the available microphone devices gathered by the [Photon](#) plugin.

3.83.3.16 bool ReliableMode [get], [set]

If true, stream data sent in reliable mode.

3.83.3.17 bool RequiresInit [get]

Returns true if something has changed in the [Recorder](#) after initialization that won't take effect unless re initialized.

3.83.3.18 POpusCodec.Enums.SamplingRate SamplingRate [get], [set]

Outgoing audio stream sampling rate.

3.83.3.19 InputSourceType SourceType [get], [set]

Audio data source.

3.83.3.20 bool TransmitEnabled [get], [set]

If true, audio transmission is enabled.

3.83.3.21 SampleTypeConv TypeConvert [get], [set]

Force creation of 'short' pipeline and convert audio data to short for 'float' audio sources.

3.83.3.22 string UnityMicrophoneDevice [get], [set]

Set or get [Unity](#) microphone device used for streaming.

3.83.3.23 object UserData [get], [set]

Custom user object to be sent in the voice stream info event.

3.83.3.24 bool VoiceDetection [get], [set]

If true, voice detection enabled.

3.83.3.25 int VoiceDetectionDelayMs [get], [set]

Keep detected state during this time after signal level dropped below threshold. Default is 500ms

3.83.3.26 float VoiceDetectionThreshold [get], [set]

Voice detection threshold (0..1, where 1 is full amplitude).

3.83.3.27 AudioUtil.IVoiceDetector VoiceDetector [get]

Returns voice activity detector for recorder's audio stream.

3.83.3.28 bool VoiceDetectorCalibrating [get]

If true, voice detector calibration is in progress.

3.84 RemoteVoiceInfo Class Reference

Information about a remote voice (incoming stream).

Properties

- [VoiceInfo Info](#) [get]
Remote voice info.
- int [ChannelId](#) [get]
ID of channel used for transmission.
- int [PlayerId](#) [get]
Player ID of voice owner.
- byte [VoiceId](#) [get]
Voice ID (unique in the room).

3.84.1 Detailed Description

Information about a remote voice (incoming stream).

3.84.2 Property Documentation

3.84.2.1 int ChannelId [get]

ID of channel used for transmission.

3.84.2.2 VoiceInfo Info [get]

Remote voice info.

3.84.2.3 int PlayerId [get]

Player ID of voice owner.

3.84.2.4 byte VoiceId [get]

Voice ID (unique in the room).

3.85 RemoteVoiceLink Class Reference

Public Member Functions

- **RemoteVoiceLink** ([VoiceInfo](#) info, int playerId, int voiceId, int channelId, ref [RemoteVoiceOptions](#) options)

Properties

- [VoiceInfo](#) Info [get]
- int **PlayerId** [get]
- int **VoiceId** [get]
- int **ChannelId** [get]

Events

- Action< float[]> **FloatFrameDecoded**
- Action **RemoteVoiceRemoved**

3.86 RemoteVoiceOptions Struct Reference

Event Actions and other options for a remote voice (incoming stream).

Properties

- Action< byte[]> [OnDecodedFrameByteAction](#) [get, set]
Register a method to be called when new data frame received. Use it to get uncompressed data as byte[].
- Action< float[]> [OnDecodedFrameFloatAction](#) [get, set]
Register a method to be called when new data frame received. Use it to get uncompressed data as float[].
- Action< short[]> [OnDecodedFrameShortAction](#) [get, set]
Register a method to be called when new data frame received. Use it to get uncompressed data as short[].
- Action [OnRemoteVoiceRemoveAction](#) [get, set]
Register a method to be called when the remote voice is removed.
- [IDecoder](#) Decoder [get, set]
Remote voice data decoder. Use to set decoder options or override it with user decoder.

3.86.1 Detailed Description

Event Actions and other options for a remote voice (incoming stream).

3.86.2 Property Documentation

3.86.2.1 `IDecoder Decoder` `[get]`, `[set]`

Remote voice data decoder. Use to set decoder options or override it with user decoder.

3.86.2.2 `Action<byte[]> OnDecodedFrameByteAction` `[get]`, `[set]`

Register a method to be called when new data frame received. Use it to get uncompressed data as `byte[]`.

3.86.2.3 `Action<float[]> OnDecodedFrameFloatAction` `[get]`, `[set]`

Register a method to be called when new data frame received. Use it to get uncompressed data as `float[]`.

3.86.2.4 `Action<short[]> OnDecodedFrameShortAction` `[get]`, `[set]`

Register a method to be called when new data frame received. Use it to get uncompressed data as `short[]`.

3.86.2.5 `Action OnRemoteVoiceRemoveAction` `[get]`, `[set]`

Register a method to be called when the remote voice is removed.

3.87 `AudioUtil.Resampler< T >` Class Template Reference

Sample-rate conversion Audio Processor.

Inherits [IProcessor< T >](#).

Public Member Functions

- [Resampler](#) (int dstSize, int channels)
Create a new [Resampler](#) instance.
- `T[]` [Process](#) (`T[]` buf)
Process a frame of audio data.
- void **Dispose** ()

Protected Attributes

- `T[]` **frameResampled**

3.87.1 Detailed Description

Sample-rate conversion Audio Processor.

This processor converts the sample-rate of the source stream. Internally, it uses `AudioUtil.Resample`.

3.87.2 Constructor & Destructor Documentation

3.87.2.1 Resampler (int *dstSize*, int *channels*)

Create a new [Resampler](#) instance.

Parameters

<i>dstSize</i>	Frame size of a destination frame. Determines output rate.
<i>channels</i>	Number of audio channels expected in both in- and output.

3.87.3 Member Function Documentation

3.87.3.1 T[] Process (T[] *buf*)

Process a frame of audio data.

Parameters

<i>buf</i>	Buffer containing input audio data
------------	------------------------------------

Returns

Buffer containing output audio data

Implements [IProcessor< T >](#).

3.88 Speaker Class Reference

Component representing remote audio stream in local scene.

Inherits [VoiceComponent](#).

Public Attributes

- int **PlayDelayMs** = 200

Protected Member Functions

- override void **Awake** ()

Properties

- bool [IsPlaying](#) [get]
Is the speaker playing right now.
- int [Lag](#) [get]
Smoothed difference between (jittering) stream and (clock-driven) audioOutput.
- Action< [Speaker](#) > [OnRemoteVoiceRemoveAction](#) [get, set]
Register a method to be called when remote voice removed.
- Realtime.Player [Actor](#) [get, set]
Per room, the connected users/players are represented with a Realtime.Player, also known as Actor.
- bool [IsLinked](#) [get]
Whether or not this [Speaker](#) has been linked to a remote voice stream.

Additional Inherited Members

3.88.1 Detailed Description

Component representing remote audio stream in local scene.

3.88.2 Property Documentation

3.88.2.1 `Realtime.Player Actor` `[get]`, `[set]`

Per room, the connected users/players are represented with a `Realtime.Player`, also known as Actor.

[Photon Voice](#) calls this Actor, to avoid a name-clash with the `Player` class in [Voice](#).

3.88.2.2 `bool IsLinked` `[get]`

Whether or not this [Speaker](#) has been linked to a remote voice stream.

3.88.2.3 `bool IsPlaying` `[get]`

Is the speaker playing right now.

3.88.2.4 `int Lag` `[get]`

Smoothed difference between (jittering) stream and (clock-driven) audioOutput.

3.88.2.5 `Action<Speaker> OnRemoteVoiceRemoveAction` `[get]`, `[set]`

Register a method to be called when remote voice removed.

3.89 SpeexLib Class Reference

Inherited by [SpeexProcessor](#).

Public Member Functions

- static `IntPtr speex_preprocess_state_init` (int frame_size, int sampling_rate)
- static void `speex_preprocess_state_destroy` (IntPtr st)
- static int `speex_preprocess_run` (IntPtr st, short[] x)
- static int `speex_preprocess_ctl` (IntPtr st, int request, IntPtr ptr)
- static `IntPtr speex_echo_state_init` (int frame_size, int filter_length)
- static `IntPtr speex_echo_state_init_mc` (int frame_size, int filter_length, int nb_mic, int nb_speakers)
- static void `speex_echo_state_destroy` (IntPtr st)
- static void `speex_echo_cancellation` (IntPtr st, short[] rec, short[] play, short[] outBuf)
- static void `speex_echo_capture` (IntPtr st, short[] rec, short[] outBuf)
- static void `speex_echo_playback` (IntPtr st, short[] play)
- static void `speex_echo_state_reset` (IntPtr st)
- static int `speex_echo_ctl` (IntPtr st, int request, IntPtr ptr)

Static Public Member Functions

- static int **speex_preprocess_ctl** (IntPtr st, int request, ref int value)
- static int **speex_preprocess_ctl** (IntPtr st, int request, ref float value)
- static int **speex_echo_ctl** (IntPtr st, int request, ref int value)
- static int **speex_echo_ctl** (IntPtr st, int request, ref float value)

Public Attributes

- const int **SPEEX_PREPROCESS_SET_DENOISE** = 0
- const int **SPEEX_PREPROCESS_GET_DENOISE** = 1
- const int **SPEEX_PREPROCESS_SET_AGC** = 2
- const int **SPEEX_PREPROCESS_GET_AGC** = 3
- const int **SPEEX_PREPROCESS_SET_VAD** = 4
- const int **SPEEX_PREPROCESS_GET_VAD** = 5
- const int **SPEEX_PREPROCESS_SET_AGC_LEVEL** = 6
- const int **SPEEX_PREPROCESS_GET_AGC_LEVEL** = 7
- const int **SPEEX_PREPROCESS_SET_DEREVERB** = 8
- const int **SPEEX_PREPROCESS_GET_DEREVERB** = 9
- const int **SPEEX_PREPROCESS_SET_DEREVERB_LEVEL** = 10
- const int **SPEEX_PREPROCESS_GET_DEREVERB_LEVEL** = 11
- const int **SPEEX_PREPROCESS_SET_DEREVERB_DECAY** = 12
- const int **SPEEX_PREPROCESS_GET_DEREVERB_DECAY** = 13
- const int **SPEEX_PREPROCESS_SET_PROB_START** = 14
- const int **SPEEX_PREPROCESS_GET_PROB_START** = 15
- const int **SPEEX_PREPROCESS_SET_PROB_CONTINUE** = 16
- const int **SPEEX_PREPROCESS_GET_PROB_CONTINUE** = 17
- const int **SPEEX_PREPROCESS_SET_NOISE_SUPPRESS** = 18
- const int **SPEEX_PREPROCESS_GET_NOISE_SUPPRESS** = 19
- const int **SPEEX_PREPROCESS_SET_ECHO_SUPPRESS** = 20
- const int **SPEEX_PREPROCESS_GET_ECHO_SUPPRESS** = 21
- const int **SPEEX_PREPROCESS_SET_ECHO_SUPPRESS_ACTIVE** = 22
- const int **SPEEX_PREPROCESS_GET_ECHO_SUPPRESS_ACTIVE** = 23
- const int **SPEEX_PREPROCESS_SET_ECHO_STATE** = 24
- const int **SPEEX_PREPROCESS_GET_ECHO_STATE** = 25
- const int **SPEEX_PREPROCESS_SET_AGC_INCREMENT** = 26
- const int **SPEEX_PREPROCESS_GET_AGC_INCREMENT** = 27
- const int **SPEEX_PREPROCESS_SET_AGC_DECREMENT** = 28
- const int **SPEEX_PREPROCESS_GET_AGC_DECREMENT** = 29
- const int **SPEEX_PREPROCESS_SET_AGC_MAX_GAIN** = 30
- const int **SPEEX_PREPROCESS_GET_AGC_MAX_GAIN** = 31
- const int **SPEEX_PREPROCESS_GET_AGC_LOUDNESS** = 33
- const int **SPEEX_PREPROCESS_GET_AGC_GAIN** = 35
- const int **SPEEX_PREPROCESS_GET_PSD_SIZE** = 37
- const int **SPEEX_PREPROCESS_GET_PSD** = 39
- const int **SPEEX_PREPROCESS_GET_NOISE_PSD_SIZE** = 41
- const int **SPEEX_PREPROCESS_GET_NOISE_PSD** = 43
- const int **SPEEX_PREPROCESS_GET_PROB** = 45
- const int **SPEEX_PREPROCESS_SET_AGC_TARGET** = 46
- const int **SPEEX_PREPROCESS_GET_AGC_TARGET** = 47
- const int **SPEEX_ECHO_GET_FRAME_SIZE** = 3
- const int **SPEEX_ECHO_SET_SAMPLING_RATE** = 24
- const int **SPEEX_ECHO_GET_SAMPLING_RATE** = 25
- const int **SPEEX_ECHO_GET_IMPULSE_RESPONSE_SIZE** = 27
- const int **SPEEX_ECHO_GET_IMPULSE_RESPONSE** = 29

3.89.1 Member Data Documentation

3.89.1.1 `const int SPEEX_ECHO_GET_FRAME_SIZE = 3`

Obtain frame size used by the AEC

3.89.1.2 `const int SPEEX_ECHO_GET_IMPULSE_RESPONSE = 29`

Get impulse response (int32[])

3.89.1.3 `const int SPEEX_ECHO_GET_IMPULSE_RESPONSE_SIZE = 27`

Get size of impulse response (int32)

3.89.1.4 `const int SPEEX_ECHO_GET_SAMPLING_RATE = 25`

Get sampling rate

3.89.1.5 `const int SPEEX_ECHO_SET_SAMPLING_RATE = 24`

Set sampling rate

3.89.1.6 `const int SPEEX_PREPROCESS_GET_AGC = 3`

Get preprocessor Automatic Gain Control state

3.89.1.7 `const int SPEEX_PREPROCESS_GET_AGC_DECREMENT = 29`

Get maximal gain decrease in dB/second (int32)

3.89.1.8 `const int SPEEX_PREPROCESS_GET_AGC_GAIN = 35`

Get current gain (int32 percent)

3.89.1.9 `const int SPEEX_PREPROCESS_GET_AGC_INCREMENT = 27`

Get maximal gain increase in dB/second (int32)

3.89.1.10 `const int SPEEX_PREPROCESS_GET_AGC_LEVEL = 7`

Get preprocessor Automatic Gain Control level (float)

3.89.1.11 `const int SPEEX_PREPROCESS_GET_AGC_LOUDNESS = 33`

Get loudness

3.89.1.12 `const int SPEEX_PREPROCESS_GET_AGC_MAX_GAIN = 31`

Get maximal gain in dB (int32)

3.89.1.13 `const int SPEEX_PREPROCESS_GET_AGC_TARGET = 47`

Get preprocessor Automatic Gain Control level (int32)

3.89.1.14 `const int SPEEX_PREPROCESS_GET_DENOISE = 1`

Get preprocessor denoiser state

3.89.1.15 `const int SPEEX_PREPROCESS_GET_DEREVERB = 9`

Get preprocessor dereverb state

3.89.1.16 `const int SPEEX_PREPROCESS_GET_DEREVERB_DECAY = 13`

Get preprocessor dereverb decay

3.89.1.17 `const int SPEEX_PREPROCESS_GET_DEREVERB_LEVEL = 11`

Get preprocessor dereverb level

3.89.1.18 `const int SPEEX_PREPROCESS_GET_ECHO_STATE = 25`

Get the corresponding echo canceller state

3.89.1.19 `const int SPEEX_PREPROCESS_GET_ECHO_SUPPRESS = 21`

Get maximum attenuation of the residual echo in dB (negative number)

3.89.1.20 `const int SPEEX_PREPROCESS_GET_ECHO_SUPPRESS_ACTIVE = 23`

Get maximum attenuation of the residual echo in dB when near end is active (negative number)

3.89.1.21 `const int SPEEX_PREPROCESS_GET_NOISE_PSD = 43`

Get noise estimate (int32[]) of squared values)

3.89.1.22 `const int SPEEX_PREPROCESS_GET_NOISE_PSD_SIZE = 41`

Get spectrum size for noise estimate (int32)

3.89.1.23 `const int SPEEX_PREPROCESS_GET_NOISE_SUPPRESS = 19`

Get maximum attenuation of the noise in dB (negative number)

3.89.1.24 `const int SPEEX_PREPROCESS_GET_PROB = 45`

Get speech probability in last frame (int32).

3.89.1.25 `const int SPEEX_PREPROCESS_GET_PROB_CONTINUE = 17`

Get probability required for the VAD to stay in the voice state (integer percent)

3.89.1.26 `const int SPEEX_PREPROCESS_GET_PROB_START = 15`

Get probability required for the VAD to go from silence to voice

3.89.1.27 `const int SPEEX_PREPROCESS_GET_PSD = 39`

Get power spectrum (int32[] of squared values)

3.89.1.28 `const int SPEEX_PREPROCESS_GET_PSD_SIZE = 37`

Get spectrum size for power spectrum (int32)

3.89.1.29 `const int SPEEX_PREPROCESS_GET_VAD = 5`

Get preprocessor [Voice](#) Activity Detection state

3.89.1.30 `const int SPEEX_PREPROCESS_SET_AGC = 2`

Set preprocessor Automatic Gain Control state

3.89.1.31 `const int SPEEX_PREPROCESS_SET_AGC_DECREMENT = 28`

Set maximal gain decrease in dB/second (int32)

3.89.1.32 `const int SPEEX_PREPROCESS_SET_AGC_INCREMENT = 26`

Set maximal gain increase in dB/second (int32)

3.89.1.33 `const int SPEEX_PREPROCESS_SET_AGC_LEVEL = 6`

Set preprocessor Automatic Gain Control level (float)

3.89.1.34 `const int SPEEX_PREPROCESS_SET_AGC_MAX_GAIN = 30`

Set maximal gain in dB (int32)

3.89.1.35 `const int SPEEX_PREPROCESS_SET_AGC_TARGET = 46`

Set preprocessor Automatic Gain Control level (int32)

3.89.1.36 `const int SPEEX_PREPROCESS_SET_DENOISE = 0`

Set preprocessor denoiser state

3.89.1.37 `const int SPEEX_PREPROCESS_SET_DEREVERB = 8`

Set preprocessor dereverb state

3.89.1.38 `const int SPEEX_PREPROCESS_SET_DEREVERB_DECAY = 12`

Set preprocessor dereverb decay

3.89.1.39 `const int SPEEX_PREPROCESS_SET_DEREVERB_LEVEL = 10`

Set preprocessor dereverb level

3.89.1.40 `const int SPEEX_PREPROCESS_SET_ECHO_STATE = 24`

Set the corresponding echo canceller state so that residual echo suppression can be performed (NULL for no residual echo suppression)

3.89.1.41 `const int SPEEX_PREPROCESS_SET_ECHO_SUPPRESS = 20`

Set maximum attenuation of the residual echo in dB (negative number)

3.89.1.42 `const int SPEEX_PREPROCESS_SET_ECHO_SUPPRESS_ACTIVE = 22`

Set maximum attenuation of the residual echo in dB when near end is active (negative number)

3.89.1.43 `const int SPEEX_PREPROCESS_SET_NOISE_SUPPRESS = 18`

Set maximum attenuation of the noise in dB (negative number)

3.89.1.44 `const int SPEEX_PREPROCESS_SET_PROB_CONTINUE = 16`

Set probability required for the VAD to stay in the voice state (integer percent)

3.89.1.45 `const int SPEEX_PREPROCESS_SET_PROB_START = 14`

Set probability required for the VAD to go from silence to voice

3.89.1.46 `const int SPEEX_PREPROCESS_SET_VAD = 4`

Set preprocessor [Voice](#) Activity Detection state

3.90 SpeexProcessor Class Reference

Inherits [SpeexLib](#), and [IProcessor< T >](#).

Classes

- struct [AECLatencyResultType](#)

Public Member Functions

- void **ResetAEC** ()
- void **AECLatencyDetectCaliberate** ()
- **SpeexProcessor** ([ILogger](#) logger, Func< long > clockMs, int frameSize, int samplingRate, int channels, int playSamplingRate, int playChannels, int playBufSize)
- void **InitAEC** ()
- short[] **Process** (short[] buf)
- void **OnAudioOutFrame** (float[] data, int outChannels)
- void **PrintInfo** ()
- void **Dispose** ()

Properties

- bool **AEC** [get, set]
- int **AECFilterLengthMs** [get, set]
- int **AECPlaybackDelayMs** [get, set]
- int **AECCurrentPlayDelayFrames** [get]
- bool **AECLatencyDetect** [get, set]
- [AECLatencyResultType](#) **AECLatencyResult** [get]
- bool **Denoise** [get, set]
- bool **AGC** [get, set]
- float **AGCLevel** [get, set]

Additional Inherited Members

3.91 TestTone Class Reference

Inherits [MonoBehaviour](#).

3.92 AudioUtil.ToneAudioPusher< T > Class Template Reference

[IAudioPusher](#) that provides a constant tone signal.

Inherits [IAudioPusher< T >](#).

Public Member Functions

- [ToneAudioPusher](#) (int frequency=440, int bufSizeMs=100, int samplingRate=441000, int channels=2)
Create a new [ToneAudioReader](#) instance
- void [SetCallback](#) (Action< T[]> callback, [ObjectFactory](#)< T[], int > bufferFactory)
Set the callback function used for pushing data
- void **Dispose** ()

Properties

- int **Channels** [get]
- int **SamplingRate** [get]
- string **Error** [get]

3.92.1 Detailed Description

[IAudioPusher](#) that provides a constant tone signal.

3.92.2 Constructor & Destructor Documentation

3.92.2.1 ToneAudioPusher (int *frequency* = 440, int *bufSizeMs* = 100, int *samplingRate* = 441000, int *channels* = 2)

Create a new [ToneAudioReader](#) instance

Parameters

<i>frequency</i>	Frequency of the generated tone (in Hz).
<i>bufSizeMs</i>	Size of buffers to push (in milliseconds).
<i>samplingRate</i>	Sampling rate of the audio signal (in Hz).
<i>channels</i>	Number of channels in the audio signal.

3.92.3 Member Function Documentation

3.92.3.1 void SetCallback (Action< T[] > *callback*, ObjectFactory< T[], int > *bufferFactory*)

Set the callback function used for pushing data

Parameters

<i>callback</i>	Callback function to use
<i>localVoice</i>	Outgoing audio stream, for context

Implements [IAudioPusher< T >](#).

3.93 AudioUtil.ToneAudioReader< T > Class Template Reference

[IAudioReader](#) that provides a constant tone signal.

Inherits [IAudioReader< T >](#).

Public Member Functions

- [ToneAudioReader](#) (Func< double > clockSec=null, double frequency=440, int samplingRate=441000, int channels=2)

Create a new [ToneAudioReader](#) instance

- void **Dispose** ()
- bool [Read](#) (T[] buf)

Fill full given frame buffer with source uncompressed data or return false if not enough such data.

Properties

- int [Channels](#) [get]
Number of channels in the audio signal.
- int [SamplingRate](#) [get]
Sampling rate of the audio signal (in Hz).
- string [Error](#) [get]
If not null, audio object is in invalid state.

3.93.1 Detailed Description

[IAudioReader](#) that provides a constant tone signal.

See also [MicWrapper](#) and [AudioClipWrapper](#) Because of current resampling algorithm, the tone is distorted if `SamplingRate` does not equal encoder sampling rate.

3.93.2 Constructor & Destructor Documentation

3.93.2.1 `ToneAudioReader (Func< double > clockSec = null, double frequency = 440, int samplingRate = 441000, int channels = 2)`

Create a new [ToneAudioReader](#) instance

Parameters

<i>clockSec</i>	Function to get current time in seconds. In Unity , pass in '()' => <code>AudioSettings.dspTime</code> for better results.
<i>frequency</i>	Frequency of the generated tone (in Hz).
<i>samplingRate</i>	Sampling rate of the audio signal (in Hz).
<i>channels</i>	Number of channels in the audio signal.

3.93.3 Member Function Documentation

3.93.3.1 `bool Read (T[] buffer)`

Fill full given frame buffer with source uncompressed data or return false if not enough such data.

Parameters

<i>buffer</i>	Buffer to fill.
---------------	-----------------

Returns

True if buffer was filled successfully, false otherwise.

Implements [IDataReader< T >](#).

3.93.4 Property Documentation

3.93.4.1 `int Channels [get]`

Number of channels in the audio signal.

3.93.4.2 `string Error [get]`

If not null, audio object is in invalid state.

3.93.4.3 `int SamplingRate [get]`

Sampling rate of the audio signal (in Hz).

3.94 ToneAudioReader Class Reference

Inherits [IAudioReader< T >](#).

Public Member Functions

- void **Dispose** ()
- bool **Read** (float[] buf)

Properties

- int **Channels** [get]
- int **SamplingRate** [get]
- string **Error** [get]

3.95 UnityAndroidAudioInAEC Class Reference

Inherits [IAudioPusher< T >](#).

Public Member Functions

- **UnityAndroidAudioInAEC** ([Voice.ILogger](#) logger)
- void **SetCallback** (Action< short[]> callback, [ObjectFactory](#)< short[], int > bufferFactory)
- void **Dispose** ()

Properties

- int **Channels** [get]
- int **SamplingRate** [get]
- string **Error** [get]

3.96 UnityAudioOut Class Reference

Inherits [ISyncAudioOut](#).

Public Member Functions

- **UnityAudioOut** (AudioSource audioSource)
- void **Start** (int frequency, int channels, int frameSamples, int playDelayMs)
- void **Service** ()
- void **Push** (float[] frame)
- void **Stop** ()
- void **Pause** ()
- void **UnPause** ()

Public Attributes

- const int **FRAME_POOL_CAPACITY** = 50

Properties

- int **Lag** [get]
- int **PlaySamplePos** [get, set]
- bool **IsPlaying** [get]

3.97 UnsupportedCodecException Class Reference

Exception thrown if an unsupported codec is encountered.

Inherits Exception.

Public Member Functions

- [UnsupportedCodecException](#) (string info, [Codec](#) codec, [ILogger](#) logger)

Create a new [UnsupportedCodecException](#).

3.97.1 Detailed Description

Exception thrown if an unsupported codec is encountered.

PhotonVoice currently only supports one Codec, [Codec.AudioOpus](#).

3.97.2 Constructor & Destructor Documentation

3.97.2.1 UnsupportedCodecException (string info, Codec codec, ILogger logger)

Create a new [UnsupportedCodecException](#).

Parameters

<i>info</i>	The info prepending standard message.
<i>codec</i>	The codec actually encountered.
<i>logger</i>	Loogger.

3.98 UnsupportedSampleTypeException Class Reference

Exception thrown if an unsupported audio sample type is encountered.

Inherits Exception.

Public Member Functions

- [UnsupportedSampleTypeException](#) (Type t)

Create a new [UnsupportedSampleTypeException](#).

3.98.1 Detailed Description

Exception thrown if an unsupported audio sample type is encountered.

PhotonVoice generally supports 32-bit floating point ("float") or 16-bit signed integer ("short") audio, but it usually won't be converted automatically due to the high CPU overhead (and potential loss of precision) involved.

3.98.2 Constructor & Destructor Documentation

3.98.2.1 UnsupportedSampleTypeException (Type t)

Create a new [UnsupportedSampleTypeException](#).

Parameters

<i>t</i>	The sample type actually encountered.
----------	---------------------------------------

3.99 OpusCodec.Util Class Reference

3.100 VoiceClient Class Reference

Base class for [Voice](#) clients implamantations

Inherits [IDisposable](#).

Public Member Functions

- delegate void [RemoteVoiceInfoDelegate](#) (int channelId, int playerId, byte voiceId, [VoiceInfo](#) voiceInfo, ref [RemoteVoiceOptions](#) options)
Remote voice info event delegate.
- IEnumerable< [LocalVoice](#) > [LocalVoicesInChannel](#) (int channelId)
Iterates through copy of all local voices list of given channel.
- void [Service](#) ()
This method dispatches all available incoming commands and then sends this client's outgoing commands. Call this method regularly (2..20 times a second).
- [LocalVoice](#) [CreateLocalVoice](#) ([VoiceInfo](#) voiceInfo, int channelId=ChannelAuto, [IEncoder](#) encoder=null)
Creates basic outgoing stream w/o data processing support. Provided encoder should generate output data stream.
- [LocalVoiceFramed](#)< T > [CreateLocalVoiceFramed](#)< T > ([VoiceInfo](#) voiceInfo, int frameSize, int channelId↔Id=ChannelAuto, [IEncoderDataFlow](#)< T > encoder=null)
Creates outgoing stream consuming sequence of values passed in array buffers of arbitrary length which repacked in frames of constant length for further processing and encoding.
- [LocalVoiceAudio](#)< T > [CreateLocalVoiceAudio](#)< T > ([VoiceInfo](#) voiceInfo, int channelId=ChannelAuto, [I↔Encoder](#) encoder=null)
Creates outgoing audio stream. Adds audio specific features (e.g. resampling, level meter) to processing pipeline and to returning stream handler.
- [Voice.LocalVoice](#) [CreateLocalVoiceAudioFromSource](#) ([Voice.VoiceInfo](#) voiceInfo, [Voice.IAudioDesc](#) source, bool forceShort=false, int channelId=ChannelAuto, [IEncoder](#) encoder=null)
Creates outgoing audio stream of type automatically assigned and adds procedures (callback or serviceable) for consuming given audio source data. Adds audio specific features (e.g. resampling, level meter) to processing pipeline and to returning stream handler.
- void [RemoveLocalVoice](#) ([LocalVoice](#) voice)
Removes local voice (outgoing data stream).
Parameters

voice	Handler of outgoing stream to be removed.
-------	---
- void **Dispose** ()

Public Attributes

- const int **ChannelAuto** = -1

Properties

- `int FramesLost` [get, set]
Lost frames counter.
- `int FramesReceived` [get]
Received frames counter.
- `int FramesSent` [get]
Sent frames counter.
- `int FramesSentBytes` [get]
Sent frames bytes counter.
- `int RoundTripTime` [get]
Average time required voice packet to return to sender.
- `int RoundTripTimeVariance` [get]
Average round trip time variation.
- `bool SuppressInfoDuplicateWarning` [get, set]
Do not log warning when duplicate info received.
- `RemoteVoiceInfoDelegate OnRemoteVoiceInfoAction` [get, set]
Register a method to be called when remote voice info arrived (after join or new new remote voice creation). Method parameters: (int channelId, int playerId, byte voiceId, [VoiceInfo](#) voiceInfo, ref [RemoteVoiceOptions](#) options);
- `int DebugLostPercent` [get, set]
Lost frames simulation ratio.
- `IEnumerable< LocalVoice > LocalVoices` [get]
Iterates through copy of all local voices list.
- `IEnumerable< RemoteVoiceInfo > RemoteVoiceInfos` [get]
Iterates through all remote voices infos.

3.100.1 Detailed Description

Base class for [Voice](#) clients implamantations

3.100.2 Member Function Documentation

3.100.2.1 `LocalVoice CreateLocalVoice (VoiceInfo voiceInfo, int channelId = ChannelAuto, IEncoder encoder = null)`

Creates basic outgoing stream w/o data processing support. Provided encoder should generate output data stream.

Parameters

<i>voiceInfo</i>	Outgoing stream parameters. Set applicable fields to read them by encoder and by receiving client when voice created.
<i>channelId</i>	Transport channel specific to transport. Set to <code>VoiceClient.ChannelAuto</code> to let transport automatically assign channel.
<i>encoder</i>	Encoder producing the stream.

Returns

Outgoing stream handler.

3.100.2.2 `LocalVoiceAudio<T> CreateLocalVoiceAudio< T > (VoiceInfo voiceInfo, int channelId = ChannelAuto, IEncoder encoder = null)`

Creates outgoing audio stream. Adds audio specific features (e.g. resampling, level meter) to processing pipeline and to returning stream handler.

Template Parameters

<i>T</i>	Element type of audio array buffers.
----------	--------------------------------------

Parameters

<i>voiceInfo</i>	Outgoing audio stream parameters. Set applicable fields to read them by encoder and by receiving client when voice created.
<i>channelId</i>	Transport channel specific to transport. Set to VoiceClient.ChannelAuto to let transport automatically assign channel.
<i>encoder</i>	Audio encoder. Set to null to use default Opus encoder.

Returns

Outgoing stream handler.

voiceInfo.sourceSamplingRate and *voiceInfo.SamplingRate* may do not match. Automatic resampling will occur in this case.

3.100.2.3 Voice.LocalVoice CreateLocalVoiceAudioFromSource (Voice.VoiceInfo *voiceInfo*, Voice.IAudioDesc *source*, bool *forceShort* = false, int *channelId* = ChannelAuto, IEncoder *encoder* = null)

Creates outgoing audio stream of type automatically assigned and adds procedures (callback or serviceable) for consuming given audio source data. Adds audio specific features (e.g. resampling, level meter) to processing pipeline and to returning stream handler.

Parameters

<i>voiceInfo</i>	Outgoing audio stream parameters. Set applicable fields to read them by encoder and by receiving client when voice created.
<i>source</i>	Streaming audio source.
<i>forceShort</i>	For audio sources producing buffers of 'float' type, creates stream of 'short' type and adds converter.
<i>channelId</i>	Transport channel specific to transport. Set to VoiceClient.ChannelAuto to let transport automatically assign channel.
<i>encoder</i>	Audio encoder. Set to null to use default Opus encoder.

Returns

Outgoing stream handler.

voiceInfo.sourceSamplingRate and *voiceInfo.SamplingRate* may do not match. Automatic resampling will occur in this case.

3.100.2.4 LocalVoiceFramed<T> CreateLocalVoiceFramed< T > (VoiceInfo *voiceInfo*, int *frameSize*, int *channelId* = ChannelAuto, IEncoderDataFlow< T > *encoder* = null)

Creates outgoing stream consuming sequence of values passed in array buffers of arbitrary length which repacked in frames of constant length for further processing and encoding.

Template Parameters

<i>T</i>	Type of data consumed by outgoing stream (element type of array buffers).
----------	---

Parameters

<i>voiceInfo</i>	Outgoing stream parameters. Set applicable fields to read them by encoder and by receiving client when voice created.
<i>channelId</i>	Transport channel specific to transport. Set to VoiceClient.ChannelAuto to let transport automatically assign channel.
<i>encoder</i>	Encoder compressing data stream in pipeline.

Returns

Outgoing stream handler.

3.100.2.5 IEnumerable<LocalVoice> LocalVoicesInChannel (int channelId)

Iterates through copy of all local voices list of given channel.

3.100.2.6 delegate void RemoteVoiceInfoDelegate (int channelId, int playerId, byte voiceId, VoiceInfo voiceInfo, ref RemoteVoiceOptions options)

Remote voice info event delegate.

3.100.2.7 void RemoveLocalVoice (LocalVoice voice)

Removes local voice (outgoing data stream).

Parameters

<i>voice</i>	Handler of outgoing stream to be removed.
--------------	---

3.100.2.8 void Service ()

This method dispatches all available incoming commands and then sends this client's outgoing commands. Call this method regularly (2..20 times a second).

3.100.3 Property Documentation

3.100.3.1 int DebugLostPercent [get], [set]

Lost frames simulation ratio.

3.100.3.2 int FramesLost [get], [set]

Lost frames counter.

3.100.3.3 int FramesReceived [get]

Received frames counter.

3.100.3.4 int FramesSent [get]

Sent frames counter.

3.100.3.5 `int FramesSentBytes` `[get]`

Sent frames bytes counter.

3.100.3.6 `IEnumerable<LocalVoice> LocalVoices` `[get]`

Iterates through copy of all local voices list.

3.100.3.7 `RemoteVoiceInfoDelegate OnRemoteVoiceInfoAction` `[get], [set]`

Register a method to be called when remote voice info arrived (after join or new new remote voice creation). Metod parameters: (int channelId, int playerId, byte voiceId, [VoiceInfo](#) voiceInfo, ref [RemoteVoiceOptions](#) options);

3.100.3.8 `IEnumerable<RemoteVoiceInfo> RemoteVoiceInfos` `[get]`

Iterates through all remote voices infos.

3.100.3.9 `int RoundTripTime` `[get]`

Average time required voice packet to return to sender.

3.100.3.10 `int RoundTripTimeVariance` `[get]`

Average round trip time variation.

3.100.3.11 `bool SuppressInfoDuplicateWarning` `[get], [set]`

Do not log warning when duplicate info received.

3.101 VoiceComponent Class Reference

Inherits [MonoBehaviour](#), and [ILoggable](#).

Inherited by [PhotonVoiceView](#), [Recorder](#), [Speaker](#), and [WebRtcAudioDsp](#).

Protected Member Functions

- virtual void **Awake** ()

Protected Attributes

- DebugLevel **LogLevel** = DebugLevel.ERROR

Properties

- [VoiceLogger](#) **Logger** `[get, protected set]`
- DebugLevel **LogLevel** `[get, set]`

3.102 VoiceConnection Class Reference

Component that represents a client voice connection to [Photon](#) Servers.

Inherits [ConnectionHandler](#), and [ILoggable](#).

Inherited by [PhotonVoiceNetwork](#).

Public Member Functions

- bool [ConnectUsingSettings](#) (AppSettings overwriteSettings=null)
Connect to [Photon](#) server using [Settings](#)

Public Attributes

- AppSettings [Settings](#)
Settings to be used by this voice connection
- [Recorder](#) [PrimaryRecorder](#)
Main [Recorder](#) to be used for transmission by default
- Func< int, byte, object, [Speaker](#) > [SpeakerFactory](#)
Special factory to link [Speaker](#) components with incoming remote audio streams

Protected Member Functions

- override void **Awake** ()
- virtual void **Update** ()
- virtual void **FixedUpdate** ()
- override void **OnDestroy** ()
- virtual void **OnVoiceStateChanged** ([ClientState](#) fromState, [ClientState](#) toState)
- override void **OnApplicationQuit** ()
- void **CalcStatistics** ()
- void **LinkSpeaker** ([Speaker](#) speaker, [RemoteVoiceLink](#) remoteVoice)

Protected Attributes

- List< [RemoteVoiceLink](#) > **cachedRemoteVoices** = new List<[RemoteVoiceLink](#)>()

Properties

- [VoiceLogger](#) [Logger](#) [get, protected set]
[Logger](#) used by this component
- DebugLevel [LogLevel](#) [get, set]
Log level for this component
- new [LoadBalancingTransport](#) **Client** [get]
- [VoiceClient](#) [VoiceClient](#) [get]
Returns underlying [Photon Voice](#) client.
- ClientState [ClientState](#) [get]
Returns [Photon Voice](#) client state.
- float [FramesReceivedPerSecond](#) [get]
Number of frames received per second.
- float [FramesLostPerSecond](#) [get]

- *Number of frames lost per second.*
float [FramesLostPercent](#) [get]
- *Percentage of lost frames.*
GameObject [SpeakerPrefab](#) [get, set]
Prefab that contains [Speaker](#) component to be instantiated when receiving a new remote audio source info

Events

- Action< [Speaker](#) > [SpeakerLinked](#)
Fires when a speaker has been linked to a remote audio stream
- Action< [RemoteVoiceLink](#) > [RemoteVoiceAdded](#)
Fires when a remote voice stream is added

3.102.1 Detailed Description

Component that represents a client voice connection to [Photon](#) Servers.

3.102.2 Member Function Documentation

3.102.2.1 bool ConnectUsingSettings (AppSettings *overwriteSettings* = null)

Connect to [Photon](#) server using [Settings](#)

Parameters

<i>overwriteSettings</i>	Overwrites Settings before connecting
--------------------------	---

Returns

If true voice connection command was sent from client

3.102.3 Member Data Documentation

3.102.3.1 Recorder PrimaryRecorder

Main [Recorder](#) to be used for transmission by default

3.102.3.2 AppSettings Settings

Settings to be used by this voice connection

3.102.3.3 Func<int, byte, object, Speaker> SpeakerFactory

Special factory to link [Speaker](#) components with incoming remote audio streams

3.102.4 Property Documentation

3.102.4.1 ClientState ClientState [get]

Returns [Photon Voice](#) client state.

3.102.4.2 float FramesLostPercent [get]

Percentage of lost frames.

3.102.4.3 float FramesLostPerSecond [get]

Number of frames lost per second.

3.102.4.4 float FramesReceivedPerSecond [get]

Number of frames received per second.

3.102.4.5 VoiceLogger Logger [get], [protected set]

[Logger](#) used by this component

3.102.4.6 DebugLevel LogLevel [get], [set]

Log level for this component

3.102.4.7 GameObject SpeakerPrefab [get], [set]

Prefab that contains [Speaker](#) component to be instantiated when receiving a new remote audio source info

3.102.4.8 VoiceClient VoiceClient [get]

Returns underlying [Photon Voice](#) client.

3.102.5 Event Documentation

3.102.5.1 Action<RemoteVoiceLink> RemoteVoiceAdded

Fires when a remote voice stream is added

3.102.5.2 Action<Speaker> SpeakerLinked

Fires when a speaker has been linked to a remote audio stream

3.103 AudioUtil.VoiceDetector< T > Class Template Reference

Simple voice activity detector triggered by signal level.

Inherits [IProcessor< T >](#), and [AudioUtil.IVoiceDetector](#).

Inherited by [AudioUtil.VoiceDetectorFloat](#), and [AudioUtil.VoiceDetectorShort](#).

Public Member Functions

- abstract T[] [Process](#) (T[] buf)
Process a frame of audio data.
- void **Dispose** ()

Protected Attributes

- int **activityDelay**
- int **autoSilenceCounter** = 0
- int **valuesCountPerSec**
- int **activityDelayValuesCount**

Properties

- bool **On** [get, set]
If true, voice detection enabled.
- float **Threshold** [get, set]
Voice detected as soon as signal level exceeds threshold.
- bool **Detected** [get, protected set]
If true, voice detected.
- DateTime **DetectedTime** [get]
Last time when switched to detected state.
- int **ActivityDelayMs** [get, set]
Keep detected state during this time after signal level dropped below threshold.

Events

- Action **OnDetected**
Called when switched to detected state.

3.103.1 Detailed Description

Simple voice activity detector triggered by signal level.

3.103.2 Member Function Documentation

3.103.2.1 abstract T[] Process (T[] buf) [pure virtual]

Process a frame of audio data.

Parameters

<i>buf</i>	Buffer containing input audio data
------------	------------------------------------

Returns

Buffer containing output audio data

Implements [IProcessor< T >](#).

3.103.3 Property Documentation

3.103.3.1 int ActivityDelayMs [get], [set]

Keep detected state during this time after signal level dropped below threshold.

3.103.3.2 bool Detected [get], [protected set]

If true, voice detected.

3.103.3.3 DateTime DetectedTime [get]

Last time when switched to detected state.

3.103.3.4 bool On [get], [set]

If true, voice detection enabled.

3.103.3.5 float Threshold [get], [set]

Voice detected as soon as signal level exceeds threshold.

3.103.4 Event Documentation

3.103.4.1 Action OnDetected

Called when switched to detected state.

3.104 AudioUtil.VoiceDetectorCalibration< T > Class Template Reference

Calibration Utility for Voice Detector

Inherits [IProcessor< T >](#).

Public Member Functions

- [VoiceDetectorCalibration](#) ([IVoiceDetector](#) voiceDetector, [ILevelMeter](#) levelMeter, int samplingRate, int channels)
Create new VoiceDetectorCalibration instance.
- void [Calibrate](#) (int durationMs)
Start calibration.
- T[] [Process](#) (T[] buf)
Process a frame of audio data.
- void **Dispose** ()

Protected Attributes

- int **calibrateCount**

Properties

- bool **IsCalibrating** [get]

3.104.1 Detailed Description

Calibration Utility for [Voice](#) Detector

Using this audio processor, you can calibrate the [IVoiceDetector.Threshold](#).

3.104.2 Constructor & Destructor Documentation

3.104.2.1 VoiceDetectorCalibration ([IVoiceDetector](#) *voiceDetector*, [ILevelMeter](#) *levelMeter*, int *samplingRate*, int *channels*)

Create new [VoiceDetectorCalibration](#) instance.

Parameters

<i>voiceDetector</i>	Voice Detector to calibrate.
<i>levelMeter</i>	Level Meter to look at for calibration.
<i>samplingRate</i>	Sampling rate of the audio signal (in Hz).
<i>numChannels</i>	Number of channels in the audio signal.

3.104.3 Member Function Documentation

3.104.3.1 void Calibrate (int *durationMs*)

Start calibration.

Parameters

<i>durationMs</i>	Duration of the calibration procedure (in milliseconds).
-------------------	--

This activates the Calibration process. It will reset the given [LevelMeter](#)'s AccumAvgPeakAmp (accumulated average peak amplitude), and when the duration has passed, use it for the [VoiceDetector](#)'s detection threshold.

3.104.3.2 T[] Process (T[] *buf*)

Process a frame of audio data.

Parameters

<i>buf</i>	Buffer containing input audio data
------------	------------------------------------

Returns

Buffer containing output audio data

Implements [IProcessor< T >](#).

3.105 AudioUtil.VoiceDetectorDummy Class Reference

Dummy [VoiceDetector](#) that doesn't actually do anything.

Inherits [AudioUtil.IVoiceDetector](#).

Properties

- bool **On** [get, set]

- float **Threshold** [get, set]
- bool **Detected** [get]
- int **ActivityDelayMs** [get, set]
- DateTime **DetectedTime** [get]
- Action **OnDetected**

Additional Inherited Members

3.105.1 Detailed Description

Dummy [VoiceDetector](#) that doesn't actually do anything.

3.106 AudioUtil.VoiceDetectorFloat Class Reference

[VoiceDetector](#) specialization for float audio.

Inherits [AudioUtil.VoiceDetector< T >](#).

Public Member Functions

- [VoiceDetectorFloat](#) (int samplingRate, int numChannels)
Create a new [VoiceDetectorFloat](#) instance.
- override float[] **Process** (float[] buffer)

Additional Inherited Members

3.106.1 Detailed Description

[VoiceDetector](#) specialization for float audio.

3.106.2 Constructor & Destructor Documentation

3.106.2.1 VoiceDetectorFloat (int samplingRate, int numChannels)

Create a new [VoiceDetectorFloat](#) instance.

Parameters

<i>samplingRate</i>	Sampling rate of the audio signal (in Hz).
<i>numChannels</i>	Number of channels in the audio signal.

3.107 AudioUtil.VoiceDetectorShort Class Reference

[VoiceDetector](#) specialization for float audio.

Inherits [AudioUtil.VoiceDetector< T >](#).

Public Member Functions

- [VoiceDetectorShort](#) (int samplingRate, int numChannels)
Create a new [VoiceDetectorFloat](#) instance
- override short[] **Process** (short[] buffer)

Additional Inherited Members

3.107.1 Detailed Description

[VoiceDetector](#) specialization for float audio.

3.107.2 Constructor & Destructor Documentation

3.107.2.1 VoiceDetectorShort (int *samplingRate*, int *numChannels*)

Create a new [VoiceDetectorFloat](#) instance

Parameters

<i>samplingRate</i>	Sampling rate of the audio signal (in Hz).
<i>numChannels</i>	Number of channels in the audio signal.

3.108 VoiceEventCode Class Reference

PhotonVoice communication uses a single type of event, but differentiates transmission Channels by encoding a channelId into [VoiceEventCode](#).

Static Public Member Functions

- static byte [GetCode](#) (int channelId)
Get the event code for the given channel ID.
- static bool [TryGetChannelID](#) (byte evCode, int maxChannels, out byte channelId)
Try to get the channel ID for the given event code.

Public Attributes

- const byte [Code0](#) = 201
Start of voice event codes range.

3.108.1 Detailed Description

PhotonVoice communication uses a single type of event, but differentiates transmission Channels by encoding a channelId into [VoiceEventCode](#).

Transmission Channels are not for selective forwarding: use InterestGroups for that. Instead, they are to differentiate opus audio from (future) other codecs or media.

For this purpose, a range of event codes of length LoadBalancingPeer.ChannelCount, starting from Code0, is used.

3.108.2 Member Function Documentation

3.108.2.1 `static byte GetCode (int channelID) [static]`

Get the event code for the given channel ID.

Parameters

<i>channelID</i>	Channel ID to get event code for.
------------------	-----------------------------------

Returns

The corresponding event code.

3.108.2.2 `static bool TryGetChannelID (byte evCode, int maxChannels, out byte channelID) [static]`

Try to get the channel ID for the given event code.

Parameters

<i>evCode</i>	Event code to find Channel ID from.
<i>maxChannels</i>	Maximum Channel ID in use.
<i>channelID</i>	(output) Channel ID found.

Returns

True if a valid channel ID could be recovered from evCode, false otherwise.

3.108.3 Member Data Documentation

3.108.3.1 `const byte Code0 = 201`

Start of voice event codes range.

Change if it conflicts with other event codes used in the same [Photon](#) room.

3.109 VoicelInfo Struct Reference

Describes stream properties.

Public Member Functions

- override string **ToString** ()

Static Public Member Functions

- static [VoicelInfo CreateAudioOpus](#) (POpusCodec.Enums.SamplingRate samplingRate, int sourceSamplingRate, int channels, OpusCodec.FrameDuration frameDurationUs, int bitrate, object userdata=null)
Create stream info for an Opus audio stream.

Properties

- [Codec](#) **Codec** [get, set]
- int [SamplingRate](#) [get, set]
Audio sampling rate (frequency, in Hz).
- int [SourceSamplingRate](#) [get, set]
Source audio sampling rate (to be resampled to SamplingRate; in Hz).
- int [Channels](#) [get, set]

- Number of channels.
 - int [FrameDurationUs](#) [get, set]
Uncompressed frame (audio packet) size in microseconds.
 - int [Bitrate](#) [get, set]
Target bitrate (in bits/second).
 - object [UserData](#) [get, set]
Optional user data. Should be serializable by [Photon](#).
 - int [FrameDurationSamples](#) [get]
Uncompressed frame (data packet) size in samples.
 - int [FrameSize](#) [get]
Uncompressed frame (data packet) size in samples.
 - int [Width](#) [get, set]
Video width (optional).
 - int [Height](#) [get, set]
Video height (optional)

3.109.1 Detailed Description

Describes stream properties.

3.109.2 Member Function Documentation

- 3.109.2.1 `static VoiceInfo CreateAudioOpus (POpusCodec.Enums.SamplingRate samplingRate, int sourceSamplingRate, int channels, OpusCodec.FrameDuration frameDurationUs, int bitrate, object userdata = null) [static]`

Create stream info for an Opus audio stream.

Parameters

<i>samplingRate</i>	Audio sampling rate.
<i>sourceSamplingRate</i>	Source audio sampling rate (to be resampled to <i>samplingRate</i> ; in Hz).
<i>channels</i>	Number of channels.
<i>frameDurationUs</i>	Uncompressed frame (audio packet) size in microseconds.
<i>bitrate</i>	Stream bitrate (in bits/second).
<i>userdata</i>	Optional user data. Should be serializable by Photon .

Returns

[VoiceInfo](#) instance.

3.109.3 Property Documentation

- 3.109.3.1 `int Bitrate` [get], [set]

Target bitrate (in bits/second).

- 3.109.3.2 `int Channels` [get], [set]

Number of channels.

3.109.3.3 int FrameDurationSamples [get]

Uncompressed frame (data packet) size in samples.

3.109.3.4 int FrameDurationUs [get], [set]

Uncompressed frame (audio packet) size in microseconds.

3.109.3.5 int FrameSize [get]

Uncompressed frame (data packet) size in samples.

3.109.3.6 int Height [get], [set]

Video height (optional)

3.109.3.7 int SamplingRate [get], [set]

Audio sampling rate (frequency, in Hz).

3.109.3.8 int SourceSamplingRate [get], [set]

Source audio sampling rate (to be resampled to SamplingRate; in Hz).

3.109.3.9 object UserData [get], [set]

Optional user data. Should be serializable by [Photon](#).

3.109.3.10 int Width [get], [set]

Video width (optional).

3.110 AudioUtil.VoiceLevelDetectCalibrate< T > Class Template Reference

Utility Audio Processor [Voice](#) Detection Calibration.

Inherits [IProcessor< T >](#).

Public Member Functions

- [VoiceLevelDetectCalibrate](#) (int samplingRate, int channels)
Create new [VoiceLevelDetectCalibrate](#) instance
- void [Calibrate](#) (int durationMs)
Start calibration
- T[] [Process](#) (T[] buf)
Process a frame of audio data.
- void **Dispose** ()

Properties

- [ILevelMeter](#) [LevelMeter](#) [get]
The [LevelMeter](#) in use.
- [IVoiceDetector](#) [VoiceDetector](#) [get]
The [VoiceDetector](#) in use

3.110.1 Detailed Description

Utility Audio Processor [Voice](#) Detection Calibration.

Encapsulates level meter, voice detector and voice detector calibrator in single instance.

3.110.2 Constructor & Destructor Documentation

3.110.2.1 VoiceLevelDetectCalibrate (int *samplingRate*, int *channels*)

Create new [VoiceLevelDetectCalibrate](#) instance

Parameters

<i>samplingRate</i>	Sampling rate of the audio signal (in Hz).
<i>numChannels</i>	Number of channels in the audio signal.

3.110.3 Member Function Documentation

3.110.3.1 void Calibrate (int *durationMs*)

Start calibration

Parameters

<i>durationMs</i>	Duration of the calibration procedure (in milliseconds).
-------------------	--

This activates the Calibration process. It will reset the given [LevelMeter](#)'s AccumAvgPeakAmp (accumulated average peak amplitude), and when the duration has passed, use it for the [VoiceDetector](#)'s detection threshold.

3.110.3.2 T[] Process (T[] *buf*)

Process a frame of audio data.

Parameters

<i>buf</i>	Buffer containing input audio data
------------	------------------------------------

Returns

Buffer containing output audio data

Implements [IProcessor< T >](#).

3.110.4 Property Documentation

3.110.4.1 ILevelMeter LevelMeter [get]

The [LevelMeter](#) in use.

3.110.4.2 `IVoiceDetector VoiceDetector` [get]

The [VoiceDetector](#) in use

3.111 VoiceLogger Class Reference

Inherits [ILogger](#).

Public Member Functions

- **VoiceLogger** (Object context, string tag, DebugLevel level=DebugLevel.ERROR)
- **VoiceLogger** (string tag, DebugLevel level=DebugLevel.ERROR)
- void **LogError** (string fmt, params object[] args)
- void **LogWarning** (string fmt, params object[] args)
- void **LogInfo** (string fmt, params object[] args)
- void **LogDebug** (string fmt, params object[] args)

Properties

- string **Tag** [get, set]
- DebugLevel **LogLevel** [get, set]
- bool **IsErrorEnabled** [get]
- bool **IsWarningEnabled** [get]
- bool **IsInfoEnabled** [get]
- bool **IsDebugEnabled** [get]

3.112 WebRtcAudioDsp Class Reference

Inherits [VoiceComponent](#).

Protected Member Functions

- override void **Awake** ()

Properties

- bool **AEC** [get, set]
- bool **AECMobile** [get, set]
- int **ReverseStreamDelayMs** [get, set]
- bool **NoiseSuppression** [get, set]
- bool **HighPass** [get, set]
- bool **Bypass** [get, set]
- bool **AGC** [get, set]
- bool **VAD** [get, set]

Additional Inherited Members

3.113 WebRTCAudioLib Class Reference

Inherited by [WebRTCAudioProcessor](#).

Classes

- struct [ConfigParam](#)
- struct [Param](#)

Public Member Functions

- static IntPtr **webrtc_audio_processor_create** (int samplingRate, int channels, int frameSize, int rev←SamplingRate, int revChannels)
- static int **webrtc_audio_processor_set_config_param** (IntPtr proc, int param, int v)
- static int **webrtc_audio_processor_init** (IntPtr proc)
- static int **webrtc_audio_processor_set_param** (IntPtr proc, int param, int v)
- static int **webrtc_audio_processor_process** (IntPtr proc, short[] buffer, int offset, out bool voiceDetected)
- static int **webrtc_audio_processor_process_reverse** (IntPtr proc, short[] buffer, int bufferSize)
- static void **webrtc_audio_processor_destroy** (IntPtr proc)

3.114 WebRTCAudioProcessor Class Reference

Inherits [WebRTCAudioLib](#), and [IProcessor< T >](#).

Public Member Functions

- **WebRTCAudioProcessor** ([ILogger](#) logger, int frameSize, int samplingRate, int channels, int reverse←SamplingRate, int reverseChannels)
- short[] **Process** (short[] buf)
- void **OnAudioOutFrameFloat** (float[] data)
- void **Dispose** ()

Properties

- int **AECStreamDelayMs** [set]
- bool **AEC** [set]
- bool **AECMobile** [set]
- int **AECMRoutingMode** [set]
- bool **AECMComfortNoise** [set]
- bool **HighPass** [set]
- bool **NoiseSuppression** [set]
- bool **AGC** [set]
- bool **VAD** [set]
- bool **Bypass** [set]

Index

- AccumAvgPeakAmp
 - Photon::Voice::AudioUtil::ILevelMeter, [37](#)
 - AcquireOrCreate
 - Photon::Voice::ObjectPool, [59](#)
 - ActivityDelayMs
 - Photon::Voice::AudioUtil::IVoiceDetector, [42](#)
 - Photon::Voice::AudioUtil::VoiceDetector, [95](#)
 - Actor
 - Photon::Voice::Unity::Speaker, [76](#)
 - AddPostProcessor
 - Photon::Voice::LocalVoiceFramed, [55](#)
 - AddPreProcessor
 - Photon::Voice::LocalVoiceFramed, [55](#)
 - Audio
 - POpusCodec::Enums, [9](#)
 - AudioClip
 - Photon::Voice::Unity::Recorder, [70](#)
 - AudioClipWrapper, [11](#)
 - AudioDesc, [11](#)
 - AudioGroup
 - Photon::Voice::Unity::Recorder, [70](#)
 - AudioInEnumerator, [12](#)
 - AudioOpus
 - Photon::Voice, [6](#)
 - AudioOutCapture, [12](#)
 - AudioSessionParameters, [12](#)
 - AudioSessionParametersPresets, [13](#)
 - AudioStreamPlayer, [13](#)
 - AudioUtil, [13](#)
 - AudioUtil.ILevelMeter, [36](#)
 - AudioUtil.IVoiceDetector, [42](#)
 - AudioUtil.LevelMeter< T >, [43](#)
 - AudioUtil.LevelMeterDummy, [44](#)
 - AudioUtil.LevelMeterFloat, [45](#)
 - AudioUtil.LevelMeterShort, [45](#)
 - AudioUtil.Resampler< T >, [74](#)
 - AudioUtil.ToneAudioPusher< T >, [82](#)
 - AudioUtil.ToneAudioReader< T >, [83](#)
 - AudioUtil.VoiceDetector< T >, [94](#)
 - AudioUtil.VoiceDetectorCalibration< T >, [96](#)
 - AudioUtil.VoiceDetectorDummy, [97](#)
 - AudioUtil.VoiceDetectorFloat, [98](#)
 - AudioUtil.VoiceDetectorShort, [98](#)
 - AudioUtil.VoiceLevelDetectCalibrate< T >, [103](#)
- Auto
 - POpusCodec::Enums, [9](#)
 - AutoConnectAndJoin
 - Photon::Voice::PUN::PhotonVoiceNetwork, [64](#)
 - AutoCreateRecorderIfNotFound
 - Photon::Voice::PUN::PhotonVoiceView, [66](#)
 - AutoCreateSpeakerIfNotFound
 - Photon::Voice::PUN::PhotonVoiceNetwork, [64](#)
 - AutoLeaveAndDisconnect
 - Photon::Voice::PUN::PhotonVoiceNetwork, [64](#)
- Bandwidth
 - POpusCodec::Enums, [8](#)
 - Bitrate
 - Photon::Voice::Unity::Recorder, [70](#)
 - Photon::Voice::VoiceInfo, [102](#)
 - BufferReaderPushAdapter
 - Photon::Voice::BufferReaderPushAdapter, [17](#)
 - BufferReaderPushAdapter< T >, [17](#)
 - BufferReaderPushAdapterAsyncPool
 - Photon::Voice::BufferReaderPushAdapterAsync↔
Pool, [18](#)
 - BufferReaderPushAdapterAsyncPool< T >, [18](#)
 - BufferReaderPushAdapterAsyncPoolCopy
 - Photon::Voice::BufferReaderPushAdapterAsync↔
PoolCopy, [20](#)
 - BufferReaderPushAdapterAsyncPoolCopy< T >, [20](#)
 - BufferReaderPushAdapterAsyncPoolFloatToShort, [21](#)
 - Photon::Voice::BufferReaderPushAdapterAsync↔
PoolFloatToShort, [21](#)
 - BufferReaderPushAdapterBase
 - Photon::Voice::BufferReaderPushAdapterBase, [22](#)
 - BufferReaderPushAdapterBase< T >, [21](#)
- Calibrate
 - Photon::Voice::AudioUtil::VoiceDetectorCalibration, [97](#)
 - Photon::Voice::AudioUtil::VoiceLevelDetect↔
Calibrate, [104](#)
 - ChannelId
 - Photon::Voice::RemoteVoiceInfo, [72](#)
 - Channels
 - POpusCodec::Enums, [8](#)
 - Photon::Voice::AudioUtil::ToneAudioReader, [84](#)
 - Photon::Voice::IAudioDesc, [29](#)
 - Photon::Voice::VoiceInfo, [102](#)
 - ClearProcessors
 - Photon::Voice::LocalVoiceFramed, [56](#)
 - ClientState
 - Photon::Voice::Unity::VoiceConnection, [93](#)
 - Code0
 - Photon::Voice::VoiceEventCode, [101](#)
 - Codec
 - Photon::Voice, [6](#)
 - ConnectAndJoin, [23](#)

- ConnectAndJoinRoom
 - Photon::Voice::PUN::PhotonVoiceNetwork, [64](#)
- ConnectUsingSettings
 - Photon::Voice::Unity::VoiceConnection, [93](#)
- Convert
 - Photon::Voice::AudioUtil, [15](#)
- Count
 - Photon::Voice::Framer, [28](#)
- Create
 - Photon::Voice::LocalVoiceAudio, [52](#)
- CreateAudioOpus
 - Photon::Voice::VoiceInfo, [102](#)
- CreateLocalVoice
 - Photon::Voice::VoiceClient, [88](#)
- CreateLocalVoiceAudio< T >
 - Photon::Voice::VoiceClient, [88](#)
- CreateLocalVoiceAudioFromSource
 - Photon::Voice::VoiceClient, [89](#)
- CreateLocalVoiceFramed< T >
 - Photon::Voice::VoiceClient, [89](#)
- CurrentAvgAmp
 - Photon::Voice::AudioUtil::ILevelMeter, [37](#)
- CurrentPeakAmp
 - Photon::Voice::AudioUtil::ILevelMeter, [37](#)
- DebugEchoMode
 - Photon::Voice::LocalVoice, [50](#)
 - Photon::Voice::Unity::Recorder, [70](#)
- DebugLostPercent
 - Photon::Voice::VoiceClient, [90](#)
- Decode
 - Photon::Voice::IDecoderQueued, [33](#)
- DecodeToByte
 - Photon::Voice::IDecoderDirect, [32](#)
 - Photon::Voice::OpusCodec::Decoder, [24](#)
- DecodeToFloat
 - Photon::Voice::IDecoderDirect, [32](#)
 - Photon::Voice::OpusCodec::Decoder, [24](#)
- DecodeToShort
 - Photon::Voice::IDecoderDirect, [32](#)
 - Photon::Voice::OpusCodec::Decoder, [24](#)
- Decoder
 - Photon::Voice::RemoteVoiceOptions, [74](#)
- Delay
 - POpusCodec::Enums, [8](#)
- Delay10ms
 - POpusCodec::Enums, [8](#)
- Delay20ms
 - POpusCodec::Enums, [8](#)
- Delay2dot5ms
 - POpusCodec::Enums, [8](#)
- Delay40ms
 - POpusCodec::Enums, [8](#)
- Delay5ms
 - POpusCodec::Enums, [8](#)
- Delay60ms
 - POpusCodec::Enums, [8](#)
- Detected
 - Photon::Voice::AudioUtil::IVoiceDetector, [42](#)
 - Photon::Voice::AudioUtil::VoiceDetector, [95](#)
- DetectedTime
 - Photon::Voice::AudioUtil::IVoiceDetector, [42](#)
 - Photon::Voice::AudioUtil::VoiceDetector, [96](#)
- Disconnect
 - Photon::Voice::PUN::PhotonVoiceNetwork, [64](#)
- Dispose
 - Photon::Voice::BufferReaderPushAdapterBase, [22](#)
 - Photon::Voice::LoadBalancingTransport, [47](#)
 - Photon::Voice::LocalVoiceFramed, [56](#)
 - Photon::Voice::ObjectPool, [59](#)
- Dummy
 - Photon::Voice::LocalVoiceAudioDummy, [54](#)
- EncodeAndGetOutput
 - Photon::Voice::IEncoderDataFlowDirect, [35](#)
 - Photon::Voice::OpusCodec::Encoder, [25](#)
- EncoderDelay
 - POpusCodec::OpusEncoder, [61](#)
- Encrypt
 - Photon::Voice::LocalVoice, [50](#)
 - Photon::Voice::Unity::Recorder, [70](#)
- Error
 - Photon::Voice::AudioUtil::ToneAudioReader, [84](#)
 - Photon::Voice::IAudioDesc, [29](#)
 - Photon::Voice::IDecoder, [31](#)
 - Photon::Voice::IEncoder, [34](#)
- FactoryPrimitiveArrayPool< T >, [26](#)
- FactoryReusableArray< T >, [27](#)
- ForceToStereo< T >
 - Photon::Voice::AudioUtil, [15](#)
- Frame
 - Photon::Voice::Framer, [28](#)
- FrameDuration
 - Photon::Voice::Unity::Recorder, [70](#)
- FrameDurationSamples
 - Photon::Voice::VoiceInfo, [102](#)
- FrameDurationUs
 - Photon::Voice::VoiceInfo, [103](#)
- FrameSize
 - Photon::Voice::LocalVoiceFramedBase, [57](#)
 - Photon::Voice::VoiceInfo, [103](#)
- Framer
 - Photon::Voice::Framer, [28](#)
- Framer< T >, [27](#)
- FramesLost
 - Photon::Voice::VoiceClient, [90](#)
- FramesLostPerSecond
 - Photon::Voice::Unity::VoiceConnection, [94](#)
- FramesLostPercent
 - Photon::Voice::Unity::VoiceConnection, [93](#)
- FramesReceived
 - Photon::Voice::VoiceClient, [90](#)
- FramesReceivedPerSecond
 - Photon::Voice::Unity::VoiceConnection, [94](#)
- FramesSent
 - Photon::Voice::LocalVoice, [50](#)
 - Photon::Voice::VoiceClient, [90](#)

- FramesSentBytes
 - Photon::Voice::LocalVoice, [51](#)
 - Photon::Voice::VoiceClient, [90](#)
- Fullband
 - POpusCodec::Enums, [8](#)
- Game
 - Photon::Voice::IOS::AudioSessionParameters←Presets, [13](#)
- GetCode
 - Photon::Voice::VoiceEventCode, [100](#)
- GetOutput
 - Photon::Voice::IEncoderQueued, [36](#)
- GlobalInterestGroup
 - Photon::Voice::LoadBalancingTransport, [49](#)
- Height
 - Photon::Voice::VoiceInfo, [103](#)
- IAudioDesc, [28](#)
- IAudioOut, [29](#)
- IAudioPusher< T >, [29](#)
- IAudioReader< T >, [30](#)
- IDataReader< T >, [30](#)
- IDecoder, [31](#)
- IDecoderDirect, [32](#)
- IDecoderQueued, [33](#)
- IDecoderQueuedOutputImageNative, [33](#)
- IEncoder, [34](#)
- IEncoderDataFlow< T >, [34](#)
- IEncoderDataFlowDirect< T >, [34](#)
- IEncoderNativeImageDirect, [35](#)
- IEncoderQueued, [35](#)
- ILocalVoiceAudio, [37](#)
- ILoggable, [38](#)
- ILogger, [38](#)
- IOSAudioForceToSpeaker, [40](#)
- IProcessor< T >, [40](#)
- IServiceable, [41](#)
- ISyncAudioOut, [41](#)
- IVoiceTransport, [43](#)
- ImageBufferInfo, [38](#)
- ImageBufferNative, [39](#)
- ImageBufferNativeAlloc, [39](#)
- ImageBufferNativeGCHandleSinglePlane, [39](#)
- ImageBufferNativePool< T >, [40](#)
- Info
 - Photon::Voice::LocalVoice, [51](#)
 - Photon::Voice::ObjectPool, [60](#)
 - Photon::Voice::RemoteVoiceInfo, [72](#)
- Init
 - Photon::Voice::ObjectPool, [59](#)
 - Photon::Voice::Unity::Recorder, [69](#)
- InputFactory
 - Photon::Voice::Unity::Recorder, [70](#)
- Instance
 - Photon::Voice::PUN::PhotonVoiceNetwork, [64](#)
- InterestGroup
 - Photon::Voice::LocalVoice, [51](#)
- Photon::Voice::Unity::Recorder, [70](#)
- IsCurrentlyTransmitting
 - Photon::Voice::LocalVoice, [51](#)
 - Photon::Voice::Unity::Recorder, [70](#)
- IsInitialized
 - Photon::Voice::Unity::Recorder, [70](#)
- IsLinked
 - Photon::Voice::Unity::Speaker, [76](#)
- IsPlaying
 - Photon::Voice::Unity::Speaker, [76](#)
- IsRecorder
 - Photon::Voice::PUN::PhotonVoiceView, [66](#)
- IsRecording
 - Photon::Voice::PUN::PhotonVoiceView, [66](#)
- IsSetup
 - Photon::Voice::PUN::PhotonVoiceView, [66](#)
- IsSpeaker
 - Photon::Voice::PUN::PhotonVoiceView, [66](#)
- IsSpeaking
 - Photon::Voice::PUN::PhotonVoiceView, [66](#)
- Lag
 - Photon::Voice::Unity::Speaker, [76](#)
- LevelMeter
 - Photon::Voice::AudioUtil::VoiceLevelDetect←Calibrate, [104](#)
 - Photon::Voice::ILocalVoiceAudio, [38](#)
 - Photon::Voice::Unity::Recorder, [70](#)
- LevelMeterFloat
 - Photon::Voice::AudioUtil::LevelMeterFloat, [45](#)
- LevelMeterShort
 - Photon::Voice::AudioUtil::LevelMeterShort, [46](#)
- LoadBalancingFrontend, [46](#)
- LoadBalancingTransport, [46](#)
 - Photon::Voice::LoadBalancingTransport, [47](#)
- LocalUserServiceable
 - Photon::Voice::LocalVoice, [51](#)
- LocalVoice, [49](#)
- LocalVoiceAudio< T >, [51](#)
- LocalVoiceAudioDummy, [53](#)
- LocalVoiceAudioFloat, [54](#)
- LocalVoiceAudioShort, [54](#)
- LocalVoiceFramed< T >, [54](#)
- LocalVoiceFramedBase, [56](#)
- LocalVoices
 - Photon::Voice::VoiceClient, [91](#)
- LocalVoicesInChannel
 - Photon::Voice::VoiceClient, [90](#)
- LogLevel
 - Photon::Voice::Unity::VoiceConnection, [94](#)
- Logger, [57](#)
 - Photon::Voice::Unity::VoiceConnection, [94](#)
- LoopAudioClip
 - Photon::Voice::Unity::Recorder, [71](#)
- Mediumband
 - POpusCodec::Enums, [8](#)
- MicWrapper, [57](#)
- MicrophoneType

- Photon::Voice::Unity::Recorder, 71
- Mono
 - POpusCodec::Enums, 8
- Music
 - POpusCodec::Enums, 9
- Narrowband
 - POpusCodec::Enums, 8
- ObjectFactory< TType, TInfo >, 57
- ObjectPool
 - Photon::Voice::ObjectPool, 59
- ObjectPool< TType, TInfo >, 58
- On
 - Photon::Voice::AudioUtil::IVoiceDetector, 42
 - Photon::Voice::AudioUtil::VoiceDetector, 96
- OnDecodedFrameByteAction
 - Photon::Voice::RemoteVoiceOptions, 74
- OnDecodedFrameFloatAction
 - Photon::Voice::RemoteVoiceOptions, 74
- OnDecodedFrameShortAction
 - Photon::Voice::RemoteVoiceOptions, 74
- OnDetected
 - Photon::Voice::AudioUtil::IVoiceDetector, 43
 - Photon::Voice::AudioUtil::VoiceDetector, 96
- OnRemoteVoiceInfoAction
 - Photon::Voice::VoiceClient, 91
- OnRemoteVoiceRemoveAction
 - Photon::Voice::RemoteVoiceOptions, 74
 - Photon::Voice::Unity::Speaker, 76
- Open
 - Photon::Voice::IDecoder, 31
 - Photon::Voice::OpusCodec::Decoder, 25
- OpusApplicationType
 - POpusCodec::Enums, 8
- OpusCodec, 60
- OpusCodec.Decoder, 23
- OpusCodec.Encoder< T >, 25
- OpusCodec.EncoderFactory, 26
- OpusCodec.EncoderFloat, 26
- OpusCodec.EncoderShort, 26
- OpusCodec.Util, 87
- OpusDecoder, 60
- OpusEncoder, 61
- OpusException, 62
- POpusCodec, 7
- POpusCodec.Enums, 8
- POpusCodec::Enums
 - Audio, 9
 - Auto, 9
 - Bandwidth, 8
 - Channels, 8
 - Delay, 8
 - Delay10ms, 8
 - Delay20ms, 8
 - Delay2dot5ms, 8
 - Delay40ms, 8
 - Delay5ms, 8
 - Delay60ms, 8
 - Fullband, 8
 - Mediumband, 8
 - Mono, 8
 - Music, 9
 - Narrowband, 8
 - OpusApplicationType, 8
 - RestrictedLowDelay, 9
 - SignalHint, 9
 - Stereo, 8
 - SuperWideband, 8
 - Voice, 9
 - Voip, 9
 - Wideband, 8
- POpusCodec::OpusEncoder
 - EncoderDelay, 61
- Photon, 3
- Photon.Voice, 3
- Photon.Voice.IOS, 6
- Photon.Voice.PUN, 6
- Photon.Voice.Unity, 6
- Photon.Voice.Unity.UtilityScripts, 7
- Photon::Voice
 - AudioOpus, 6
 - Codec, 6
- Photon::Voice::AudioUtil
 - Convert, 15
 - ForceToStereo< T >, 15
 - Resample< T >, 15
 - ResampleAndConvert, 15, 17
- Photon::Voice::AudioUtil::ILevelMeter
 - AccumAvgPeakAmp, 37
 - CurrentAvgAmp, 37
 - CurrentPeakAmp, 37
 - ResetAccumAvgPeakAmp, 36
- Photon::Voice::AudioUtil::IVoiceDetector
 - ActivityDelayMs, 42
 - Detected, 42
 - DetectedTime, 42
 - On, 42
 - OnDetected, 43
 - Threshold, 42
- Photon::Voice::AudioUtil::LevelMeter
 - Process, 44
 - ResetAccumAvgPeakAmp, 44
- Photon::Voice::AudioUtil::LevelMeterDummy
 - ResetAccumAvgPeakAmp, 45
- Photon::Voice::AudioUtil::LevelMeterFloat
 - LevelMeterFloat, 45
- Photon::Voice::AudioUtil::LevelMeterShort
 - LevelMeterShort, 46
- Photon::Voice::AudioUtil::Resampler
 - Process, 75
 - Resampler, 75
- Photon::Voice::AudioUtil::ToneAudioPusher
 - SetCallback, 83
 - ToneAudioPusher, 83
- Photon::Voice::AudioUtil::ToneAudioReader

- Channels, [84](#)
- Error, [84](#)
- Read, [84](#)
- SamplingRate, [84](#)
- ToneAudioReader, [84](#)
- Photon::Voice::AudioUtil::VoiceDetector
 - ActivityDelayMs, [95](#)
 - Detected, [95](#)
 - DetectedTime, [96](#)
 - On, [96](#)
 - OnDetected, [96](#)
 - Process, [95](#)
 - Threshold, [96](#)
- Photon::Voice::AudioUtil::VoiceDetectorCalibration
 - Calibrate, [97](#)
 - Process, [97](#)
 - VoiceDetectorCalibration, [97](#)
- Photon::Voice::AudioUtil::VoiceDetectorFloat
 - VoiceDetectorFloat, [98](#)
- Photon::Voice::AudioUtil::VoiceDetectorShort
 - VoiceDetectorShort, [99](#)
- Photon::Voice::AudioUtil::VoiceLevelDetectCalibrate
 - Calibrate, [104](#)
 - LevelMeter, [104](#)
 - Process, [104](#)
 - VoiceDetector, [104](#)
 - VoiceLevelDetectCalibrate, [104](#)
- Photon::Voice::BufferReaderPushAdapter
 - BufferReaderPushAdapter, [17](#)
 - Service, [18](#)
- Photon::Voice::BufferReaderPushAdapterAsyncPool
 - BufferReaderPushAdapterAsyncPool, [18](#)
 - Service, [18](#)
- Photon::Voice::BufferReaderPushAdapterAsyncPool↵
 - Copy
 - BufferReaderPushAdapterAsyncPoolCopy, [20](#)
 - Service, [20](#)
- Photon::Voice::BufferReaderPushAdapterAsyncPool↵
 - FloatToShort
 - BufferReaderPushAdapterAsyncPoolFloatToShort, [21](#)
 - Service, [21](#)
- Photon::Voice::BufferReaderPushAdapterBase
 - BufferReaderPushAdapterBase, [22](#)
 - Dispose, [22](#)
 - Service, [22](#)
- Photon::Voice::Framer
 - Count, [28](#)
 - Frame, [28](#)
 - Framer, [28](#)
- Photon::Voice::IAudioDesc
 - Channels, [29](#)
 - Error, [29](#)
 - SamplingRate, [29](#)
- Photon::Voice::IAudioPusher
 - SetCallback, [30](#)
- Photon::Voice::IDataReader
 - Read, [31](#)
- Photon::Voice::IDecoder
 - Error, [31](#)
 - Open, [31](#)
- Photon::Voice::IDecoderDirect
 - DecodeToByte, [32](#)
 - DecodeToFloat, [32](#)
 - DecodeToShort, [32](#)
- Photon::Voice::IDecoderQueued
 - Decode, [33](#)
- Photon::Voice::IEncoder
 - Error, [34](#)
- Photon::Voice::IEncoderDataFlowDirect
 - EncodeAndGetOutput, [35](#)
- Photon::Voice::IEncoderQueued
 - GetOutput, [36](#)
- Photon::Voice::ILocalVoiceAudio
 - LevelMeter, [38](#)
 - VoiceDetector, [38](#)
 - VoiceDetectorCalibrate, [37](#)
 - VoiceDetectorCalibrating, [38](#)
- Photon::Voice::IOS::AudioSessionParametersPresets
 - Game, [13](#)
 - VoIP, [13](#)
- Photon::Voice::IProcessor
 - Process, [40](#)
- Photon::Voice::IServiceable
 - Service, [41](#)
- Photon::Voice::LoadBalancingTransport
 - Dispose, [47](#)
 - GlobalInterestGroup, [49](#)
 - LoadBalancingTransport, [47](#)
 - SendDebugEchoVoicesInfo, [47](#)
 - Service, [49](#)
 - VoiceClient, [49](#)
- Photon::Voice::LocalVoice
 - DebugEchoMode, [50](#)
 - Encrypt, [50](#)
 - FramesSent, [50](#)
 - FramesSentBytes, [51](#)
 - Info, [51](#)
 - InterestGroup, [51](#)
 - IsCurrentlyTransmitting, [51](#)
 - LocalUserServiceable, [51](#)
 - Reliable, [51](#)
 - RemoveSelf, [50](#)
 - TransmitEnabled, [51](#)
- Photon::Voice::LocalVoiceAudio
 - Create, [52](#)
 - VoiceDetectorCalibrate, [52](#)
 - VoiceDetectorCalibrating, [53](#)
- Photon::Voice::LocalVoiceAudioDummy
 - Dummy, [54](#)
 - VoiceDetectorCalibrate, [53](#)
- Photon::Voice::LocalVoiceFramed
 - AddPostProcessor, [55](#)
 - AddPreProcessor, [55](#)
 - ClearProcessors, [56](#)
 - Dispose, [56](#)

- PushData, [56](#)
- PushDataAsync, [56](#)
- PushDataAsyncReady, [56](#)
- Photon::Voice::LocalVoiceFramedBase
 - FrameSize, [57](#)
- Photon::Voice::ObjectPool
 - AcquireOrCreate, [59](#)
 - Dispose, [59](#)
 - Info, [60](#)
 - Init, [59](#)
 - ObjectPool, [59](#)
 - Release, [60](#)
- Photon::Voice::OpusCodec::Decoder
 - DecodeToByte, [24](#)
 - DecodeToFloat, [24](#)
 - DecodeToShort, [24](#)
 - Open, [25](#)
- Photon::Voice::OpusCodec::Encoder
 - EncodeAndGetOutput, [25](#)
- Photon::Voice::PUN::PhotonVoiceNetwork
 - AutoConnectAndJoin, [64](#)
 - AutoCreateSpeakerIfNotFound, [64](#)
 - AutoLeaveAndDisconnect, [64](#)
 - ConnectAndJoinRoom, [64](#)
 - Disconnect, [64](#)
 - Instance, [64](#)
 - VoiceRoomNameSuffix, [64](#)
- Photon::Voice::PUN::PhotonVoiceView
 - AutoCreateRecorderIfNotFound, [66](#)
 - IsRecorder, [66](#)
 - IsRecording, [66](#)
 - IsSetup, [66](#)
 - IsSpeaker, [66](#)
 - IsSpeaking, [66](#)
 - RecorderInUse, [66](#)
 - SetupDebugSpeaker, [66](#)
 - SpeakerInUse, [66](#)
 - UsePrimaryRecorder, [66](#)
- Photon::Voice::RemoteVoiceInfo
 - ChannelId, [72](#)
 - Info, [72](#)
 - PlayerId, [73](#)
 - VoiceId, [73](#)
- Photon::Voice::RemoteVoiceOptions
 - Decoder, [74](#)
 - OnDecodedFrameByteAction, [74](#)
 - OnDecodedFrameFloatAction, [74](#)
 - OnDecodedFrameShortAction, [74](#)
 - OnRemoteVoiceRemoveAction, [74](#)
- Photon::Voice::SpeexLib
 - SPEEX_ECHO_GET_FRAME_SIZE, [78](#)
 - SPEEX_ECHO_GET_IMPULSE_RESPONSE, [78](#)
 - SPEEX_ECHO_GET_IMPULSE_RESPONSE_←
SIZE, [78](#)
 - SPEEX_ECHO_GET_SAMPLING_RATE, [78](#)
 - SPEEX_ECHO_SET_SAMPLING_RATE, [78](#)
 - SPEEX_PREPROCESS_GET_AGC, [78](#)
 - SPEEX_PREPROCESS_GET_AGC_DECREM_←
ENT, [78](#)
 - SPEEX_PREPROCESS_GET_AGC_GAIN, [78](#)
 - SPEEX_PREPROCESS_GET_AGC_INCREM_←
NT, [78](#)
 - SPEEX_PREPROCESS_GET_AGC_LEVEL, [78](#)
 - SPEEX_PREPROCESS_GET_AGC_LOUDNE_←
SS, [78](#)
 - SPEEX_PREPROCESS_GET_AGC_MAX_GAIN, [78](#)
 - SPEEX_PREPROCESS_GET_AGC_TARGET, [78](#)
 - SPEEX_PREPROCESS_GET_DENOISE, [79](#)
 - SPEEX_PREPROCESS_GET_DEREVERB, [79](#)
 - SPEEX_PREPROCESS_GET_DEREVERB_DE_←
CAY, [79](#)
 - SPEEX_PREPROCESS_GET_DEREVERB_LE_←
VEL, [79](#)
 - SPEEX_PREPROCESS_GET_ECHO_STATE, [79](#)
 - SPEEX_PREPROCESS_GET_ECHO_SUPPR_←
ESS, [79](#)
 - SPEEX_PREPROCESS_GET_ECHO_SUPPR_←
ESS_ACTIVE, [79](#)
 - SPEEX_PREPROCESS_GET_NOISE_PSD, [79](#)
 - SPEEX_PREPROCESS_GET_NOISE_PSD_SI_←
ZE, [79](#)
 - SPEEX_PREPROCESS_GET_NOISE_SUPPR_←
ESS, [79](#)
 - SPEEX_PREPROCESS_GET_PROB, [79](#)
 - SPEEX_PREPROCESS_GET_PROB_CONTIN_←
UE, [79](#)
 - SPEEX_PREPROCESS_GET_PROB_START, [80](#)
 - SPEEX_PREPROCESS_GET_PSD, [80](#)
 - SPEEX_PREPROCESS_GET_PSD_SIZE, [80](#)
 - SPEEX_PREPROCESS_GET_VAD, [80](#)
 - SPEEX_PREPROCESS_SET_AGC, [80](#)
 - SPEEX_PREPROCESS_SET_AGC_DECREM_←
ENT, [80](#)
 - SPEEX_PREPROCESS_SET_AGC_INCREM_←
NT, [80](#)
 - SPEEX_PREPROCESS_SET_AGC_LEVEL, [80](#)
 - SPEEX_PREPROCESS_SET_AGC_MAX_GAIN, [80](#)
 - SPEEX_PREPROCESS_SET_AGC_TARGET, [80](#)
 - SPEEX_PREPROCESS_SET_DENOISE, [80](#)
 - SPEEX_PREPROCESS_SET_DEREVERB, [80](#)
 - SPEEX_PREPROCESS_SET_DEREVERB_DE_←
CAY, [81](#)
 - SPEEX_PREPROCESS_SET_DEREVERB_LE_←
VEL, [81](#)
 - SPEEX_PREPROCESS_SET_ECHO_STATE, [81](#)
 - SPEEX_PREPROCESS_SET_ECHO_SUPPRE_←
SS, [81](#)
 - SPEEX_PREPROCESS_SET_ECHO_SUPPRE_←
SS_ACTIVE, [81](#)
 - SPEEX_PREPROCESS_SET_NOISE_SUPPR_←
ESS, [81](#)
 - SPEEX_PREPROCESS_SET_PROB_CONTIN_←
UE, [81](#)

- SPEEX_PREPROCESS_SET_PROB_START, 81
- SPEEX_PREPROCESS_SET_VAD, 81
- Photon::Voice::Unity::Recorder
 - AudioClip, 70
 - AudioGroup, 70
 - Bitrate, 70
 - DebugEchoMode, 70
 - Encrypt, 70
 - FrameDuration, 70
 - Init, 69
 - InputFactory, 70
 - InterestGroup, 70
 - IsCurrentlyTransmitting, 70
 - IsInitialized, 70
 - LevelMeter, 70
 - LoopAudioClip, 71
 - MicrophoneType, 71
 - PhotonMicrophoneDeviceId, 71
 - PhotonMicrophoneEnumerator, 71
 - ReInit, 69
 - ReliableMode, 71
 - RequiresInit, 71
 - SamplingRate, 71
 - SourceType, 71
 - TransmitEnabled, 71
 - TypeConvert, 71
 - UnityMicrophoneDevice, 71
 - UserData, 71
 - VoiceDetection, 72
 - VoiceDetectionDelayMs, 72
 - VoiceDetectionThreshold, 72
 - VoiceDetector, 72
 - VoiceDetectorCalibrate, 69
 - VoiceDetectorCalibrating, 72
- Photon::Voice::Unity::Speaker
 - Actor, 76
 - IsLinked, 76
 - IsPlaying, 76
 - Lag, 76
 - OnRemoteVoiceRemoveAction, 76
- Photon::Voice::Unity::VoiceConnection
 - ClientState, 93
 - ConnectUsingSettings, 93
 - FramesLostPerSecond, 94
 - FramesLostPercent, 93
 - FramesReceivedPerSecond, 94
 - LogLevel, 94
 - Logger, 94
 - PrimaryRecorder, 93
 - RemoteVoiceAdded, 94
 - Settings, 93
 - SpeakerFactory, 93
 - SpeakerLinked, 94
 - SpeakerPrefab, 94
 - VoiceClient, 94
- Photon::Voice::UnsupportedCodecException
 - UnsupportedCodecException, 86
- Photon::Voice::UnsupportedSampleTypeException
 - UnsupportedSampleTypeException, 86
- Photon::Voice::VoiceClient
 - CreateLocalVoice, 88
 - CreateLocalVoiceAudio< T >, 88
 - CreateLocalVoiceAudioFromSource, 89
 - CreateLocalVoiceFramed< T >, 89
 - DebugLostPercent, 90
 - FramesLost, 90
 - FramesReceived, 90
 - FramesSent, 90
 - FramesSentBytes, 90
 - LocalVoices, 91
 - LocalVoicesInChannel, 90
 - OnRemoteVoiceInfoAction, 91
 - RemoteVoiceInfoDelegate, 90
 - RemoteVoiceInfos, 91
 - RemoveLocalVoice, 90
 - RoundTripTime, 91
 - RoundTripTimeVariance, 91
 - Service, 90
 - SuppressInfoDuplicateWarning, 91
- Photon::Voice::VoiceEventCode
 - Code0, 101
 - GetCode, 100
 - TryGetChannelID, 101
- Photon::Voice::VoiceInfo
 - Bitrate, 102
 - Channels, 102
 - CreateAudioOpus, 102
 - FrameDurationSamples, 102
 - FrameDurationUs, 103
 - FrameSize, 103
 - Height, 103
 - SamplingRate, 103
 - SourceSamplingRate, 103
 - UserData, 103
 - Width, 103
- PhotonMicrophoneDeviceId
 - Photon::Voice::Unity::Recorder, 71
- PhotonMicrophoneEnumerator
 - Photon::Voice::Unity::Recorder, 71
- PhotonVoiceCreatedParams, 62
- PhotonVoiceLagSimulationGui, 63
- PhotonVoiceNetwork, 63
- PhotonVoiceStatsGui, 65
- PhotonVoiceView, 65
- PlayerId
 - Photon::Voice::RemoteVoiceInfo, 73
- PrimaryRecorder
 - Photon::Voice::Unity::VoiceConnection, 93
- PrimitiveArrayPool< T >, 67
- Process
 - Photon::Voice::AudioUtil::LevelMeter, 44
 - Photon::Voice::AudioUtil::Resampler, 75
 - Photon::Voice::AudioUtil::VoiceDetector, 95
 - Photon::Voice::AudioUtil::VoiceDetectorCalibration, 97

- Photon::Voice::AudioUtil::VoiceLevelDetect↔
Calibrate, 104
- Photon::Voice::IProcessor, 40
- PushData
 - Photon::Voice::LocalVoiceFramed, 56
- PushDataAsync
 - Photon::Voice::LocalVoiceFramed, 56
- PushDataAsyncReady
 - Photon::Voice::LocalVoiceFramed, 56
- Relnit
 - Photon::Voice::Unity::Recorder, 69
- Read
 - Photon::Voice::AudioUtil::ToneAudioReader, 84
 - Photon::Voice::IDataReader, 31
- Recorder, 67
- Recorder.PhotonVoiceCreatedParams, 62
- RecorderInUse
 - Photon::Voice::PUN::PhotonVoiceView, 66
- Release
 - Photon::Voice::ObjectPool, 60
- Reliable
 - Photon::Voice::LocalVoice, 51
- ReliableMode
 - Photon::Voice::Unity::Recorder, 71
- RemoteVoiceAdded
 - Photon::Voice::Unity::VoiceConnection, 94
- RemoteVoiceInfo, 72
- RemoteVoiceInfoDelegate
 - Photon::Voice::VoiceClient, 90
- RemoteVoiceInfos
 - Photon::Voice::VoiceClient, 91
- RemoteVoiceLink, 73
- RemoteVoiceOptions, 73
- RemoveLocalVoice
 - Photon::Voice::VoiceClient, 90
- RemoveSelf
 - Photon::Voice::LocalVoice, 50
- RequiresInit
 - Photon::Voice::Unity::Recorder, 71
- Resample< T >
 - Photon::Voice::AudioUtil, 15
- ResampleAndConvert
 - Photon::Voice::AudioUtil, 15, 17
- Resampler
 - Photon::Voice::AudioUtil::Resampler, 75
- ResetAccumAvgPeakAmp
 - Photon::Voice::AudioUtil::ILevelMeter, 36
 - Photon::Voice::AudioUtil::LevelMeter, 44
 - Photon::Voice::AudioUtil::LevelMeterDummy, 45
- RestrictedLowDelay
 - POpusCodec::Enums, 9
- RoundTripTime
 - Photon::Voice::VoiceClient, 91
- RoundTripTimeVariance
 - Photon::Voice::VoiceClient, 91
- SPEEX_ECHO_GET_FRAME_SIZE
 - Photon::Voice::SpeexLib, 78
- SPEEX_ECHO_GET_IMPULSE_RESPONSE
 - Photon::Voice::SpeexLib, 78
- SPEEX_ECHO_GET_IMPULSE_RESPONSE_SIZE
 - Photon::Voice::SpeexLib, 78
- SPEEX_ECHO_GET_SAMPLING_RATE
 - Photon::Voice::SpeexLib, 78
- SPEEX_ECHO_SET_SAMPLING_RATE
 - Photon::Voice::SpeexLib, 78
- SPEEX_PREPROCESS_GET_AGC
 - Photon::Voice::SpeexLib, 78
- SPEEX_PREPROCESS_GET_AGC_DECREMENT
 - Photon::Voice::SpeexLib, 78
- SPEEX_PREPROCESS_GET_AGC_GAIN
 - Photon::Voice::SpeexLib, 78
- SPEEX_PREPROCESS_GET_AGC_INCREMENT
 - Photon::Voice::SpeexLib, 78
- SPEEX_PREPROCESS_GET_AGC_LEVEL
 - Photon::Voice::SpeexLib, 78
- SPEEX_PREPROCESS_GET_AGC_LOUDNESS
 - Photon::Voice::SpeexLib, 78
- SPEEX_PREPROCESS_GET_AGC_MAX_GAIN
 - Photon::Voice::SpeexLib, 78
- SPEEX_PREPROCESS_GET_AGC_TARGET
 - Photon::Voice::SpeexLib, 78
- SPEEX_PREPROCESS_GET_DENOISE
 - Photon::Voice::SpeexLib, 79
- SPEEX_PREPROCESS_GET_DEREVERB
 - Photon::Voice::SpeexLib, 79
- SPEEX_PREPROCESS_GET_DEREVERB_DECAY
 - Photon::Voice::SpeexLib, 79
- SPEEX_PREPROCESS_GET_DEREVERB_LEVEL
 - Photon::Voice::SpeexLib, 79
- SPEEX_PREPROCESS_GET_ECHO_STATE
 - Photon::Voice::SpeexLib, 79
- SPEEX_PREPROCESS_GET_ECHO_SUPPRESS
 - Photon::Voice::SpeexLib, 79
- SPEEX_PREPROCESS_GET_ECHO_SUPPRESS↔
ACTIVE
 - Photon::Voice::SpeexLib, 79
- SPEEX_PREPROCESS_GET_NOISE_PSD
 - Photon::Voice::SpeexLib, 79
- SPEEX_PREPROCESS_GET_NOISE_PSD_SIZE
 - Photon::Voice::SpeexLib, 79
- SPEEX_PREPROCESS_GET_NOISE_SUPPRESS
 - Photon::Voice::SpeexLib, 79
- SPEEX_PREPROCESS_GET_PROB
 - Photon::Voice::SpeexLib, 79
- SPEEX_PREPROCESS_GET_PROB_CONTINUE
 - Photon::Voice::SpeexLib, 79
- SPEEX_PREPROCESS_GET_PROB_START
 - Photon::Voice::SpeexLib, 80
- SPEEX_PREPROCESS_GET_PSD
 - Photon::Voice::SpeexLib, 80
- SPEEX_PREPROCESS_GET_PSD_SIZE
 - Photon::Voice::SpeexLib, 80
- SPEEX_PREPROCESS_GET_VAD
 - Photon::Voice::SpeexLib, 80
- SPEEX_PREPROCESS_SET_AGC

- Photon::Voice::SpeexLib, [80](#)
- SPEEX_PREPROCESS_SET_AGC_DECREMENT
 - Photon::Voice::SpeexLib, [80](#)
- SPEEX_PREPROCESS_SET_AGC_INCREMENT
 - Photon::Voice::SpeexLib, [80](#)
- SPEEX_PREPROCESS_SET_AGC_LEVEL
 - Photon::Voice::SpeexLib, [80](#)
- SPEEX_PREPROCESS_SET_AGC_MAX_GAIN
 - Photon::Voice::SpeexLib, [80](#)
- SPEEX_PREPROCESS_SET_AGC_TARGET
 - Photon::Voice::SpeexLib, [80](#)
- SPEEX_PREPROCESS_SET_DENOISE
 - Photon::Voice::SpeexLib, [80](#)
- SPEEX_PREPROCESS_SET_DEREVERB
 - Photon::Voice::SpeexLib, [80](#)
- SPEEX_PREPROCESS_SET_DEREVERB_DECAY
 - Photon::Voice::SpeexLib, [81](#)
- SPEEX_PREPROCESS_SET_DEREVERB_LEVEL
 - Photon::Voice::SpeexLib, [81](#)
- SPEEX_PREPROCESS_SET_ECHO_STATE
 - Photon::Voice::SpeexLib, [81](#)
- SPEEX_PREPROCESS_SET_ECHO_SUPPRESS
 - Photon::Voice::SpeexLib, [81](#)
- SPEEX_PREPROCESS_SET_ECHO_SUPPRESS_↔
 - ACTIVE
 - Photon::Voice::SpeexLib, [81](#)
- SPEEX_PREPROCESS_SET_NOISE_SUPPRESS
 - Photon::Voice::SpeexLib, [81](#)
- SPEEX_PREPROCESS_SET_PROB_CONTINUE
 - Photon::Voice::SpeexLib, [81](#)
- SPEEX_PREPROCESS_SET_PROB_START
 - Photon::Voice::SpeexLib, [81](#)
- SPEEX_PREPROCESS_SET_VAD
 - Photon::Voice::SpeexLib, [81](#)
- SamplingRate
 - Photon::Voice::AudioUtil::ToneAudioReader, [84](#)
 - Photon::Voice::IAudioDesc, [29](#)
 - Photon::Voice::Unity::Recorder, [71](#)
 - Photon::Voice::VoiceInfo, [103](#)
- SendDebugEchoVoicesInfo
 - Photon::Voice::LoadBalancingTransport, [47](#)
- Service
 - Photon::Voice::BufferReaderPushAdapter, [18](#)
 - Photon::Voice::BufferReaderPushAdapterAsync↔
 - Pool, [18](#)
 - Photon::Voice::BufferReaderPushAdapterAsync↔
 - PoolCopy, [20](#)
 - Photon::Voice::BufferReaderPushAdapterAsync↔
 - PoolFloatToShort, [21](#)
 - Photon::Voice::BufferReaderPushAdapterBase, [22](#)
 - Photon::Voice::IServiceable, [41](#)
 - Photon::Voice::LoadBalancingTransport, [49](#)
 - Photon::Voice::VoiceClient, [90](#)
- SetCallback
 - Photon::Voice::AudioUtil::ToneAudioPusher, [83](#)
 - Photon::Voice::IAudioPusher, [30](#)
- Settings
 - Photon::Voice::Unity::VoiceConnection, [93](#)
- SetupDebugSpeaker
 - Photon::Voice::PUN::PhotonVoiceView, [66](#)
- SignalHint
 - POpusCodec::Enums, [9](#)
- SourceSamplingRate
 - Photon::Voice::VoiceInfo, [103](#)
- SourceType
 - Photon::Voice::Unity::Recorder, [71](#)
- Speaker, [75](#)
- SpeakerFactory
 - Photon::Voice::Unity::VoiceConnection, [93](#)
- SpeakerInUse
 - Photon::Voice::PUN::PhotonVoiceView, [66](#)
- SpeakerLinked
 - Photon::Voice::Unity::VoiceConnection, [94](#)
- SpeakerPrefab
 - Photon::Voice::Unity::VoiceConnection, [94](#)
- SpeexLib, [76](#)
- SpeexProcessor, [81](#)
- SpeexProcessor.AECLatencyResultType, [11](#)
- Stereo
 - POpusCodec::Enums, [8](#)
- SuperWideband
 - POpusCodec::Enums, [8](#)
- SuppressInfoDuplicateWarning
 - Photon::Voice::VoiceClient, [91](#)
- TestTone, [82](#)
- Threshold
 - Photon::Voice::AudioUtil::IVoiceDetector, [42](#)
 - Photon::Voice::AudioUtil::VoiceDetector, [96](#)
- ToneAudioPusher
 - Photon::Voice::AudioUtil::ToneAudioPusher, [83](#)
- ToneAudioReader, [84](#)
 - Photon::Voice::AudioUtil::ToneAudioReader, [84](#)
- TransmitEnabled
 - Photon::Voice::LocalVoice, [51](#)
 - Photon::Voice::Unity::Recorder, [71](#)
- TryGetChannelID
 - Photon::Voice::VoiceEventCode, [101](#)
- TypeConvert
 - Photon::Voice::Unity::Recorder, [71](#)
- UnityAndroidAudioInAEC, [85](#)
- UnityAudioOut, [85](#)
- UnityMicrophoneDevice
 - Photon::Voice::Unity::Recorder, [71](#)
- UnsupportedCodecException, [86](#)
 - Photon::Voice::UnsupportedCodecException, [86](#)
- UnsupportedSampleTypeException, [86](#)
 - Photon::Voice::UnsupportedSampleTypeException, [86](#)
- UsePrimaryRecorder
 - Photon::Voice::PUN::PhotonVoiceView, [66](#)
- UserData
 - Photon::Voice::Unity::Recorder, [71](#)
 - Photon::Voice::VoiceInfo, [103](#)
- VoIP

- Photon::Voice::IOS::AudioSessionParameters↔
 - Presets, [13](#)
- Voice
 - POpusCodec::Enums, [9](#)
- VoiceClient, [87](#)
 - Photon::Voice::LoadBalancingTransport, [49](#)
 - Photon::Voice::Unity::VoiceConnection, [94](#)
- VoiceComponent, [91](#)
- VoiceConnection, [92](#)
- VoiceDetection
 - Photon::Voice::Unity::Recorder, [72](#)
- VoiceDetectionDelayMs
 - Photon::Voice::Unity::Recorder, [72](#)
- VoiceDetectionThreshold
 - Photon::Voice::Unity::Recorder, [72](#)
- VoiceDetector
 - Photon::Voice::AudioUtil::VoiceLevelDetect↔
 - Calibrate, [104](#)
 - Photon::Voice::ILocalVoiceAudio, [38](#)
 - Photon::Voice::Unity::Recorder, [72](#)
- VoiceDetectorCalibrate
 - Photon::Voice::ILocalVoiceAudio, [37](#)
 - Photon::Voice::LocalVoiceAudio, [52](#)
 - Photon::Voice::LocalVoiceAudioDummy, [53](#)
 - Photon::Voice::Unity::Recorder, [69](#)
- VoiceDetectorCalibrating
 - Photon::Voice::ILocalVoiceAudio, [38](#)
 - Photon::Voice::LocalVoiceAudio, [53](#)
 - Photon::Voice::Unity::Recorder, [72](#)
- VoiceDetectorCalibration
 - Photon::Voice::AudioUtil::VoiceDetectorCalibration, [97](#)
- VoiceDetectorFloat
 - Photon::Voice::AudioUtil::VoiceDetectorFloat, [98](#)
- VoiceDetectorShort
 - Photon::Voice::AudioUtil::VoiceDetectorShort, [99](#)
- VoiceEventCode, [99](#)
- VoiceId
 - Photon::Voice::RemoteVoiceInfo, [73](#)
- VoiceInfo, [101](#)
- VoiceLevelDetectCalibrate
 - Photon::Voice::AudioUtil::VoiceLevelDetect↔
 - Calibrate, [104](#)
- VoiceLogger, [105](#)
- VoiceRoomNameSuffix
 - Photon::Voice::PUN::PhotonVoiceNetwork, [64](#)
- Voip
 - POpusCodec::Enums, [9](#)
- WebRTCAudioLib, [105](#)
- WebRTCAudioLib.ConfigParam, [23](#)
- WebRTCAudioLib.Param, [62](#)
- WebRTCAudioProcessor, [106](#)
- WebRtcAudioDsp, [105](#)
- Wideband
 - POpusCodec::Enums, [8](#)
- Width
 - Photon::Voice::VoiceInfo, [103](#)