

Python

```
import reflex as rx
```

```
# 1. STATE (Backend Logic)
```

```
class TodoState(rx.State):
```

```
    items: list[str] = ["Learn Python", "Build a full-stack app"]
```

```
    new_item: str = ""
```

```
    def add_item(self):
```

```
        if self.new_item.strip():
```

```
            self.items.append(self.new_item)
```

```
            self.new_item = ""
```

```
    def delete_item(self, item: str):
```

```
        self.items.remove(item)
```

```
# 2. UI COMPONENTS (Frontend)
```

```
def todo_item(item: str) -> rx.Component:
```

```
    return rx.hstack(
```

```
        rx.text(item, font_size="1.25em", flex_grow=1),
```

```
        rx.button(
```

```
            "X"
```

```
            on_click=lambda: TodoState.delete_item(item)
```

```
            color_scheme="red"
```

```
            variant="ghost"
```

```
        ),
```

```
        width="100%",
```

```
        padding="0.5em",
```

```
        border_bottom="1px solid #EAEAEA"
```

```
    )
```

```
def index() -> rx.Component:
```

```
    return rx.center(
```

```
        rx.vstack(
```

```
            rx.heading("Python Full-Stack To-Do", size="8", margin_bottom="0.5em")
```

```

        rx.hstack(
            rx.input(
                placeholder="Add a new task..."
                value=TodoState.new_item
                on_change=TodoState.set_new_item
                width="300px"
            ),
            rx.button("Add", on_click=TodoState.add_item, color_scheme="blue"),
            width="100%"
        ),
        rx.divider(margin_y="1em"),
        rx.vstack(
            rx.foreach(TodoState.items, todo_item),
            width="100%",
            align_items="stretch"
        ),
        padding="2em",
        border_radius="lg",
        box_shadow="lg",
        background_color="white",
        width="450px",
    ),
    height="100vh",
    background_color="#F7F9FA"
)

```

### # 3. APP SETUP

```

app = rx.App()
app.add_page(index, title="Pure Python Full-Stack App")

```