

IRCT FLOW (PLUTUS TO CLEARING):

1. When Plutus send an JSON file to GC2

CONNECTIVITY_PROFILE							
PROFILE_ID	FLOW_NAME	FLOW_FAMILY	INPUT_CHANNEL	LOCAL_LOCATION	PROFILE_TYPE	CONNECTION_KEY	CLEARING_TYPE_ID
IRCT_IN_CP01	GXPTOGC2	MLIRCT-TPT4	CLOUDKAFKA	kafka_topic	RECEIVE	MLIRCT-CLOUDKAFKA-PR	MLIRCT-TC

An Entry will be made in CONNECTIVITY_PROFILE table with pre-filled information.

MESSAGE_PROFILE					
MESSAGE_CODE	PROFILE_ID	CLEARING_TYPE_ID	PARENT_MESSAGE_CODE	MIME_TYPE	MAPPING_KEY
IRCT_IN_MP01	IRCT_IN_CP01	MLIRCT-TPT4		application/json	

An Entry will be made in MESSAGE_PROFILE table with pre-filled information.

- 2.

Initially the workflow ID will be null in this table.

INBOUND_PAYLOAD					
INBOUND_PAYLOAD_ID	WORKFLOW_ID	NAME	STATUS	PAYLOAD(TEXT)	PROFILE_ID
abcd-egh-001	MLIRCT0001	KAFKA	Received	JSON raw data	IRCT_IN_CP01

WORKFLOW_ITEM								
WORKFLOW_ID	CLEARING_TYPE_ID	PARENT_WORKFLOW_ID	SOURCE_REFERENCE	TARGET_REFERENCE	UNIQUE_KEY	STATUS	MESSAGE_CODE	INBOUND_PAYLOAD_ID
MLIRCT0001	MLIRCT-TPT4		FIRMROOTID_001		FIRMROOTID_001	CREATED/ACCEPTED	IRCT_IN_MP01	abcd-egh-001

When any transaction is created with in JPMC we will identify the transaction using firmrootID which is same across all microservices. We will receive this from PLUTUS in IRCT flow.

Initially the status is Created. We will receive payload. We will validate the payload, and Once everything is correct then the status is changed to Accepted. Then the workflow ID generated will be persisted in INBOUND_PAYLOAD table

Till now Half of the flow is done.

Using GC2 tool we will create a jar file using C24 tool. (JSON to XML) .Now we need to send this XML file to Clearing.

CONNECTIVITY_PROFILE							
PROFILE_ID	FLOW_NAME	FLOW_FAMILY	INPUT_CHANNEL	LOCAL_LOCATION	PROFILE_TYPE	CONNECTION_KEY	CLEARING_TYPE_ID
IRCT_IN_CP01	GXPTOGC2	MLIRCT-TPT4	CLOUDKAFKA	kafka_topic	RECEIVE	MLIRCT-CLOUDKAFKA-PR	MLIRCT-TC
IRCT_OUT_CP02	GC2TOCLR	MLIRCT-TPT4	QUEUE	gc2toclearing	SEND	MLIRCT-RABBIT_MQ-PRM	MLIRCT-TC

MESSAGE_PROFILE					
MESSAGE_CODE	PROFILE_ID	CLEARING_TYPE_ID	PARENT_MESSAGE_CODE	MIME_TYPE	MAPPING_KEY
IRCT_IN_MP01	IRCT_IN_CP01	MLIRCT-TPT4		application/json	
IRCT_OUT_MP02	IRCT_OUT_CP02	MLIRCT-TPT4	IRCT_IN_MP01	text/xml	AUSIRCTTRANSFORM

Now we will use Outbound Workflow ID

OUTBOUND_WORKFLOW_ITEM								
OUTBOUND_WORKFLOW_ID	WORKFLOW_ID	STATUS	PROFILE_ID	TARGET_REFERENCE	MESSAGE_ID	TARGET_NAME	MESSAGE_CODE	OUTBOUND_PAYLOAD_ID
xyz-pqrs-001	MLIRCT0001	SENT	IRCT_IN_CP01	FIRMROOTID_001	MESSAGE_001	MLIRCT-TPT4	IRCT_IN_MP01	OBPLID_001

MessageID we will create in GC2 and send to Clearing. We will identify the acknowledgment is related to earlier transaction based on the messageID we will receive from Clearing.

Based on Message ID we will get FirmrootID and identify this acknowledgment is related to this transaction.

There are multiple status – Created, Accepted, Inprogress, Ready To send, sent.

OUTBOUND_PAYLOAD				
OUTBOUND_PAYLOAD_ID	WORKFLOW_ID	STATUS	PAYLOAD(TEXT)	PROFILE_ID
OBPLID_001	MLIRCT0001	SENT	XML (raw data)	IRCT_IN_CP01

IRCT flow is done Now.

IRCT – ACK Flow:

1. We will get “XML” file from Clearing to GC2

An Entry will be made in Connectivity_Profile and Message_Profile

CONNECTIVITY_PROFILE							
PROFILE_ID	FLOW_NAME	FLOW_FAMILY	INPUT_CHANNEL	LOCAL_LOCATION	PROFILE_TYPE	CONNECTION_KEY	CLEARING_TYPE_ID
IRCT_IN_CP01	GXPTG2	MLIRCT-TPT4	CLOUDKAFKA	kafka_topic	RECEIVE	MLIRCT-CLOUDKAFKA-PR	MLIRCT-TC
IRCT_OUT_CP02	GC2TOCLR	MLIRCT-TPT4	QUEUE	gc2toclearing	SEND	MLIRCT-RABBIT_MQ-PRM	MLIRCT-TC
ACK							
IRCT_IN_ACK_CP01	CLRTG2	MLIRCT-4	QUEUE	gc2toclearing	RECEIVE	MLIRCT-RABBIT_MQ-PRM	MLIRCT-TC

MESSAGE_PROFILE					
MESSAGE_CODE	PROFILE_ID	CLEARING_TYPE_ID	PARENT_MESSAGE_CODE	MIME_TYPE	MAPPING_KEY
IRCT_IN_MP01	IRCT_IN_CP01	MLIRCT-TPT4		application/json	
IRCT_OUT_MP02	IRCT_OUT_CP02	MLIRCT-TPT4	IRCT_IN_MP01	text/xml	AUSIRCTTRANSFORM
ACK					
IRCT_IN_ACK_MP01	IRCT_IN_ACK_CP01	MLIRCT-TPT4		text/xml	

INBOUND_PAYLOAD					
INBOUND_PAYLOAD_ID	WORKFLOW_ID	NAME	STATUS	PAYLOAD(TEXT)	PROFILE_ID
abcd-egh-001	MLIRCT0001	KAFKA	Received	JSON raw data	IRCT_IN_CP01
ACK					
INBPLID_001	WRKFLWACK_001	QUEUE	Received	Xml raw data	IRCT_IN_ACK_CP01

Now Half part is done in IRCT-ACK flow.

Now GC2 need to create a FirmrootID and we will get MessageID which was part IRCT FLOW and we will get WorkFlow ID and we will update in Parent WorkFlow ID. As well

WORKFLOW_ITEM								
WORKFLOW_ID	CLEARING_TYPE_ID	PARENT_WORKFLOW_ID	SOURCE_REFERENCE	TARGET_REFERENCE	UNIQUE_KEY	STATUS	MESSAGE_CODE	INBOUND_PAYLOAD_ID
MLIRCT0001	MLIRCT-TPT4		FIRMROOTID_001		FIRMROOTID_001	CREATED/ACCEPTED	IRCT_IN_MP01	abcd-egh-001
ACK								
WRKFLWACK_001	MLIRCT-TPT4			MESSAGE_001	MESSAGE_001	CREATED/ACCEPTED	IRCT_IN_ACK_MP01	INBPLID_001

OUTBOUND_WORKFLOW_ITEM								
OUTBOUND_WORKFLOW_ID	WORKFLOW_ID	STATUS	PROFILE_ID	TARGET_REFERENCE	MESSAGE_ID	TARGET_NAME	MESSAGE_CODE	OUTBOUND_PAYLOAD_ID
xyz-pqrs-001	MLIRCT0001	SENT	IRCT_IN_CP01	FIRMROOTID_001	MESSAGE_001	MLIRCT-TPT4	IRCT_IN_MP01	OBPLID_001
ACK								
OBWFID_001	WRKFLWACK_001	SENT	IRCT_IN_ACK_CP01	FIRMROOTID_001	MESSAGE_001	MLIRCT-TPT4	IRCT_IN_ACK_MP01	OBPLID_002

OUTBOUND_PAYLOAD				
OUTBOUND_PAYLOAD_ID	WORKFLOW_ID	STATUS	PAYLOAD(TEXT)	PROFILE_ID
OBPLID_001	MLIRCT0001	SENT	XML (raw data)	IRCT_IN_CP01
ACK				
OBPLID_002	WRKFLWACK_001	SENT	JSON (raw data)	IRCT_IN_ACK_CP01