Status	Finished
Started	Saturday, 26 September 2026, 11:00 AM
Completed	Saturday, 26 September 2026, 11:03 AM
Duration	3 mins 18 secs
Grade	**15.00** out of 15.00 (**100**%)

Question **1**

Correct

Mark 1.00 out of 1.00

What will be the output of below Python code?

```
tupl=("python","programming","Computer")
print(tupl[-3:0])
```

a. () ✓

b. Computer

c. Error

d. (Computer)

Question **2**

Correct

Mark 1.00 out of 1.00

What is printed when the following code is run?

```
tup = ('30', '3', '2', '8')
print(sorted(tup,reverse = True))
```

a. ['30', '8', '3', '2']

b. ['2', '3', '30', '8']

c. ['8', '30', '3', '2'] ✓

d. ['2', '3', '8', '30']

Question **3**

Correct

Mark 1.00 out of 1.00

What will be the output of the below Python code?

t1=(55,12,78,64,25)

t1.pop(12)

print(tuple1)

- a. (12)
- b. 12
- c. (55,78,64,25)
- d. Error ✓

Question **4**

Correct

Mark 1.00 out of 1.00

What is the output of the following

```
set1 = {1, 2, 3, 4, 5}
set2 = {6, 7, 1, 3, 4, 8, 2, 5}

print(set1.issubset(set2))
print(set2.issuperset(set1))
```

- a. False
  False
- b. True ✓
  True
- c. True
  False
- d. False
  True

Question **5**

Correct

Mark 1.00 out of 1.00

A python tuple can be created without using any parentheses. (True/False)

a. False

b. True ✓

Question **6**

Correct

Mark 1.00 out of 1.00

What is the output of the given below program?

```
my_t1 = (1, 2, 3, 4)
my_t1.append( (5, 6, 7) )
print(len(my_t1))
```

a. 2

b. 1

c. Error ✓

d. 5

Question **7**

Correct

Mark 1.00 out of 1.00

What is the output of the given below program?

```
t = (58, 47, 36, 25, 14, 3)
x = t[2:-1]
print(x)
```

a. (36, 25, 14) ✓

b. (3,14,25)

c. Error

d. (58,47,36,25)

Question **8**

Correct

Mark 1.00 out of 1.00

What is the output of the following set operation

```
sampleSet = {"Yellow", "Orange", "Black"}
sampleSet.update(["Blue", "Green", "Red"])
print(sampleSet)
```

a. TypeError: update() doesn't allow list as a argument.

b. Name Error

c. {'Yellow', 'Orange', 'Black', ["Blue", "Green", "Red"]}

d. {'Yellow', 'Orange', 'Red', 'Black', 'Green', 'Blue'} ✓

Question **9**

Correct

Mark 1.00 out of 1.00

Write the Output of the following Code?

t = (15,83,83,52,60,45,52,85,100)

print(min(t)+max(t)+t.count(52))

a. Error

b. 100

c. 2

d. 117 ✓

Question **10**

Correct

Mark 1.00 out of 1.00

What will be the output of following Python code?

```
list1=[1,3,4,2]

x=list1.pop(2)

print(set([x]))
```

a. {4} ✓

b. {1,3,4}

c. {2}

d. {1,3,2}

Question **11**

Correct

Mark 1.00 out of 1.00

Select which is true for Python tuple?

a. A tuple maintains the order of items ✓

b. None of these

c. A tuple is unordered

d. We can change the tuple once created

Question **12**

Correct

Mark 1.00 out of 1.00

What will be the output of following Python code?

```
set1={0,0,9}

print(set1)
```

a. It will throw an error as there are two 0 while creating the set.

b. {9}

c. {0,9} ✓

d. {0,0,9}

Question **13**

Correct

Mark 1.00 out of 1.00

What is the output of the following union operation

```
set1 = {10, 20, 30, 40}
set2 = {50, 20, "10", 60}

set3 = set1.union(set2)
print(set3)
```

a. {40, 10, 50, 20, 60, 30}

b. SynatxError: Different types cannot be used with sets

c. {40, '10', 50, 20, 60, 30}

d. {40, 10, '10', 50, 20, 60, 30} ✓

Question **14**

Correct

Mark 1.00 out of 1.00

What is the output of the following code

```
aSet = {1, 'rec', ('cse', 'ece'), True}
print(aSet)
```

a. {'rec', 1, ('cse', 'ece')} ✓

b. Error

c. {'rec', True, ('cse', 'ece')}

d. {'rec', 1, ('cse', 'ece'),True}

Question **15**

Correct

Mark 1.00 out of 1.00

What is the output of the following

```
set1 = {10, 20, 30, 40, 50}
set2 = {60, 70, 10, 30, 40, 80, 20, 50}

print(set1.issubset(set2))
print(set2.issuperset(set1))
```

a. True
False

b. False
False

c. True ✓
True

d. False
True