

S.NO	BEAM	ELEVATION	TYPE	SIZE		CLEAR SPAN (L)	TOP REINFORCEMENT				BOTTOM REINFORCEMENT			STIRRUPS
				WIDTH (W)	DEPTH (D)		A	B	C	D1(mm)	G	E	D2(mm)	S1
1	B6	TOC EL 16075	TYPE-2	300	600	4700	3-Y16-A16	-	-	-	3-Y16-A17	-	-	47-A13-Y8@100±C/C
2	B11 & B122	TOC EL 16250	TYPE-2	300	450	2900	3-Y16-A76	-	-	-	3-Y16-A76	-	-	29-A28-Y8@100±C/C
3	B13a	TOC EL 16075	TYPE-2	300	450	3600	3-Y16-A78	-	-	-	3-Y16-A78	-	-	36-A28@100±C/C
4	B31 & B104	TOC EL 16250	TYPE-2	300	450	6900	3-Y16-A79	-	-	-	2-Y20-A80	-	-	69-A28@100±C/C
5	B57	TOC EL 16250	TYPE-2	300	450	670	2-Y20-A80a	-	-	-	3-Y16-A81	-	-	7-A28@100±C/C
6	B71 & B72	TOC EL 16250	TYPE-2	300	450	3600	3-Y16-A78	-	-	-	3-Y16-A79a	-	-	36-A28@100±C/C
7	B36 & B99	TOC EL 16250	TYPE-2	300	600	6390	3-Y20-A85	-	-	-	3-Y16-A86	-	-	64-A13@100±C/C
8	B245	TOC EL 16250	TYPE-1	300	600	5400	2-Y16-A87	2-Y16-A88	-	1450	3-A87	-	-	54-A13@100±C/C
9	B134	TOC EL 16250	TYPE-1	300	600	3215	3-Y20-A89	2-Y20-A81a	-	875	3-Y16-A90	-	-	33-A13@100±C/C
10	B135	TOC EL 16075	TYPE-1	300	350	3635	3-Y16-A92	-	2-Y16-A92a	1000	3-A92	-	-	37-A14-Y8@100±C/C
11	B246	TOC EL 16250	TYPE-2	300	450	3365	3-Y16-A92b	-	2-Y16-A93	1000	3-A92b	-	-	34-A14@100±C/C
12	B247	TOC EL 16250	TYPE-2	300	450	3635	3-A92	-	-	-	3-A92	-	-	37-A14@100±C/C
13	B279 TO B282, B284 TO B289 B291 TO B294	TOC EL 16250	TYPE-2	230	300	450	3-Y16-A94	-	-	-	3-Y16-A94	-	-	5-A15-Y8@100±C/C
14	B214	TOC EL 16250	TYPE-2	300	450	3265	3-Y16-A97	-	-	-	3-Y16-A98	-	-	33-A28@100±C/C
15	B75a	TOC EL 16250	TYPE-2	300	450	2100	3-Y20-A99	-	-	-	3-Y16-A102	-	-	21-A28@100±C/C
16	B191a & B191b	TOC EL 16250	TYPE-2	300	600	2100	3-Y16-A104	-	-	-	3-A102	-	-	21-A13@100±C/C
17	B79a	TOC EL 16250	TYPE-2	300	450	3600	3-Y16-A107	-	-	-	3-Y16-A107	-	-	36-A28@100±C/C
18	B116	TOC EL 16250	TYPE-1	300	600	7200	3-Y20-A110	-	2-Y20-A112	1900	4-Y16-A113	2-Y16-A111	1100	72-A13@100±C/C
19	B134a, B141a, B246a, B251a, B103b & B41b	TOC EL 14950	TYPE-1	300	450	2685	3-Y16-A117	-	-	-	3-Y16-A119	2-Y12-A120	500	27-A28@100±C/C
20	B65b & B83b	TOC EL 14950	TYPE-1	300	450	3500	3-Y20-A121	-	-	-	3-Y16-A122	2-Y12-A123	500	35-A28@100±C/C
21	B4c, B131c, B161c & B244b	TOC EL 14950	TYPE-1	300	450	6800	3-Y16-A124	-	-	-	3-Y16-A126	2-Y12-A127	500	68-A28@100±C/C
22	B233a	TOC EL 14950	TYPE-1	300	450	3150	3-Y16-A128	2-Y16-A129	-	-	3-Y20-A131	2-Y12-A132	500	32-A28@100±C/C
23	B244a & B159a	TOC EL 14950	TYPE-1	300	450	2400	3-Y16-A133	-	-	-	3-A133	-	-	24-A28@100±C/C