CONTENTS

Sl.No:	Title	Page No.
	Abstract	(i)
	List of Figures	(v)
	List of Tables	(vii)
	List of symbols and acronyms	(viii)

CHAPTER 1

INTRODUCTION

1.1 LOAD FREQUENCY CONTROL IN A SINGLE AREA POWER SYSTEM
- 1.1.1 REASONS FOR THE NEED OF MAINTAINING CONSTANT FREQUENCY
- 1.1.2 LOAD FREQUENCY CONTROL

1.2 MATHEMATICAL MODELLING OF A LFC SYSTEM
- 1.2.1 MATHEMATICAL MODELLING OF AGENERATOR
- 1.2.2 MATHEMATICAL MODELLING OFLOAD
- 1.2.3 MATHEMATICAL MODELLING FOR PRIMEMOVER
- 1.2.4 MATHEMATICAL MODELLING FOR GOVERNOR

1.3 AUTOMATIC GENERATION CONTROL
- 1.3.1 AGC IN A SINGLEAREA

1.4 FREQUENCY RESPONSES OF LFC SYSTEM
- 1.4.1 FREQUENCY RESPONSE WITHOUT THE PI CONTROLLER
- 1.4.2 FREQUENCY RESPONSE WITH THE PI CONTROLLER

1.5 CONCLUSION.

CHAPTER 2

ELECTRIC VEHICLE TO GRID TECHNOLOGY

2.1 INTRODUCTION:

2.2 CONCEPT OF ELECTRIC VEHICLE TO GRID TECHNOLOGY

2.3 ELECTRIC VEHICLE

2.4 WHY DO WE USE PLUG IN EV FOR V2G TECHNOLOGY?

2.5 WHAT IS V2G CHARGING OR EV SMART CHARGING?

2.6 ELECTRIC VEHICLE AGGREGATOR
2.6.1 AN EV AGGREGATOR MODEL
2.6.2 LFC MODELINCLUDING EV AGGREGATORS WITH DELAYS

CHAPTER 3
MATHEMATICAL MODELLING OF LOAD FREQUENCY CONTROL SYSTEMS INTEGRATED WITH EV AGGREGATOR

3.1 INTRODUCTION

3.1.1 MATHEMATICAL MODELLING OF LFC SYSTEM WITH EV AGGREGATOR:
3.1.2 VARIABLE DESCRIPTION
3.1.3 PARAMETER DESCRIPTION:
3.1.4 CONTROLLER PARAMETERS AND PARTICIPATION FACTORS:
3.1.5 EV AGGREGATOR PARAMETERS:

CHAPTER 4

SIMULATIONS AND RESULTS

4.1 DELAY DEPENDENT STABILITY
4.1.1 BENCHMARK SYSTEM PARAMETERS
4.1.2 MATLAB CODE FOR COMPUTATION OF STABILITY DELAY MARGIN
4.1.3 MATLAB OUTPUT FOR DIFFERENT K_P AND K_I VALUES
4.1.4 SIMULATION RESULTS

4.2 COMPUTATION OF STABILITY DELAY MARGINS
4.2.1 MATLAB CODE FOR COMPUTATION OF STABILITY REGIONS

4.2.2 STABILITY REGION CURVE FOR TIME DELAY FOR VARIOUS PARTICIPATION FACTORS.

4.3 CONCLUSION

CHAPTER 5

5.0 CONCLUSION.

CHAPTER 6

6.0 REFERENCE PAPERS AND BASE PAPERS