NATO-22 Barbed Tape Concertina (BTC)

High-security concertina razor wire · NATO-22 blade profile · BTC barbed tape specification

Parameter	NATO-22
Blade Thickness (mm)	0.5
Barb Length (mm)	22
Barb Width (mm)	16
Barb Spacing (mm)	40
Core Wire Diameter (mm)	2.5
Materials	Galvanized / stainless steel
Coil Types	Single coil / cross / flat wrap
Standard Reference	ASTM F1910 where applicable

Applications

Military & border perimeters · airports · prisons · substations · solar farm perimeters
Compatible with Kestrel 3D panel and 358 anti-climb fence systems (Y-post mounted)

BTO-22 / BTO-10 Blade Profiles

Parameter	BTO-22 | BTO-10
Blade Thickness (mm)	0.5±0.05 | 0.5±0.05
Barb Length (mm)	22±1 | 10±1
Barb Width (mm)	16±1 | 13±1
Barb Spacing (mm)	35±1 | 25±1
Core Wire Diameter (mm)	2.5±0.1 | 2.5±0.1

Standard Coil Dimensions

Outer Dia / Loops / Clips	Loop Spacing · Extended
450 mm · 56 · 3	406 mm · 11 m
720 mm · 56 · 3	533 mm · 15 m
900 mm · 50 · 5	600 mm · 15 m
965 mm · 56 · 5	533 mm · 15 m
1000 mm · 56 · 5	533 mm · 15 m

About Kestrel Metal

Kestrel Metal Products Co., Ltd. — manufacturer of security fences, wire mesh, gabions and razor wire, headquartered in Anping County, Hebei (China wire mesh industrial hub) since 2014.
200+ projects delivered across 50+ countries · ISO 9001:2015 certified · CE marked products.
Reference projects include a 500MW solar farm perimeter (Australia) and 10,000-acre cattle ranch fencing.

Commercial Terms

Term	Detail
Lead Time	**15-25 days**
Incoterms	**FOB Tianjin / Shanghai**
Payment	**T/T · L/C at sight**
Quality Management	**ISO 9001:2015**
Coating Compliance	**EN 10244-2 (zinc coating)**

Full technical datasheets: www.kestrelmetal.com/download-wire-mesh-technical-datasheet.html

Contact: kalee@kestrelmetal.com · +86 178 3238 3339 · Quote response within 24 hours