

NAME	KALEES PANDI.T
REG NO	230701135
CLASS/SEC	CSE A
SUBJECT	FUNDAMENTALS OF DATA SCIENCE
SUBJECT CODE	CS23334
TITLE	FDS LAB EXPERIMENTS

#Experiment_01_A

#KALEES PANDI.T

#230701135

#30/07/24

```
import pandas as pd import
```

```
matplotlib.pyplot as plt data =
```

```
{‘Year’: list(range(2010, 2021)),
```


```
‘Job Postings’: [150, 300, 450, 600, 800, 1200, 1600, 2100, 2700, 3400, 4200]}
```

```
df = pd.DataFrame(data) plt.plot(df[‘Year’], df[‘job Postings rob Postings’],
```

```
marker=‘o’) plt.title(‘Trend of Data Science Job Postings’) plt.xlabel(‘Year’)
```

```
plt.ylabel(‘Number of Job Postings’) plt.show()
```

Output:



```
In [2]: import pandas
x=[1,7,2]
y=pandas.DataFrame(x,index=["a","b","c"])
print(y)
```

```


0
a  1
b  7
c  2
```

```
In [3]: import pandas
x={'Subjects':["Math","Physics","English"], 'Marks': [89,92,96]}
print(pandas.DataFrame(x))
```

```

Subjects  Marks
0      Math    89
1  Physics    92
2  English    96
```

```
In [19]: import matplotlib.pyplot as plt
roles=['Data Analyst','Data Engineer','Data Scientist','ML Engineer','Business Analyst']
counts=[300,500,450,200,150]
color=['violet','indigo','blue','green','yellow']
plt.bar(roles,counts,color=color)
plt.title('Distribution of Data Science Roles')
plt.xlabel('Role')
plt.ylabel('Count')
plt.show()
```



#Experiment_01_B

#KALEES PANDI.T

#230701135 #06/08/24 import

numpy as np import pandas as

pd

df=pd.read_csv('Salary_data.csv'

) df df.info()

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 30 entries, 0 to 29
Data columns (total 2 columns):
#   Column          Non-Null Count  Dtype
---  -
0   YearsExperience  30 non-null    float64
1   Salary          30 non-null    int64
dtypes: float64(1), int64(1)
memory usage: 612.0 bytes
```

df.dropna(inplace=True)

df.info()

```

<class 'pandas.core.frame.DataFrame'>
RangeIndex: 30 entries, 0 to 29
Data columns (total 2 columns):
#   Column          Non-Null Count  Dtype
---  -
0   YearsExperience  30 non-null    float64
1   Salary          30 non-null    int64
dtypes: float64(1), int64(1)
memory usage: 612.0 bytes
df.describe()

```

	YearsExperience	Salary
count	30.000000	30.000000
mean	5.313333	76003.000000
std	2.837888	27414.429785
min	1.100000	37731.000000
25%	3.200000	56720.750000
50%	4.700000	65237.000000
75%	7.700000	100544.750000
max	10.500000	122391.000000

```

features=df.iloc[:,[0]].values      label=df.iloc[:,[1]].values      from
sklearn.model_selection              import          train_test_split
x_train,x_test,y_train,y_test=train_test_split(features,label,test_size=0.2,random_s
t from sklearn.linear_model import LinearRegression model=LinearRegression()
model.fit(x_train,y_train)

```

```

LinearRegression
LinearRegression()

```

```
model.score(x_train,y_train)
```

```
0.9603182547438908
```

```
model.score(x_test,y_test)
```

```
0.9184170849214232
```

```
model.coef_
```

```
array([[9281.30847068]])
```

```
model.intercept_
```

```
array([27166.73682891])
```

```

import pickle
pickle.dump(model,open('SalaryPred.model','wb'))
model=pickle.load(open('SalaryPred.model','rb'))
yr_of_exp=float(input("Enter Years of Experience:
")) yr_of_exp_NP=np.array([[yr_of_exp]])

Salary=model.predict(yr_of_exp_NP)

Enter Years of Experience: 44

print("Estimated Salary for {} years of experience is {}".format(yr_of_exp,Salary)

Estimated Salary for 44.0 years of experience is [[435544.30953887]]:

```

```

#PANDAS FUNCTIONS import
numpy as np import pandas as pd
list=[[1,'Smith',50000],[2,'Jones',60000
]] df=pd.DataFrame(list)

df

```

	0	1	2
0	1	Smith	50000
1	2	Jones	60000

```

df.columns=['Empd','Name','Salary']

df

```

	Empd	Name	Salary
0	1	Smith	50000
1	2	Jones	60000

```

df.info()

```

```

<class 'pandas.core.frame.DataFrame'>
RangeIndex: 2 entries, 0 to 1
Data columns (total 3 columns):
#   Column  Non-Null Count  Dtype
---  -
0   Empd    2 non-null        int64
1   Name    2 non-null        object
2   Salary  2 non-null        int64
dtypes: int64(2), object(1)
memory usage: 176.0+ bytes

```

```

df=pd.read_csv("/content/50_Startups.csv")
df.info()

```

```

<class 'pandas.core.frame.DataFrame'>
RangeIndex: 50 entries, 0 to 49
Data columns (total 5 columns):
#   Column          Non-Null Count  Dtype
---  ---
0    R&D Spend      50 non-null    float64
1    Administration 50 non-null    float64
2    Marketing Spend 50 non-null    float64
3    State           50 non-null    object
4    Profit          50 non-null    float64
dtypes: float64(4), object(1)
memory usage: 2.1+ KB

```

df.head()

df.tail()

import numpy as np import pandas as pd

df = pd.read_csv("/content/employee.csv")

df.head()

df.tail()

```

<class 'pandas.core.frame.DataFrame'>
RangeIndex: 7 entries, 0 to 6
Data columns (total 3 columns):
#   Column  Non-Null Count  Dtype
---  ---
0    emp id  7 non-null      int64
1    name    7 non-null      object
2    salary  7 non-null      int64
dtypes: int64(2), object(1)
memory usage: 296.0+ bytes

```

df.info()

df.salary()

salary	
0	5000
1	6000
2	7000
3	5000
4	8000
5	3000
6	6000

type(df.salary)

```

df.salary.mean()
df.salary.median()

↔ 6000.0

df.salary.mode()

↔
  salary
0    5000
1    6000

df.salary.var()

↔ 2571428.5714285714

df.salary.std()

↔ 1603.5674514745463

```

```

empCol=df.columns
empCol

```

```

Index(['emp id', 'name ', 'salary'], dtype='object')

```

```

emparray=df.values
employee_DF=pd.DataFrame(emparray,columns=empCol) #OUTLIER
DETECTION

```

```

#KALEES PANDI.T

```

```

#230701135 #13/08/24 import numpy as np array=np.random.randint(1,100,16) #
randomly generate 16 numbers between 1 to 100 array

```

```

#array([21, 72, 69, 45, 61, 43, 43, 59, 62, 42, 90, 25, 54, 86, 80, 13], dtype=int32)
array.mean()          np.percentile(array,25)          np.percentile(array,50)
np.percentile(array,75) np.percentile(array,100) #outliers detection def
outDetection(array):

```

```

    sorted(array)

```

```

    Q1,Q3=np.percentile(array,[25,75])

```

```

    ) IQR=Q3-Q1 lr=Q1-(1.5*IQR)

```

```

    ur=Q3+(1.5*IQR)

```

```

    return lr,ur lr,ur=outDetection(array)


```

```
lr,ur
```


```
import seaborn as sns
```

```
%matplotlib inline
```

```
sns.displot(array)
```




```
sns.distplot(array)
```



```
new_array=array[(array>lr) & (array<ur)]
```

```
new_array
```


```
sns.displot(new_array)
```




```
lr1,ur1=outDetection(new_array)
```

```
lr1,ur1 final_array=new_array[(new_array>lr1) & (new_array<ur1)] final_array
```

```
sns.distplot(final_array)
```



```
#Experiment_03

#KALEES PANDI.T

#230701135 #20/08/24 import
numpy as np import pandas as pd
df=pd.read_csv("Hotel_Dataset.csv"
)

df
```

	CustomerID	Age_Group	Rating(1-5)	Hotel	FoodPreference	Bill	NoOfPax	EstimatedSalary	Age_Group.1
0	1	20-25	4	Ibis	veg	1300	2	40000	20-25
1	2	30-35	5	LemonTree	Non-Veg	2000	3	59000	30-35
2	3	25-30	6	RedFox	Veg	1322	2	30000	25-30
3	4	20-25	-1	LemonTree	Veg	1234	2	120000	20-25
4	5	35+	3	Ibis	Vegetarian	989	2	45000	35+
5	6	35+	3	Ibys	Non-Veg	1909	2	122220	35+
6	7	35+	4	RedFox	Vegetarian	1000	-1	21122	35+
7	8	20-25	7	LemonTree	Veg	2999	-10	345673	20-25
8	9	25-30	2	Ibis	Non-Veg	3456	3	-99999	25-30
9	9	25-30	2	Ibis	Non-Veg	3456	3	-99999	25-30
10	10	30-35	5	RedFox	non-Veg	-6755	4	87777	30-35

```
df.duplicated()
```

```
0    False
1    False
2    False
3    False
4    False
5    False
6    False
7    False
8    False
9     True
10   False
dtype: bool
```

```
df.info()
```

```

<class 'pandas.core.frame.DataFrame'>
RangeIndex: 11 entries, 0 to 10
Data columns (total 9 columns):
#   Column                Non-Null Count  Dtype
---  ---
0   CustomerID            11 non-null    int64
1   Age_Group              11 non-null    object
2   Rating(1-5)           11 non-null    int64
3   Hotel                  11 non-null    object
4   FoodPreference         11 non-null    object
5   Bill                  11 non-null    int64
6   NoOfPax               11 non-null    int64
7   EstimatedSalary        11 non-null    int64
8   Age_Group.1           11 non-null    object
dtypes: int64(5), object(4)
memory usage: 924.0+ bytes

```

```
df.drop_duplicates(inplace=True)
```

```
df
```

	CustomerID	Age_Group	Rating(1-5)	Hotel	FoodPreference	Bill	NoOfPax	EstimatedSalary	Age_Group.1
0	1	20-25	4	Ibis	veg	1300	2	40000	20-25
1	2	30-35	5	LemonTree	Non-Veg	2000	3	59000	30-35
2	3	25-30	6	RedFox	Veg	1322	2	30000	25-30
3	4	20-25	-1	LemonTree	Veg	1234	2	120000	20-25
4	5	35+	3	Ibis	Vegetarian	989	2	45000	35+
5	6	35+	3	Ibys	Non-Veg	1909	2	122220	35+
6	7	35+	4	RedFox	Vegetarian	1000	-1	21122	35+
7	8	20-25	7	LemonTree	Veg	2999	-10	345673	20-25
8	9	25-30	2	Ibis	Non-Veg	3456	3	-99999	25-30
10	10	30-35	5	RedFox	non-Veg	-6755	4	87777	30-35

```
len(df)
```

```
index=np.array(list(range(0,len(df))
```

```
)) df.set_index(index,inplace=True)
```

```
index array([0, 1, 2, 3, 4, 5, 6, 7, 8,
```

```
9]) df
```

	CustomerID	Age_Group	Rating(1-5)	Hotel	FoodPreference	Bill	NoOfPax	EstimatedSalary	Age_Group.1
0	1	20-25	4	Ibis	veg	1300	2	40000	20-25
1	2	30-35	5	LemonTree	Non-Veg	2000	3	59000	30-35
2	3	25-30	6	RedFox	Veg	1322	2	30000	25-30
3	4	20-25	-1	LemonTree	Veg	1234	2	120000	20-25
4	5	35+	3	Ibis	Vegetarian	989	2	45000	35+
5	6	35+	3	Ibys	Non-Veg	1909	2	122220	35+
6	7	35+	4	RedFox	Vegetarian	1000	-1	21122	35+
7	8	20-25	7	LemonTree	Veg	2999	-10	345673	20-25
8	9	25-30	2	Ibis	Non-Veg	3456	3	-99999	25-30
9	10	30-35	5	RedFox	non-Veg	-6755	4	87777	30-35

```
df.drop(['Age_Group.1'],axis=1,inplace=True)
```

```
df
```

```
df.CustomerID.loc[df.CustomerID<0]=np.nan
```

```
df.Bill.loc[df.Bill<0]=np.nan
```

```
df.EstimatedSalary.loc[df.EstimatedSalary<0]=np.nan
```

df

	CustomerID	Age_Group	Rating(1-5)	Hotel	FoodPreference	Bill	NoOfPax	EstimatedSalary
0	1.0	20-25	4.0	Ibis	veg	1300.0	2	40000.0
1	2.0	30-35	5.0	LemonTree	Non-Veg	2000.0	3	59000.0
2	3.0	25-30	NaN	RedFox	Veg	1322.0	2	30000.0
3	4.0	20-25	NaN	LemonTree	Veg	1234.0	2	120000.0
4	5.0	35+	3.0	Ibis	Vegetarian	989.0	2	45000.0
5	6.0	35+	3.0	Ibys	Non-Veg	1909.0	2	122220.0
6	7.0	35+	4.0	RedFox	Vegetarian	1000.0	-1	21122.0
7	8.0	20-25	NaN	LemonTree	Veg	2999.0	-10	345673.0
8	9.0	25-30	2.0	Ibis	Non-Veg	3456.0	3	NaN
9	10.0	30-35	5.0	RedFox	non-Veg	NaN	4	87777.0

```
df['NoOfPax'].loc[(df['NoOfPax']<1) | (df['NoOfPax']>20)]=np.nan
```

df

```
df.Age_Group.unique()
```

```
array(['20-25', '30-35', '25-30', '35+'], dtype=object)
```

```
df.Hotel.unique()
```

```
array(['Ibis', 'LemonTree', 'RedFox', 'Ibys'], dtype=object)
```

```
df.Hotel.replace(['Ibys'],'Ibis',inplace=True)
```

```
df.FoodPreference.unique
```

```
<bound method Series.unique of 0          veg
1      Non-Veg
2      Veg
3      Veg
4      Vegetarian
5      Non-Veg
6      Vegetarian
7      Veg
8      Non-Veg
9      non-Veg
Name: FoodPreference, dtype: object>
```

```
df.FoodPreference.replace(['Vegetarian','veg'],'Veg',inplace=True)
```

```
df.FoodPreference.replace(['non-Veg'],'Non-Veg',inplace=True)
```

```
df.EstimatedSalary.fillna(round(df.EstimatedSalary.mean()),inplace=True)
```

```
df.NoOfPax.fillna(round(df.NoOfPax.median()),inplace=True)
```

```
df['Rating(1-5)'].fillna(round(df['Rating(1-5)'].median()), inplace=True)
```

```
df.Bill.fillna(round(df.Bill.mean()),inplace=True) df
```

CustomerID	Age_Group	Rating(1-5)	Hotel	FoodPreference	Bill	NoOfPax	EstimatedSalary	
0	1.0	20-25	4.0	Ibis	Veg	1300.0	2.0	40000.0
1	2.0	30-35	5.0	LemonTree	Non-Veg	2000.0	3.0	59000.0
2	3.0	25-30	4.0	RedFox	Veg	1322.0	2.0	30000.0
3	4.0	20-25	4.0	LemonTree	Veg	1234.0	2.0	120000.0
4	5.0	35+	3.0	Ibis	Veg	989.0	2.0	45000.0
5	6.0	35+	3.0	Ibis	Non-Veg	1909.0	2.0	122220.0
6	7.0	35+	4.0	RedFox	Veg	1000.0	2.0	21122.0
7	8.0	20-25	4.0	LemonTree	Veg	2999.0	2.0	345673.0
8	9.0	25-30	2.0	Ibis	Non-Veg	3456.0	3.0	96755.0
9	10.0	30-35	5.0	RedFox	Non-Veg	1801.0	4.0	87777.0

```
#Experiment_04
```

```
#KALEES PANDI.T
```

```
#230701135 #27/08/24 import numpy as np import
```

```
pandas as pd df=pd.read_csv("/content/pre-
```

```
process_datasample.csv")
```

```
df
```

	Country	Age	Salary	Purchased
0	France	44.0	72000.0	No
1	Spain	27.0	48000.0	Yes
2	Germany	30.0	54000.0	No
3	Spain	38.0	61000.0	No
4	Germany	40.0	NaN	Yes
5	France	35.0	58000.0	Yes
6	Spain	NaN	52000.0	No
7	France	48.0	79000.0	Yes
8	NaN	50.0	83000.0	No
9	France	37.0	67000.0	Yes

```
df.info()
```

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 10 entries, 0 to 9
Data columns (total 4 columns):
#   Column      Non-Null Count  Dtype
---  ---
0   Country     9 non-null     object
1   Age         9 non-null     float64
2   Salary      9 non-null     float64
3   Purchased   10 non-null    object
dtypes: float64(2), object(2)
memory usage: 448.0+ bytes
```

```
df.Country.mode()
```

```
Country
0  France
```

```
df.Country.mode()[0] type(df.Country.mode())
```

```
df.Country.fillna(df.Country.mode()[0],inplace=True
```

```
e) df.Age.fillna(df.Age.median(),inplace=True)
```

```
df.Salary.fillna(round(df.Salary.mean()),inplace=True
```

```
e)
```

```
df
```

	Country	Age	Salary	Purchased
0	France	44.0	72000.0	No
1	Spain	27.0	48000.0	Yes
2	Germany	30.0	54000.0	No
3	Spain	38.0	61000.0	No
4	Germany	40.0	63778.0	Yes
5	France	35.0	58000.0	Yes
6	Spain	38.0	52000.0	No
7	France	48.0	79000.0	Yes
8	France	50.0	83000.0	No

```
pd.get_dummies(df.Country)
```

```
updated_dataset=pd.concat([pd.get_dummies(df.Country),df.iloc[:,[1,2,3]]],axis=1)
```

```
France Germany Spain Age Salary Purchased
```

```
0 True False False 44.0 72000.0 No
```

```
1 False False True 27.0 48000.0 Yes
```

```
2 False True False 30.0 54000.0 No
```

```
3 False False True 38.0 61000.0 No
```

```
4 False True False 40.0 63778.0 Yes
```

```
5 True False False 35.0 58000.0 Yes
```

```
6 False False True 38.0 52000.0 No
```

```
7 True False False 48.0 79000.0 Yes
```

```
8 True False False 50.0 83000.0 No
```

```
9 True False False 37.0 67000.0 Yes df.info()
```

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 10 entries, 0 to 9
Data columns (total 4 columns):
#   Column      Non-Null Count  Dtype
---  -
0   Country     10 non-null    object
1   Age         10 non-null    float64
2   Salary      10 non-null    float64
3   Purchased   10 non-null    object
dtypes: float64(2), object(2)
memory usage: 448.0+ bytes
```

```
updated_dataset.Purchased.replace(['No','Yes'],[0,1],inplace=True) updated_dataset
```

	France	Germany	Spain	Age	Salary	Purchased
0	True	False	False	44.0	72000.0	0
1	False	False	True	27.0	48000.0	1
2	False	True	False	30.0	54000.0	0
3	False	False	True	38.0	61000.0	0
4	False	True	False	40.0	63778.0	1
5	True	False	False	35.0	58000.0	1
6	False	False	True	38.0	52000.0	0
7	True	False	False	48.0	79000.0	1
8	True	False	False	50.0	83000.0	0
9	True	False	False	37.0	67000.0	1

```
# EDA
```

```
#Experiment_01
```

```
#KALEES PANDI.T
```

```
#230701135
```

```
#03/09/24
```

```
import seaborn as sns import
```

```
pandas as pd import numpy as
```

```
np import matplotlib.pyplot as
```


```
plt %matplotlib inline
```

```
tips=sns.load_dataset('tips')
```


```
tips.head()
```

	total_bill	tip	sex	smoker	day	time	size
0	16.99	1.01	Female	No	Sun	Dinner	2
1	10.34	1.66	Male	No	Sun	Dinner	3
2	21.01	3.50	Male	No	Sun	Dinner	3
3	23.68	3.31	Male	No	Sun	Dinner	2
4	24.59	3.61	Female	No	Sun	Dinner	4


```
sns.displot(tips.total_bill,kde=True)
```




```
sns.jointplot(x=tips.tip,y=tips.total_bill)
```


```
sns.jointplot(x=tips.tip,y=tips.total_bill,kind="reg")
```




```
sns.jointplot(x=tips.tip,y=tips.total_bill,kind="hex")
```




```
sns.pairplot(tips)
```




```
sns.heatmap(tips.corr(numeric_only=True),annot=True)
```



```
sns.boxplot(tips.total_bill)
```





```
sns.countplot(tips.sex)
```



```
tips.sex.value_counts().plot(kind='pie')
```

```
tips.sex.value_counts().plot(kind='bar')
```



```
#Random Sampling and Sampling Distribution
```

```
#KALEES PANDI.T
```

```
#230701135
```

```
#10/09/24
```

```

import numpy as np
import matplotlib.pyplot as plt

population_mean = 50
population_std = 10
population_size = 100000
population = np.random.normal(population_mean, population_std, population_size)

plt.figure(figsize=(8, 5))
plt.hist(population, bins=50, color='skyblue', edgecolor='black', alpha=0.7)
plt.title('Population Distribution')
plt.xlabel('Value')
plt.ylabel('Frequency')
plt.axvline(population_mean, color='red', linestyle='dashed', linewidth=1.5, label='Population Mean')
plt.legend()
plt.show()


sample_sizes = [30, 50, 100]
num_samples = 1000
sample_means = {}

for size in sample_sizes:
    sample_means[size] = []
    for _ in range(num_samples):
        sample = np.random.choice(population, size=size, replace=False)
        sample_means[size].append(np.mean(sample))

plt.figure(figsize=(12, 8))
for i, size in enumerate(sample_sizes):
    plt.subplot(len(sample_sizes), 1, i + 1)
    plt.hist(sample_means[size], bins=30, alpha=0.7, color='orange', edgecolor='black', label=f'Sample Size {size}')
    plt.axvline(np.mean(population), color='red', linestyle='dashed', linewidth=1.5, label='Population Mean')
    plt.title(f'Sampling Distribution of the Sample Mean (Sample Size {size})')
    plt.xlabel('Sample Mean')
    plt.ylabel('Frequency')
    plt.legend()
    plt.tight_layout()
    plt.show()

plt.figure(figsize=(12, 8))
for i, size in enumerate(sample_sizes):
    plt.subplot(len(sample_sizes), 1, i + 1)
    plt.hist(sample_means[size], bins=30, alpha=0.7, color='purple', edgecolor='black', label=f'Sample Size {size}', density=True)
    plt.axvline(np.mean(population), color='red', linestyle='dashed', linewidth=1.5, label='Population Mean')
    plt.title(f'Sampling Distribution (Sample Size {size}) - CLT Demonstration')
    plt.xlabel('Sample Mean')
    plt.ylabel('Density')
    plt.legend()
    plt.tight_layout()
    plt.show()

```



#KALEES PANDI.T

#230701135

#10/09/24

#Z_TEST

```
import numpy as np
import scipy.stats as stats
sample_data = np.array([
152, 148, 151, 149, 147, 153, 150, 148, 152, 149,
151, 150, 149, 152, 151, 148, 150, 152, 149, 150,
148, 153, 151, 150, 149, 152, 148, 151, 150, 153
])
population_mean = 150 sample_mean =
np.mean(sample_data) sample_std =
np.std(sample_data, ddof=1) n =
len(sample_data)
z_statistic = (sample_mean - population_mean) / (sample_std / np.sqrt(n))
p_value = 2 * (1 - stats.norm.cdf(np.abs(z_statistic)))
print(f'Sample Mean: {sample_mean:.2f}')
print(f'Z-Statistic: {z_statistic:.4f}') print(f'P-
Value: {p_value:.4f}') alpha = 0.05 if p_value <
alpha:
print("Reject the null hypothesis: The average weight is significantly different from 150 grams.")
else: print("Fail to reject the null hypothesis: There is no significant difference in average weight
from 150 grams.")
```

```
Sample Mean: 150.20
Z-Statistic: 0.6406
P-Value: 0.5218
Fail to reject the null hypothesis: There is no significant difference in average weight from 150 grams.
```

T-Test

230701135

KALEES PANDI.T

08.10.2024

```
import numpy as np import scipy.stats as stats np.random.seed(42)
sample_size = 25 sample_data = np.random.normal(loc=102, scale=15,
size=sample_size) population_mean = 100 sample_mean =
np.mean(sample_data) sample_std = np.std(sample_data, ddof=1) n =
```

```

len(sample_data) t_statistic, p_value = stats.ttest_1samp(sample_data,
population_mean) print(f"Sample Mean: {sample_mean:.2f}")

print(f"T-Statistic:
{t_statistic:.4f}") print(f"P-Value:
{p_value:.4f}") alpha = 0.05 if
p_value < alpha:

print("Reject the null hypothesis: The average IQ score is significantly different from 100.")
else:

print("Fail to reject the null hypothesis: There is no significant difference in average IQ score from
100."

```

```

Sample Mean: 99.55
T-Statistic: -0.1577
P-Value: 0.8760
Fail to reject the null hypothesis: There is no significant difference in average IQ score from 100.

```

ANOVATEST

230701135

KALEES PANDI.T

08.10.2024

```

import numpy as np
import scipy.stats as stats
np.random.seed(42)
n_plants = 25
growth_A = np.random.normal(loc=10, scale=2, size=n_plants)
growth_B = np.random.normal(loc=12, scale=3, size=n_plants)
growth_C = np.random.normal(loc=15, scale=2.5, size=n_plants)
f_statistic, p_value = stats.f_oneway(growth_A, growth_B,
growth_C) print("Treatment A Mean Growth:", np.mean(growth_A))
print("Treatment B Mean Growth:", np.mean(growth_B))
print("Treatment C Mean Growth:", np.mean(growth_C))
print() print(f"F-Statistic: {f_statistic:.4f}") print(f"P-
Value: {p_value:.4f}") alpha = 0.05 if p_value < alpha:
print("Reject the null hypothesis: There is a significant difference in mean growth rates among
the three treatments.") else:
print("Fail to reject the null hypothesis: There is no significant difference in mean growth rates
among the three treatments.") if p_value < alpha:
all_data = np.concatenate([growth_A, growth_B, growth_C])
treatment_labels = ['A'] * n_plants + ['B'] * n_plants + ['C'] * n_plants
tukey_results = pairwise_tukeyhsd(all_data, treatment_labels, alpha=0.05)
print("\nTukey's HSD Post-hoc Test:") print(tukey_results)

```

```
Treatment A Mean Growth: 9.672983882683818
Treatment B Mean Growth: 11.137680744437432
Treatment C Mean Growth: 15.265234904828972

F-Statistic: 36.1214
P-Value: 0.0000
Reject the null hypothesis: There is a significant difference in mean growth rates among the three treatments.
```

Feature Scaling

#KALEES PANDI.T

#230701135

#20/10/24 import numpy as np import pandas as pd df =

pd.read_csv('/content/pre-process_datasample.csv')

df

```
Country Age Salary Purchased
0 France 44.0 72000.0 No
1 Spain 27.0 48000.0 Yes
2 Germany 30.0 54000.0 No
3 Spain 38.0 61000.0 No
4 Germany 40.0 NaN Yes
5 France 35.0 58000.0 Yes
6 Spain NaN 52000.0 No
7 France 48.0 79000.0 Yes
8 NaN 50.0 83000.0 No
9 France 37.0 67000.0 Yes
```

df['Country'].fillna(df['Country'].mode()[0],

inplace=True) features = df.iloc[:, :-1].values label =

df.iloc[:, -1].values

from sklearn.impute import SimpleImputer age_imputer =

SimpleImputer(strategy="mean") salary_imputer =

SimpleImputer(strategy="mean")

age_imputer.fit(features[:, [1]])

salary_imputer.fit(features[:, [2]]) features[:, [1]] =

age_imputer.transform(features[:, [1]]) features[:, [2]] =

salary_imputer.transform(features[:, [2]]) print("Features

after handling missing values:") features


```
array([[ 'France', 44.0, 72000.0],
       [ 'Spain', 27.0, 48000.0],
       [ 'Germany', 30.0, 54000.0],
       [ 'Spain', 38.0, 61000.0],
       [ 'Germany', 40.0, 63777.77777777778],
       [ 'France', 35.0, 58000.0],
       [ 'Spain', 38.77777777777778, 52000.0],
       [ 'France', 48.0, 79000.0],
       [ 'France', 50.0, 83000.0],
       [ 'France', 37.0, 67000.0]], dtype=object)
```

```
from sklearn.preprocessing import OneHotEncoder
oh = OneHotEncoder(sparse_output=False)
Country = oh.fit_transform(features[:, [0]])
print("OneHotEncoded 'Country' column:")
```

Country

```
array([[1., 0., 0.],
       [0., 0., 1.],
       [0., 1., 0.],
       [0., 0., 1.],
       [0., 1., 0.],
       [1., 0., 0.],
       [0., 0., 1.],
       [1., 0., 0.]])
```

```
final_set = np.concatenate((Country, features[:, [1, 2]]), axis=1)
print("Final dataset with OneHotEncoded 'Country' and other features:")
final_set
```

```
array([[1.0, 0.0, 0.0, 44.0, 72000.0],
       [0.0, 0.0, 1.0, 27.0, 48000.0],
       [0.0, 1.0, 0.0, 30.0, 54000.0],
       [0.0, 0.0, 1.0, 38.0, 61000.0],
       [0.0, 1.0, 0.0, 40.0, 63777.77777777778],
       [1.0, 0.0, 0.0, 35.0, 58000.0],
       [0.0, 0.0, 1.0, 38.77777777777778, 52000.0],
       [1.0, 0.0, 0.0, 48.0, 79000.0],
       [1.0, 0.0, 0.0, 50.0, 83000.0],
       [1.0, 0.0, 0.0, 37.0, 67000.0]], dtype=object)
```

```
from sklearn.preprocessing import StandardScaler sc
= StandardScaler()
```

```

sc.fit(final_set) feat_standard_scaler =
sc.transform(final_set) print("Standardized
features:")

feat_standard_scaler

array([[ 1.00000000e+00, -5.00000000e-01, -6.54653671e-01,
        7.58874362e-01, 7.49473254e-01],
       [-1.00000000e+00, -5.00000000e-01, 1.52752523e+00,
        -1.71150388e+00, -1.43817841e+00],
       [-1.00000000e+00, 2.00000000e+00, -6.54653671e-01,
        -1.27555478e+00, -8.91265492e-01],
       [-1.00000000e+00, -5.00000000e-01, 1.52752523e+00,
        -1.13023841e-01, -2.53200424e-01],
       [-1.00000000e+00, 2.00000000e+00, -6.54653671e-01,
        1.77608893e-01, 6.63219199e-16],
       [ 1.00000000e+00, -5.00000000e-01, -6.54653671e-01,
        -5.48972942e-01, -5.26656882e-01],
       [-1.00000000e+00, -5.00000000e-01, 1.52752523e+00,
        0.00000000e+00, -1.07356980e+00],
       [ 1.00000000e+00, -5.00000000e-01, -6.54653671e-01,
        1.34013983e+00, 1.38753832e+00],
       [ 1.00000000e+00, -5.00000000e-01, -6.54653671e-01,
        1.63077256e+00, 1.75214693e+00],
       [ 1.00000000e+00, -5.00000000e-01, -6.54653671e-01,
        -2.58340208e-01, 2.93712492e-01]])

```

```

from sklearn.preprocessing import MinMaxScaler
mms = MinMaxScaler(feature_range=(0, 1))
mms.fit(final_set) feat_minmax_scaler =
mms.transform(final_set) print("Normalized
features:") print(feat_minmax_scaler)

```

```

array([[1. , 0. , 0. , 0.73913043, 0.68571429],
       [0. , 0. , 1. , 0. , 0. ],
       [0. , 1. , 0. , 0.13043478, 0.17142857],
       [0. , 0. , 1. , 0.47826087, 0.37142857],
       [0. , 1. , 0. , 0.56521739, 0.45079365],
       [1. , 0. , 0. , 0.34782609, 0.28571429],
       [0. , 0. , 1. , 0.51207729, 0.11428571],
       [1. , 0. , 0. , 0.91304348, 0.88571429],
       [1. , 0. , 0. , 1. , 1. ],
       [1. , 0. , 0. , 0.43478261, 0.54285714]])
# Linear Regression

#KALEES PANDI.T

#230701135

#29/10/24 import numpy as np

import pandas as pd

```

```
df=pd.read_csv('Salary_data.csv')
df.info()
df.dropna(inplace=True)
df.info() df.describe()
```

```
YearsExperience Salary count 30.000000
30.000000 mean 5.313333 76003.000000 std 2.837888
27414.429785
min 1.100000 37731.000000
25% 3.200000 56720.750000
50% 4.700000 65237.000000
75% 7.700000 100544.750000
max 10.500000 122391.000000
```

```
features=df.iloc[:,[0]].values label=df.iloc[:,[1]].values from sklearn.model_selection
import train_test_split
x_train,x_test,y_train,y_test=train_test_split(features,label,test_size=0.2,random_state=23
) from sklearn.linear_model import LinearRegression model=LinearRegression()
model.fit(x_train,y_train) model.score(x_train,y_train) model.score(x_test,y_test)
model.coef_ model.intercept_
import pickle pickle.dump(model,open('SalaryPred.model','wb'))
model=pickle.load(open('SalaryPred.model','rb')) yr_of_exp=float(input("Enter
Years of Experience: ")) yr_of_exp_NP=np.array([[yr_of_exp]])
Salary=model.predict(yr_of_exp_NP) print("Estimated Salary for {} years of
experience is {}: ".format(yr_of_exp,Salary))
```

```

# Logistic Regression

#KALEES PANDI.T

#230701135

#29/10/24 import numpy as np
import pandas as pd

df=pd.read_csv('Social_Network_Ads.csv')

df

User ID Gender Age EstimatedSalary Purchased
0 15624510 Male 19 19000 0
1 15810944 Male 35 20000 0
2 15668575 Female 26 43000 0
3 15603246 Female 27 57000 0
4 15804002 Male 19 76000 0
... ..
395 15691863 Female 46 41000 1
396 15706071 Male 51 23000 1
397 15654296 Female 50 20000 1
398 15755018 Male 36 33000 0
399 15594041 Female 49 36000 1

400 rows × 5 columns

df.head()

User ID Gender Age EstimatedSalary Purchased
0 15624510 Male 19 19000 0
1 15810944 Male 35 20000 0
2 15668575 Female 26 43000 0
3 15603246 Female 27 57000 0
4 15804002 Male 19 76000 0

features=df.iloc[:,[2,3]].values
s_label=df.iloc[:,4].values

features_label

```

```
array([0, 0, 0, 0, 0, 0, 0, 1, 0, 0, 0, 0, 0, 0, 0, 0, 1, 1, 1, 1, 1, 1,
1, 1, 1, 1, 1, 1, 0, 0, 0, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0,
0, 0, 0, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 1, 0, 0, 0, 0,
0, 0, 0, 0, 0, 0, 0, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 1, 0, 0, 0, 0, 0,
0, 0, 0, 0, 0, 0, 1, 0, 0, 0, 0, 0, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0,
0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0,
1, 0, 0, 0, 0, 0, 0, 0, 0, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0,
1, 0, 0, 0, 0, 0, 0, 0, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0,
0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 1, 0, 1, 0,
1, 0, 1, 0, 1, 1, 0, 0, 0, 1, 0, 0, 0, 1, 0, 1, 1, 1, 0, 0, 1, 1, 0,
1, 1, 0, 1, 1, 0, 1, 0, 0, 0, 1, 1, 0, 1, 1, 0, 1, 0, 1, 0, 0,
1, 1, 0, 1, 0, 0, 1, 1, 0, 1, 1, 0, 1, 0, 0, 1, 0, 0, 1, 1, 1, 1,
1, 0, 1, 1, 1, 1, 0, 1, 1, 0, 1, 0, 1, 1, 1, 1, 0, 0, 0, 1, 1,
0, 1, 1, 1, 1, 1, 0, 0, 0, 1, 1, 0, 0, 1, 0, 1, 0, 1, 1, 0, 1, 0, 1,
1, 0, 1, 1, 0, 0, 0, 1, 1, 0, 1, 0, 0, 1, 0, 1, 0, 0, 1, 1, 0, 0, 1,
1, 0, 1, 1, 0, 0, 1, 0, 1, 0, 1, 1, 1, 0, 1, 0, 1, 1, 1, 0, 1, 1, 1,
1, 0, 1, 1, 1, 0, 1, 0, 1, 0, 0, 1, 1, 0, 1, 1, 1, 1, 1, 0, 1, 1,
1, 1, 1, 1, 0, 1, 1, 1, 0, 1], dtype=int64)
```

```
from sklearn.model_selection import train_test_split
from sklearn.linear_model import LogisticRegression
for i in range(1,401):

x_train,x_test,y_train,y_test=train_test_split(features,label,test_size=0.2,random_state=i)

model=LogisticRegression()

model.fit(x_train,y_train)

train_score=model.score(x_train,y_train
) test_score=model.score(x_test,y_test)

if test_score>train_score:

print("Test {} Train {} Random State {}".format(test_score,train_score,i)

x_train,x_test,y_train,y_test=train_test_split(features,label,test_size=0.2,random_state=314
) finalModel=LogisticRegression() finalModel.fit(x_train,y_train)

print(finalModel.score(x_train,y_train)) print(finalModel.score(x_test,y_test)) from

sklearn.metrics import classification_report

print(classification_report(label,finalModel.predict(features)))

# K-MEANS CLUSTERING

#KALEES PANDI.T

#230701135 #05/11/24 import numpy

as np import pandas as pd import
```

```

matplotlib.pyplot as plt
import
seaborn as sns %matplotlib inline
df=pd.read_csv('Mall_Customers.csv'
)

```

```
df.info()
```

```


<class 'pandas.core.frame.DataFrame'>
RangeIndex: 200 entries, 0 to 199
Data columns (total 5 columns):
#   Column              Non-Null Count  Dtype
---  -
0   CustomerID          200 non-null    int64
1   Gender              200 non-null    object
2   Age                 200 non-null    int64
3   Annual Income (k$)  200 non-null    int64
4   Spending Score (1-100) 200 non-null    int64
dtypes: int64(4), object(1)
memory usage: 7.9+ KB

```

```
df.head()
```

	CustomerID	Gender	Age	Annual Income (k\$)	Spending Score (1-100)
0	1	Male	19	15	39
1	2	Male	21	15	81
2	3	Female	20	16	6
3	4	Female	23	16	77
4	5	Female	31	17	40

```
sns.pairplot(df)
```



```
features=df.iloc[:,[3,4]].values from
```

```
sklearn.cluster import KMeans
```



```
model=KMeans(n_clusters=5)
```

```
model.fit(features)
```

```
KMeans(n_clusters=5)
```

```
KMeans(n_clusters=5)
```

In a Jupyter environment, please rerun this cell to show the HTML representation or trust the notebook.

On GitHub, the HTML representation is unable to render, please try loading this page with nbviewer.org.

```
Final=df.iloc[:,[3,4]]
```

```
Final['label']=model.predict(features)
```

```
Final.head()
```

	Annual Income (k\$)	Spending Score (1-100)	label
0	15	39	4
1	15	81	2
2	16	6	4
3	16	77	2
4	17	40	4


```
sns.set_style("whitegrid")
```

```
sns.FacetGrid(Final,hue="label",height=8) \
```

```
.map(plt.scatter,"Annual Income (k$)", "Spending Score (1-100)") \
```

```
.add_legend();
```

```
plt.show()
```



```
features_el=df.iloc[:,[2,3,4]].values  
from sklearn.cluster import KMeans  
wcss=[] for i in range(1,10):  
  
model=KMeans(n_clusters=i)  
model.fit(features_el)  
wcss.append(model.inertia_)  
plt.plot(range(1,10),wcss)
```

