

# YAMLvars

a YAML variable parser for LuaLaTeX

Kale Ewasiuk (kalekje@gmail.com)

2023-08-06

YAMLvars is a LuaLaTeX-based package to help make definitions or produce LaTeX code using a YAML file. This package might be useful for you if you want to batch create documents by pushing various sets YAML data to a fixed LaTeX template, or just find it easier to read document metadata from a YAML file compared to the standard title, author, etc. commands.

## 1 Package Options

**useyv** By default, when you specify a YAML variable, it will be defined using `\gdef` (only if it wasn't defined previously). If you use this setting, unless otherwise specified, YAML variables will be accessible under the `\yvv{<var>}` command. This also allows numbers and symbols in the variable names. Note that internally, the variables are stored in the command sequence `yv--<var>`.

**parseCLI** If this option is enabled, any arguments passed to your `lualatex` compile command that end in ".yaml" will be used, separated by a space. If two yaml files are passed, the first one will be the declaration file, and the second will be the parsing file. They will be used at the beginning of the document. If one yaml file is passed, it will be treated as a parsing file, so you should declare the variables somewhere in the preamble. This option is offered to help with automation scripts. An example is shown in Section 8.

**allowundeclared** It might be helpful to define something in your YAML parsing doc without declaring it. If you want this flexibility, use this setting. Note that existing definitions will not be overwritten and an error will be thrown if the name exists. Alternatively, you can use the commands `\AllowUndeclaredYV` or `\ForbidUndeclaredYV` to toggle this behavior.

**overwritedefs** Danger! This will allow you to `\gdef` commands with YAML. Caution should be taken to not set definitions like `\begin`, `\section`, etc.

## 2 Dependencies

**Note:** This package requires the `tinyyaml` package, available on CTAN.

The distribution: <https://github.com/api7/luatinyyaml>

<https://ctan.org/pkg/luatinyyaml>

The YAML specification: <https://yaml.org/spec/>

Many of the “transform” and “processing” functions built-in to this package rely on other packages, like `hyperref`, or `xspace` for example, but they are not loaded, and this package will only load `penlightplus`, `luacode`, `luakeys`, and `etoolbox`.

## 3 Declaring variables

A declaration file can either be parsed with the command `declareYAMLvarsFile` command, or, if you want to do it  $\LaTeX$ , you can put the YAML code in the `declareYAMLvars` environment. It is a declaring YAML document is (like all YAML) key-value dictionary: The top level key is the name of the variable to be defined/used. If the value of the top level is a string: it’s interpreted as a single transform function to be applied. Otherwise, it must be a table that contains at least one of the following keys:

`xfm` (transform, may be a string or list of strings),

`prc` (processing, must be a single string), or

`dft` (default value, if being defined. Must be a string).

If you want to change the way a variable is initialized, you can change the function `YAMLvars.dec.PRC = function (var) ... end` where `PRC` is how the variable will be processed (`gdef`, `yvdef`, `length`, or something of your choosing).

The default value for variables is the Lua `nil`. `YAMLvars` will first check if the definition exists, if so, an error will be thrown so that we avoid overwriting. If the token is available, it is set to a package error, so that if the variable no defined later on, an error will tell the user they forgot to set it. This will be overwritten when you parse the variables and assign a value to it.

**If you want a case-insensitive variable** In the declaration YAML document, add a `lowercasevar: true` under the variable name. This will make the variable name lowercase before any transforms or processing is done. For example, if you have `title` as a YAML variable to set the `prc` function `setdocvar`, a user could write `Title` in the parsing file and still have it work. You can toggle this behaviour globally with the commands `\lowercasevarYVon` and `\lowercasevarYVoff` See the last example below.

You can change the default `xfm`, `prc`, or `dft` by changing the value (in Lua): `YAMLvars.xfmDefault = ''` etc.

Here is an example of a declaration document.

```
\begin{declareYAMLvars}
Location: addxspace          # sets xfm=addxspace
People: [arrsortlastnameAZ, list2nl]  # BAD! don't do.
People:
  xfm: [arrsortlastnameAZ, list2nl]    # Correct way
Company:
  dft: Amazon                    # Change default only
Revisions:
  dft: '1 & \today & initial version \\'
  xfm: [sortZA, list2tab]
Rhead:
  prc: setRightHead

author:
  xfm: list2and      # (joins a list with \and (or lets a single string be passed)
  prc: setdocvar # calls \author{val}
  lowercasevar: true # allows user to use Title: or TITLE:

title:
  xfm: lb2nl      # (make line-breaks \)
  prc: setdocvar # calls \title{val}
  lowercasevar: true # allows user to use Title: or TITLE:
\end{declareYAMLvars}
```

To change how a variable is declared (initialize), you can modify or add functions in `YAMLvars.dec` table, where the index is the same as the `prc` name. This function accepts two variables, the var name, and the default value set by `dft`. For lengths and toggles (from `etoolbox`), these functions are used to initialize lengths with `newlength` and `newtoggle`.

## 4 Parsing variables

A YAML file to be parsed will contain the variables as the top level keys, similar to declaring. The value can be anything you want; as long as you have applied appropriate transform and declaring functions to it so that it can be useful. For example, a value specified as a YAML list will first be interpreted as a Lua table (with numeric indexes/keys). You could declare a series of transforms functions to sort this table, map functions, and convert it to a series of `LATEX` \items.

Here is an example of a parsing document.

```

\begin{parseYAMLvars}
Location: Planet Earth
People:                # a YAML list
  - Some One           # turns into Lua table
  - No Body
# company assumed Amazon if not set here
Rhead: \today
\end{parseYAMLvars}

```

## 5 xfm – Transform Functions

These functions accept two arguments: (**var**, **val**) where **var** is the variable (or key) and **val** is the value. The transforms are specified as a list and are iteratively applied to the **val**. Usually, the final **xfm** function should produce a string so it can be defined.

Hint: if for some reason, your **xfm** and **prc** depends on other variables, you can access them within the function with `YAMLvars.varsvals`

### 5.1 Defining your own transform functions

After the package is loaded, you may add your function (somewhere in Lua) by adding it to the `YAMLvars.xfm` table. For example, if you wanted to wrap a variable’s value with “xxx”, here’s how you could do that.

```

function myfunction(var, val)
    return 'xxx'..val..'xxx'
end
YAMLvars.xfm['addmyfunction'] = myfunction

```

If you want to run some Lua code and write in your YAML file (weird idea, but maybe useful for one-off functions), you can do so by specifying a transform function with an `=` in it to make a lambda function. For example, a **xfm** equal to “`= '---'..x..'---'`” would surround your YAML variable’s value with em-dashes. You can access the variable name with this lambda function with `v`. If you want to just execute code (instead of settings `x = ,` use `/`).

## 6 prc – Processing Functions

Like the transform functions, the processing function must accept (**var**, **val**). Only one processing function is applied to the final (**var**, **val**) after the transforms are done.

This package includes `gdef` to set a definition, `yvdef` to define a variable under the `yv` command. `title`, `author`, `date` to set `\@title`, `\@author`, `\@date`, respectively

## 7 Some Examples

```
1  %! language = yaml
2  \begin{declareYAMLvars}
3  address:
4    xfm:
5      - list2nl
6      - = x..'!!!'
7  name: null
8
9  title:
10    xfm:
11      - lb2nl
12  #      - / YAMLvars.prvcmd(↵
        titletext, YAMLvars.varsvals['↵
        atitle']:gsub('\n', ' ')..'\\↵
        xspace{}')
13 \end{declareYAMLvars}
14
15 %! language = yaml
16 \begin{parseYAMLvars}
17 title: |-
18     A Multiline
19     Monumental Title!
20
21 name: Joe Smith
22 address:
23   - 1234 Fake St.
24   - City
25 \end{parseYAMLvars}
26
27 \title
28
29 %\titletext!
30
31 \name
32
33 \address
```

A Multiline  
Monumental Title!  
Joe Smith  
1234 Fake St.  
City!!!

## 8 Automation Example

Suppose you had a number of bills of sales in yaml format and wanted to produce some nice pdfs. The following code shows how this could be done.

## 8.1 The main tex template

```
%% main.tex
\documentclass{article}
\usepackage[paperheight=4in,paperwidth=3in,margin=0.25in]{geometry}
\usepackage[pl,func,extras]{penlight}
\usepackage[useyv,parseCLI]{YAMLvars} % using command line option to make files
\usepackage{hyperref}
\usepackage{xspace}
\usepackage{luacode}

\setlength{\parindent}{0ex}
\setlength{\parskip}{0.75em}

\begin{luacode*} -- adding a custom function, put hfill between k-v pairs
    function YAMLvars.xfm.kv2hfill(var, val)
        local t = {}
        for k, v in pairs(val) do
            t[#t+1] = k..'\\hfill '..tostring(v)
        end
        return t
    end
\end{luacode*}

%! language = yaml
\begin{declareYAMLvars}
Customer: addxspace
Date: addxspace
Items:
    xfm: [kv2hfill, arr2itemize]
\end{declareYAMLvars}

\begin{document}
    Bill of sale for: \hfill \yv{Customer}\\
    Purchased: \hfill \yv{Date}\\
    \begin{itemize}
        \item[] ITEM \hfill PRICE
        \yv{Items} % the yaml variable
        \begin{luacode*}
            totalcost = pl.tablex.reduce('+',
                pl.tablex.values(YAMLvars.varsvals['Items']), 0)
            tex.print('\\item[] TOTAL:\\hfill'..tostring(totalcost))
        \end{luacode*}
    \end{itemize}
\end{document}
```



```
\end{document}
```

## 8.2 The lua automation script

```
--automate.lua
for f in io.popen('dir .'):lines() do -- get all files and info in cwd
    local i, j = f:find('%S*%.yaml') -- find fnames
    if i ~= nil then
        f = f:sub(i,j) -- extract .yaml file name (no space in fname allowed)
        os.execute('lualatex -output-format=pdf main.tex '.. f)
                                -- compile w/ yaml file as arg
        local fnew = f:gsub('yaml', 'pdf') -- file name for output pdf
        os.remove(fnew) -- delete if it exists already
        os.rename('main.pdf', fnew) -- change main.pdf to same as yaml file name
    end
end
end
```

## 8.3 The yaml data files

```
# sale1.yaml
Customer: Someone Cold
Date: January 2, 2021
Items:
    Toque: 12
    Mitts: 5.6
    Boots: 80
```

```
# sale2.yaml
Customer: Someone Warm
Date: July 1, 2021
Items:
    Beer (24 pk): 24
    Sunscreen: 5
    Hat: 12
```

## 9 xfm, dec, prc functions (from yamllvars.lua)

```
1
2 function YAMLvars.xfm.arrsort2ZA(var, val)
3     return pl.array2d.sortOP(val, pl.operator.strgt)
4 end
5
6 function YAMLvars.xfm.addrule2arr(var, val)
7     return pl.array2d.map_slice2(_1..'\\\\\\\\'.. YAMLvars.setts.↵
8         tabmidrule..' ', val, 1,-1,-2,-1)
9 end
10
11 function YAMLvars.xfm.arr2tabular(var, val)
12     return pl.array2d.toTeX(val)..'\\\\\\'
13 end
14
15 function YAMLvars.xfm.list2items(var, val)
16     return pl.List(val):map('\\\\item '._1):join(' ')
17 end
18
19 YAMLvars.xfm.arr2itemize = YAMLvars.xfm.list2items
20
21 function YAMLvars.xfm.arrsortAZ(var, val)
22     return pl.List(val):sort(pl.operator.strlt)
23 end
24
25 function YAMLvars.xfm.arrsortZA(var, val)
26     return pl.List(val):sort(pl.operator.strgt)
27 end
28
29 local function complastname(a, b)
30     a = a:split(' ')
31     b = b:split(' ')
32     a = a[#a]
33     b = b[#b]
34     return a < b
35 end
36
37 function YAMLvars.xfm.arrsortlastnameAZ(var, val)
38     val = pl.List(val):sort(complastname)
39     return val
40 end
41
42 function YAMLvars.xfm.list2nl(var, val)
43     if type(val) == 'string' then
44         return val
45     end
46     return pl.List(val):join('\\\\\\ ')
```

```

47 function YAMLvars.xfm.list2and(var, val) -- for doc vars like ↵
    author, publisher
48     if type(val) == 'string' then
49         return val
50     end
51     return pl.List(val):join('\\and ')
52 end
53
54
55 function YAMLvars.xfm.lb2nl(var, val) --linebreak in text 2 newline↵
    \\
56     val, _ = val:gsub('\n', '\\\\n ')
57     return val
58 end
59
60 function YAMLvars.xfm.lb2newline(var, val) --linebreak in text 2 ↵
    newline \\
61     val, _ = val:gsub('\n', '\\newline ')
62     return val
63 end
64
65 function YAMLvars.xfm.lb2par(var, val) --linebreak in text 2 new l
66     val, _ = val:gsub('\n%s*\n', '\\par ')
67     return val
68 end
69
70 function YAMLvars.xfm.lowercase(var, val)
71     return val:lower()
72 end
73
74
75 -- dec laraation functions, -- -- -- -- -- -- -- -- -- -- -- ↵
    -- -- -- -- -- -- -- -- -- -- -- -- -- -- -- --
76
77 function YAMLvars.dec.gdef(var, dft)
78     YAMLvars.deccmd(var, dft)
79 end
80
81 function YAMLvars.dec.yvdef(var, dft)
82     YAMLvars.deccmd('yv--'..var, dft)
83 end
84
85 function YAMLvars.dec.toggle(var, dft)
86     tex.print('\\global\\newtoggle{'..var..'}')
87     YAMLvars.prc.toggle(var, dft)
88 end
89
90 function YAMLvars.dec.length(var, dft)
91     tex.print('\\global\\newlength{\\'..var..'}')

```

```

92       YAMLvars.prc.length(var, dft)
93   end
94
95
96
97   -- prc functions (processing) -- -- -- -- -- -- -- -- -- -- -- ←
    -- -- -- -- -- -- -- -- -- -- -- -- -- -- --
98
99   function YAMLvars.prc.gdef(var, val)
100     --token.set_macro(var, val, 'global') -- old way, don't do as ←
        it will cause issues if val contains undef'd macros
101     pl.tex.defcmd(var, val)
102     YAMLvars.debugtalk(var..' = '..val, 'prc gdef')
103   end
104
105   function YAMLvars.prc.yvdef(var, val)
106     pl.tex.defmacro('yv--'..var, val)
107     YAMLvars.debugtalk('yv--'..var..' = '..val, 'prc yvdef')
108   end
109
110   function YAMLvars.prc.toggle(t, v) -- requires penlight extras
111     local s = ''
112     if pl.hasval(v) then
113       s = '\\global\\toggletrue{'.t..'}'
114     else
115       s = '\\global\\togglefalse{'.t..'}'
116     end
117     tex.print(s)
118     YAMLvars.debugtalk(s, 'prc toggle')
119   end
120
121   function YAMLvars.prc.length(t, v)
122     v = v or 'Opt'
123     local s = '\\global\\setlength{\\global\\'.t..''}{'..v..''}
124     tex.print(s)
125     YAMLvars.debugtalk(s, 'prc length')
126   end
127
128
129
130   function YAMLvars.prc.setATvar(var, val) -- set a @var directly: eg←
        \\gdef\\@title{val}
131     pl.tex.defcmdAT('@'..var, val)
132   end
133
134
135   function YAMLvars.prc.setdocvar(var, val) -- call a document var \←
        var{val} = \\title{val}
136     -- YAML syntax options

```



184       else