

SENDPK.COM

BULK SMS API DOCUMENTATION

Send Single, Bulk, Unicode, Dynamic and OTP SMS via a plain HTTP API

PTA-Approved SMS Aggregator · Serving Pakistan since 2014

Base URL: <https://sendpk.com/api/>

Version 1.0 · Document prepared: July 13, 2026

Sources: new.sendpk.com/api.php · Postman Collection (documenter.getpostman.com)

Table of Contents

1. Introduction
2. Getting Started
3. Authentication
4. Sender ID (Masking)
5. Base URL & Endpoints
6. Request Parameters
7. Response Format
8. Status Codes
9. API Endpoints
 - 9.1 Fixed / OTP SMS
 - 9.2 Send Single SMS
 - 9.3 Send Bulk SMS
 - 9.4 Send Unicode SMS
 - 9.5 Dynamic / Personalized SMS
 - 9.6 Check Balance
 - 9.7 Delivery Report
10. Code Examples (Reusable Helper Functions)
11. Best Practices
12. Frequently Asked Questions
13. Support & Contact

1. Introduction

The SendPK Bulk SMS API lets you send Single, Bulk, Unicode, Dynamic (mail-merge) and OTP SMS directly from your website or software over a plain HTTP request — no SDK and no OAuth handshake required. It is the exact same API that powers the SendPK web portal, and is fully compatible with PHP, ASP, .NET, JSP, C# and Java integrations.

This document consolidates the official developer reference published at new.sendpk.com/api.php together with the endpoints exposed in SendPK's public Postman collection, and adds ready-to-use sample code in several popular programming languages.

Important — Local Traffic Only: This channel is strictly for terminating local/Pakistani-origin companies, products and services. Terminating traffic on behalf of any international entity, directly or indirectly, is treated as a violation of these terms and can lead to legal action for damages or losses incurred.

Account Verification: Before your Sender ID can be approved and activated, account verification is required (CNIC, Face ID, a legal agreement on letterhead, or NTN). Verify your account to display your own message; otherwise, the default demo text will be appended to outgoing messages.

Key Capabilities

- Plain HTTP GET/POST — no SDK required; call the endpoint from any language that can make an HTTP request.
- Single & Bulk sends — send to one recipient or a comma-separated list in exactly the same call.
- Dynamic mail-merge — upload a spreadsheet and send a uniquely personalized message to every row in one call.
- Unicode-ready — send emoji and regional-script text by setting `type=unicode`.
- JSON & XML output — add `format=json` or `format=xml` for a structured response.
- Fixed-SMS & OTP templates — fill a pre-approved template with `template_id` and a small JSON payload.

2. Getting Started

From signup to your first delivered SMS in a few minutes:

1. Create your free account — sign up with your name, mobile number and email; no paperwork to get started.
2. Get your Sender ID approved — verify your account for the route your business needs: Semi Branded, Branded or Short Code (OTP) SMS.
3. Grab your API key — copy your unique `api_key` from your dashboard's Profile page; it authenticates every API call you make.
4. Call the API — hit `api/sms.php` with your API key, sender ID, recipient and message.
5. Track delivery & balance — poll `delivery.php` for a message's status and `balance.php` for your remaining credit.

Sign up: <https://sendpk.com/Register.php>

3. Authentication

Every request is authenticated with a single `api_key` parameter. The older username / password login-pair authentication is deprecated — use `api_key` on every call shown in this document.

Where to find it

Log in to your dashboard and open Profile → API Key to copy your unique `api_key`.

Sending it

Pass `api_key` as a plain request parameter on every call, via the GET query string or the POST body:

```
?api_key=3f9a2b7c6e1d4c2a9b0e8d5f1a2b3c4d&sender=YourBrand&mobile=923001234567&message=Hello
```

Security Warning: Treat your `api_key` like a password. Never expose it in client-side JavaScript, public repositories, or mobile app bundles — always call this API from your own backend server.

4. Sender ID (Masking)

The sender parameter is the name recipients see as the message sender. It must match a Sender ID that has been approved for your account.

Route	Sender ID
Simple SMS	Sent from a pre-approved shared name such as "SMS Alert" — instant approval.

Route	Sender ID
Branded SMS	Your own company or brand name — requires a one-time mask approval.
Short Code / OTP	Delivered via a dedicated short code route for time-critical codes — default short code is 8584.

5. Base URL & Endpoints

There is one endpoint per operation — sending, dynamic/mail-merge sending, checking a delivery report, and checking your balance.

Purpose	Endpoint
Send SMS (single, bulk, unicode, fixed/OTP)	https://sendpk.com/api/sms.php
Dynamic / personalized SMS from a file	https://sendpk.com/api/personalised.php
Delivery report	https://sendpk.com/api/delivery.php
Check balance	https://sendpk.com/api/balance.php

GET vs. POST: Both GET and POST are supported. GET is the simplest for quick testing; POST keeps your `api_key` out of server access logs in production.

6. Request Parameters

Every parameter the `sms.php` endpoint accepts:

Parameter	Description
api_key <i>(required)</i>	Your unique API key, from Profile → API Key.
sender <i>(required)</i>	Your approved Sender ID / brand name.
mobile <i>(required)</i>	Recipient mobile number, or a comma-separated list for bulk sends, e.g. 923001234567,923101234567.
message <i>(required)</i>	The message text. For Fixed-SMS/OTP templates, pass a JSON string of your template's variables instead, e.g. <code>{"name":"Umair","pin":"456723"}</code> .
network <i>(optional)</i>	One of Jazz, Zong, Ufone, Telenor. Use it to route SMS on ported/MNP numbers, or to force a specific operator.
type <i>(optional)</i>	Set to unicode to send emoji or non-Latin script text.
template_id <i>(optional)</i>	Your approved Fixed-SMS/OTP template ID.
format <i>(optional)</i>	Set to json, xml or plain (case-insensitive) to choose the response format.

The Dynamic / Personalized SMS endpoint accepts its own url and duplicate parameters instead of mobile — see Section 9.5.

7. Response Format

By default the API replies with a short plain-text line. Add `format=json` or `format=xml` on any request to get the same status/ID pair back as structured data instead.

Successful Response

```
OK ID:29346
```

The number after ID: is your unique message ID — save it if you plan to check the delivery report later.

8. Status Codes

Every response starts with OK on success, or a numeric code that indicates exactly what went wrong.

Code	Meaning
OK	Message was successfully accepted for delivery.
1	API key is invalid, expired, or your account is disabled.
2	API key is empty.
3	Reserved (legacy code, unused with api_key auth).
4	Sender ID is empty.
5	Recipient is empty.
6	Message is empty.
7	Invalid recipient number.
8	Insufficient credit — top up your balance to continue sending.
9	SMS rejected.

9. API Endpoints

One core endpoint (sms.php) covers several send modes, plus a dedicated endpoint for file-based mail-merge sending, a balance-check endpoint, and a delivery-report endpoint. Pick the flavor that matches what you are sending.

Method	Endpoint	Purpose
POST/GET	sms.php	Fixed / OTP SMS — fill a pre-approved template with JSON variables.
POST/GET	sms.php	Send Single SMS — one message to one recipient.
POST/GET	sms.php	Send Bulk SMS — the same message to many recipients in one call.
POST/GET	sms.php	Send Unicode SMS — emoji and regional-script messages.
POST	personalised.php	Dynamic / Personalized SMS — mail-merge a unique message per row from an uploaded file.
GET	balance.php	Check Balance — your remaining SMS credit.
GET	delivery.php	Delivery Report — status of a previously sent message.

9.1 Fixed / OTP SMS

Per PTA guidelines, SMS falls into two categories: transactional (critical/informational messages and OTPs) and promotional (marketing content). Fixed-SMS templates keep transactional content pre-approved and PTA-compliant — only the variable parts change per message. Variables are written as #variable_name# in the approved template; you fill them in with a JSON object of matching keys.

GET <https://sendpk.com/api/sms.php>

Parameters

Parameter	Description
template_id <i>(required)</i>	Your approved Fixed-SMS/OTP template ID.
message <i>(required)</i>	JSON string of variable values, e.g. {"name":"Umair","pin":"456723"}.

Request Example

```
GET
https://sendpk.com/api/sms.php?api_key=3f9a2b7c6e1d4c2a9b0e8d5f1a2b3c4d&sender=8584&mobile=923001234567&tem
```

Creating a Template

1. Log in to your dashboard and open the SMS Templates section from your account.
2. Open Fixed-SMS-Templates, found in the top-right corner of the SMS Templates page.
3. Submit your content, writing your message with #variable_name# placeholders for anything that changes per recipient.
4. Wait for approval — once approved you'll get a template_id, ready to use immediately.

Tip: Short Code / OTP templates typically send from a shared short code (e.g. 8584) rather than a custom brand name.

9.2 Send Single SMS

Sends one message to one recipient.

GET <https://sendpk.com/api/sms.php>

Request Example

```
GET
https://sendpk.com/api/sms.php?api_key=3f9a2b7c6e1d4c2a9b0e8d5f1a2b3c4d&sender=YourBrand&mobile=923001234567
table is ready, see you soon!
```

Response Example

```
OK ID:29346
```

Sample Code

cURL

```
curl -G 'https://sendpk.com/api/sms.php' \
-d 'api_key=3f9a2b7c6e1d4c2a9b0e8d5f1a2b3c4d' \
-d 'sender=YourBrand' \
-d 'mobile=923001234567' \
-d 'message=Your table is ready, see you soon!'
```

PHP

```
<?php
$post = http_build_query([
    'api_key' => '3f9a2b7c6e1d4c2a9b0e8d5f1a2b3c4d',
    'sender' => 'YourBrand',
    'mobile' => '923001234567',
    'message' => 'Your table is ready, see you soon!',
]);

$result = file_get_contents('https://sendpk.com/api/sms.php?' . $post);

if (strpos($result, 'OK') === 0) {
    echo 'Sent! ' . $result;
} else {
    echo 'Error code: ' . $result;
}
```

JavaScript (Node.js / Fetch)

```
const params = new URLSearchParams({
  api_key: '3f9a2b7c6e1d4c2a9b0e8d5f1a2b3c4d',
  sender: 'YourBrand',
  mobile: '923001234567',
  message: 'Your table is ready, see you soon!',
});
```

```
});

const res = await fetch('https://sendpk.com/api/sms.php?' + params);
const text = await res.text();
console.log(text); // e.g. "OK ID:29346"
```

Python

```
import requests

response = requests.get('https://sendpk.com/api/sms.php', params={
    'api_key': '3f9a2b7c6e1d4c2a9b0e8d5f1a2b3c4d',
    'sender': 'YourBrand',
    'mobile': '923001234567',
    'message': 'Your table is ready, see you soon!',
})

print(response.text) # e.g. "OK ID:29346"
```

Java (HttpClient)

```
import java.net.URI;
import java.net.http.HttpClient;
import java.net.http.HttpRequest;
import java.net.http.HttpResponse;
import java.net.URLEncoder;
import java.nio.charset.StandardCharsets;

public class SendSms {
    public static void main(String[] args) throws Exception {
        String apiKey = "3f9a2b7c6e1d4c2a9b0e8d5f1a2b3c4d";
        String sender = URLEncoder.encode("YourBrand", StandardCharsets.UTF_8);
        String mobile = "923001234567";
        String message = URLEncoder.encode("Your table is ready, see you soon!",
        StandardCharsets.UTF_8);

        String url = String.format(
            "https://sendpk.com/api/sms.php?api_key=%s&sender=%s&mobile=%s&message=%s",
            apiKey, sender, mobile, message);

        HttpClient client = HttpClient.newHttpClient();
        HttpRequest request = HttpRequest.newBuilder(URI.create(url)).GET().build();
        HttpResponse<String> response = client.send(request,
        HttpResponse.BodyHandlers.ofString());

        System.out.println(response.body()); // e.g. "OK ID:29346"
    }
}
```

C# (.NET HttpClient)

```
using System;
using System.Net.Http;
using System.Threading.Tasks;
```

```
class SendSms
{
    static async Task Main()
    {
        var client = new HttpClient();
        var apiKey = "3f9a2b7c6e1d4c2a9b0e8d5f1a2b3c4d";
        var sender = Uri.EscapeDataString("YourBrand");
        var mobile = "923001234567";
        var message = Uri.EscapeDataString("Your table is ready, see you soon!");

        var url =
        $"https://sendpk.com/api/sms.php?api_key={apiKey}&sender={sender}&mobile={mobile}&message={message}";

        var response = await client.GetStringAsync(url);
        Console.WriteLine(response); // e.g. "OK ID:29346"
    }
}
```

9.3 Send Bulk SMS

Sends the same message to multiple recipients in a single call. Separate numbers with a comma — duplicates and invalid numbers are filtered automatically.

GET <https://sendpk.com/api/sms.php>

Request Example

```
GET
https://sendpk.com/api/sms.php?api_key=3f9a2b7c6e1d4c2a9b0e8d5f1a2b3c4d&sender=YourBrand&mobile=923001234567
Sale! 30% off everything today only.
```

Response Example

```
OK ID:29347
```

Sample Code

cURL

```
curl -G 'https://sendpk.com/api/sms.php' \
-d 'api_key=3f9a2b7c6e1d4c2a9b0e8d5f1a2b3c4d' \
-d 'sender=YourBrand' \
-d 'mobile=923001234567,923101234567' \
-d 'message=Flash Sale! 30% off everything today only.'
```

PHP

```
<?php
$post = http_build_query([
    'api_key' => '3f9a2b7c6e1d4c2a9b0e8d5f1a2b3c4d',
    'sender' => 'YourBrand',
    'mobile' => '923001234567,923101234567',
    'message' => 'Flash Sale! 30% off everything today only.',
]);

$result = file_get_contents('https://sendpk.com/api/sms.php?' . $post);
echo $result;
```

JavaScript (Fetch)

```
const params = new URLSearchParams({
  api_key: '3f9a2b7c6e1d4c2a9b0e8d5f1a2b3c4d',
  sender: 'YourBrand',
  mobile: '923001234567,923101234567',
  message: 'Flash Sale! 30% off everything today only.',
});

const res = await fetch('https://sendpk.com/api/sms.php?' + params);
console.log(await res.text());
```

Python

```
import requests

response = requests.get('https://sendpk.com/api/sms.php', params={
    'api_key': '3f9a2b7c6e1d4c2a9b0e8d5f1a2b3c4d',
    'sender': 'YourBrand',
    'mobile': '923001234567,923101234567',
    'message': 'Flash Sale! 30% off everything today only.',
})

print(response.text)
```

9.4 Send Unicode SMS

Set type=unicode to send emoji, Urdu, or any other non-Latin script text. Unicode messages have a shorter per-part character limit than plain text, exactly as with any standard SMS.

GET <https://sendpk.com/api/sms.php>

Request Example

```
GET
https://sendpk.com/api/sms.php?api_key=3f9a2b7c6e1d4c2a9b0e8d5f1a2b3c4d&sender=YourBrand&mobile=92300123456
```

Tip: URL-encode the message parameter (as shown above) whenever it contains Unicode characters.

9.5 Dynamic / Personalized SMS

Send bulk SMS with unique information for every contact in a file (.txt, .csv, .xls or .xlsx) — no need to loop single sends. Reference each column in your message with #B#, #C#, #D# (matching the spreadsheet's column letters), and every recipient gets their own row's values filled in automatically.

POST <https://sendpk.com/api/personalised.php>

Parameters

Parameter	Description
api_key <i>(required)</i>	Your API key.
sender <i>(required)</i>	Your approved Sender ID / brand name.
url <i>(required)</i>	A publicly reachable link to your uploaded .txt/.csv/.xls/.xlsx file.
message <i>(required)</i>	Your message with #COLUMN# placeholders, e.g. #B# pulls from column B of the file.
format <i>(optional)</i>	Set to json, xml or plain.
duplicate <i>(optional)</i>	0 removes duplicate numbers, 1 keeps them. Defaults to keeping duplicates.

Request Example

```
GET
https://sendpk.com/api/personalised.php?api_key=3f9a2b7c6e1d4c2a9b0e8d5f1a2b3c4d&sender=YourBrand&url=https
Son #B# Got #C# Marks In #D#, Your Son Result Is #E#. Please contact the school principal for more details.
```

Sample Output

If column B holds a name, C a score, D a subject and E a result, each recipient gets their own filled-in copy:

```
Your Son Ali Ahmad Got 1123 Marks In Mathematics, Your Son Result Is Pass. Please contact
the school
principal for more details.
```

```
Your Son Mustafa Kamal Got 330 Marks In Mathematics, Your Son Result Is Fail. Please
contact the school
principal for more details.
```

9.6 Check Balance

Checks your remaining SMS credit through a simple HTTP call — handy for showing a live balance inside your own app or dashboard.

GET <https://sendpk.com/api/balance.php>

Request Example

```
GET https://sendpk.com/api/balance.php?api_key=3f9a2b7c6e1d4c2a9b0e8d5f1a2b3c4d
```

Returns your remaining SMS credit as a plain number, or the matching status code (Section 8) if the request fails.

9.7 Delivery Report

Looks up the current delivery status of a previously sent message using the message ID returned by the send API.

GET <https://sendpk.com/api/delivery.php>

Request Example

```
GET https://sendpk.com/api/delivery.php?api_key=3f9a2b7c6e1d4c2a9b0e8d5f1a2b3c4d&id=29346
```

Pass the message id from the OK ID: response you received when the message was sent.

10. Code Examples — Reusable Helper Functions

A reusable helper function you can paste directly into your project to start sending SMS in one line.

Shell (cURL)

```
# Reusable shell function
send_sms() {
  curl -s -G 'https://sendpk.com/api/sms.php' \
    -d "api_key=$SENDPK_API_KEY" \
    -d "sender=$SENDPK_SENDER" \
    -d "mobile=$1" \
    -d "message=$2"
}

send_sms "923001234567" "Hello from cURL!"
```

PHP

```
<?php
function sendSms(string $mobile, string $message): string {
    static $apiKey = '3f9a2b7c6e1d4c2a9b0e8d5f1a2b3c4d';
    static $sender = 'YourBrand';
    static $url = 'https://sendpk.com/api/sms.php';

    return file_get_contents($url . '?' . http_build_query([
        'api_key' => $apiKey,
        'sender' => $sender,
        'mobile' => $mobile,
        'message' => $message,
    ]));
}

$result = sendSms('923001234567', 'Hello from PHP!');
echo strpos($result, 'OK') === 0 ? 'Sent! ' . $result : 'Error: ' . $result;
```

JavaScript

```
async function sendSms(mobile, message) {
    const API_KEY = '3f9a2b7c6e1d4c2a9b0e8d5f1a2b3c4d';
    const params = new URLSearchParams({
        api_key: API_KEY,
        sender: 'YourBrand',
        mobile,
        message,
    });
    const res = await fetch('https://sendpk.com/api/sms.php?' + params);
    return res.text();
}

const result = await sendSms('923001234567', 'Hello from JavaScript!');
console.log(result);
```

Python

```
import requests

API_KEY = '3f9a2b7c6e1d4c2a9b0e8d5f1a2b3c4d'
SENDER = 'YourBrand'
API_URL = 'https://sendpk.com/api/sms.php'

def send_sms(mobile: str, message: str) -> str:
    response = requests.get(API_URL, params={
        'api_key': API_KEY,
        'sender': SENDER,
        'mobile': mobile,
        'message': message,
    })
    return response.text

result = send_sms('923001234567', 'Hello from Python!')
print(result)
```

11. Best Practices

- Always check that the response starts with OK before assuming a message was accepted.
- Save the message ID from each OK ID: response if you plan to check its delivery report later.
- Call the API from your backend, never directly from a browser or mobile app, to keep your api_key private.
- Use format=json if you'd rather parse a structured response than a plain-text line.
- For bulk sends, pass a comma-separated mobile list; for per-recipient personalization at scale, use the Dynamic SMS endpoint instead of looping single sends.

12. Frequently Asked Questions

Q: What do I use as my API key?

A: Copy your unique api_key from your dashboard's Profile page. It replaces the older username/password login-pair auth, which is now deprecated for this API.

Q: Can I send to multiple recipients in one call?

A: Yes — pass a comma-separated mobile list, e.g. 923001234567,923101234567, and the same message is sent to everyone in the list.

Q: How do I send a unique message per recipient at scale?

A: Use the Dynamic / Personalized SMS endpoint — upload a .csv/.xls/.xlsx file and reference its columns with #B#, #C#, etc. in your message.

Q: How do I send emoji or Urdu text?

A: Set type=unicode and URL-encode your message parameter.

Q: What is Fixed-SMS / template_id?

A: It's a pre-approved message template with #variable# placeholders. You fill the placeholders by passing a small JSON object as your message parameter alongside your approved template_id — commonly used for OTP and other transactional messages.

Q: Why did I get status code 8?

A: Your account has insufficient credit. Top up your balance from your dashboard to continue sending.

Q: How do I check if a message was delivered?

A: Call delivery.php with the message id you received in the original OK ID: response.

Q: Can I get JSON or XML responses instead of plain text?

A: Yes — add format=json or format=xml to any request and the same status/ID pair is returned in that structure instead.

13. Support & Contact

Our team can help with integration questions, Sender ID approval, or troubleshooting delivery issues.

Channel	Detail
Company	SendPK — PTA-Approved SMS Aggregator (NTN: 6396772)
Address	Lahore, Punjab, Pakistan
Phone / WhatsApp	+92 313 4126153
Website	https://sendpk.com
API Docs	https://new.sendpk.com/api.php
Postman Collection	https://documenter.getpostman.com/view/9576087/2s9YyvBg5s
Offline Docs (zip)	https://sendpk.com/Api.zip