



## INTRODUCTION TO RELATIONAL DATABASES IN SQL



# Your first database


**Timo Grossenbacher**  
Data Journalist

# Investigating universities in Switzerland


## Eidgenössische Technische Hochschule Zürich

Zu dieser Hochschule gehören rund **18'600 Studierende** und **Professor/innen**. Es besteht ein jährlicher Aufwand von rund **1.6 Mrd. Fr.**, wovon **8.8 %** aus **privaten Drittmitteln** stammen (BFS, 2014).

Jeder Punkt in der Grafik zeigt eine von insgesamt **516 Interessenbindungen**.  



Stand der Daten: Juni 2015  
Quelle: Pressestelle  
Interessenbindungen beinhalten auch Mandate in Verwaltungs- und Stiftungsräten sowie Vereinsvorstände, die im Auftrag der ETH Zürich von Professor/innen wahrgenommen werden. ETHZ und EPFL teilen sich den Universitätsrat («ETH-Rab»).





# A relational database:

- real-life *entities* become *tables*
  - reduced redundancy
  - data integrity by *relationships*
- e.g. professors, universities, companies
  - e.g. only one entry in `companies` for the bank "Credit Suisse"
  - e.g. a professor can work at multiple universities and companies, a company can employ multiple professors



# Throughout this course you will:

- work with the data I used for my investigation
- create a relational database from scratch
- learn three concepts:
  - *constraints*
  - *keys*
  - *referential integrity*

You'll need: Basic understanding of SQL, as taught in [Intro to SQL for Data Science](#).

# Your first duty: Have a look at the PostgreSQL database

```
SELECT table_schema, table_name
FROM information_schema.tables;
```

table_schema	table_name
pg_catalog	pg_statistic
pg_catalog	pg_type
pg_catalog	pg_policy
pg_catalog	pg_authid
pg_catalog	pg_shadow
public	university_professors
pg_catalog	pg_settings
pg_catalog	pg_hba_file_rules
pg_catalog	pg_file_settings
pg_catalog	pg_config
...	



# Have a look at the columns of a certain table

```
SELECT table_name, column_name, data_type
FROM information_schema.columns
WHERE table_name = 'pg_config';
```

table_name	column_name	data_type
pg_config	name	text
pg_config	setting	text



## INTRODUCTION TO RELATIONAL DATABASES IN SQL

**Let's do this.**



## INTRODUCTION TO RELATIONAL DATABASES IN SQL

# Tables: At the core of every database

Timo Grossenbacher  
Data Journalist





# Redundancy in the university\_professors table

```
SELECT * FROM  
university_professors  
LIMIT 3;
```


# Redundancy in the university\_professors table

```
-[ RECORD 1 ]-----+-----  
firstname      | Karl  
lastname       | Aberer  
university     | ETH Lausanne  
university_shortcode | EPF  
university_city | Lausanne  
function       | Chairman of L3S Advisory Board  
organization   | L3S Advisory Board  
organization_sector | Education & research  
-[ RECORD 2 ]-----+-----  
firstname      | Karl  
lastname       | Aberer  
university     | ETH Lausanne  
university_shortcode | EPF  
university_city | Lausanne  
function       | Member Conseil of Zeno-Karl Schindler Foundation  
organization   | Zeno-Karl Schindler Foundation  
organization_sector | Education & research  
-[ RECORD 3 ]-----+-----  
firstname      | Karl  
lastname       | Aberer  
(truncated)  
function       | Member of Conseil Fondation IDIAP  
organization   | Fondation IDIAP  
(truncated)
```

```
-[ RECORD 1 ]-----+-----  
firstname      | Karl  
lastname       | Aberer  
university     | ETH Lausanne  
university_shortname | EPF  
university_city | Lausanne  
function       | Chairman of L3S Advisory Board  
organisation   | L3S Advisory Board  
organisation_sector | Education & research  
-[ RECORD 2 ]-----+-----  
firstname      | Karl  
lastname       | Aberer  
university     | ETH Lausanne  
university_shortname | EPF  
university_city | Lausanne  
function       | Member Conseil of Zeno-Karl Schindler Foundation  
organisation   | Zeno-Karl Schindler Foundation  
organisation_sector | Education & research  
-[ RECORD 3 ]-----+-----  
firstname      | Karl  
lastname       | Aberer  
(truncated)  
function       | Member of Conseil Fondation IDIAP  
organisation   | Fondation IDIAP  
(truncated)
```




# Currently: One "entity type" in the database






# A better database model with three entity types

Old:




New:





# A better database model with four entity types






# Create new tables with CREATE TABLE

```
CREATE TABLE table_name (  
  column_a data_type,  
  column_b data_type,  
  column_c data_type  
);
```



# Create new tables with CREATE TABLE

```
CREATE TABLE weather (  
  clouds text,  
  temperature numeric,  
  weather_station char(5)  
);
```







## INTRODUCTION TO RELATIONAL DATABASES IN SQL

**Let's practice!**



## INTRODUCTION TO RELATIONAL DATABASES IN SQL


# Update your database as the structure changes

Timo Grossenbacher

Data Journalist




# The current database model





# The current database model





# Only store DISTINCT data in the new tables

```
SELECT COUNT(*)  
FROM university_professors;
```

```
count  
-----  
1377
```

```
SELECT COUNT(DISTINCT organization)  
FROM university_professors;
```

```
count  
-----  
1287
```



# INSERT DISTINCT records INTO the new tables

```
INSERT INTO organizations
SELECT DISTINCT organization,
               organization_sector
FROM university_professors;
```

Output: INSERT 0 1287

```
INSERT INTO organizations
SELECT organization,
               organization_sector
FROM university_professors;
```

Output: INSERT 0 1377



# The INSERT INTO statement

```
INSERT INTO table_name (column_a, column_b)
VALUES ("value_a", "value_b");
```



# RENAME a COLUMN in affiliations

```
CREATE TABLE affiliations (  
  firstname text,  
  lastname text,  
  university_shortcode text,  
  function text,  
  organisation text  
);
```

```
ALTER TABLE table_name  
RENAME COLUMN old_name TO new_name;
```





# DROP a COLUMN in affiliations

```
CREATE TABLE affiliations (  
  firstname text,  
  lastname text,  
  university_shortname text,  
  function text,  
  organization text  
);
```

```
ALTER TABLE table_name  
DROP COLUMN column_name;
```

# A professor is uniquely identified by firstname, lastname only

```
SELECT DISTINCT firstname, lastname,  
                university_shortcode  
FROM university_professors  
ORDER BY lastname;
```

```
-[ RECORD 1 ]-----+-----  
firstname      | Karl  
lastname       | Aberer  
university_shortcode | EPF  
-[ RECORD 2 ]-----+-----  
firstname      | Reza Shokrollah  
lastname       | Abhari  
university_shortcode | ETH  
-[ RECORD 3 ]-----+-----  
firstname      | Georges  
lastname       | Abou Jaoudé  
university_shortcode | EPF
```

(truncated)

(551 records)

```
SELECT DISTINCT firstname, lastname  
FROM university_professors  
ORDER BY lastname;
```


```
-[ RECORD 1 ]-----  
firstname | Karl  
lastname  | Aberer  
-[ RECORD 2 ]-----  
firstname | Reza Shokrollah  
lastname  | Abhari  
-[ RECORD 3 ]-----  
firstname | Georges  
lastname  | Abou Jaoudé
```

(truncated)

(551 records)



# A professor is uniquely identified by firstname, lastname only





## INTRODUCTION TO RELATIONAL DATABASES IN SQL

**Let's get to work!**