

← [course home \(/table-of-contents\)](/table-of-contents)

Hooray! It's opposite day. Linked lists go the opposite way today.

Write a function for reversing a linked list. Do it in place.

Your function will have one input: the head of the list.

Your function should return the new head of the list.

Here's a sample linked list node class:

```
class LinkedListNode(object):  
  
    def __init__(self, value):  
        self.value = value  
        self.next = None
```

Python 3.6 ▼

Gotchas

We can do this in $O(1)$ space. So don't make a new list; use the existing list nodes!

We can do this in $O(n)$ time.

Careful—even the right *approach* will fail if done in the wrong *order*.

Try drawing a picture of a small linked list and running your function by hand. Does it actually work?

The most obvious edge cases are:

1. the list has 0 elements
2. the list has 1 element

Does your function correctly handle those cases?

Breakdown

Our first thought might be to build our reversed list "from the beginning," starting with the head of the final *reversed* linked list.

The head of the reversed list will be the *tail* of the input list. To get to that node we'll have to walk through the whole list once ($O(n)$ time). And that's just to get started.

That seems inefficient. **Can we reverse the list while making just one walk from head to tail of the input list?**

We can reverse the list by changing the next pointer of each node. Where should each node's next pointer...point?

Each node's next pointer should point to the *previous* node.

How can we move each node's next pointer to its *previous* node in one pass from head to tail of our current list?

Solution

In one pass from head to tail of our input list, we point each node's next pointer to the previous item.

The order of operations is important here! We're careful to copy `current_node.next` into `next` *before* setting `current_node.next` to `previous_node`. Otherwise "stepping forward" at the end could actually mean stepping *back* to `previous_node`!

```
def reverse(head_of_list):
    current_node = head_of_list
    previous_node = None
    next_node = None

    # Until we have 'fallen off' the end of the list
    while current_node:
        # Copy a pointer to the next element
        # before we overwrite current_node.next
        next_node = current_node.next

        # Reverse the 'next' pointer
        current_node.next = previous_node

        # Step forward in the list
        previous_node = current_node
        current_node = next_node

    return previous_node
```

We return `previous_node` because when we exit the list, `current_node` is `None`. Which means that the last node we visited—`previous_node`—was the tail of the *original* list, and thus the head of our *reversed* list.

Complexity

$O(n)$ time and $O(1)$ space. We pass over the list only once, and maintain a constant number of variables in memory.

Bonus

This in-place reversal destroys the input linked list. What if we wanted to keep a copy of the original linked list? Write a function for reversing a linked list out-of-place.

What We Learned

It's one of those problems where, even once you know the procedure, it's hard to write a bug-free solution. Drawing it out helps a lot. Write out a sample linked list and walk through your code by hand, step by step, running each operation on your sample input to see if the final output is what you expect. This is a great strategy for *any* coding interview question.

← [course home \(/table-of-contents\)](/table-of-contents)

Next up: Kth to Last Node in a Singly-Linked List →
([/question/kth-to-last-node-in-singly-linked-list?
course=fc1§ion=linked-lists](/question/kth-to-last-node-in-singly-linked-list?course=fc1§ion=linked-lists))

Want more coding interview help?

Check out **interviewcake.com** for more advice, guides, and practice questions.