

← [course home \(/table-of-contents\)](#)

Write a function to check that a binary tree is a valid binary search tree.↴


Here's a sample binary tree node class:

```
class BinaryTreeNode(object):  
  
    def __init__(self, value):  
        self.value = value  
        self.left = None  
        self.right = None  
  
    def insert_left(self, value):  
        self.left = BinaryTreeNode(value)  
        return self.left  
  
    def insert_right(self, value):  
        self.right = BinaryTreeNode(value)  
        return self.right
```

Python 3.6 ▼

Gotchas

Consider this example:



Notice that when you check the blue node against its parent, it seems correct. However, it's greater than the root, so it should be in the root's right subtree. So we see that **checking a node against its parent isn't sufficient to prove that it's in the correct spot.**

We can do this in $O(n)$ time and $O(n)$ additional space, where n is the number of nodes in our tree. Our additional space is $O(\lg n)$ if our tree is balanced.

Breakdown

One way to break the problem down is to come up with a way to confirm that a single node is in a valid place relative to its ancestors. Then if every node passes this test, our whole tree is a valid BST.

What makes a given node "correct" relative to its ancestors in a BST? Two things:

- if a node is in the ancestor's *left* subtree, then it must be *less* than the ancestor, and
- if a node is in the ancestor's *right* subtree, then it must be *greater* than the ancestor.


So we could do a walk through our binary tree, **keeping track of the ancestors for each node and whether the node should be greater than or less than each of them.** If each of these greater-than or less-than relationships holds true for each node, our BST is valid.

The simplest ways to traverse the tree are depth-first and breadth-first. They have the same time cost (they each visit each node once). Depth-first traversal of a tree uses memory proportional to the depth of the tree, while breadth-first traversal uses memory proportional to the breadth of the tree (how many nodes there are on the "level" that has the most nodes).

Because the tree's breadth can as much as double each time it gets one level deeper, **depth-first traversal is likely to be more space-efficient than breadth-first traversal**, though they are strictly both $O(n)$ additional space in the worst case. The space savings are obvious if we know our binary tree is balanced—its depth will be $O(\lg n)$ and its breadth will be $O(n)$.

But we're not just storing the nodes themselves in memory, we're also storing the value from each ancestor and whether it should be less than or greater than the given node. Each node has $O(n)$ ancestors ($O(\lg n)$ for a balanced binary tree), so that gives us $O(n^2)$ additional memory cost ($O(n \lg n)$ for a balanced binary tree). We can do better.

Let's look at the inequalities we'd need to store for a given node:



Notice that we would end up testing that the blue node is <20 , <30 , and <50 . Of course, <30 and <50 are implied by <20 . So instead of storing each ancestor, we can just keep track of a `lower_bound` and `upper_bound` that our node's value must fit inside.

Solution

We do a depth-first walk through the tree, testing each node for validity as we go. If a node appears in the *left* subtree of an ancestor, it must be less than that ancestor. If a node appears in the *right* subtree of an ancestor, it must be greater than that ancestor.

Instead of keeping track of every ancestor to check these inequalities, we just check the largest number it must be greater than (its `lower_bound`) and the smallest number it must be less than (its `upper_bound`).

```
def is_binary_search_tree(root):

    # Start at the root, with an arbitrarily low lower bound
    # and an arbitrarily high upper bound
    node_and_bounds_stack = [(root, -float('inf'), float('inf'))]

    # Depth-first traversal
    while len(node_and_bounds_stack):
        node, lower_bound, upper_bound = node_and_bounds_stack.pop()

        # If this node is invalid, we return false right away
        if (node.value <= lower_bound) or (node.value >= upper_bound):
            return False

        if node.left:
            # This node must be less than the current node
            node_and_bounds_stack.append((node.left, lower_bound, node.value))
        if node.right:
            # This node must be greater than the current node
            node_and_bounds_stack.append((node.right, node.value, upper_bound))

    # If none of the nodes were invalid, return true
    # (at this point we have checked all nodes)
    return True
```

Instead of allocating a stack ourselves, we could write a **recursive function** that uses the call stack. This would work, but it would be **vulnerable to stack overflow**. However, the code does end up quite a bit cleaner:

```
def is_binary_search_tree(root,
                          lower_bound=-float('inf'),
                          upper_bound=float('inf')):
    if not root:
        return True

    if (root.value >= upper_bound or root.value <= lower_bound):
        return False

    return (is_binary_search_tree(root.left, lower_bound, root.value)
            and is_binary_search_tree(root.right, root.value, upper_bound))
```

Checking if an in-order traversal of the tree is sorted is a great answer too, especially if you're able to implement it without storing a full list of nodes.

Complexity

$O(n)$ time and $O(n)$ space.

The time cost is easy: for valid binary search trees, we'll have to check *all* n nodes.

Space is a little more complicated. Because we're doing a depth first search, `node_and_bounds_stack` will hold at most d nodes where d is the depth of the tree (the number of levels in the tree from the root node down to the lowest node). So we *could* say our space cost is $O(d)$.

But we can also relate d to n . In a balanced tree, d is $\log_2 n$ ([/concept/binary-tree#property2](#)). And the *more unbalanced* the tree gets, the closer d gets to n .

In the worst case, the tree is a straight line of right children from the root where every node in that line also has a left child. The traversal will walk down the line of right children, adding a new left child to the stack at each step. When the traversal hits the rightmost node, the stack will hold *half* of the n total nodes in the tree. Half n is $O(n)$, so our worst case space cost is $O(n)$.

Bonus

What if the input tree has duplicate values?

What if `-float('inf')` or `float('inf')` appear in the input tree?

What We Learned

We could think of this as a greedy approach. We start off by trying to solve the problem in just one walk through the tree. So we ask ourselves what values we need to track in order to do that. Which leads us to our stack that tracks upper and lower bounds.

We could also think of this as a sort of "**divide and conquer**" approach. The idea in general behind divide and conquer is to break the problem down into two or more subproblems, solve them, and then use that solution to solve the original problem.

In *this* case, we're dividing the problem into subproblems by saying, "This tree is a valid binary search tree if the left subtree is valid and the right subtree is valid." This is more apparent in the recursive formulation of the answer above.

Of course, it's just fine that our approach *could be* thought of as greedy or *could be* thought of as divide and conquer. It can be both. The point here isn't to create strict categorizations so we can debate whether or not something "counts" as divide and conquer.

Instead, the point is to recognize the underlying *patterns* behind algorithms, so we can get better at thinking through problems.

Sometimes we'll have to kinda smoosh together two or more different patterns to get our answer.

← [course home \(/table-of-contents\)](/table-of-contents)

Next up: 2nd Largest Item in a Binary Search Tree →
([/question/second-largest-item-in-bst?
course=fc1§ion=dynamic-programming-recursion](/question/second-largest-item-in-bst?course=fc1§ion=dynamic-programming-recursion))

Want more coding interview help?

Check out **interviewcake.com** for more advice, guides, and practice questions.