

KUNTUR

Google Ads API tool design document — Basic Access application

Field	Value
Tool name	KUNTUR
Developer	Carlos Augusto Espinoza — independent developer
Location	Lima, Peru
Website	https://kalin79.github.io/kuntur-site/
Privacy policy	https://kalin79.github.io/kuntur-site/privacidad.html
Contact	c.augusto.espinoza@gmail.com
Manager account (MCC)	115-720-4954
API version in use	Google Ads API v25 (REST interface)
Document date	3 September 2026

1. Summary

KUNTUR is a reporting and advisory tool that reads advertising performance data from Google Ads, aggregates it, and produces a written analysis with prioritised recommendations for the account owner. It is operated as a managed service: the developer runs the analysis on behalf of each client and delivers the resulting report.

The tool only reads data. It does not create, modify, pause or remove campaigns, ad groups, ads, budgets, bids, keywords or any other entity. No mutate service of the Google Ads API is called anywhere in the codebase.

Access model: clients link their Google Ads account to the manager account 115-720-4954, or authorise the application directly through Google's OAuth consent screen. The client can revoke that access at any time from their own Google account, without contacting the developer.

2. Business model and audience

Business model. A fee-based advisory service for small and medium advertisers. The client pays for a periodic performance analysis of their own advertising accounts. There is no resale of data, no advertising network, no lead generation from the data, and no third party ever receives the client's account data.

Audience. Small and medium businesses in Peru that invest in digital advertising and do not have an in-house media analyst, plus small agencies that need to justify their recommendations to clients with figures. Each client is the owner of the accounts being analysed.

Scale. The tool is being used by its developer for a small number of client accounts (fewer than ten in the first year). Each account is analysed roughly once every two to four weeks, over a thirty-day reporting window.

3. What the tool does with the Google Ads API

All Google Ads API usage is read-only reporting through GAQL queries issued to the `searchStream` endpoint of the REST interface. The three queries below are the complete set of report requests the tool makes.

Resource queried	Purpose	Frequency
campaign	Daily performance per campaign: the primary unit of analysis and budget reallocation advice.	Once per analysis, 30-day window
ad_group	Daily performance per ad group, to locate which part of a campaign drives its result.	Once per analysis, 30-day window
ad_group_ad	Daily performance per ad, to identify creative that under- or over-performs.	Once per analysis, 30-day window
customer	Account name, currency and time zone, cached when the account is connected.	On connection, and on manual connection test
customer_client	Lists the accounts linked to the manager account, used only for diagnostics in the administration panel.	On demand

Fields requested

Only entity identifiers and aggregate performance metrics are requested. Representative campaign-level query:

```
SELECT campaign.id, campaign.name, campaign.status,
       campaign.advertising_channel_type, segments.date,
       metrics.impressions, metrics.clicks, metrics.cost_micros,
       metrics.conversions, metrics.conversions_value,
       metrics.video_views, metrics.engagements
FROM campaign
WHERE segments.date BETWEEN '2026-08-01' AND '2026-08-30'
    AND campaign.status != 'REMOVED'
```

The tool does **not** request user lists, Customer Match audiences, billing data, or any field that could identify an individual who saw or clicked an ad.

Search terms are deliberately excluded from the current implementation. Search term reports can contain personal information typed by users into the search box. If they are ever incorporated, a filter that discards strings matching e-mail, phone and national-ID patterns will run before the data reaches any downstream processing.

4. Data flow

A single analysis runs as a chain of queued jobs. Each step is recorded so that any figure in the final report can be traced back to the API response that produced it.

Step	What happens
1. Authorisation	The account owner grants access through Google's OAuth consent screen (scope: <code>adwords</code>), or links their account to the manager account. Refresh tokens are stored encrypted at application level.

2. Retrieval	Three GAQL queries per account over a 30-day window. Responses are streamed and mapped: cost_micros is divided by 1,000,000 and dates are kept in the account's own time zone.
3. Storage	Rows are written to PostgreSQL with an idempotent upsert keyed on account, entity level, entity id and date, so a window can be re-synchronised without duplication when the platform restates conversions.
4. Aggregation	SQL aggregates the daily rows into period totals, per-campaign and per-ad summaries, and a weekly trend. Derived metrics (CPA, CPC, CTR, ROAS, CPV and others) are computed in SQL and application code, never by the language model.
5. Analysis	The aggregated summary is sent to the Anthropic Claude API, which returns a structured analysis validated against a strict JSON schema. No credentials, identifiers or personal data are included in that payload.
6. Delivery	Findings are stored, reviewed by the developer, and rendered into a report (spreadsheet, document and PDF) delivered to the client.

5. Who uses the tool

Access to the administration panel is restricted to the developer, who is the only person able to connect accounts, run analyses and download reports. Clients receive the resulting report by e-mail or through an expiring signed link; they do not log into the system in the current implementation.

A future version is planned in which clients would be able to sign in to view their own reports. That version will not change the read-only nature of the API usage, and each client would only ever see data from their own accounts, enforced at the database query level.

6. Security and data handling

- **Credentials.** Access and refresh tokens are encrypted at application level before being written to the database, so a database dump does not expose access to any client account. Tokens are never written to logs or audit records; an automated test dumps the entire audit log and fails if any token value appears in it.
- **No write operations.** The codebase contains no call to any Google Ads mutate service. This is enforced by code review and is being covered by an automated test that fails if a write call is introduced.
- **Audit trail.** Every account connection, credential change and report download is recorded with the acting user and timestamp.
- **Report storage.** Generated reports are written to private storage, never to a publicly served directory, and are delivered through signed links with an expiry date.
- **Retention.** Performance metrics are kept for 24 months, generated reports for 12 months, and revoked credentials are deleted after 30 days. Clients may request earlier deletion of all their data.
- **Backups.** The database is backed up daily and the backup copy stored off-machine is encrypted.

7. Technical implementation

Component	Detail
Platform	PHP 8.3 · Laravel 13 · Filament 5 administration panel

Database	PostgreSQL 15
API client	Direct HTTPS calls to the Google Ads API REST interface, pinned to v25. The official PHP client library is not used, to avoid the gRPC and protobuf dependency weight; the API version is therefore declared explicitly in configuration.
Rate limiting	Requests are queued, and HTTP 429 responses are retried with exponential backoff (60s, 300s, 900s) rather than immediate retry.
Error handling	Every retrieval run is recorded with its status, row count and error message, so a partial failure is visible rather than silently producing an incomplete report.
Testing	Recorded API responses are used as fixtures so the ingestion path can be tested without consuming quota. The current test suite covers metric conversion, idempotency of re-synchronisation, and credential protection.

8. Compliance

The developer has read the Google Ads API Terms and Conditions and the Required Minimum Functionality policy, and confirms the following about this tool:

- It is used only to access advertising accounts whose owners have expressly authorised access, either through the OAuth consent screen or through a manager account link they accepted.
- It does not aggregate or compare data across advertisers, and does not disclose one client's data to another.
- It does not use Google Ads data for any purpose other than producing the analysis the account owner has requested.
- It is not resold, sublicensed or made available to third parties as a self-service product at this time.
- The developer token is used solely with this tool, which the developer built and maintains.

Carlos Augusto Espinoza · Lima, Peru · c.augusto.espinoza@gmail.com · <https://kalin79.github.io/kuntur-site/>