

HealthcareAgent

FastAPI backend with PostgreSQL persistence for prescriptions, lab reports, clinical notes, and user metadata.

Users authenticate with bearer tokens, and user-facing IDs are UUIDs instead of integers.

Database

Copy `.env.example` to `.env` and set your local database settings. At minimum, set `POSTGRES_PASSWORD` for Docker and `DATABASE_URL` for the app:

```
POSTGRES_PASSWORD=your_password
DATABASE_URL=postgresql+psycopg2://postgres:postgres@localhost:5432/healthcareagent
```

Set `DATABASE_URL` before running the app if you are not using a `.env` file:

```
set
DATABASE_URL=postgresql+psycopg2://postgres:postgres@localhost:5432/healthcareagent
```

To run PostgreSQL locally with Docker:

```
docker compose up -d postgres
```

Create the database in PostgreSQL first, then start the app:

```
uvicorn main:app --reload
```

On startup, the app tries to create the required tables automatically.

Authentication

The API exposes two user roles: `patient` and `doctor`.

- `POST /api/auth/register` creates a user and returns a bearer token.
- `POST /api/auth/login` returns a bearer token for an existing user.
- `GET /api/auth/me` returns the authenticated user profile.

Send the token in the `Authorization: Bearer <token>` header for protected routes.

API

The main endpoints are mounted under `/api`:

- `POST /api/add-prescription`
- `GET /api/get-prescription?patient_id=<uuid>`
- `POST /api/add-clinical-note`
- `GET /api/get-clinical-note?patient_id=<uuid>`
- `POST /api/add-lab-report`
- `GET /api/get-lab-report?patient_id=<uuid>&report_date=...`
- `POST /api/talk`