

```
(kali㉿kali)-[~]  
$ curl -I https://1a7f612f0f9949d41ea1cad2ce180846.bunabyte.com/  
HTTP/2 200  
accept-ranges: bytes  
access-control-allow-origin: *  
age: 2268229  
cache-control: public, max-age=0, must-revalidate  
content-disposition: inline  
content-type: text/html; charset=utf-8  
date: Thu, 21 May 2026 13:09:20 GMT  
etag: "17df7c74c87255e0f4b837bc269c9404"  
last-modified: Sat, 25 Apr 2026 07:05:30 GMT  
server: Vercel  
strict-transport-security: max-age=63072000  
x-session-flag: QkJ7aDNhZDNyc19hcjNfZnVuX3QwXzN4cGwwcjN9  
x-vercel-cache: HIT  
x-vercel-id: cdg1::q7wwk-1779368960160-a7b1510409de  
content-length: 2269  
  
(kali㉿kali)-[~]  
$ echo "QkJ7aDNhZDNyc19hcjNfZnVuX3QwXzN4cGwwcjN9" | base64 -d  
BB{h3ad3rs_ar3_fun_t0_3xpl0r3}
```

At its absolute simplest: the purpose of **curl** is to **fetch or send data over a network using the command line**.

If you give **curl** a web address, it will go get the raw data from that address and bring it back to your terminal screen.