

FSR

March 6, 2021

```
[9]: import matplotlib.pyplot as plt
import numpy as np
from os import listdir
from sklearn import linear_model
from sklearn.linear_model import lasso_path
from warnings import filterwarnings
filterwarnings('ignore')

np.random.seed(2019)

def extract_temp(file_name,col_ind):
    data_aux = np.loadtxt(file_name, usecols=range(10))
    data = data_aux[:,col_ind]
    err_count = 0
    ind_errs = []
    for ind in range(data.shape[0]):
        if data[ind] > 100 or data[ind] < -100:
            err_count = err_count + 1
            ind_errs.append(ind)
            data[ind] = data[ind-1]
    print("File name: " + file_name)
    print("Errors: " + str(err_count) + " Indices: " + str(ind_errs))
    return data

def create_data_matrix(str_path):
    file_name_list = listdir(str_path)
    file_name_list.sort()
    col_ind = 8 # 8 = last 5 minutes, 9 = average over the whole hour
    data_matrix = []
    ind = 0
    for file_name in file_name_list:
        if file_name[0] == '.':
            continue
        else:
            print("Station " + str(ind))
            ind = ind + 1
            data_aux = extract_temp(str_path + file_name,col_ind)
```

```

        if len(data_matrix) == 0:
            data_matrix = data_aux
        else:
            data_matrix = np.vstack((data_matrix, data_aux))
    return data_matrix.T

def FSR(X, y, num_features=20):
    '''
    X: feature matrix
    y: response
    return
        coeff: coefficient betta
    '''
    S = []
    r = y
    coeff = np.zeros(shape=X.shape[1])
    iteration = 1
    position = np.linspace(0, X.shape[1]-1, num = X.shape[1])
    while iteration <= num_features:
        i_val = np.empty(shape=len(position), dtype=float)
        for i in range(len(position)):
            i_val[i] = np.linalg.norm(X[:, i].T @ r)
        i_star = np.argmax(i_val)
        S.append(int(position[i_star]))
        position = np.delete(position, i_star)
        beta = np.linalg.inv(X[:, S].T @ X[:, S]) @ X[:, S].T @ y
        r = y - X[:, S] @ beta
        for elem in range(len(S)):
            coeff[S[elem]] = beta[elem]
        iteration += 1
    return coeff

```

```

[10]: str_path = "./weather/"

load_files = False
if load_files:
    str_path_2015 = str_path + "hourly/2015/"
    data_matrix = create_data_matrix(str_path_2015)
    str_path_2016 = str_path + "hourly/2016/"
    data_matrix_2016 = create_data_matrix(str_path_2016)
else:
    data_matrix = np.load(str_path + "hourly_temperature_2015.npy")
    data_matrix_2016 = np.load(str_path + "hourly_temperature_2016.npy")

file_name_list = listdir(str_path + "hourly/2015/")
file_name_list.sort()

```

```

ind_response = 78 # 53 = Manhattan, 18 = Troy has 2 correlated features
# 23 = Williams dense linear model 30 = Death Valley 16 = AL_Talladega_10_NNE
    ↳ good for elastic net
# 78 = ND Jamestown also good for enet
print("Response is " + str(file_name_list[ind_response]))
y_raw = data_matrix[:,ind_response]
y_2016 = data_matrix_2016[:,ind_response]
ind_X = np.hstack((np.arange(0,ind_response),np.
    ↳ arange(ind_response+1,data_matrix.shape[1])))
X_raw = data_matrix[:,ind_X]
X_2016 = data_matrix_2016[:,ind_X]
n_features = X_raw.shape[1]

n_train_values = 40
n_test = int(1e3)
n_val = int(1e3)
n_train_max = data_matrix.shape[0] - n_test # 5e2
n_train_min = 133
n_train_list = np.around(np.logspace(np.log10(n_train_min),np.
    ↳ log10(n_train_max),n_train_values))

train_error_lasso_vec = []
val_error_lasso_vec = []
test_error_lasso_vec = []
test_2016_lasso_vec = []
train_error_ridge_vec = []
val_error_ridge_vec = []
test_error_ridge_vec = []
test_2016_ridge_vec = []

train_error_fsr_vec = []
val_error_fsr_vec = []
test_error_fsr_vec = []
test_2016_fsr_vec = []

coeffs_lasso_matrix = np.zeros((n_features,len(n_train_list)))
coeffs_ridge_matrix = np.zeros((n_features,len(n_train_list)))
coeffs_fsr_matrix = np.zeros((n_features,len(n_train_list)))
lambda_lasso_vec = []
lambda_ridge_vec = []
n_features_fsr_vec = []

n_lambda = 50
lambdas_ridge_aux = np.logspace(-5, 2, n_lambda)
lambdas_lasso = np.logspace(-5, 2, n_lambda)
eps = 1e-5 # the smaller it is the longer is the path
fixed_n = n_train_list[9]

```

```

i_m = 0
for n_train in n_train_list:
    lambdas_ridge = lambdas_ridge_aux * n_train
    aux_ind = np.random.permutation(range(data_matrix.shape[0]))
    ind_test = aux_ind[:n_test]
    ind_val = aux_ind[n_test:(n_test+n_val)]
    X_test = X_raw[ind_test,:]
    y_test = y_raw[ind_test]
    X_val = X_raw[ind_val,:]
    y_val = y_raw[ind_val]
    ind_train = aux_ind[(n_test+n_val):int(n_test+n_val+n_train)]
    X_train = X_raw[ind_train,:]
    y_train = y_raw[ind_train]

    center_vec = X_train.mean(axis=0)
    X_train_centered = X_train - center_vec
    col_norms = np.linalg.norm(X_train_centered, axis=0) / np.sqrt(n_train)
    X_train_norm = np.true_divide(X_train_centered, col_norms)
    X_test_centered = X_test - center_vec
    X_test_norm = np.true_divide(X_test_centered, col_norms)
    X_val_centered = X_val - center_vec
    X_val_norm = np.true_divide(X_val_centered, col_norms)
    X_2016_centered = X_2016 - center_vec
    X_2016_norm = np.true_divide(X_2016_centered, col_norms)
    y_train_center = y_train.mean()
    y_train_centered = y_train - y_train_center
    norm_y_train = np.linalg.norm(y_train_centered) / np.sqrt(n_train)
    y_train_norm = y_train_centered / norm_y_train

    print("Computing regularization path using the lasso...")
    lambdas_lasso, coeffs_lasso, _ = lasso_path(X_train_norm, y_train_norm,
↪eps, normalize=False,
                                                alphas = lambdas_lasso,
↪fit_intercept=False)

    min_error_val = 1e4
    i_lambda = 0
    val_error_lasso_lambdas = np.zeros(n_lambda)
    train_error_lasso_lambdas = np.zeros(n_lambda)
    for i, coeffs_est in enumerate(coeffs_lasso.T):
        y_val_lasso = norm_y_train * np.dot(X_val_norm, coeffs_est) +
↪y_train_center
        error_val = np.linalg.norm(y_val - y_val_lasso) / np.sqrt(len(y_val))
        # error_val_vec.append(error_val)
        if error_val < min_error_val:
            min_error_val = error_val

```

```

        lambda_best_lasso = lambdas_lasso[i]
        coeffs_lasso_best = coeffs_est
        y_train_lasso = norm_y_train * np.dot(X_train_norm, coeffs_est) +
→y_train_center
        train_error_lasso_lambdas[i] = np.linalg.norm(y_train - y_train_lasso
→) / np.sqrt(len(y_train))
        val_error_lasso_lambdas[i] = error_val
        lambda_lasso_vec.append(lambda_best_lasso)
        y_train_lasso = norm_y_train * np.dot(X_train_norm, coeffs_lasso_best) +
→y_train_center
        y_test_lasso = norm_y_train * np.dot(X_test_norm, coeffs_lasso_best) +
→y_train_center
        y_2016_lasso = norm_y_train * np.dot(X_2016_norm, coeffs_lasso_best) +
→y_train_center
        train_error_lasso = np.linalg.norm(y_train - y_train_lasso) / np.
→sqrt(len(y_train))
        test_error_lasso = np.linalg.norm(y_test - y_test_lasso) / np.
→sqrt(len(y_test))
        test_2016_lasso = np.linalg.norm(y_2016 - y_2016_lasso) / np.
→sqrt(len(y_2016))
        train_error_lasso_vec.append(train_error_lasso)
        val_error_lasso_vec.append(min_error_val)
        test_error_lasso_vec.append(test_error_lasso)
        test_2016_lasso_vec.append(test_2016_lasso)
        coeffs_lasso_matrix[:,i_m] = coeffs_lasso_best

if n_train == fixed_n:
    coeffs_lasso_fixed = np.copy(coeffs_lasso)
    plt.figure()
    plt.plot(lambdas_lasso,coeffs_lasso.T)
    plt.plot(lambdas_lasso,val_error_lasso_lambdas/10.,marker='o')
    plt.plot(lambdas_lasso,train_error_lasso_lambdas/10.,marker='x')
    plt.xscale('log')
    plt.title('Lasso: n = ' + str(n_train))

    plt.figure(figsize=(8,6))
    plt.
→plot(lambdas_lasso,train_error_lasso_lambdas,marker='o',linestyle='none',color='purple',lab
→error')
    plt.
→plot(lambdas_lasso,val_error_lasso_lambdas,marker='o',linestyle='none',color='red',label='V
→error')
    plt.xlabel(r"Regularization parameter ( $\lambda$ )",fontsize=14)
    plt.ylabel('Average error (deg Celsius)',fontsize=14)
    plt.gcf().subplots_adjust(bottom=0.15)

```

```

plt.xscale('log')
plt.legend(loc = 'lower right',fontsize=14)

# ridge regression
clf = linear_model.Ridge(fit_intercept=False, normalize=False,)
min_error_val = 1e3
lambda_best = 0
coeffs_ridge = np.zeros((n_features,n_lambda))
val_error_ridge_lambdas = np.zeros(n_lambda)
for ind_a,a in enumerate(lambdas_ridge):
    # print "lambda: " + str(a)
    clf.set_params(alpha=a)
    clf.fit(X_train_norm, y_train_norm)
    coeffs_ridge[:,ind_a] = clf.coef_
    y_val_ridge = norm_y_train * np.dot(X_val_norm, clf.coef_) + y_train_center
    error_val = np.linalg.norm(y_val - y_val_ridge) / np.sqrt(len(y_val))
    val_error_ridge_lambdas[ind_a] = error_val
    # error_val_vec.append(error_val)
    if error_val < min_error_val:
        min_error_val = error_val
        lambda_best = a
        coeffs_ridge_best = clf.coef_
    lambda_ridge_vec.append(lambda_best)
    y_train_ridge = norm_y_train * np.dot(X_train_norm, coeffs_ridge_best) + y_train_center
    y_test_ridge = norm_y_train * np.dot(X_test_norm, coeffs_ridge_best) + y_train_center
    y_2016_ridge = norm_y_train * np.dot(X_2016_norm, coeffs_ridge_best) + y_train_center
    train_error_ridge = np.linalg.norm(y_train - y_train_ridge) / np.
    sqrt(len(y_train))
    test_error_ridge = np.linalg.norm(y_test - y_test_ridge) / np.
    sqrt(len(y_test))
    test_2016_ridge = np.linalg.norm(y_2016 - y_2016_ridge) / np.
    sqrt(len(y_2016))
    train_error_ridge_vec.append(train_error_ridge)
    val_error_ridge_vec.append(min_error_val)
    test_error_ridge_vec.append(test_error_ridge)
    test_2016_ridge_vec.append(test_2016_ridge)
    coeffs_ridge_matrix[:,i_m] = coeffs_ridge_best

if n_train == fixed_n:
    coeffs_ridge_fixed = np.copy(coeffs_ridge)
    plt.figure(figsize=(8,6))

```

```

    # plt.plot(lambdas_ridge, val_error_lasso_lambdas/10., marker='o')
    for ind in range(n_features):
        plt.plot(lambdas_ridge, coeffs_ridge[ind, :], color='skyblue')
        plt.xscale('log')
        plt.title('Ridge: n = ' + str(n_train))

# FSR
min_error_val = 1e3
n_features_best_fsr = 0
n_feature = X_train_norm.shape[1]
coeffs_fsr = np.zeros((X_train_norm.shape[1], X_train_norm.shape[1]))
val_error_fsr_lambdas = np.zeros(n_feature)
train_error_fsr_lambdas = np.zeros(n_feature)
for i, a in enumerate(range(1, n_feature)):
    coeffs_fsr = FSR(X_train_norm, y_train_norm, num_features=a)
    y_train_fsr = norm_y_train * np.dot(X_train_norm, coeffs_fsr) +
    ↪ y_train_center
    y_val_fsr = norm_y_train * np.dot(X_val_norm, coeffs_fsr) +
    ↪ y_train_center
    error_val = np.linalg.norm(y_val - y_val_fsr) / np.sqrt(len(y_val))
    # error_val_vec.append(error_val)
    if error_val < min_error_val:
        min_error_val = error_val
        n_features_best_fsr = a
        coeffs_fsr_best = coeffs_est

    train_error_fsr_lambdas[i] = np.linalg.norm(y_train - y_train_fsr) /
    ↪ np.sqrt(len(y_train))
    val_error_fsr_lambdas[i] = error_val
    n_features_fsr_vec.append(n_features_best_fsr)

    y_train_fsr = norm_y_train * np.dot(X_train_norm, coeffs_fsr_best) +
    ↪ y_train_center

    y_train_fsr = norm_y_train * np.dot(X_train_norm, coeffs_fsr_best) +
    ↪ y_train_center
    y_test_fsr = norm_y_train * np.dot(X_test_norm, coeffs_fsr_best) +
    ↪ y_train_center
    y_2016_fsr = norm_y_train * np.dot(X_2016_norm, coeffs_fsr_best) +
    ↪ y_train_center
    train_error_fsr = np.linalg.norm(y_train - y_train_fsr) / np.
    ↪ sqrt(len(y_train))
    test_error_fsr = np.linalg.norm(y_test - y_test_fsr) / np.sqrt(len(y_test))
    test_2016_fsr = np.linalg.norm(y_2016 - y_2016_fsr) / np.sqrt(len(y_2016))
    train_error_fsr_vec.append(train_error_fsr)

```

```

val_error_fsr_vec.append(min_error_val)
test_error_fsr_vec.append(test_error_fsr)
test_2016_fsr_vec.append(test_2016_fsr)

coeffs_fsr_matrix[:,i_m] = coeffs_fsr_best


if n_train == fixed_n:
    plt.figure(figsize=(8,6))
    plt.
    plot(range(len(train_error_fsr_lambdas)),train_error_fsr_lambdas,marker='o',linestyle='none',color='red')
    plt.
    plot(range(len(val_error_fsr_lambdas)),val_error_fsr_lambdas,marker='o',linestyle='none',color='blue')
    plt.xlabel(r"Number of features",fontsize=14)
    plt.ylabel('Average error (deg Celsius)',fontsize=14)
    plt.gcf().subplots_adjust(bottom=0.15)
    plt.legend(loc = 'lower right',fontsize=14)


i_m = i_m + 1


```


[illegible]

Computing regularization path using the lasso...
Computing regularization path using the lasso...
Computing regularization path using the lasso...
Computing regularization path using the lasso...
Computing regularization path using the lasso...
Computing regularization path using the lasso...
Computing regularization path using the lasso...
Computing regularization path using the lasso...
Computing regularization path using the lasso...
Computing regularization path using the lasso...
Computing regularization path using the lasso...
Computing regularization path using the lasso...
Computing regularization path using the lasso...
Computing regularization path using the lasso...
Computing regularization path using the lasso...









```
[11]: # xticks=(np.array([200,500,1000,2000,5000]))
# xtick_labels = ('200','500','1000','2000','5000')
plt.figure(figsize=(12,6))
linestyle = 'None'
plt.
    ↳plot(n_train_list,train_error_ridge_vec,linestyle=linestyle,marker='x',color='purple',label=
    ↳error (RR)")
plt.
    ↳plot(n_train_list,test_error_ridge_vec,linestyle=linestyle,marker='x',color='red',label="Tes
    ↳error (RR)")
plt.
    ↳plot(n_train_list,test_2016_ridge_vec,linestyle=linestyle,marker='x',color='green',label="Te
    ↳error 2016 (RR)")
plt.
    ↳plot(n_train_list,train_error_lasso_vec,linestyle=linestyle,marker='o',color='purple',label=
    ↳error (lasso)")
plt.
    ↳plot(n_train_list,test_error_lasso_vec,linestyle=linestyle,marker='o',color='red',label="Tes
    ↳error (lasso)")
```

```

plt.
    ↳plot(n_train_list,test_2016_lasso_vec,linestyle=linstyle,marker='o',color='green',label="Te
    ↳error 2016 (lasso)")
plt.
    ↳plot(n_train_list,train_error_fsr_vec,linestyle=linstyle,marker='+',color='purple',label="T
    ↳error (FSR)")
plt.
    ↳plot(n_train_list,test_error_fsr_vec,linestyle=linstyle,marker='+',color='red',label="Test_
    ↳error (FSR)")
plt.
    ↳plot(n_train_list,test_2016_fsr_vec,linestyle=linstyle,marker='+',color='green',label="Test_
    ↳error 2016 (FSR)")
# plt.ylim((-0.5,7))
plt.xscale('log')
plt.xlabel('Number of training data',fontsize=14)
plt.ylabel('Average error (deg Celsius)',fontsize=14)
#plt.xticks(xticks,xtick_labels)
plt.tick_params(labelsize=12)
plt.legend(fontsize=14)
plt.gcf().subplots_adjust(bottom=0.15)

plt.figure(figsize=(8,6))
plt.plot(n_train_list,lambda_lasso_vec,marker='o',linestyle='none')
plt.xscale('log')
plt.yscale('log')
plt.ylabel(r"Regularization parameter ( $\lambda$ )",fontsize=14)
plt.xlabel('Number of training data (n)',fontsize=14)
# plt.xticks(xticks,xtick_labels)
plt.tick_params(labelsize=12)
# plt.gcf().subplots_adjust(left=0.2)
plt.gcf().subplots_adjust(bottom=0.15)

plt.figure(figsize=(8,6))
plt.plot(n_train_list,n_features_fsr_vec,marker='o',linestyle='none')
plt.xscale('log')
#plt.yscale('log')
plt.ylabel(r"Number of features",fontsize=14)
plt.xlabel('Number of training data (n)',fontsize=14)
# plt.xticks(xticks,xtick_labels)
plt.tick_params(labelsize=12)
# plt.gcf().subplots_adjust(left=0.2)
plt.gcf().subplots_adjust(bottom=0.15)

n_largest = 3
color_list = ['black','red','purple','green','orange']

```

```

sorted_coeffs = np.argsort(np.abs(coeffs_lasso_matrix[:,-1]))
largest_coeffs = sorted_coeffs[-1:(-n_largest-1):-1]
plt.figure(figsize=(8,6))
for ind in range(n_features):
    plt.plot(n_train_list,coeffs_lasso_matrix[ind,:],color='skyblue')
for ind in range(len(largest_coeffs)):
    ind_name = largest_coeffs[ind]
    if ind_name>=ind_response:
        ind_name = ind_name + 1
    aux_name = file_name_list[ind_name]
    aux_name = aux_name[14:]
    aux_name = aux_name[:-7]
    table = str.maketrans(dict.fromkeys('_0123456789'))
    aux_name = aux_name.translate(table)
    aux_name = aux_name[2:] + ", " + aux_name[:2]
    plt.plot(n_train_list,coeffs_lasso_matrix[largest_coeffs[ind],:
↪],color=color_list[ind],label=aux_name)
plt.ylim((-0.6,0.6))
plt.xscale('log')
plt.xlabel('Number of training data',fontsize=14)
plt.ylabel('Coefficients',fontsize=14)
# plt.xticks(xticks,xtick_labels)
plt.tick_params(labels=12)
# plt.gcf().subplots_adjust(left=0.2)
plt.gcf().subplots_adjust(bottom=0.15)
#plt.legend(loc = 'upper right',bbox_to_anchor=(1.3, 1.))
plt.legend(loc = 'lower right',fontsize=14)
aux_name = file_name_list[ind_response]
aux_name = aux_name[14:]
aux_name = aux_name[:-7]
table = str.maketrans(dict.fromkeys('_0123456789'))
aux_name = aux_name.translate(table)
aux_name = aux_name[2:] + ", " + aux_name[:2]
# plt.title(aux_name)

sorted_coeffs = np.argsort(np.abs(coeffs_lasso_matrix[:,-1]))
largest_coeffs = sorted_coeffs[-1:(-n_largest-1):-1]
plt.figure(figsize=(8,6))
for ind in range(n_features):
    plt.plot(n_train_list,coeffs_lasso_matrix[ind,:],color='skyblue')
for ind in range(len(largest_coeffs)):
    ind_name = largest_coeffs[ind]
    if ind_name>=ind_response:
        ind_name = ind_name + 1
    aux_name = file_name_list[ind_name]
    aux_name = aux_name[14:]
    aux_name = aux_name[:-7]

```

```

        table = str.maketrans(dict.fromkeys('_0123456789'))
        aux_name = aux_name.translate(table)
        aux_name = aux_name[2:] + ", " + aux_name[:2]
        plt.plot(n_train_list, coeffs_lasso_matrix[largest_coeffs[ind], :
→], color=color_list[ind], label=aux_name)
plt.ylim((-0.6, 0.6))
plt.xscale('log')
plt.xlabel('Number of training data', fontsize=14)
plt.ylabel('Coefficients', fontsize=14)
# plt.xticks(xticks, xtick_labels)
plt.tick_params(labelsize=12)
# plt.gcf().subplots_adjust(left=0.2)
plt.gcf().subplots_adjust(bottom=0.15)
# plt.legend(loc = 'upper right', bbox_to_anchor=(1.3, 1.))
plt.legend(loc = 'lower right', fontsize=14)
aux_name = file_name_list[ind_response]
aux_name = aux_name[14:]
aux_name = aux_name[:-7]
table = str.maketrans(dict.fromkeys('_0123456789'))
aux_name = aux_name.translate(table)
aux_name = aux_name[2:] + ", " + aux_name[:2]
# plt.title(aux_name)

plt.figure(figsize=(8,6))
for ind in range(n_features):
    plt.plot(lambdas_ridge, coeffs_ridge_fixed[ind, :], color='skyblue')
    plt.xscale('log')
for ind in range(len(largest_coeffs)):
    ind_name = largest_coeffs[ind]
    if ind_name >= ind_response:
        ind_name = ind_name + 1
    aux_name = file_name_list[ind_name]
    aux_name = aux_name[14:]
    aux_name = aux_name[:-7]
    table = str.maketrans(dict.fromkeys('_0123456789'))
    aux_name = aux_name.translate(table)
    aux_name = aux_name[2:] + ", " + aux_name[:2]
    plt.plot(lambdas_ridge, coeffs_ridge_fixed[largest_coeffs[ind], :
→], color=color_list[ind], label=aux_name)
plt.xlabel(r"Regularization parameter ( $\lambda/n$ )", fontsize=14)
plt.ylabel('Coefficients', fontsize=14)
plt.gcf().subplots_adjust(bottom=0.15)
plt.legend(loc = 'upper right', fontsize=14)
plt.xscale('log')


plt.figure(figsize=(8,6))
for ind in range(n_features):


```


```


plt.plot(lambdas_lasso, coeffs_lasso_fixed[ind,:], color='skyblue')
plt.xscale('log')
for ind in range(len(largest_coeffs)):
    ind_name = largest_coeffs[ind]
    if ind_name >= ind_response:
        ind_name = ind_name + 1
    aux_name = file_name_list[ind_name]
    aux_name = aux_name[14:]
    aux_name = aux_name[:-7]
    table = str.maketrans(dict.fromkeys('_0123456789'))
    aux_name = aux_name.translate(table)
    aux_name = aux_name[2:] + ", " + aux_name[2:]
    plt.plot(lambdas_lasso, coeffs_lasso_fixed[largest_coeffs[ind], :
↪], color=color_list[ind], label=aux_name)
plt.xlabel(r"Regularization parameter ( $\lambda/n$ )", fontsize=14)
plt.ylabel('Coefficients', fontsize=14)
plt.gcf().subplots_adjust(bottom=0.15)
plt.legend(loc = 'upper right', fontsize=14)
plt.xscale('log')


```

















[]: