Workshop: Projectile Motion

An introduction to computing trajectories

Jonas van den Brink j.v.brink@fys.uio.no

Simula Research Laboratory Oslo, Norway

January 29, 2015





Equations of motion

$$\frac{\mathrm{d}\vec{r}}{\mathrm{d}t} = \vec{v}(t), \qquad \frac{\mathrm{d}\vec{v}}{\mathrm{d}t} = \vec{a}(t)$$

Newtons 2. law of motion

$$\vec{F} = m\vec{a}$$

Newtons 2. law of motion

$$\vec{F} = m\vec{a}$$



Newtons 2. law of motion

$$\vec{F} = m\vec{a}$$



$$\vec{F}(r, v, t) = m\vec{a}(r, v, t).$$

Our algorithm is now as follows

- 1. Find the physical forces of the system.
- 2. Use Newtons 2. law to find the acceleration
- 3. Calculate $\vec{v}(t)$ and $\vec{r}(t)$ by solving the equations of motion

Our algorithm is now as follows

- 1. Find the physical forces of the system.
- 2. Use Newtons 2. law to find the acceleration
- 3. Calculate $\vec{v}(t)$ and $\vec{r}(t)$ by solving the equations of motion

In this workshop, we will solve step number 3 numerically, using the Euler method.

The Euler Method

A method for solving ordinary differential equations (ODEs)

From the definition of the derivative

$$\frac{\mathrm{d}v}{\mathrm{d}t} = \lim_{\Delta t \to 0} \frac{v(t + \Delta t) - v(t)}{\Delta t} = a(t)$$

From the definition of the derivative

$$\frac{\mathrm{d}v}{\mathrm{d}t} = \lim_{\Delta t \to 0} \frac{v(t + \Delta t) - v(t)}{\Delta t} = a(t)$$

We now remove the limit, making Δt a very small constant

$$\frac{v(t+\Delta t)-v(t)}{\Delta t}\approx a(t)$$

From the definition of the derivative

$$rac{\mathrm{d} v}{\mathrm{d} t} = \lim_{\Delta t o 0} rac{v(t + \Delta t) - v(t)}{\Delta t} = a(t)$$

We now remove the limit, making Δt a very small constant

$$rac{v(t+\Delta t)-v(t)}{\Delta t}pprox a(t)$$

Solving for $v(t+\Delta t)$ gives

$$v(t + \Delta t) \approx v(t) + a(t) \cdot \Delta t$$

We can solve the equations of motion by stepping forward in time

$$v(t + \Delta t) = v(t) + a(t) \cdot \Delta t$$

We can solve the equations of motion by stepping forward in time

$$v(t + \Delta t) = v(t) + a(t) \cdot \Delta t$$

If a(t) and v(t) are known, we can calculate $v(t+\Delta t)$

We can solve the equations of motion by stepping forward in time

$$v(t+\Delta t)=v(t)+a(t)\cdot \Delta t$$
 If $a(t)$ and $v(t)$ are known, we can calculate $v(t+\Delta t)$
$$v(t)$$

$$v(t+\Delta t)$$

We only focus on multiples of our time-step

```
t \in \{0, \Delta t, 2\Delta t, 3\Delta t, \ldots\}
t_i \equiv i \cdot \Delta t
```

We only focus on multiples of our time-step

$$t \in \{0, \Delta t, 2\Delta t, 3\Delta t, \ldots\}$$

 $t_i \equiv i \cdot \Delta t$

Introduce the shorthand

$$v(t_i) \equiv v_i$$

 $r(t_i) \equiv r_i$

We only focus on multiples of our time-step


$$t \in \{0, \Delta t, 2\Delta t, 3\Delta t, \ldots\}$$

 $t_i \equiv i \cdot \Delta t$

Introduce the shorthand

$$v(t_i) \equiv v_i$$

 $r(t_i) \equiv r_i$



$$v_{i+1} = v_i + a_i \cdot \Delta t$$

$$v_{i+1} = v_i + a_i \cdot \Delta t$$

$$r_{i+1} = r_i + v_i \cdot \Delta t$$

$$v_{i+1} = v_i + a_i \cdot \Delta t$$

 $r_{i+1} = r_i + v_i \cdot \Delta t$

For each time step, we must calculate the acceleration

$$a_i = a(r_i, v_i, t_i).$$

$$v_{i+1} = v_i + a_i \cdot \Delta t$$

$$r_{i+1} = r_i + v_i \cdot \Delta t$$

For each time step, we must calculate the acceleration

$$a_i = a(r_i, v_i, t_i).$$

We repeat these steps, starting at our initial conditions v_0 and r_0 , until we have reached our end-time t_N

$$i = 0, 1, 2, 3, \ldots, N$$
.

Algorithm for the Euler method

for $i = 0, 1, 2, 3, \dots, N-1$:

- 1. Use the previous results x_i and v_i to compute the acceleration: $a_i = F(x_i, v_i, t_i)/m$.
- 2. Compute the new velocity: $v_{i+1} = v_i + a_i \Delta t$.
- 3. Compute the new position: $r_{i+1} = r_i + v_i \Delta t$.

Implementation

Moving from physics and math to actual computer code

- for $i = 0, 1, 2, 3, \dots, N-1$:
 - 1. Use the previous results x_i and v_i to compute the acceleration: $a_i = F(x_i, v_i, t_i)/m$.
 - 2. Compute the new velocity: $v_{i+1} = v_i + a_i \Delta t$.
 - 3. Compute the new position: $r_{i+1} = r_i + v_i \Delta t$.

- for i = 0, 1, 2, 3, ..., N 1:
 - 1. Use the previous results x_i and v_i to compute the acceleration: $a_i = F(x_i, v_i, t_i)/m$.
 - 2. Compute the new velocity: $v_{i+1} = v_i + a_i \Delta t$.
 - 3. Compute the new position: $r_{i+1} = r_i + v_i \Delta t$.



```
for i in range(N):
    a[i] = F(x[i], v[i], t[i])/m
    v[i+1] = v[i] + a[i]*dt
    r[i+1] = r[i] + v[i]*dt
```

for i = 0, 1, 2, 3, ..., N - 1:

- 1. Use the previous results x_i and v_i to compute the acceleration: $a_i = F(x_i, v_i, t_i)/m$.
- 2. Compute the new velocity: $v_{i+1} = v_i + a_i \Delta t$.
- 3. Compute the new position: $r_{i+1} = r_i + v_i \Delta t$.



```
for i in range(N):
    a[i] = F(x[i], v[i], t[i])/m
    v[i+1] = v[i] + a[i]*dt
    r[i+1] = r[i] + v[i]*dt
```

We want the code to look as much as possible like the physics and math we write on paper

$$t_i \Rightarrow t[i]$$
 $v_i \Rightarrow v[i]$ $r_i \Rightarrow r[i]$

We also need various bookeeping code

Here we define the arrays we will be using

```
# Import various functions meant for numerical science
from pylab import *
t_0 = 0 \# Start time, s
t_{end} = 10 \# End time, s
N = 1000 \# Number of time steps
# Create a uniformly spaced time-array
t = linspace(t_0, t_end, N+1)
# Calculate the size of a time step
dt = t[1] - t[0]
# Create empty acceleration, velocity and position arrays
a = zeros((2, N+1))
v = zeros((2, N+1))
r = zeros((2, N+1))
# Set initial conditions
v[0] = (10,0) # inital velocity, m/s
r[0] = (0,1) # initial position, m
```

We also need various bookeeping code

Here we define physical constants for our system and define the function that describes the forces

```
m = 5.5 # mass, kg
g = 9.81 # acceleration of gravity, m/s^2
rho = 1.3 # air density, kg/m^3
C_D = 0.45 # drag coefficient
d = 0.11 # diameter of cannonball, m
A = pi*d**2 # cross-sectional area, m^2

def F(x, v, t):
    return -(0, m*g) - 0.5*rho*C_D*A*abs(v)*v
```

This example show the forces acting on the cannonball as it sails through the air

$$F(x, v, t) = F_g + F_d(\vec{v}) = -mg\vec{k} - \frac{1}{2}\rho C_D A |\vec{v}|\vec{v}$$





Results

- Can plot numerical result vs known solution
- Can plot with and without drag

• Can plot for various inital angles

Examples of possible projects

- Catapults, cannons, throwing of objects. Can include analytical and experimental data.
- Skydiver and plot the g-forces, can illustrate why a parachute needs to open slowly!
- Bungee-jumping! Great for teaching spring forces and programming technicalities.
- Block and spring, harmonic Oscillator
- Orbits of planets in the solar system with real data from NASA
- Pendulum (also with large angles!)