

1.PHP Connect to MySQL

Example (MySQLi Object-Oriented)

```
<?php
$servername = "localhost";
$username = "username";
$password = "password";

// Create connection
$conn = new mysqli($servername, $username, $password);

// Check connection
if ($conn->connect_error) {
    die("Connection failed: " . $conn->connect_error);
}
echo "Connected successfully";
?>
```

Example (MySQLi Procedural)

```
<?php
$servername = "localhost";
$username = "username";
$password = "password";

// Create connection
$conn = mysqli_connect($servername, $username, $password);

// Check connection
if (!$conn) {
    die("Connection failed: " . mysqli_connect_error());
}
echo "Connected successfully";
?>
```

Example (PDO)

```
<?php
$servername = "localhost";
$username = "username";
$password = "password";

try {
    $conn = new PDO("mysql:host=$servername;dbname=myDB", $username, $password);
    // set the PDO error mode to exception
    $conn->setAttribute(PDO::ATTR_ERRMODE, PDO::ERRMODE_EXCEPTION);
    echo "Connected successfully";
}
catch(PDOException $e)
{
    echo "Connection failed: " . $e->getMessage();
}
```

```
}  
?>
```

2. PHP Create a MySQL Database

Example (MySQLi Object-oriented)

```
<?php  
$servername = "localhost";  
$username = "username";  
$password = "password";  
  
// Create connection  
$conn = new mysqli($servername, $username, $password);  
// Check connection  
if ($conn->connect_error) {  
    die("Connection failed: " . $conn->connect_error);  
}  
  
// Create database  
$sql = "CREATE DATABASE myDB";  
if ($conn->query($sql) === TRUE) {  
    echo "Database created successfully";  
} else {  
    echo "Error creating database: " . $conn->error;  
}  
  
$conn->close();  
?>
```

Example (MySQLi Procedural)

```
<?php  
$servername = "localhost";  
$username = "username";  
$password = "password";  
  
// Create connection  
$conn = mysqli_connect($servername, $username, $password);  
// Check connection  
if (!$conn) {  
    die("Connection failed: " . mysqli_connect_error());  
}  
  
// Create database  
$sql = "CREATE DATABASE myDB";  
if (mysqli_query($conn, $sql)) {  
    echo "Database created successfully";  
} else {  
    echo "Error creating database: " . mysqli_error($conn);  
}  
}
```

```
mysqli_close($conn);  
?>
```

Example (PDO)

```
<?php  
$servername = "localhost";  
$username = "username";  
$password = "password";  
  
try {  
    $conn = new PDO("mysql:host=$servername", $username, $password);  
    // set the PDO error mode to exception  
    $conn->setAttribute(PDO::ATTR_ERRMODE, PDO::ERRMODE_EXCEPTION);  
    $sql = "CREATE DATABASE myDBPDO";  
    // use exec() because no results are returned  
    $conn->exec($sql);  
    echo "Database created successfully<br>";  
}  
catch(PDOException $e)  
{  
    echo $sql . "<br>" . $e->getMessage();  
}  
  
$conn = null;  
?>
```

3.Create a MySQL Table Using MySQLi and PDO

Example (MySQLi Object-oriented)

```
<?php  
$servername = "localhost";  
$username = "username";  
$password = "password";  
$dbname = "myDB";  
  
// Create connection  
$conn = new mysqli($servername, $username, $password, $dbname);  
// Check connection  
if ($conn->connect_error) {  
    die("Connection failed: " . $conn->connect_error);  
}  
  
// sql to create table  
$sql = "CREATE TABLE MyGuests (  
id INT(6) UNSIGNED AUTO_INCREMENT PRIMARY KEY,  
firstname VARCHAR(30) NOT NULL,  
lastname VARCHAR(30) NOT NULL,  
email VARCHAR(50),  
reg_date TIMESTAMP
```

```

    );

    if ($conn->query($sql) === TRUE) {
        echo "Table MyGuests created successfully";
    } else {
        echo "Error creating table: " . $conn->error;
    }

    $conn->close();
    ?>

```

Example (MySQLi Procedural)

```

<?php
$servername = "localhost";
$username = "username";
$password = "password";
$dbname = "myDB";

// Create connection
$conn = mysqli_connect($servername, $username, $password, $dbname);
// Check connection
if (!$conn) {
    die("Connection failed: " . mysqli_connect_error());
}

// sql to create table
$sql = "CREATE TABLE MyGuests (
id INT(6) UNSIGNED AUTO_INCREMENT PRIMARY KEY,
firstname VARCHAR(30) NOT NULL,
lastname VARCHAR(30) NOT NULL,
email VARCHAR(50),
reg_date TIMESTAMP
)";

if (mysqli_query($conn, $sql)) {
    echo "Table MyGuests created successfully";
} else {
    echo "Error creating table: " . mysqli_error($conn);
}

mysqli_close($conn);
?>

```

Example (PDO)

```

<?php
$servername = "localhost";
$username = "username";
$password = "password";
$dbname = "myDBPDO";

try {
    $conn = new PDO("mysql:host=$servername;dbname=$dbname", $username,

```

```

$password);
    // set the PDO error mode to exception
    $conn->setAttribute(PDO::ATTR_ERRMODE, PDO::ERRMODE_EXCEPTION);

    // sql to create table
    $sql = "CREATE TABLE MyGuests (
    id INT(6) UNSIGNED AUTO_INCREMENT PRIMARY KEY,
    firstname VARCHAR(30) NOT NULL,
    lastname VARCHAR(30) NOT NULL,
    email VARCHAR(50),
    reg_date TIMESTAMP
    )";

    // use exec() because no results are returned
    $conn->exec($sql);
    echo "Table MyGuests created successfully";
}
catch(PDOException $e)
{
    echo $sql . "<br>" . $e->getMessage();
}

$conn = null;
?>

```

4. PHP Insert Data Into MySQL

Example (MySQLi Object-oriented)

```

<?php
$servername = "localhost";
$username = "username";
$password = "password";
$dbname = "myDB";

// Create connection
$conn = new mysqli($servername, $username, $password, $dbname);
// Check connection
if ($conn->connect_error) {
    die("Connection failed: " . $conn->connect_error);
}

$sql = "INSERT INTO MyGuests (firstname, lastname, email)
VALUES ('John', 'Doe', 'john@example.com')";

if ($conn->query($sql) === TRUE) {
    echo "New record created successfully";
} else {
    echo "Error: " . $sql . "<br>" . $conn->error;
}

$conn->close();
?>

```

Example (MySQLi Procedural)

```
<?php
$servername = "localhost";
$username = "username";
$password = "password";
$dbname = "myDB";

// Create connection
$conn = mysqli_connect($servername, $username, $password, $dbname);
// Check connection
if (!$conn) {
    die("Connection failed: " . mysqli_connect_error());
}

$sql = "INSERT INTO MyGuests (firstname, lastname, email)
VALUES ('John', 'Doe', 'john@example.com')";

if (mysqli_query($conn, $sql)) {
    echo "New record created successfully";
} else {
    echo "Error: " . $sql . "<br>" . mysqli_error($conn);
}

mysqli_close($conn);
?>
```

Example (PDO)

```
<?php
$servername = "localhost";
$username = "username";
$password = "password";
$dbname = "myDBPDO";

try {
    $conn = new PDO("mysql:host=$servername;dbname=$dbname", $username,
$password);
    // set the PDO error mode to exception
    $conn->setAttribute(PDO::ATTR_ERRMODE, PDO::ERRMODE_EXCEPTION);
    $sql = "INSERT INTO MyGuests (firstname, lastname, email)
VALUES ('John', 'Doe', 'john@example.com')";
    // use exec() because no results are returned
    $conn->exec($sql);
    echo "New record created successfully";
}
catch(PDOException $e)
{
    echo $sql . "<br>" . $e->getMessage();
}

$conn = null;
?>
```

5. PHP Get ID of Last Inserted Record

Example (MySQLi Object-oriented)

```
<?php
$servername = "localhost";
$username = "username";
$password = "password";
$dbname = "myDB";

// Create connection
$conn = new mysqli($servername, $username, $password, $dbname);
// Check connection
if ($conn->connect_error) {
    die("Connection failed: " . $conn->connect_error);
}

$sql = "INSERT INTO MyGuests (firstname, lastname, email)
VALUES ('John', 'Doe', 'john@example.com')";

if ($conn->query($sql) === TRUE) {
    $last_id = $conn->insert_id;
    echo "New record created successfully. Last inserted ID is: " . $last_id;
} else {
    echo "Error: " . $sql . "<br>" . $conn->error;
}

$conn->close();
?>
```

Example (MySQLi Procedural)

```
<?php
$servername = "localhost";
$username = "username";
$password = "password";
$dbname = "myDB";

// Create connection
$conn = mysqli_connect($servername, $username, $password, $dbname);
// Check connection
if (!$conn) {
    die("Connection failed: " . mysqli_connect_error());
}

$sql = "INSERT INTO MyGuests (firstname, lastname, email)
VALUES ('John', 'Doe', 'john@example.com')";

if (mysqli_query($conn, $sql)) {
    $last_id = mysqli_insert_id($conn);
    echo "New record created successfully. Last inserted ID is: " . $last_id;
} else {
```

```

        echo "Error: " . $sql . "<br>" . mysqli_error($conn);
    }

    mysqli_close($conn);
?>

```

Example (PDO)

```

<?php
$servername = "localhost";
$username = "username";
$password = "password";
$dbname = "myDBPDO";

try {
    $conn = new PDO("mysql:host=$servername;dbname=$dbname", $username,
$password);
    // set the PDO error mode to exception
    $conn->setAttribute(PDO::ATTR_ERRMODE, PDO::ERRMODE_EXCEPTION);
    $sql = "INSERT INTO MyGuests (firstname, lastname, email)
VALUES ('John', 'Doe', 'john@example.com')";
    // use exec() because no results are returned
    $conn->exec($sql);
    $last_id = $conn->lastInsertId();
    echo "New record created successfully. Last inserted ID is: " . $last_id;
}
catch(PDOException $e)
{
    echo $sql . "<br>" . $e->getMessage();
}

$conn = null;
?>

```

6.PHP Insert Multiple Records Into MySQL

Example (MySQLi Object-oriented)

```

<?php
$servername = "localhost";
$username = "username";
$password = "password";
$dbname = "myDB";

// Create connection
$conn = new mysqli($servername, $username, $password, $dbname);

```



```

// Check connection
if ($conn->connect_error) {
    die("Connection failed: " . $conn->connect_error);
}

$sql = "INSERT INTO MyGuests (firstname, lastname, email)
VALUES ('John', 'Doe', 'john@example.com')";
$sql .= "INSERT INTO MyGuests (firstname, lastname, email)
VALUES ('Mary', 'Moe', 'mary@example.com')";
$sql .= "INSERT INTO MyGuests (firstname, lastname, email)
VALUES ('Julie', 'Dooley', 'julie@example.com')";

if ($conn->multi_query($sql) === TRUE) {
    echo "New records created successfully";
} else {
    echo "Error: " . $sql . "<br>" . $conn->error;
}

$conn->close();
?>

<?php
$servername = "localhost";
$username = "username";
$password = "password";
$dbname = "myDB";

// Create connection
$conn = mysqli_connect($servername, $username, $password, $dbname);
// Check connection
if (!$conn) {
    die("Connection failed: " . mysqli_connect_error());
}

$sql = "INSERT INTO MyGuests (firstname, lastname, email)
VALUES ('John', 'Doe', 'john@example.com')";
$sql .= "INSERT INTO MyGuests (firstname, lastname, email)
VALUES ('Mary', 'Moe', 'mary@example.com')";
$sql .= "INSERT INTO MyGuests (firstname, lastname, email)
VALUES ('Julie', 'Dooley', 'julie@example.com')";

if (mysqli_multi_query($conn, $sql)) {
    echo "New records created successfully";
} else {
    echo "Error: " . $sql . "<br>" . mysqli_error($conn);
}

mysqli_close($conn);
?>

```

Example (PDO)

```

<?php
$servername = "localhost";
$username = "username";
$password = "password";
$dbname = "myDBPDO";

try {
    $conn = new PDO("mysql:host=$servername;dbname=$dbname", $username,
$password);
    // set the PDO error mode to exception
    $conn->setAttribute(PDO::ATTR_ERRMODE, PDO::ERRMODE_EXCEPTION);

    // begin the transaction
    $conn->beginTransaction();
    // our SQL statements
    $conn->exec("INSERT INTO MyGuests (firstname, lastname, email)
VALUES ('John', 'Doe', 'john@example.com')");
    $conn->exec("INSERT INTO MyGuests (firstname, lastname, email)
VALUES ('Mary', 'Moe', 'mary@example.com')");
    $conn->exec("INSERT INTO MyGuests (firstname, lastname, email)
VALUES ('Julie', 'Dooley', 'julie@example.com')");

    // commit the transaction
    $conn->commit();
    echo "New records created successfully";
}
catch(PDOException $e)
{
    // roll back the transaction if something failed
    $conn->rollback();
    echo "Error: " . $e->getMessage();
}

$conn = null;
?>

```

7. PHP Prepared Statements

Example (MySQLi with Prepared Statements)

```

<?php
$servername = "localhost";
$username = "username";
$password = "password";
$dbname = "myDB";

// Create connection
$conn = new mysqli($servername, $username, $password, $dbname);

// Check connection
if ($conn->connect_error) {
    die("Connection failed: " . $conn->connect_error);
}

```

```

// prepare and bind
$stmt = $conn->prepare("INSERT INTO MyGuests (firstname, lastname, email) VALUES
(?, ?, ?)");
$stmt->bind_param("sss", $firstname, $lastname, $email);

// set parameters and execute
$firstname = "John";
$lastname = "Doe";
$email = "john@example.com";
$stmt->execute();

$firstname = "Mary";
$lastname = "Moe";
$email = "mary@example.com";
$stmt->execute();

$firstname = "Julie";
$lastname = "Dooley";
$email = "julie@example.com";
$stmt->execute();

echo "New records created successfully";

$stmt->close();
$conn->close();
?>

```

Example (PDO with Prepared Statements)

```

<?php
$servername = "localhost";
$username = "username";
$password = "password";
$dbname = "myDBPDO";

try {
    $conn = new PDO("mysql:host=$servername;dbname=$dbname", $username,
$password);
    // set the PDO error mode to exception
    $conn->setAttribute(PDO::ATTR_ERRMODE, PDO::ERRMODE_EXCEPTION);

    // prepare sql and bind parameters
    $stmt = $conn->prepare("INSERT INTO MyGuests (firstname, lastname, email)
VALUES (:firstname, :lastname, :email)");
    $stmt->bindParam(':firstname', $firstname);
    $stmt->bindParam(':lastname', $lastname);
    $stmt->bindParam(':email', $email);

    // insert a row
    $firstname = "John";
    $lastname = "Doe";
    $email = "john@example.com";
    $stmt->execute();
}

```

```

        // insert another row
        $firstname = "Mary";
        $lastname = "Moe";
        $email = "mary@example.com";
        $stmt->execute();

        // insert another row
        $firstname = "Julie";
        $lastname = "Dooley";
        $email = "julie@example.com";
        $stmt->execute();

        echo "New records created successfully";
    }
} catch(PDOException $e)
{
    echo "Error: " . $e->getMessage();
}
$conn = null;
?>

```

8. PHP Select Data From MySQL

Example (MySQLi Object-oriented)

```

<?php
$servername = "localhost";
$username = "username";
$password = "password";
$dbname = "myDB";

// Create connection
$conn = new mysqli($servername, $username, $password, $dbname);
// Check connection
if ($conn->connect_error) {
    die("Connection failed: " . $conn->connect_error);
}

$sql = "SELECT id, firstname, lastname FROM MyGuests";
$result = $conn->query($sql);

if ($result->num_rows > 0) {
    // output data of each row
    while($row = $result->fetch_assoc()) {
        echo "id: " . $row["id"]. " - Name: " . $row["firstname"]. " " .
        $row["lastname"]. "<br>";
    }
} else {
    echo "0 results";
}
$conn->close();
?>

```

Example (MySQLi Procedural)

```
<?php
$servername = "localhost";
$username = "username";
$password = "password";
$dbname = "myDB";

// Create connection
$conn = mysqli_connect($servername, $username, $password, $dbname);
// Check connection
if (!$conn) {
    die("Connection failed: " . mysqli_connect_error());
}

$sql = "SELECT id, firstname, lastname FROM MyGuests";
$result = mysqli_query($conn, $sql);

if (mysqli_num_rows($result) > 0) {
    // output data of each row
    while($row = mysqli_fetch_assoc($result)) {
        echo "id: " . $row["id"]. " - Name: " . $row["firstname"]. " " .
$row["lastname"]. "<br>";
    }
} else {
    echo "0 results";
}

mysqli_close($conn);
?>
```

Example (MySQLi Object-oriented)

```
<?php
$servername = "localhost";
$username = "username";
$password = "password";
$dbname = "myDB";

// Create connection
$conn = new mysqli($servername, $username, $password, $dbname);
// Check connection
if ($conn->connect_error) {
    die("Connection failed: " . $conn->connect_error);
}

$sql = "SELECT id, firstname, lastname FROM MyGuests";
$result = $conn->query($sql);

if ($result->num_rows > 0) {
    echo "<table><tr><th>ID</th><th>Name</th></tr>";
    // output data of each row
```

```

        while($row = $result->fetch_assoc()) {
            echo "<tr><td>".$row["id"]."</td><td>".$row["firstname"]."
".$row["lastname"]."</td></tr>";
        }
        echo "</table>";
    } else {
        echo "0 results";
    }
    $conn->close();
?>

```

Example (PDO)

```

<?php
echo "<table style='border: solid 1px black;'>";
echo "<tr><th>Id</th><th>Firstname</th><th>Lastname</th></tr>";

class TableRows extends RecursiveIteratorIterator {
    function __construct($it) {
        parent::__construct($it, self::LEAVES_ONLY);
    }

    function current() {
        return "<td style='width:150px;border:1px solid black;'>" .
parent::current(). "</td>";
    }

    function beginChildren() {
        echo "<tr>";
    }

    function endChildren() {
        echo "</tr>" . "\n";
    }
}

$servername = "localhost";
$username = "username";
$password = "password";
$dbname = "myDBPDO";

try {
    $conn = new PDO("mysql:host=$servername;dbname=$dbname", $username,
$password);
    $conn->setAttribute(PDO::ATTR_ERRMODE, PDO::ERRMODE_EXCEPTION);
    $stmt = $conn->prepare("SELECT id, firstname, lastname FROM MyGuests");
    $stmt->execute();

    // set the resulting array to associative
    $result = $stmt->setFetchMode(PDO::FETCH_ASSOC);
    foreach(new TableRows(new RecursiveArrayIterator($stmt->fetchAll())) as $k=
>$v) {
        echo $v;
    }
}

```

```

    }
    catch(PDOException $e) {
        echo "Error: " . $e->getMessage();
    }
    $conn = null;
    echo "</table>";
?>

```

9. PHP Delete Data From MySQL

Example (MySQLi Object-oriented)

```

<?php
$servername = "localhost";
$username = "username";
$password = "password";
$dbname = "myDB";

// Create connection
$conn = new mysqli($servername, $username, $password, $dbname);
// Check connection
if ($conn->connect_error) {
    die("Connection failed: " . $conn->connect_error);
}

// sql to delete a record
$sql = "DELETE FROM MyGuests WHERE id=3";

if ($conn->query($sql) === TRUE) {
    echo "Record deleted successfully";
} else {
    echo "Error deleting record: " . $conn->error;
}

$conn->close();
?>

```

Example (MySQLi Procedural)

```

<?php
$servername = "localhost";
$username = "username";
$password = "password";
$dbname = "myDB";

// Create connection
$conn = mysqli_connect($servername, $username, $password, $dbname);
// Check connection
if (!$conn) {
    die("Connection failed: " . mysqli_connect_error());
}

// sql to delete a record

```

```

$sql = "DELETE FROM MyGuests WHERE id=3";

if (mysqli_query($conn, $sql)) {
    echo "Record deleted successfully";
} else {
    echo "Error deleting record: " . mysqli_error($conn);
}

mysqli_close($conn);
?>

```

Example (PDO)

```

<?php
$servername = "localhost";
$username = "username";
$password = "password";
$dbname = "myDBPDO";

try {
    $conn = new PDO("mysql:host=$servername;dbname=$dbname", $username,
$password);
    // set the PDO error mode to exception
    $conn->setAttribute(PDO::ATTR_ERRMODE, PDO::ERRMODE_EXCEPTION);

    // sql to delete a record
    $sql = "DELETE FROM MyGuests WHERE id=3";

    // use exec() because no results are returned
    $conn->exec($sql);
    echo "Record deleted successfully";
}
catch(PDOException $e)
{
    echo $sql . "<br>" . $e->getMessage();
}

$conn = null;
?>

```

10.PHP Update Data in MySQL

Example (MySQLi Object-oriented)

```

<?php
$servername = "localhost";
$username = "username";
$password = "password";
$dbname = "myDB";

// Create connection
$conn = new mysqli($servername, $username, $password, $dbname);
// Check connection

```



```

if ($conn->connect_error) {
    die("Connection failed: " . $conn->connect_error);
}

$sql = "UPDATE MyGuests SET lastname='Doe' WHERE id=2";

if ($conn->query($sql) === TRUE) {
    echo "Record updated successfully";
} else {
    echo "Error updating record: " . $conn->error;
}

$conn->close();
?>

```

Example (MySQLi Procedural)

```

<?php
$servername = "localhost";
$username = "username";
$password = "password";
$dbname = "myDB";

// Create connection
$conn = mysqli_connect($servername, $username, $password, $dbname);
// Check connection
if (!$conn) {
    die("Connection failed: " . mysqli_connect_error());
}

$sql = "UPDATE MyGuests SET lastname='Doe' WHERE id=2";

if (mysqli_query($conn, $sql)) {
    echo "Record updated successfully";
} else {
    echo "Error updating record: " . mysqli_error($conn);
}

mysqli_close($conn);
?>

```

Example (PDO)

```

<?php
$servername = "localhost";
$username = "username";
$password = "password";
$dbname = "myDBPDO";

try {
    $conn = new PDO("mysql:host=$servername;dbname=$dbname", $username,
$password);
    // set the PDO error mode to exception
    $conn->setAttribute(PDO::ATTR_ERRMODE, PDO::ERRMODE_EXCEPTION);
}

```

```
$sql = "UPDATE MyGuests SET lastname='Doe' WHERE id=2";

// Prepare statement
$stmt = $conn->prepare($sql);

// execute the query
$stmt->execute();

// echo a message to say the UPDATE succeeded
echo $stmt->rowCount() . " records UPDATED successfully";
}
catch(PDOException $e)
{
    echo $sql . "<br>" . $e->getMessage();
}

$conn = null;

?>
```