Kally Tang

Recreational Activity Classes API

Spring 2021

Oregon State University

url: https://tangka-activities-api.wl.r.appspot.com

(url same for sign up)

Table of Contents

Data Model	
Create an Activity	3
View an Activity	
View an Activity	
List all Activities	10
Edit an Activity (PUT)	12
Edit an Activity (PATCH)	15
Delete an Activity	19
Create an Attendee	20
Get an Attendee	23
List all Attendees	25
Edit an Attendee (PUT)	28
Edit an Attendee(PATCH)	31
Delete an Attendee	34
Add an Attendee to an Activity	35
Remove an Attendee from an Activity	37

Data Model

The user will be the instructor for the course, and activity will hold the user's id in the instructor attribute.

Activity

name	String	Name of the class
instructor	String	userID of the user
description	String	Description of the class
room	int	Room number of activity
start	Int	Time in seconds
end	int	Time in seconds
num_attendees int		Number of attendees for the class
attendee_list List of objects		List of attendees
public	boolean If the course is private or public	

Attendee

first_name	String	First name of attendee
last_name	String	Last name of attendee
email	String	Email of attendee
phone	int	Phone number of user
activities_list	List of objects	List of the activities that the attendee is
		attending.

I am implementing a many to many relation between attendees and activities. Attendees can be "registered" to an activity or removed from the activity.

The user needs to supply user identifier, user must supply a jwt token.

The application uses a function to verify whether the jwt token is valid.

The user has a one to many relationship with activities.

Create an Activity

POST/activities

Post request to create an activity

Request

Path Parameters

None

Request Body

Required

Request Body Format

JSON

Request Accept Types:

application/JSON

Request JSON Attributes

Name	Туре	Description	Required?
name	String	Name of the class	Yes
description	String	Description of the activity	Yes
room	Int	The room number of the class, rooms range	Yes
		from 1- 300	
start	int	Start time must be in time since Epoch in	Yes
		seconds	
end	int	End time must be in time since epoch in	Yes
		seconds	
public	Boolean	Whether the class is public or private	Yes

Request Body Example

```
"name": "Knitting Club Meet Up",
    "room": 100,
    "public": true,
    "start": 1622638837,
    "end": 1622674837,
    "description": "No knowledge of knitting is required."
}
```

Response

Response Body Format:

JSON

Response Content-Type

Application/json

Response Statuses

Outcome	Status Code	Notes	
Success	201 Created		
Failure	400 Bad Request	 name attribute Any characters allowed. must be within the range of 5 to 30 characters long. Does not need to be unique Extraneous leading and ending spaces are removed from the name. description attribute must be a string Length must be within range of 5 to 50 characters Any characters is accepted as long as description is not made up of only spaces. start and end must be an integer, representing time since Epoch in seconds start time must be earlier than end time. There must be no overlaps with time and room for different activities room must be an integer empty fields are rejected. Other fields other than the accepted fields are not accepted 	
Failure	401 Unauthorized	If user is not signed, or the token has expired	
Failure	403 Forbidden	If the room is taken during date and time or room number does not exist, room ranges from 1 to 300	
Failure	406 Not Acceptable	When user requests a Content-Type that is not supported by the endpoint. Application/Json is the only acceptable type the client can request in the Accept header	
Failure	415 Unsupported Media Type	User sends data type that is not supported by the API	

Response examples

- Datastore will automatically generate an ID and store it with entity that is created.
- Self attribute will contain a live link to the REST resource corresponding to the activity.

Success

```
Status: 201 Created
{
    "name": "Knitting Club Meet Up",
    "description": "No knowledge of knitting is required.",
    "start": 1622638837,
    "end": 1622674837,
    "room": 100,
    "instructor": "auth0|60b6b343c8c21a0068887cfb",
    "public": true,
    "id": "5646488461901824",
    "self": "http://localhost:8080/activities/5646488461901824"
}
```

Failure

```
Status: 400 Bad Request
{
    "Error": "The request object is missing at least one of the required attributes."
}
```

Failure

```
Status 400 Bad Request
{
    "Error": "The request object has at least one attribute that is not allowed"
}
```

Failure

```
Status 401 Unauthorized
{
    "Error": "Missing Authorization token."
}
```

```
Status 403 Bad Request
{
   "Error": "The time overlaps with another activity. Please choose a different time."
}
```

```
Status 406 Not Acceptable
{
    "Error": "Content type requested is not supported by API."
}
```

Failure

```
Status 404 Not Found
{
    "Error": "No activity with this id exists."
}
```

```
Status 415
{
    "Error": "Unsupported Media Type"
}
```

View an Activity

View an Activity

Get an existing activity by id

```
GET /activities/:activity_id
```

Request

Path Parameters

Name	Туре	Description	
activity_id	String	ID of the boat	

Request Accept MIME Types:

application/JSON

Request Body

None

Response

Response Body Format

JSON

HTML

Response Content-Type

application/json

Response Statuses

Outcome	Status Code	Notes
Success	200 OK	
Failure	403	Forbidden, user cannot access private activity because it does not belong to user and or no token
Failure	404 Not Found	No activity with this activity_id exists
Failure	406 Not Acceptable	When the client requests a content type not supported by the API.

Response Examples

```
Status 200
{
    "instructor": "auth0|60b55aea63019d0069dc3f25",
    "description": "Senior care bingo night, with prizes",
    "room": 200,
    "public": true,
    "start": 1622582557,
    "end": 1622584837,
    "name": "Bingo Night",
    "id": "6583134694932480",
    "self": "http://localhost:8080/activities/6583134694932480"
}
```

Note: if attendees aren't added num attendees and attendee list will not be part of the object.

```
Status 403
{
    "Error": "The activity requested is private and you are unauthorized to view act ivity."
}
```

```
Status 404 Not Found
{
    "Error": "No activity with this id exists."
}
```

```
Status 406 Not Acceptable
{
    "Error": "Content type requested is not supported by API."
}
```

List all Activities

Get a list of paginated activities, if user is unauthorized, all public boats will be listed. If user is authorized, user is able to view their activities they have created.

GET /activities

Request

Path Parameters

Name	Туре	Description	Required?
limit	int	To specify number of boats to get	No
offset	int	To specify offset number	No

Request Body

None

Request Accept Types:

application/JSON

Response

Response Body Format

application/JSON

Response Statuses

Outcome	Status Code	Notes
Success	200	

Response Examples

Success

```
"next": "http://localhost:8080/activities?limit=5&offset=5",
"count": 6,
"activities": [
        "name": "Macrame Morning Class",
        "description": "Beginners welcome!",
        "instructor": "auth0|60b55aea63019d0069dc3f25",
        "public": true,
        "end": 1623738375,
        "room": 300,
        "start": 1623734775,
        "id": "4604777296035840",
        "self": "http://localhost:8080/activities/4604777296035840"
    },
        "public": true,
        "name": "Knitting Club Meet Up",
        "attendee list": [
            {
                "attendee_id": "6716239321759744",
                "self": "http://localhost:8080/attendees/6716239321759744"
```

```
],
    "end": 1622674837,
    "description": "No knowledge of knitting is required.",
   "start": 1622638837,
    "room": 100,
    "instructor": "auth0|60b55aea63019d0069dc3f25",
    "num attendees": 1,
    "id": "4623564690948096",
    "self": "http://localhost:8080/activities/4623564690948096"
},
   "start": 1622582557,
   "end": 1622584837,
    "name": "Bingo Night",
    "description": "Senior care bingo night, with prizes",
    "room": 200,
    "attendee list": [],
    "instructor": "auth0|60b55aea63019d0069dc3f25",
    "public": true,
   "num attendees": 0,
    "id": "4753547346313216",
    "self": "http://localhost:8080/activities/4753547346313216"
},
    "public": true,
    "name": "Couple's Movie Night II",
   "instructor": "auth0|60b55aea63019d0069dc3f25",
    "description": "Scary movie night.",
   "start": 1622698131,
   "end": 1622701731,
   "room": 1,
    "id": "5368977068916736",
    "self": "http://localhost:8080/activities/5368977068916736"
},
    "description": "Disney movies week.",
   "end": 1622701731,
   "name": "Kids's Movie Night",
    "room": 33,
   "start": 1622698131,
    "instructor": "auth0|60b55aea63019d0069dc3f25",
    "public": true,
    "id": "5749464597790720",
   "self": "http://localhost:8080/activities/5749464597790720"
```

Edit an Activity (PUT)

Put edit to create an activity

```
PUT/activities/:activity_id
```

Request

Path Parameters

Name	Type	Description	
activity_id	String	ID of the activity	

Request Body

Required

Request Body Format

JSON

Request Accept Types:

application/JSON

Request JSON Attributes

Name	Туре	Description	Required?
name	String	Name of the class	Yes
description	String	Description of the activity	Yes
room	Int	The room number of the class, rooms range from 1- 300	Yes
start	int	Start time must be in time since Epoch in seconds	Yes
end	int	End time must be in time since epoch in seconds	Yes
public	Boolean	Whether the class is public or private	Yes

Request Body Example

```
"name": "Knitting Club Meet Up",
    "room": 100,
    "public": true,
    "start": 1622638837,
    "end": 1622674837,
    "description": "No knowledge of knitting is required."
}
```

Response

Response Body Format:

JSON

Response Content-Type

Application/json

Response Statuses

Outcome	Status Code	Notes
Success	204 No content	
Failure	204 No content 400 Bad Request	If request data does not follow the following requirements, it will be rejected: • name attribute • Any characters allowed. • must be within the range of 5 to 30 characters long. • Does not need to be unique • Extraneous leading and ending spaces are removed from the name. • description attribute • must be a string • Length must be within range of 5 to 50 characters • Any characters is accepted as long as description is not made up of only spaces. • start and end • must be an integer, representing time since Epoch in seconds • start time must be earlier than end time. • There must be no overlaps with time and room for different activities • room must be an integer • empty fields are rejected. • Other fields other than the accepted fields are not accepted • All fields must be sent in the request body, if any are missing, it is rejected
Failure	401 Unauthorized	If user is not signed, or the token has expired
Failure	403 Forbidden	If the room is taken during date and time or room number
Failure	404 Net 5	does not exist, room ranges from 1 to 300
Failure	404 Not Found	If activity_id does not exist
Failure	415 Unsupported Media Type	User sends data type that is not supported by the API

Response examples

- Datastore will automatically generate an ID and store it with entity that is created.
- Self attribute will contain a live link to the REST resource corresponding to the activity.

Status 204 No Content

Failure

```
Status: 400 Bad Request
{
    "Error": "The request object is missing at least one of the required attributes."
}
```

Failure

```
Status 400 Bad Request
{
    "Error": "The request object has at least one attribute that is not allowed"
}
```

```
Status 401 Unauthorized
{
    "Error": "Missing Authorization token."
}
```

```
Status 403
{
    "Error": "You are not authorized to delete requested activity"
}
```

```
Status 403
{
    "Error": "The time overlaps with another activity. Please choose a different time."
}
```

```
Status 404
{
    "Error": "No activity with this id exists."
}
```

```
Status 415
{
    "Error": "Unsupported Media Type"
}
```

Edit an Activity (PATCH)

```
PATCH/activities/:activity_id
```

Patch request to edit an activity.

Request

Path Parameters

Name	Туре	Description
activity_id	String	ID of the activity

Request Body

Required

Request Body Format

JSON

Request Accept Types:

application/JSON

Request JSON Attributes

Name	Type	Description	Required?
name	String	Name of the class	No
description	String	Description of the activity	No
room	Int	The room number of the class, rooms range from 1-300	No
start	int	Start time must be in time since Epoch in seconds	No
end	int	End time must be in time since epoch in seconds	No
public	Boolean	Whether the class is public or private	No

Request Body Example

```
"name": "Knitting Club Meet Up",
    "room": 10,
    "public": true,
    "start": 1622638837,
    "description": "No knowledge of knitting is required."
}
```

Response

Response Body Format:

JSON

Response Content-Type

Application/json

Response Statuses

Outcome	Status Code	Notes	
Success	204 No content		
Failure	400 Bad Request	name attribute	
		 Any characters allowed. 	
		 must be within the range of 5 to 30 	
		characters long.	
		 Does not need to be unique 	
		 Extraneous leading and ending spaces are 	
		removed from the name.	
		description attribute	
		 must be a string 	
		 Length must be within range of 5 to 50 	
		characters	
		 Any characters is accepted as long as 	
		description is not made up of only spaces.	
		start and end	
		 must be an integer, representing time since 	
		Epoch in seconds	
		 start time must be earlier than end time. 	
		 There must be no overlaps with time and 	
		room for different activities	
		 room must be an integer 	
		 empty fields are rejected. 	
		Other fields other than the accepted fields are not	
		accepted	
Failure	401 Unauthorized	If user is not signed, or the token has expired	
Failure	403 Forbidden	If the room is taken during date and time or room number	
		does not exist, room ranges from 1 to 300 or user attempts to	
		make changes to activity that was not created by user.	
Failure	404 Not Found	If activity_id does not exist	
Failure	415 Unsupported	User sends data type that is not supported by the API	
	Media Type		

Response examples

- Datastore will automatically generate an ID and store it with entity that is created.
- Self attribute will contain a live link to the REST resource corresponding to the activity.

Success

```
Status 204 No Content
```

Failure

```
Status: 400 Bad Request
{
    "Error": "The request object is missing at least one of the required attributes."
}
```

Failure

```
Status 400 Bad Request
{
    "Error": "The request object has at least one attribute that is not allowed"
}
```

Failure

```
Status 401 Unauthorized
{
    "Error": "Missing Authorization token."
}
```

```
Status 403
{
    "Error": "You are not authorized to delete requested activity"
}
```

```
Status 403
{
    "Error": "The time overlaps with another activity. Please choose a different time."
}
```

```
Status 404
{
    "Error": "No activity with this id exists."
}
```

```
Status 415
{
    "Error": "Unsupported Media Type"
}
```

Delete an Activity

Allows you to delete a activity with authentication.

DELETE /activities/:activity_id

Request

Path Parameters

Name	Туре	Description
activity_id	String	ID of the activity

Request Body

None

Response

No body

Response Body Format

Success: No body Failure: JSON

Response Statuses

Outcome	Status Code	Notes
Success	204 No Content	
Failure	401 Unauthorized	If user attempts to delete activity without a token
Failure	403 Forbidden	If user has valid token activity is was not created by user,
		then return forbidden error
Failure	404 Not Found	No activity with this activity_id exists

Response Examples

Success

Status: 204 No Content

```
Status 401
{
    "Error": "Missing Authorization token."
}
```

```
Status 403
{
    "Error": "You are not authorized to delete requested activity"
}
```

```
Status: 404 Not Found
{
    "Error": "No activity with this id exists."
}
```

Create an Attendee

Post request to create an attendee

POST/attendees

Request

Path Parameters

None

Request Body

Required

Request Body Format

JSON

Request Accept Types:

application/JSON

Request JSON Attributes

Name	Туре	Description	Required?
first_name	String	First name of attendee	Yes
last_name	String	Last name of attendee	Yes
phone_number	int	Phone number of attendee	Yes
email	String	Email of attendee	Yes

Request Body Example

```
{
    "first_name":"Joy",
    "last_name":"Day",
    "email":"maryday@esq.com",
    "phone":6553333541
}
```

Response

Response Body Format:

JSON

Response Content-Type

Application/json

Response Statuses

Outcome	Status Code	Notes
Success	201 Created	
Failure	400	 first_name and last_name must be strings phone must be an integer with 10 digits email must be string
Failure	401 Unauthorized	If user is not signed, or the token has expired

Failure	403 Forbidden	If the attendee's first_name and last_name and email and
		phone is the exact same, an error will return indicating that
		the user already exists.
Failure	406 Not Acceptable	When user requests a Content-Type that is not supported by
		the endpoint.
		Application/Json is the only acceptable type the client can
		request in the Accept header
Failure	415 Unsupported	User sends data type that is not supported by the API
	Media Type	

Response examples

- Datastore will automatically generate an ID and store it with entity that is created.
- Self attribute will contain a live link to the REST resource corresponding to the activity.

Success

```
Status: 201 Created
{
    "first_name": "Jane",
    "last_name": "Doe",
    "email": "janedoe@gmail.com",
    "phone": 6552302558,
    "id": "4693933435125760",
    "self": "http://localhost:8080/attendees/4693933435125760"
}
```

Failure

```
Status: 400 Bad Request
{
    "Error": "The request object is missing at least one of the required attributes."
}
```

```
Status 400 Bad Request
{
    "Error": "The request object has at least one attribute that is not allowed"
}
```

```
Status 401 Unauthorized
{
    "Error": "Missing Authorization token."
}
```

Failure

```
Status 406 Not Acceptable
{
    "Error": "Content type requested is not supported by API."
}
```

```
Status 415
{
    "Error": "Unsupported Media Type"
}
```

Get an Attendee

Get an existing attendee by id

```
GET /attendees/:attendee_id
```

Request

Path Parameters

Name	Туре	Description
attendee_id	String	ID of the boat

Request Accept MIME Types:

application/JSON

Request Body

None

Response

Response Body Format

JSON

HTML

Response Content-Type

application/json

Response Statuses

Outcome	Status Code	Notes
Success	200 OK	
Failure	404 Not Found	No attendee with attendee_id exists
Failure	406 Not	When the client requests a content type not supported by the
	Acceptable	API.

Response Examples

- Note: if activities were added to the attendee, num_activities and activities_list will not be part of the response.

Success:

```
],
    "email": "janedoe@gmail.com",
    "last_name": "Doe",
    "phone": 6552302558,
    "num_activities": 2,
    "id": "6716239321759744",
    "self": "http://localhost:8080/attendees/6716239321759744/6716239321759744"
}
```

```
Status 200
{
    "instructor": "auth0|60b55aea63019d0069dc3f25",
    "name": "Kids's Movie Night",
    "description": "Disney movies week.",
    "end": 1622701731,
    "start": 1622698131,
    "room": 33,
    "public": true,
    "id": "5749464597790720",
    "self": "http://localhost:8080/activities/5749464597790720"
}
```

```
Status 404 Not Found
{
    "Error": "No attendee with this id exists."
}
```

List all Attendees

Get a list of paginated attendees

GET /attendees

Request

Path Parameters

Name	Type	Description	Required?
limit	int	To specify number of boats to get	No
offset	int	To specify offset number	No

Request Body

None

Request Accept Types:

application/JSON

Response

Response Body Format

application/JSON

Response Statuses

Outcome	Status Code	Notes
Success	200	

Response Examples

Success

```
Status 200
    "next": "http://localhost:8080/attendees?limit=5&offset=5",
    "count": 6,
    "attendees": [
        {
            "email": "johndoe@esq.com",
            "activity list": [
                {
                    "activity id": "4753547346313216",
                    "self": "http://localhost:8080/activities/4753547346313216"
                }
            ],
            "phone": 5558881111,
            "last_name": "Doe",
            "first name": "John",
            "id": "4569992624340992",
            "self": "http://localhost:8080/attendees/4569992624340992",
            "num activities": 1
        },
            "first_name": "Mary",
```

```
"phone": 6553333541,
        "email": "maryday@esq.com",
        "last_name": "Day",
        "id": "5519570970345472",
        "self": "http://localhost:8080/attendees/5519570970345472"
    },
        "first name": "Jake",
        "email": "johndoe@esq.com",
        "phone": 6552522254,
        "last name": "Doe",
        "id": "5879447253155840",
        "self": "http://localhost:8080/attendees/5879447253155840"
    },
        "first name": "Joy",
        "email": "maryday@esq.com",
        "last_name": "Day",
        "phone": 6553333541,
        "id": "6645470877188096",
        "self": "http://localhost:8080/attendees/6645470877188096"
    },
        "first name": "Sam",
        "last name": "Doe",
        "phone": 6552522254,
        "email": "johndoe@esq.com",
        "id": "6664258272100352",
        "self": "http://localhost:8080/attendees/6664258272100352"
]
```

Success

```
"email": "maryday@esq.com",
            "phone": 6553333541,
            "last name": "Day",
            "first name": "Mary",
            "id": "5519570970345472",
            "self": "http://localhost:8080/attendees/5519570970345472"
        },
            "phone": 6552522254,
            "last name": "Doe",
            "email": "johndoe@esq.com",
            "first name": "Jake",
            "id": "5879447253155840",
            "self": "http://localhost:8080/attendees/5879447253155840"
        },
            "last name": "Day",
            "email": "maryday@esq.com",
            "first name": "Joy",
            "phone": 6553333541,
            "id": "6645470877188096",
            "self": "http://localhost:8080/attendees/6645470877188096"
        },
            "email": "johndoe@esq.com",
            "last name": "Doe",
            "first_name": "Sam",
            "phone": 6552522254,
           "id": "6664258272100352",
            "self": "http://localhost:8080/attendees/6664258272100352"
       }
   ]
}
```

Edit an Attendee (PUT)

Post request to edit an attendee

```
PUT /attendees/:attendee_id
```

Request

Path Parameters

Name	Туре	Description
attendee_id	String	ID of the boat

Request Body

Required

Request Body Format

JSON

Request Accept Types:

application/JSON

Request JSON Attributes

Name	Туре	Description	Required?
first_name	String	First name of attendee	Yes
last_name	String	Last name of attendee	Yes
phone_number	int	Phone number of attendee	Yes
email	String	Email of attendee	Yes

Request Body Example

```
{
    "first_name":"Joy",
    "last_name":"Day",
    "email":"maryday@esq.com",
    "phone":6553333541
}
```

Response

Response Body Format:

JSON

Response Content-Type

Application/json

Response Statuses

Outcome	Status Code	Notes
Success	201 Created	
Failure	400	The values of attributes must be of the correct type
		 first_name and last_name must be strings
		 phone must be an integer with 10 digits

		email must be string
		if fields other than first_name, last_name, phone and email
		are in the request.
		if any of the fields are missing, an error is returned .
Failure	401 Unauthorized	If user is not signed, or the token has expired
Failure	403 Forbidden	If the attendee's first_name and last_name and email and
		phone is the exact same as another attendee, an error will
		return indicating that the user already exists.
Failure	404 Not Found	If attendee_id does not exist
Failure	415 Unsupported	User sends data type that is not supported by the API
	Media Type	

Response examples

- Datastore will automatically generate an ID and store it with entity that is created.
- Self attribute will contain a live link to the REST resource corresponding to the activity.

Success

```
Status 204 No Content
```

Failure

```
Status: 400 Bad Request

{
    "Error": "The request object is missing at least one of the required attributes."
}
```

Failure

```
Status 400 Bad Request
{
    "Error": "The request object has at least one attribute that is not allowed"
}
```

```
Status 401 Unauthorized
{
    "Error": "Missing Authorization token."
}
```

```
Status 404 Not Found
{
    "Error": "No attendee with this id exists."
}
```

```
Status 415
{
    "Error": "Unsupported Media Type"
}
```

Edit an Attendee(PATCH)

Edit fields of attendee

PATCH /attendees/:attendee_id

Request

Path Parameters

Name	Туре	Description
attendee_id	String	ID of the boat

Request Body

Required

Request Body Format

JSON

Request Accept Types:

application/JSON

Request JSON Attributes

Name	Туре	Description	Required?
first_name	String	First name of attendee	No
last_name	String	Last name of attendee	No
phone_number	int	Phone number of attendee	No
email	String	Email of attendee	No

Request Body Example

```
{
    "first_name":"Joy",
    "last_name":"Day",
    "email":"maryday@esq.com",
    "phone":6553333541
}
```

Response

Response Body Format:

JSON

Response Content-Type

Application/json

Response Statuses

Outcome	Status Code	Notes
Success	201 Created	
Failure	400	The values of attributes must be of the correct type
		 first_name and last_name must be strings
		 phone must be an integer with 10 digits

		email must be string
		if fields other than first_name, last_name, phone and email
		are in the request, request is rejected.
		If the user sends an empty object, request is rejected
Failure	401 Unauthorized	If user is not signed, or the token has expired
Failure	403 Forbidden	If the attendee's first_name and last_name and email and
		phone is the exact same, an error will return indicating that
		the user already exists.
Failure	404 Not Found	If attendee_id does not exist
Failure	415 Unsupported	User sends data type that is not supported by the API
	Media Type	

Response examples

- Datastore will automatically generate an ID and store it with entity that is created.
- Self attribute will contain a live link to the REST resource corresponding to the activity.

Success

```
Status 204 No Content
```

Failure

```
Status: 400 Bad Request

{
    "Error": "The request object is missing at least one of the required attributes."
}
```

Failure

```
Status 400 Bad Request
{
    "Error": "The request object has at least one attribute that is not allowed"
}
```

```
Status 401 Unauthorized
{
    "Error": "Missing Authorization token."
}
```

```
Status 404 Not Found
{
    "Error": "No attendee with this id exists."
}
```

```
Status 415
{
    "Error": "Unsupported Media Type"
}
```

Delete an Attendee

Allows you to delete an attendee, will update activities that have attendee_id in attendee_list

DELETE /attendees/:attendee_id

Request

Path Parameters

Name	Туре	Description	
attendee_id	String	ID of the attendee	

Request Body

None

Response

No body

Response Body Format

Success: No body Failure: JSON

Response Statuses

Outcome	Status Code	Notes
Success	204 No Content	
Failure	401 Unauthorized	If user does not have a token
Failure	404 Not Found	No attendee with this activity_id exists

Response Examples

Success

```
Status: 204 No Content
```

Failure

```
Status 401 Unauthorized
{
    "Error": "Missing Authorization token."
}
```

```
Status: 404 Not Found
{
    "Error": "No attendee with this id exists."
}
```

Add an Attendee to an Activity

Assign an attendee to a class.

PUT/activities/:activity_id/attendees/:attendee_id

Request

Path Parameters

Name	Туре	Description	
activity_id	String	ID of the boat	
attendee_id	String	ID of the load	

Request Body

None

Response

No body

Response Body Format

Success: No body Failure: JSON Response Statuses

Outcome	Status Code	Notes
Success	204 No Content	Succeeds only if the user is authorized to make changes
		to the class and the activity_id and the attendee_id exist.
Failure	401 Unauthorized	Requests send without an auth token is rejected
Failure	403 Forbidden	Fails if attendee is already assigned the activity or the
		user is not authorized or activity does not belong to the
		user.
Failure	404 Not Found	No activity with this activity_id exists, and/or no attendee
		with this attendee_id exits.

Response Examples

Success

Status: 204 No Content

```
Status: 401 Forbidden
{
    "Error": "Missing Authorization token."
}
```

```
Status: 403 Forbidden
{
    "Error": "The attendee is already registered for this activity."
}
```

```
Status: 403 Forbidden

{
    "Error": "You are not authorized to add attendees to this activity."
}
```

```
Status: 404 Not Found
{
    "Error": "No activity with this activity_id exists and/or attendee with this att
endee_id."
}
```

Remove an Attendee from an Activity

Assign an attendee to a class.

DELETE/activities/:activity_id/attendees/:attendee_id

Request

Path Parameters

Name	Type	Description	
activity_id	String	ID of the boat	
attendee_id	String	ID of the load	

Request Body

None

Response

No body

Response Body Format

Success: No body Failure: JSON Response Statuses

Outcome	Status Code	Notes
Success	204 No Content	Succeeds only if the user is authorized to make changes
		to the class and the activity_id and the attendee_id exist.
Failure	401 Unauthorized	Requests send without an auth token is rejected
Failure	403 Forbidden	Fails if attendee is not assigned the activity or the user is not authorized or activity does not belong to the user.
Failure	404 Not Found	No activity with this activity_id exists, and/or no attendee with this attendee_id exits.

Response Examples

Success

```
Status: 204 No Content
```

```
Status: 401 Forbidden
{
    "Error": "Missing Authorization token."
}
```

```
Status: 403 Forbidden
{
    "Error": "The attendee is already registered for this activity."
}
```

```
Status: 403 Forbidden
{
    "Error": "You are not authorized to add attendees to this activity."
}
```

```
Status: 404 Not Found

{
    "Error": "No activity with this activity_id exists and/or attendee with this att
endee_id."
}
```