

# Graph Neural Networks Demystified

An overview of the essential concepts in Stanford CS224W (Lectures 1~9)  
with only oversimplified examples

Ng Yen Kaow

# Embeddings

- Relatively small vectors associated with each object where similar objects have similar embeddings
- Using the embeddings of graph elements, various tasks can be performed
  - Cluster nodes in a graph
  - Predict properties of a node
  - Predict if two nodes may be connected
  - Classify entire graphs
- To perform each task, use the embedding with a suitable ML method
  - e.g. clustering can be performed with  $k$ -means

# Obtaining embeddings

- Embeddings can be formed with or learned from features
  - Node-level features
    - Degree
    - Centrality (eigenvector/ betweenness/ closeness)
    - Clustering coefficient
    - Graphlets
    - Structure-based features
  - Link-level features
    - Distance-based features
    - Local/global neighborhood overlap
  - Graph-level features
    - Graph kernels
- Task-independent embeddings can be learned from unsupervised learning

# Task-independent embeddings

- Unsupervised extraction by random walks

- **DeepWalk**

- Estimate pairwise distance between nodes (hence their co-occurrence probability)
  - Usable for finding product relatedness in recommender
- Node embeddings
  1. Estimate node distances with random walks
  2. Train a neural network (with node input and embedding output) such that distances between embeddings agree with estimated distances

- **Anonymous Walk**

- Embeddings for entire graphs

- **Simpler method: just add up neighbors**

# Embeddings by adding neighbors

- Sum up the features of (self and) neighbor nodes
  - Features of nodes in close proximity will become similar

Example: Let  $h_i^j$  denote features of node  $i$  at iteration  $j$  and let  $h_1^0 = (1 \ 0 \ 0)$ ,  $h_2^0 = (0 \ 1 \ 0)$ , and  $h_3^0 = (0 \ 0 \ 1)$



- $h_1 \equiv h_2$  after only 1 iteration

# Embeddings by adding neighbors

- To cluster nodes in a graph, will it work if we
  1. Start with a unique feature for each node, and
  2. Repeatedly add up neighboring features, and
  3. Finally, cluster the resultant features with some method like  $k$ -means?




Let's try with karate club network


# Embeddings by adding neighbors

## □ Karate club


Initial




3<sup>rd</sup> iteration



4<sup>th</sup> iteration




5<sup>th</sup> iteration




(converged)

1<sup>st</sup> iteration



2<sup>nd</sup> iteration



# Adding neighbors w/ linear algebra

- Let matrix  $H$  be a matrix where each row is a node and each column is a feature
  - $H$  have  $\dim |V| \times d$
- Let  $A$  be an adjacency matrix
  - Let  $\hat{A} = A + I$  where  $I$  is the identity matrix
- Then, **sum** is simply  $\hat{A}H$

Permutation invariant so that the outcome is the same regardless of node order within matrix

$$\begin{pmatrix} a & b & c \\ \dots & & \\ \dots & & \end{pmatrix} \begin{pmatrix} h_1 \\ h_2 \\ h_3 \end{pmatrix} = \begin{pmatrix} ah_1 + bh_2 + ch_3 \\ \dots \\ \dots \end{pmatrix}$$

e.g.



$$\begin{pmatrix} 1 & 1 & 0 \\ 1 & 1 & 0 \\ 0 & 0 & 1 \end{pmatrix} \begin{pmatrix} h_1 \\ h_2 \\ h_3 \end{pmatrix} = \begin{pmatrix} h_1 + h_2 \\ h_1 + h_2 \\ h_3 \end{pmatrix}$$



# Adding neighbors w/ linear algebra

- Let matrix  $H$  be a matrix where each row is a node and each column is a feature
  - $H$  have  $\dim |V| \times d$
- Let  $A$  be an adjacency matrix
  - Let  $\hat{A} = A + I$  where  $I$  is the identity matrix
- Further **normalize** each row of  $\hat{A}$  to sum to 1

$$\begin{pmatrix} 1/3 & 1/3 & 1/3 \\ & \dots & \\ & & \dots \end{pmatrix} \begin{pmatrix} h_1 \\ h_2 \\ h_3 \end{pmatrix} = \begin{pmatrix} (h_1 + h_2 + h_3)/3 \\ & \dots & \\ & & \dots \end{pmatrix}$$

Note that  
**normalize**  
does the same  
thing as **mean**

e.g.



$$\begin{pmatrix} .5 & .5 & 0 \\ .5 & .5 & 0 \\ 0 & 0 & 1 \end{pmatrix} \begin{pmatrix} h_1 \\ h_2 \\ h_3 \end{pmatrix} = \begin{pmatrix} (h_1 + h_2)/2 \\ (h_1 + h_2)/2 \\ h_3 \end{pmatrix}$$

# Adding neighbors w/ linear algebra

- Let matrix  $H$  be a matrix where each row is a node and each column is a feature
  - $H$  have  $\dim |V| \times d$
- Let  $A$  be an adjacency matrix
  - Let  $\hat{A} = A + I$  where  $I$  is the identity matrix
- Further **normalize** each row of  $\hat{A}$  to sum to 1
  - To perform this normalization, it suffices that we let  $\hat{A} \leftarrow D^{-1}\hat{A}$  where  $D$  is the diagonal node degree matrix

- In PyTorch, use

```
torch.nn.functional.normalize(A, p=1, dim=1)
```

Normalized  $\hat{A}$  is  
in general **not**  
**symmetric**

- Or, use  $\hat{A} \leftarrow D^{-\frac{1}{2}}\hat{A}D^{-\frac{1}{2}}$ , the “spectral” variant

- In PyTorch, use


```
D = torch.diag(torch.sum(A, 1)).inverse().sqrt()  
D = torch.mm(torch.mm(D, A), D)
```

The “spectral”  
variant is  
symmetric, but  
**not normalized**

# Adding neighbors w/ linear algebra


- Redo karate club with normalized  $\hat{A} \leftarrow D^{-1}\hat{A}$

Initial




2<sup>nd</sup> iteration

$k$ -means on  $\hat{A}^2 H$




1<sup>st</sup> iteration

$k$ -means on  $\hat{A} H$



3<sup>rd</sup> iteration

$k$ -means on  $\hat{A}^3 H$



(no change)

# Adding neighbors: evaluation

## □ Why do we need normalization

- Without normalization, feature values for the nodes of high centrality would quickly add up, making them distinct from the nodes of low centrality

## □ How many iterations should be used?

Early (RNN-like) GNNs are iterated until convergence but they quickly ran out of favor to Graph Convolutional Networks (GCNs) where the number of iterations is fixed as defined by the number of convolutional layers

- Each iteration would “bunch up” neighboring features of 1 hop away (receptive field)
- We should determine the number of iterations by the **nature of the graph**

# Nature of the graph

- The **Cheeger constant** (or expansion constant) of an **unweighted** graph  $G(E, V)$  is

$$h(G) = \min_{S \subseteq V} \frac{|\{(u, v) | u \in S, v \in \bar{S}\}|}{\min(|S|, |\bar{S}|)}$$

- $|\{(u, v) | u \in S, v \in \bar{S}\}|$  indicates how well vertices in  $S$  are connected to vertices in  $\bar{S}$
- $\min(|S|, |\bar{S}|)$  favors  $S$  where  $|S| \approx |\bar{S}|$
- For weighted graphs, a similar measure called conductance can be defined with edge weights  $(a_{uv})$

$$\phi(G) = \min_{S \subseteq V} \frac{\sum_{v \in S, u \in \bar{S}} a_{vu}}{\min\left(\sum_{v \in S, u \in V} a_{vu}, \sum_{v \in \bar{S}, u \in V} a_{vu}\right)}$$

# Nature of the graph

- The **Cheeger constant** (or expansion constant) of an **unweighted** graph  $G(E, V)$  is

$$h(G) = \min_{S \subseteq V} \frac{|\{(u, v) | u \in S, v \in \bar{S}\}|}{\min(|S|, |\bar{S}|)}$$

- A large  $h(G)$  indicates a **highly-connected graph**
  - A feature in a highly-connected graph will propagate in the graph very quickly
  - A random walk in a highly-connected graph converges in  $O(\log|V|)$  steps to an almost uniform distribution (mixing time)
  - Upon which the embedding of every node is influenced almost equally by any other node

# Nature of the graph


- Examine the number of steps required for the clusters in the karate club to mix

- The clusters are respectively of sizes 18, 11, 5

$$\log(18) = 4.17$$

$$\log(11) = 3.46$$


$$\log(5) = 2.32$$



- 5 iterations/ steps suffice for nodes in the respective clusters to influence each other equally

# Nature of the graph

- Examine the number of steps required for the clusters in the karate club to mix
- Will increasing the number of iterations eventually spread the features uniformly across the entire karate club graph?
- Depends on whether the limiting distribution  $x^*$  (e.g.  $D^{-1}\hat{A}x^* = x^*$ ) is everywhere constant





# Relationship to spectral clustering

- For the (Ng, Weiss, and Jordan 2001) normalized Laplacian, spectral clustering finds the distribution  $x$  where

$$D^{-1/2} A D^{-1/2} x = x$$

That is, the eigenvector corresponding to  $\lambda = 1$

- For **single-valued feature** and **at convergence**, our earlier GNN gives  $x$  where

$$D^{-1/2} \hat{A} D^{-1/2} x = x$$

where  $\hat{A} = A + I$

- Note especially the difference between  $A$  (for the Laplacian) and  $\hat{A}$  (from our earlier GNN)
  - $D^{-1/2} \hat{A} D^{-1/2}$  in fact approximates the eigenspace (see Chebyshev approximation in later slides)

# Relationship to PageRank

For simplicity consider eigenvector centrality problem, that is, the undirected version of PageRank

- Problem Statement. Suppose each node  $v$  corresponds to a value  $x_v$  which is the sum of its neighbors' values

$$x_v = \frac{1}{\lambda} \sum_{u \in N(v)} x_u$$

where  $\lambda$  is some given constant and positive factor

Given adjacency matrix  $A$  of a graph  $G$ , solve  $x_v$  for all  $v \in G$

- Problem is equivalent to that of finding vector  $x$  such that

$$Ax = \lambda x$$

- Again, problem is equivalent to that of adding up all neighboring **single-valued features**, but **excluding that of self**, until condition is fulfilled **at convergence**

# Adding neighbors: evaluation

## □ Benefits of strategy

- Simplicity
- Efficiently computed with adjacency matrix

## □ Disadvantage of strategy

- Embeddings produced are of size of the number of nodes in the graph

⇒ Learn a **transformation matrix**

$$W: R^{|V|} \rightarrow R^d \text{ for some smaller } d$$

# Transformation matrix $W$

- $W$  is typically a linear transformation layer of size  $|V| \times d$  where  $d$  is the target dimensionality of the embeddings
- Combined with the adjacency matrix  $\hat{A}$ , we now have a complete matrix formulation for computing embedding  $h_v$  of a node  $v$  from (itself and) its neighbors, in the form of

$$h_v \leftarrow (\hat{A})_v HW$$

where

- $(\hat{A})_v$  is the row in  $\hat{A}$  for the node  $v$ , and
- $H$  is a matrix containing the features/embeddings of all the nodes (of course, only the rows in  $H$  with non-zero entries in  $(\hat{A})_v$  are needed for computing  $h_v$ )



**Variations in this formula lead to various frameworks**

# Variations

- Message-aggregation (MSG-AGG)
  - First transform features/embeddings (MSG), then aggregate transformed embeddings (AGG)

$$h_v \leftarrow \underbrace{(\hat{A})_v}_{\text{aggregate}} \overbrace{(HW)}^{\text{message}}$$

- Separate computation of self and neighbors
  - Exclude entry for  $v$  from  $(\hat{A})_v$ , and let

$$h_v \leftarrow \text{AGG} \left( \overbrace{(\hat{A})_v HW}^{\text{Aggregate only neighbors}}, \overbrace{h_v W'}^{\text{Self}} \right)$$

Learn a different transformation for self

Also denoted as  $B$

where  $\text{AGG}$  is, for instance, concatenation

# Frameworks

## □ Graph Convolutional Network (GCN)

$$h_v \leftarrow (\hat{A})_v (HW) \quad (\text{basically just MSG-AGG})$$

## □ GraphSAGE

- Exclude entry for  $v$  from  $(\hat{A})_v$

$$h_v \leftarrow \underbrace{\left( \underbrace{\text{CONCAT} \left( \underbrace{\text{AGG} \left( (\hat{A})_v H \right)}_{\text{Aggregate neighbors}}, \underbrace{h_v}_{\text{Self}} \right)}_{\text{Concatenate self \& aggregated neighbors}} \right)}_{\text{Transform}} W$$

AGG can be one of many options including MLP, LSTM, *etc.*

(Why use these? See Graph Isomorphism Network)

$\Rightarrow$  AGG is learnable

# Frameworks

## □ Graph Attention Networks (GAN)

- Instead of learning AGG, learn  $\hat{A}$ 
  - Generalize the adjacency matrix  $\hat{A}$  to **attention weights**  $\Lambda = (\alpha_{vu})$

$$h_v \leftarrow (\hat{A})_v HW \Rightarrow h_v \leftarrow (\Lambda)_v HW$$

where  $\alpha_{vu} = \frac{\exp(e_{vu})}{\sum_{x \in N(v)} \exp(e_{vx})}$ , and

$e_{vu}$  is a measure of how related  $u$  and  $v$  are

- $e_{vu}$  is usually computed as  $\text{LINEAR}(\text{CONCAT}(h_v W, h_u W))$
- Do not confuse with Generative Adversarial Networks which is for generating anime pics

- Implemented in PyTorch Geometric (PyG) as GCNConv (GCN), SAGEConv (GraphSAGE), and GATConv (GAN)

- See <https://pytorch-geometric.readthedocs.io/en/latest/modules/nn.html>

# Frameworks

## □ Message Passing Neural Network (MPNN)

- Involve  $N(v)$  in the transformation  $W$  for  $v$

$$h_v \leftarrow (\hat{A})_v HW$$

$$\Rightarrow h_v \leftarrow H \bigoplus_{u \in N(v)} \phi(h_v, h_u)$$

This change allows us to incorporate edge features in the embedding

$$\Rightarrow h_v \leftarrow H \bigoplus_{u \in N(v)} \phi(h_v, h_u, e_{vu})$$


- How to compute  $\phi(h_v, h_u, e_{vu})$  algebraically?
  - Let edge features be in a 3D matrix  $E$
  - Then,  $(\hat{A})_v H$  and  $(\hat{A})_v (E)_v$  gives us two matrices with matching rows (each row corresponding to  $h_u$  and  $e_{vu}$  respectively)
  - Concatenate  $(\hat{A})_v H$  and  $(\hat{A})_v (E)_v$  and give as input to an NN

- A similar framework, Principal Neighborhood Aggregation (PNAConv), is implemented in PyG (these frameworks are not discussed in CS224W)



# In practical use

- At this point we have not mentioned activation function or other elements of DL
  - For activation function just let  $h_v \leftarrow \sigma(h_v)$
  - Mix and match as you like
- Embeddings can be used for many downstream tasks
  - We have earlier used  $k$ -means for clustering the final output
  - Better performed by constructing a neural network directly with the GNN layers



# In practical use

## □ Adding graph elements

### ■ Features

- Similar to feature engineering

### ■ Virtual nodes

- Connecting all the nodes in a sparse but apparent subgraph to a virtual node will allow those nodes to better communicate

### ■ Virtual edges


- Create new graph by systematically adding edges
- Example: Given a bipartite graph, breaking the graph into two of only nodes of the same type is good for some analyses
  - Let  $A$  be the adjacency matrix of the bipartite graph  $G$
  - $A^2$  then gives the number of paths of distance 2 between nodes in  $G$ 
    - ⇒ an adjacency matrix between nodes of the same type
    - ⇒ allows us to separate  $G$  into two graphs, each of same node type
  - $A + A^2$  can form an adjacency matrix with heterogeneous edges

# Training GNNs


- Using node embeddings as input to a prediction function
  - Embedding of 1 node can be used directly
  - Embeddings of 2 nodes can be
    - Concatenated to form an **edge embedding**
    - Projected on each other to get their similarity
  - Embeddings of nodes of the entire graph can be
    - Summed, averaged, searched for max/min, *etc.*
    - Clustered, then the clusters summed, average, *etc.*, in a hierarchical fashion
- **Edge embeddings from edge features** are also possible, though not discussed in CS224W
  - The framework **Node and Edge features in graph Neural Networks (NENN)** (not yet in PyG)

# Distinguishing node embeddings


- Should C and D have the same embedding in the following graphs? Given that features are given by the colors and mutually exclusive (orthogonal)



Yes?



No?




Should?


- How about A and B?
- Idea:** Two nodes should have the same **embedding** if they have the same **feature** and **neighborhood structure**, and vice versa

# Distinguishing node embeddings


- Given a GCN of 2 layers, the embedding of A is computed as follows



Rearranged w.r.t. distance from A



Computation graph of A's embedding



# Distinguishing node embeddings

- Given a GCN of 2 layers, the embedding of A is computed as follows

- Let  $h_A^0 = [1|0|0|0|0|0]$ ,  $h_B^0 = [0|1|0|0|0|0]$ ,  $h_C^0 = [0|0|1|0|0|0]$ ,  $h_D^0 = [0|0|0|1|0|0]$ ,  $h_E^0 = [0|0|0|0|1|0]$ ,  $h_F^0 = [0|0|0|0|0|1]$ , and let AGG be **addition**. Then

- $h_B^1 = \text{AGG}(\{h_A^0, h_F^0, h_E^0\}, \{h_B^0\}) = 1|1|0|0|1|1$
- $h_C^1 = \text{AGG}(\{h_A^0, h_D^0, h_E^0\}, \{h_C^0\}) = 1|0|1|1|1|0$
- $h_D^1 = \text{AGG}(\{h_A^0, h_F^0, h_C^0\}, \{h_D^0\}) = 1|0|1|1|0|1$
- $h_A^1 = \text{AGG}(\{h_B^0, h_C^0, h_D^0\}, \{h_A^0\}) = 1|1|1|1|0|0$

Compute  $\text{AGG}(X)$  as  $\hat{A}H$ , where  $\hat{A}$  is the adjacency matrix (with self loop), and  $H$  is a matrix containing all the embeddings in  $X$


- Finally the embedding of A is
  - $h_A^2 = \text{AGG}(\{h_B^1, h_C^1, h_D^1\}, \{h_A^1\}) = 4|2|3|3|2|2$
- Similarly,
  - $h_B^2 = 2|4|2|2|2|2$
  - $h_C^2 = 3|2|4|3|2|1$
  - $h_D^2 = 3|2|3|4|1|2$
  - $h_E^2 = 2|2|2|1|3|1$
  - $h_F^2 = 2|2|1|2|1|3$

# Distinguishing node embeddings

- Given a GCN of 2 layers, the embedding of A is computed as follows

- Let  $h_A^0 = [1\ 0\ 0\ 0\ 0\ 0]$ ,  $h_B^0 = [0\ 1\ 0\ 0\ 0\ 0]$ ,  $h_C^0 = [0\ 0\ 1\ 0\ 0\ 0]$ ,  $h_D^0 = [0\ 0\ 0\ 1\ 0\ 0]$ ,  $h_E^0 = [0\ 0\ 0\ 0\ 1\ 0]$ ,  $h_F^0 = [0\ 0\ 0\ 0\ 0\ 1]$ , and let AGG be **addition**. Then

- $h_A^2 = 4\ 2\ 3\ 3\ 2\ 2$   
 $h_B^2 = 2\ 4\ 2\ 2\ 2\ 2$   
 $h_C^2 = 3\ 2\ 4\ 3\ 2\ 1$   
 $h_D^2 = 3\ 2\ 3\ 4\ 1\ 2$   
 $h_E^2 = 2\ 2\ 2\ 1\ 3\ 1$   
 $h_F^2 = 2\ 2\ 1\ 2\ 1\ 3$




By induction they will be distinct for all subsequent iterations

- For a graph with **distinct node features**, the embeddings will be distinct under **addition** regardless of **neighborhood structure** or **iterations**
  - With the exception of “twin nodes” that are connected only to each other (in which case they will become equal after the first iteration)

# Distinguishing node embeddings

- Given a GCN of 2 layers, the embedding of A is computed as follows

- Let  $h_A^0 = h_B^0 = \begin{bmatrix} 1 & 0 & 0 \end{bmatrix}$ ,  $h_C^0 = h_D^0 = \begin{bmatrix} 0 & 1 & 0 \end{bmatrix}$ ,  $h_E^0 = h_F^0 = \begin{bmatrix} 0 & 0 & 1 \end{bmatrix}$ , and let AGG be **addition**. Then, for the following graph




$h_A^1 = 2 2 0$	$h_A^2 = 6 6 4$	}	$h_A^2 \neq h_B^2$
$h_B^1 = 2 0 2$	$h_B^2 = 6 4 4$		
$h_C^1 = 1 2 1$	$h_C^2 = 5 7 3$	}	$h_C^2 = h_D^2$
$h_D^1 = 1 2 1$	$h_D^2 = 5 7 3$		
$h_E^1 = 1 1 1$	$h_E^2 = 4 3 4$	}	$h_E^2 = h_F^2$
$h_F^1 = 1 1 1$	$h_F^2 = 4 3 4$		

- Two nodes with the **same feature** will always have the same embedding under **addition** if and only if they have the same **neighborhood structure**
  - What about other AGG functions, e.g. **mean**?



# Distinguishing node embeddings

- Let  $h_A^0 = h_D^0 = h_E^0 = \begin{bmatrix} 1 & 0 \end{bmatrix}$ ,  $h_B^0 = h_C^0 = \begin{bmatrix} 0 & 1 \end{bmatrix}$ , and let AGG be **mean**. Then, for the following graph



$$h_A^1 = 0.5 \mid 0.5$$

$$h_B^1 = 0.33 \mid 0.67$$

$$h_C^1 = 0.5 \mid 0.5$$

$$h_D^1 = 0.5 \mid 0.5$$

$$h_E^1 = 0.5 \mid 0.5$$

Compute  $AGG(X)$  as  $\hat{A}H$  with normalized  $\hat{A}$

- As expected,  $h_A^1 = h_D^1 = h_E^1$  due to the same feature and neighborhood structure (within 1 hop)
- However,  $h_A^1 = h_C^1$  in spite of their differences in both features and neighborhood structure
  - ⇒ **mean** cannot get distinct embeddings for distinct nodes
    - Even though this is true only for the first iteration in this example, similar examples can be obtained for any number of layers

# Distinguishing node embeddings

- While our earlier examples did not consider the transformation  $W$  or the activation function  $\sigma$ , the arguments are just as valid with them considered
- A function that can distinguish the nodes of distinct feature and neighborhood structure is one that is **injective**
  - **mean** and **max** are not injective
  - On the other hand, **sum** has problems as mentioned
- Theorem (Xu *et al.* 2019). Any injective AGG function can be expressed as  $\Phi(\sum_{x \in S} f(x))$  for some non-linear  $\Phi$  and linear  $f$
- Since MLP is able to approximate any function, we can learn  $\Phi$  and  $f$  with non-linear  $\text{MLP}_{\Phi}$  and linear  $\text{MLP}_f$

$$\text{AGG} = \text{MLP}_{\Phi} \left( \sum_{x \in S} \text{MLP}_f(x) \right)$$

⇒ **Graph Isomorphism Network (GIN)**

# Graph Fourier transform

- GCN has an alternative theoretical basis in terms of graph Fourier transform
- Let  $U$  be a eigenbasis of some Laplacian  $L$
- Then  $U^T x$  is a projection of distribution  $x$  on eigenbasis  $U$

$$\blacksquare \quad U^T x = \begin{bmatrix} \leftarrow & \mu_1 & \rightarrow \\ \leftarrow & \mu_2 & \rightarrow \\ & \vdots & \end{bmatrix} x = \begin{bmatrix} \mu_1^T x \\ \mu_2^T x \\ \vdots \end{bmatrix} = \begin{bmatrix} a_1 \\ a_2 \\ \vdots \end{bmatrix} = \dot{x}, \text{ where } a_i =$$

$\mu_i x$  is the projection onto  $\mu_i$

- The projected space is  $\sum_i a_i \mu_i$

# Graph Fourier transform

- GCN has an alternative theoretical basis in terms of graph Fourier transform
- Let  $U$  be a eigenbasis of some Laplacian  $L$
- Then  $U^T x$  is a projection of distribution  $x$  on eigenbasis  $U$ ,  $U^T x = \dot{x}$
- An application of  $U$  would transform  $\dot{x}$  back into  $x$

$$\begin{aligned} U \dot{x} &= \begin{bmatrix} \uparrow & \uparrow & & \\ \mu_1 & \mu_2 & \dots & \\ \downarrow & \downarrow & & \end{bmatrix} \begin{bmatrix} a_1 \\ a_2 \\ \vdots \end{bmatrix} = \begin{bmatrix} \mu_{11} a_1 + \mu_{21} a_2 + \dots \\ \mu_{12} a_1 + \mu_{22} a_2 + \dots \\ \vdots \end{bmatrix} \\ &= \mu_1 a_1 + \mu_2 a_2 + \dots = \mu_1 \mu_1^T x + \mu_2 \mu_2^T x + \dots \\ &= \left( \sum_i \mu_i \mu_i^T \right) x = I x = x \end{aligned}$$

Homework: prove  $\sum_i \mu_i \mu_i^T = I$

# Graph Fourier transform

- GCN has an alternative theoretical basis in terms of graph Fourier transform
- Let  $U$  be a eigenbasis of some Laplacian  $L$
- Then  $U^T x$  is a projection of distribution  $x$  on eigenbasis  $U$ ,  $U^T x = \dot{x}$
- An application of  $U$  would transform  $\dot{x}$  back into  $x$ ,  $U(\dot{x}) = U(U^T x) = x$  (Since  $UU^T = I$ , this is a no brainer)
- Denote  $U^T x$  as  $F(x)$  and  $U\dot{x}$  as  $F^{-1}(\dot{x})$

# Graph Fourier transform

- A convolution of  $x$  in the Fourier domain of a graph  $G$  is  $x * g = F^{-1}(F(x) \odot F(g)) = U(U^\top x \odot U^\top g)$

where  $g$  is the filter corresponding to  $G$ ,  
and  $\odot$  is the element-wise (Hadamard) product

- Suppose  $U^\top g = \begin{bmatrix} g_1 \\ g_2 \\ \vdots \end{bmatrix}$ . Let  $g_\theta = \text{diag}(U^\top g) = \begin{bmatrix} g_1 & 0 & 0 \\ 0 & g_2 & 0 \\ 0 & 0 & \ddots \end{bmatrix}$

Then we can write  $x * g_\theta = U g_\theta U^\top x$

$$U^\top x \odot U^\top g = \begin{bmatrix} a_1 \\ a_2 \\ \vdots \end{bmatrix} \odot \begin{bmatrix} g_1 \\ g_2 \\ \vdots \end{bmatrix} = \begin{bmatrix} a_1 g_1 \\ a_2 g_2 \\ \vdots \end{bmatrix}$$

$$g_\theta U^\top x = \begin{bmatrix} g_1 & 0 & 0 \\ 0 & g_2 & 0 \\ 0 & 0 & \ddots \end{bmatrix} \begin{bmatrix} a_1 \\ a_2 \\ \vdots \end{bmatrix} = \begin{bmatrix} a_1 g_1 \\ a_2 g_2 \\ \vdots \end{bmatrix}$$

# Graph Fourier transform

- A convolution of  $x$  in the Fourier domain of a graph  $G$  is  $x * g = F^{-1}(F(x) \odot F(g)) = U(U^\top x \odot U^\top g)$

where  $g$  is the filter corresponding to  $G$ ,  
and  $\odot$  is the element-wise (Hadamard) product

- Suppose  $U^\top g = \begin{bmatrix} g_1 \\ g_2 \\ \vdots \end{bmatrix}$ . Let  $g_\theta = \text{diag}(U^\top g) = \begin{bmatrix} g_1 & 0 & 0 \\ 0 & g_2 & 0 \\ 0 & 0 & \ddots \end{bmatrix}$

Then we can write  $x * g_\theta = U g_\theta U^\top x$

- $g_\theta$  is a function of only the eigenvalues

$$g(L) = g(U\Lambda U^\top) = U g_\theta(\Lambda) U^\top$$

- $g_\theta$  can be seen as a scaling where each  $g_i$  scales  $\mu_i x$ , a convolution of  $x_i$  and  $x_i$ 's neighbors  
**according to the eigenvector  $\mu_i$**

- If eigenvector  $\mu_1 = [1 \ 1 \ 0]$ , then  $x_1$  is “convolved” with  $x_2$  before being scaled by  $g_1$

# Graph Fourier transform

□ A convolution of  $x$  in the Fourier domain of a graph  $G$  is

- Whereas in earlier discussions of GNNs the neighbors of  $x_i$  are according to the graph structure, here they are given by the eigenvectors
- We call the earlier GNNs **spatial**, and call these eigenbasis GNNs **spectral**

We will later see that the GCN is both spatial and spectral

■  $g_\theta$  can be seen as a scaling where  $g_i$  scales  $\mu_i x$ , a convolution of  $x_i$  and  $x_i$ 's neighbors according to the eigenvector  $\mu_i$

- If eigenvector  $\mu_1 = [1 \ 1 \ 0]$ , then  $x_1$  is “convolved” with  $x_2$  before being scaled by  $g_1$



# Chebyshev approximation for $U$

- However, computing  $U$  is  $O(N^3)$  and computing  $U^T x$  is  $O(N^2) \Rightarrow$  expensive
- Approximate  $g_\theta$  with Chebyshev polynomials

$$g_{\theta'}(\Lambda) \approx \sum_{i=0}^K \theta'_i T_i(\tilde{\Lambda})$$

where

- $\tilde{\Lambda} = \frac{2}{\lambda_{\max}} \Lambda - I_N$  ( $\lambda_{\max}$  is the largest eigenvalue)
- $\theta' \in \mathbb{R}^K$  are Chebyshev coefficients, and
- The polynomials  $T_i(x)$  are computed with a recurrence relation
  - $T_0(x) = 1, T_1(x) = x$  (base case)
  - $T_{n+1}(x) = 2xT_n(x) - T_{n-1}(x)$

# Chebyshev approximation for $U$

- However, computing  $U$  is  $O(N^3)$  and computing  $U^\top x$  is  $O(N^2) \Rightarrow$  expensive
- Approximate  $g_\theta$  with Chebyshev polynomials

$$g_{\theta'}(\Lambda) \approx \sum_{i=0}^K \theta'_i T_i(\tilde{\Lambda})$$

- Now

$$x * g_{\theta'} = U g_\theta U^\top x \approx U \left( \sum_{i=0}^K \theta'_i T_i(\tilde{\Lambda}) \right) U^\top x$$

- Since  $T(L) = UT(\Lambda)U^\top$

$$x * g_{\theta'} \approx \sum_{i=0}^K \theta'_i T_i(\tilde{L}) x$$

# Chebyshev approximation for $U$

□ Hence we have  $x * g_{\theta'} \approx \sum_{i=0}^K \theta'_i T_i(\tilde{L}) x$

□ Furthermore, from the Chebyshev recurrence

$$T_{n+1}(\tilde{L}) = 2\tilde{L}T_n(\tilde{L}) - T_{n-1}(\tilde{L})$$

□ Denote  $\bar{x}_k = T_k(\tilde{L})x$ , this becomes

$$\bar{x}_{n+1} = 2\tilde{L}\bar{x}_n - \bar{x}_{n-1} \text{ (or } \bar{x}_n = 2\tilde{L}\bar{x}_{n-1} - \bar{x}_{n-2}\text{)}$$

□ Then,  $x * g_{\theta'} \approx \sum_{i=0}^K \theta'_i T_i(\tilde{L})x = [\theta'_0 \quad \theta'_1 \quad \cdots] \begin{bmatrix} \bar{x}_0 \\ \bar{x}_1 \\ \vdots \end{bmatrix}$

■ ...and can be computed in  $O(K|E|)$  time from  $\tilde{L}$

□ We precompute  $\bar{x}_0, \bar{x}_1, \dots$ , with the recurrence relation, and learn  $\theta'_0, \theta'_1, \dots$

# $K = 1$ approximation (GCN)

□ Hence we have  $x * g_{\theta'} \approx \sum_{i=0}^K \theta'_i T_i(\tilde{L}) x$

□ Finally, GCN takes  $K = 1$  to obtain

$$x * g_{\theta'} \approx \theta'_0 x + \theta'_1 \tilde{L} x = \theta'_0 x + \theta'_1 \left( \frac{2}{\lambda_{\max}} L - I_N \right) x$$

■ Furthermore let  $\lambda_{\max} = 2 \Rightarrow x * g_{\theta'} \approx \theta'_0 x + \theta'_1 (L - I_N) x$

■ Let  $\theta'_0$  and  $\theta'_1$  be the parameters to be learned

□ Using the unweighted normalized Laplacian,  $L = D^{-1/2}(D - A)D^{-1/2} = I_N - D^{-1/2}AD^{-1/2}$ , then

$$x * g_{\theta'} = \theta'_0 x - \theta'_1 D^{-1/2} A D^{-1/2} x$$

□ Further constraint the number of parameters by letting

$$\theta'_0 = -\theta'_1 = \theta, x * g_{\theta'} = \theta (I_N + D^{-1/2} A D^{-1/2}) x$$

# $K = 1$ approximation (GCN)

- However,  $x * g_{\theta'} = \theta(I_N + D^{-1/2}AD^{-1/2})x$  has eigenvalues in range of  $[0, 2]$   
 $\Rightarrow$  Numerical instability in repeated applications
  - Merge  $I_N$  within  $A$  prior to the normalization with  $D^{-1}$ 
    - Let  $\hat{A} = A + I$  and normalize  $\hat{A}$   
 $\Rightarrow x * g_{\theta'} = \theta \hat{D}^{-1/2} \hat{A} \hat{D}^{-1/2} x$   
where  $\hat{D}_{ii} = \sum_j \hat{A}_{ij}$
- $\Rightarrow$  After all the **manipulations**,  $x * g_{\theta'}$  is finally a **spatial** operation where the neighbors are described by the graph adjacency matrix  $\hat{A}$

# GNN history: RecGNN to ConvGNN

- 1997 Sperduti and Starita [Supervised neural networks for the classification of structures](#)
- LeNet-5 1998
- 2005 Gori *et al.* [A new model for learning in graph domains](#) (*first use of the term GNN*)
- 2009 Scarselli *et al.* [The graph neural network model](#)
- Hammond *et al.* [Wavelets on graph via spectral graph theory](#)
- Micheli [Neural networks for graph: A contextual constructive approach](#)
- 2010 Gallicchio and Micheli [Graph echo state networks](#)
- AlexNet (U of T) wins ILSVRC 2012
- 2013 Shuman *et al.* [The emerging field of signal processing on graphs](#) 2013
- Bruna *et al.* [Spectral networks and locally-connected networks on graphs](#)
- ZFNet (NYU) wins ILSVRC
- GoogLeNet and VGGNet wins ILSVRC 2014
- 2015 Henaff *et al.* [Deep convolutional networks on graph-structured data](#) 2015
- (*First use of the term “deep” and “convolutional” for GNN*) ResNet wins ILSVRC
- 2016 Defferrard *et al.* [Convolutional neural networks on graphs with fast localized spectral filtering](#)
- Kipf and Welling [Semi-supervised classification with graph convolutional networks \(GCN\)](#)
- Atwood and Towsley [Diffusion-convolutional neural networks](#)
- Niepert *et al.* [Learning convolutional neural networks for graphs](#)
- 2017 Gilmer *et al.* [Neural message passing for quantum chemistry](#)
- (*Unified terminology for spatial approaches and brought GCN along*)

RecGNN
Graph Fourier Transform
Spectral ConvGNN
Spatial ConvGNN

# GNN history: RecGNN to ConvGNN

1997 Sperduti and Starita [Supervised neural networks for the classification of structures](#)

LeCun LeNet-5 1998

2005 Gori *et al.* [A new model for learning in graph domains](#) (*first use of the term GNN*)

2009 Scarselli *et al.* [The graph neural network model](#)

Hammond *et al.* [Wavelets on graph via spectral graph theory](#)

Micheli [Neural networks for graph: A contextual constructive approach](#)

2010 Gallicchio and Micheli [Graph echo state networks](#)

Sutskever+Hinton AlexNet (U of T) wins ILSVRC 2012

2013 Shuman *et al.* [The emerging field of signal processing on graphs](#) 2013

LeCun Bruna *et al.* [Spectral networks and locally-connected networks on graphs](#)

ZFNet (NYU) wins ILSVRC

LeCun

Google

GoogLeNet and VGGNet wins ILSVRC 2014

2015 Henaff *et al.* [Deep convolutional networks on graph-structured data](#) 2015

(*First use of the term “deep” and “convolutional” for GNN*)

ResNet wins ILSVRC

Microsoft

2016 Defferrard *et al.* [Convolutional neural networks on graphs with fast localized spectral filtering](#)

Google Kipf and Welling [Semi-supervised classification with graph convolutional networks](#) (GCN)

Atwood and Towsley [Diffusion-convolutional neural networks](#)

Niepert *et al.* [Learning convolutional neural networks for graphs](#)

2017 Gilmer *et al.* [Neural message passing for quantum chemistry](#)

Google (*Unified terminology for spatial approaches and brought GCN along*)

RecGNN

Graph Fourier Transform

Spectral ConvGNN

Spatial ConvGNN