


Common Loss functions in machine learning



Ravindra Parmar
Sep 2, 2018 · 5 min read



Loss functions and optimizations

Machines learn by means of a loss function. It's a method of evaluating how well specific algorithm models the given data. If predictions deviates too much from actual results, loss function would cough up a very large number. Gradually, with the help of some optimization function, loss function learns to reduce the error in prediction. In this article we will go through several loss functions and their applications in the domain of machine/deep learning.

There's no one-size-fits-all loss function to algorithms in machine learning. There are various factors involved in choosing a loss function for specific problem such as type of machine learning algorithm chosen, ease of calculating the derivatives and to some degree the percentage of outliers in the data set.

Top highlight

Broadly, loss functions can be classified into two major categories depending upon the type of learning task we are dealing with — **Regression losses** and **Classification losses**. In classification, we are trying to predict output from set of finite categorical values i.e Given large data set of images of hand written digits, categorizing them into one of 0–9 digits. Regression, on the other hand, deals with predicting a continuous value for example given floor area, number of rooms, size of rooms, predict the price of room.

NOTE

n - Number of training examples.
 i - i th training example in a data set.
 $y(i)$ - Ground truth label for i th training example.
 $\hat{y}_{\text{hat}}(i)$ - Prediction for i th training example.

Regression Losses

Mean Square Error/Quadratic Loss/L2 Loss

Mathematical formulation :-

$$MSE = \frac{\sum_{i=1}^n (y_i - \hat{y}_i)^2}{n}$$

Mean Squared Error

As the name suggests, *Mean square error* is measured as the average of squared difference between predictions and actual observations. It's only concerned with the average magnitude of error irrespective of their direction. However, due to squaring, predictions which are far away from actual values are penalized heavily in comparison to less deviated predictions. Plus MSE has nice mathematical properties which makes it easier to calculate gradients.

```
import numpy as np

y_hat = np.array([0.000, 0.166, 0.333])
y_true = np.array([0.000, 0.254, 0.998])

def rmse(predictions, targets):
    differences = predictions - targets
    differences_squared = differences ** 2
    mean_of_differences_squared = differences_squared.mean()
    rmse_val = np.sqrt(mean_of_differences_squared)
    return rmse_val

print("d is: " + str(["%.8f" % elem for elem in y_hat]))
print("p is: " + str(["%.8f" % elem for elem in y_true]))

rmse_val = rmse(y_hat, y_true)
print("rms error is: " + str(rmse_val))
```

Mean Absolute Error/L1 Loss

Mathematical formulation :-

$$MAE = \frac{\sum_{i=1}^n |y_i - \hat{y}_i|}{n}$$

Mean absolute error

Mean absolute error, on the other hand, is measured as the average of sum of absolute differences between predictions and actual observations. Like MSE, this as well measures the magnitude of error without considering their direction. Unlike MSE, MAE needs more complicated tools such as linear programming to compute the gradients. Plus MAE is more robust to outliers since it does not make use of square.

```
import numpy as np

y_hat = np.array([0.000, 0.166, 0.333])
y_true = np.array([0.000, 0.254, 0.998])

print("d is: " + str(["%.8f" % elem for elem in y_hat]))
print("p is: " + str(["%.8f" % elem for elem in y_true]))

def mae(predictions, targets):
    differences = predictions - targets
    absolute_differences = np.absolute(differences)
    mean_absolute_differences = absolute_differences.mean()
    return mean_absolute_differences

mae_val = mae(y_hat, y_true)
print("mae error is: " + str(mae_val))
```

Mean Bias Error

This is much less common in machine learning domain as compared to it's counterpart. This is same as MSE with the only difference that we don't take absolute values. Clearly there's a need for caution as positive and negative errors could cancel each other out. Although less accurate in practice, it could determine if the model has positive bias or negative bias.

Mathematical formulation :-

$$MBE = \frac{\sum_{i=1}^n (y_i - \hat{y}_i)}{n}$$

Mean bias error

Classification Losses

Hinge Loss/Multi class SVM Loss

In simple terms, the score of correct category should be greater than sum of scores of all incorrect categories by some safety margin (usually one). And hence hinge loss is used for maximum-margin classification, most notably for support vector machines. Although not differentiable, it's a convex function which makes it easy to work with usual convex optimizers used in machine learning domain.

Mathematical formulation :-

$$SVM_{Loss} = \sum_{j \neq y_i} \max(0, s_j - s_{y_i} + 1)$$

SVM Loss or Hinge Loss

Consider an example where we have three training examples and three classes to predict — Dog, cat and horse. Below the values predicted by our algorithm for each of the classes :-



	Image #1	Image #2	Image #3
Dog	-0.39	-4.61	1.03
Cat	1.49	3.28	-2.37
Horse	4.21	1.46	-2.27

Hinge loss/ Multi class SVM loss

Computing hinge losses for all 3 training examples :-

```
## 1st training example
max(0, (-4.61) - (-0.39) + 1) + max(0, (4.21) - (-0.39) + 1)
max(0, 2.88) + max(0, 5.6)
2.88 + 5.6
8.48 (High loss as very wrong prediction)

## 2nd training example
max(0, (-4.61) - (3.28) + 1) + max(0, (1.46) - (3.28) + 1)
max(0, -6.89) + max(0, -0.82)
0 + 0
0 (Zero loss as correct prediction)

## 3rd training example
max(0, (1.03) - (-2.27) + 1) + max(0, (-2.37) - (-2.27) + 1)
max(0, 4.3) + max(0, 0.9)
4.3 + 0.9
5.2 (High loss as very wrong prediction)
```

Cross Entropy Loss/Negative Log Likelihood

This is the most common setting for classification problems. Cross-entropy loss increases as the predicted probability diverges from the actual label.

Mathematical formulation :-

$$CrossEntropyLoss = -(y_i \log(\hat{y}_i) + (1 - y_i) \log(1 - \hat{y}_i))$$

Cross entropy loss

Notice that when actual label is 1 ($y(i) = 1$), second half of function disappears where as in case actual label is 0 ($y(i) = 0$) first half is dropped off. In short, we are just multiplying the log of the actual predicted probability for the ground truth class. An important aspect of this is that cross entropy loss penalizes heavily the predictions that are *confident but wrong*.

```
import numpy as np

predictions = np.array([[0.25, 0.25, 0.25, 0.25],
                        [0.01, 0.01, 0.01, 0.96]])
targets = np.array([[0, 0, 0, 1],
                   [0, 0, 0, 1]])

def cross_entropy(predictions, targets, epsilon=1e-10):
    predictions = np.clip(predictions, epsilon, 1 - epsilon)
    N = predictions.shape[0]
    ce_loss = -np.sum(np.sum(targets * np.log(predictions + 1e-5))) / N
    return ce_loss

cross_entropy_loss = cross_entropy(predictions, targets)
print("Cross entropy loss is: " + str(cross_entropy_loss))
```

Artificial Intelligence

Deep Learning

Machine Learning



Optimization



1.1K claps



9 responses



WRITTEN BY

Ravindra Parmar

Follow

Software professional. Machine/Deep Learning Enthusiast. An active member of
<https://stackoverflow.com/users/4047092/ravi>



Towards Data Science

A Medium publication sharing concepts, ideas, and codes.

Following


More from Towards Data Science



You Don't Have to Use Docker Anymore



Martin Heinz in Towards...Science
Oct 15 · 10 min read



1.3K




9


More from Towards Data Science




Python is Slowly Losing its Charm



Jason Dsouza in Towar...Science
Oct 6 · 4 min read



2.4K



9


More from Towards Data Science



Go Programming Language for Artificial Intelligence and Data Science of the 20s



Dasarath SK in Toward...Science
Oct 9 · 4 min read



1.3K



9

Learn more.

Medium is an open platform where 170 million readers come to find insightful and dynamic thinking. Here, expert and undiscovered voices alike dive into the heart of any topic and bring new ideas to the surface. [Learn more](#)

Make Medium yours.

Follow the writers, publications, and topics that matter to you, and you'll see them on your homepage and in your inbox. [Explore](#)

Share your thinking.

If you have a story to tell, knowledge to share, or a perspective to offer — welcome home. It's easy and free to post your thinking on any topic. [Write on Medium](#)