

# CSE 374 Programming concepts and tools

Winter 2024


Instructor: Alex McKinney



**STL**

# C++'s Standard Library

C++'s Standard Library consists of four major pieces:

1. The entire C standard library
2. C++'s input/output stream library
  - `std::cin`, `std::cout`, `stringstream`, `fstream`, etc.
3. C++'s standard template library (**STL**) 
  - Containers, iterators, algorithms (sort, find, etc.), numerics
4. C++'s miscellaneous library
  - Strings, exceptions, memory allocation, localization

# STL Containers

A **container** is an object that stores (in memory) a collection of other objects (elements)

- Implemented as class templates, so hugely flexible

Several different classes of container

- Sequence containers (`vector`, `deque`, `list`, ...)
- Associative containers (`set`, `map`, `multiset`, `multimap`, `bitset`, ...)
- Differ in algorithmic cost and supported operations

# STL Containers

STL containers store by **value**, not by reference

- When you insert an object, the container makes a **copy**
- If the container needs to rearrange objects, it makes copies
  - e.g. if you sort a `vector`, it will make many, many copies
  - e.g. if you insert into a `map`, that may trigger several copies
- What if you don't want this (disabled copy constructor or copying is expensive)?
  - You can insert a wrapper object with a pointer to the object
    - We'll learn about these “**smart pointers**” soon

# Our Tracer Class

Wrapper class for an `int` `value_`

Two fields:  
`value`  
`id` (unique to the instance)

- Also holds unique `int` `id_` (increasing from 0)
- Default ctor (set unique `id_` for each instance), ctor, dtor, `op=`, `op<` defined
- `friend` function `operator<<` defined
- Private helper method `PrintID()` to return "`(id_, value_)`" as a string
- Class and member definitions can be found in `Tracer.h` and `Tracer.cc`

Useful for tracing behaviors of containers

- All methods print identifying messages
- Unique `id_` allows you to follow individual instances

# Demo: Tracer Walkthrough



# STL **vector**

A generic, dynamically resizable array

- <https://cplusplus.com/reference/vector/vector/>
- Elements are stored in **contiguous** memory locations
  - Like a normal C array, or the ArrayList in Java!
  - Elements can be accessed using pointer arithmetic if you'd like
  - Random access is  $O(1)$  time
    - Pointer arithmetic, then access
- Adding/removing from the end is cheap (amortized constant time)
- Inserting/deleting from the middle or start is expensive (linear time)
  - Need to shift all of the elements in the array



# vector/Tracer Example

vectorfun.cc

```
#include <iostream>
#include <vector>
#include "Tracer.h"
```

Most containers are declared in library of same name

```
using namespace std;
```

```
int main(int argc, char** argv) {
    Tracer a, b, c;
    vector<Tracer> vec;
```

Construct three tracer instances & empty vector

```
    cout << "vec.push_back " << a << endl;
    vec.push_back(a);
    cout << "vec.push_back " << b << endl;
    vec.push_back(b);
    cout << "vec.push_back " << c << endl;
    vec.push_back(c);
```

Add tracers to end of vector

```
    cout << "vec[0]" << endl << vec[0] << endl;
    cout << "vec[2]" << endl << vec[2] << endl;
    return EXIT_SUCCESS;
```

Array syntax to access elements

```
}
```

# Dynamic Resizing

What's going on here?

- Answer: a C++ vector (like Java's ArrayList) is initially small, but grows if needed as elements are added
  - Implemented by allocating a new, larger underlying array, copy existing elements to new array, and then replace previous array with new one
- And vector starts out *really* small by default, so it needs to grow almost immediately!
  - But you can specify an initial capacity if “really small” is an inefficient initial size (use `reserve()` member function)

# Demo: Vectors



# STL iterator

Each container class has an associated `iterator` class (e.g. `vector<int>::iterator`) used to iterate through elements of the container

- <https://cplusplus.com/reference/iterator/>
- `iterator range` is from `begin` up to `end` i.e., `[begin, end)`
  - **`end` is one past the last container element!**
- Some container iterators support more operations than others
  - All can be incremented (`++`), copied, copy-constructed
  - Some can be dereferenced on RHS (e.g. `x = *it;`)
  - Some can be dereferenced on LHS (e.g. `*it = x;`)
  - Some can be decremented (`--`)
  - Some support random access (`[]`, `+`, `-`, `+=`, `-=`, `<`, `>` operators)

# iterator Example

vectoriterator.cc

```
#include <vector>
#include "Tracer.h"
using namespace std;

int main(int argc, char** argv) {
    Tracer a, b, c;
    vector<Tracer> vec;

    vec.push_back(a);
    vec.push_back(b);
    vec.push_back(c);

    cout << "Iterating:" << endl;
    vector<Tracer>::iterator it;
    for (it = vec.begin(); it < vec.end(); it++) {
        cout << *it << endl;
    }
    cout << "Done iterating!" << endl;
    return EXIT_SUCCESS;
}
```

(first element, one past the end, increment to next element)

← Dereference to access element

# Type Inference (C++11)

The `auto` keyword can be used to infer types

- Simplifies your life if, for example, functions return complicated types
- The expression using `auto` must contain explicit initialization for it to work

Compiler knows return value of `Factors()`



???? No information to infer type



```
// Calculate and return a vector  
// containing all factors of n  
std::vector<int> Factors(int n);  
  
void foo(void) {  
    // Manually identified type  
    std::vector<int> facts1 =  
        Factors(324234);  
  
    // Inferred type  
    auto facts2 = Factors(12321);  
  
    // Compiler error here  
    auto facts3;  
}
```

# auto and Iterators

Life becomes much simpler!

```
for (vector<Tracer>::iterator it = vec.begin(); it < vec.end(); it++) {  
    cout << *it << endl;  
}
```



```
for (auto it = vec.begin(); it < vec.end(); it++) {  
    cout << *it << endl;  
}
```


# Range for Statement (C++11)

Syntactic sugar similar to Java's `foreach`

```
for ( declaration : expression ) {  
    statements  
}
```

- `declaration` defines loop variable
- `expression` is an object representing a sequence
  - Strings, initializer lists, arrays with an explicit length defined, STL containers that support iterators

`str = sequence of characters`



```
// Prints out a string, one  
// character per line  
std::string str("hello");  
  
for ( auto c : str ) {  
    std::cout << c << std::endl;  
}
```



# Updated iterator Example

vectoriterator\_2011.cc

```
#include <vector>
#include "Tracer.h"

using namespace std;

int main(int argc, char** argv) {
    Tracer a, b, c;
    vector<Tracer> vec;

    vec.push_back(a);
    vec.push_back(b);
    vec.push_back(c);

    cout << "Iterating:" << endl;
    for (auto& p : vec) {           // p is a reference (alias) of vec
        cout << p << endl;         // element here; not a new copy
    }

    cout << "Done iterating!" << endl;
    return EXIT_SUCCESS;
}
```

Look at how much more simplified this is!  
No begin(), end(), or dereferencing! :O

# STL Algorithms

A set of functions to be used on ranges of elements

- **Range**: any sequence that can be accessed through *iterators* or *pointers*, like arrays or some of the containers
- General form: `algorithm(begin, end, ...);`

Algorithms operate directly on range *elements* rather than the containers they live in

- Make use of elements' copy ctor, =, ==, !=, <
- Some do not modify elements
  - e.g. `find`, `count`, `for_each`, `min_element`, `binary_search`
- Some do modify elements
  - e.g. `sort`, `transform`, `copy`, `swap`

# Algorithms Example

vectoralgos.cc

```
#include <vector>
#include <algorithm>
#include "Tracer.h"
using namespace std;

void PrintOut(const Tracer& p) {
    cout << " printout: " << p << endl;
}

int main(int argc, char** argv) {
    Tracer a, b, c;
    vector<Tracer> vec;

    vec.push_back(c);
    vec.push_back(a);
    vec.push_back(b);
    cout << "sort:" << endl;
    sort(vec.begin(), vec.end());
    cout << "done sort!" << endl;
    for_each(vec.begin(), vec.end(), PrintOut);
    return EXIT_SUCCESS;
}
```

Sort elements from  
[vec.begin(), vec.end())

Runs function on each  
element. In this case, prints  
out each element.

# STL `list`

A generic doubly-linked list

- <https://cplusplus.com/reference/list/list/>
- Elements are **not** stored in contiguous memory locations
  - Does not support random access (e.g. cannot do `list[5]`)
- Some operations are much more efficient than vectors
  - Constant time insertion, deletion anywhere in list
  - Can iterate forward or backwards
    - Backward: `--`
    - Forward: `++`
- Has a built-in sort member function
  - Doesn't copy! Manipulates list structure instead of element values

# list Example

listexample.cc

```
#include <list>
#include <algorithm>
#include "Tracer.h"
using namespace std;

void PrintOut(const Tracer& p) {
    cout << " printout: " << p << endl;
}

int main(int argc, char** argv) {
    Tracer a, b, c;
    list<Tracer> lst;

    lst.push_back(c);
    lst.push_back(a);
    lst.push_back(b);
    cout << "sort:" << endl;
    lst.sort();
    cout << "done sort!" << endl;
    for_each(lst.begin(), lst.end(), PrintOut);
    return EXIT_SUCCESS;
}
```

Use case is similar to vector, but internal implementation is different.

Won't copy elements, just modifies the next and prev pointers.

# STL `map`

One of C++'s *associative* containers: a key/value table, implemented as a search tree

- <https://cplusplus.com/reference/map/>
- General form: `map<key_type, value_type> name;`
- Keys must be *unique*
  - `multimap` allows duplicate keys
- Efficient lookup ( $O(\log n)$ ) and insertion ( $O(\log n)$ )
  - Access value via `name[key]`
    - If key doesn't exist in map, it is added to the map
- Elements are type `pair<key_type, value_type>` and are stored in *sorted* order (key is field `first`, value is field `second`)
  - Key type must support less-than operator (`<`)

# map Example

mapexample.cc

```
void PrintOut(const pair<Tracer,Tracer>& p) {  
    cout << "printout: [" << p.first << "," << p.second << "]" << endl;  
}
```


```
int main(int argc, char** argv) {  
    Tracer a, b, c, d, e, f;  
    map<Tracer,Tracer> table;  
    map<Tracer,Tracer>::iterator it;
```

```
    table.insert(pair<Tracer,Tracer>(a, b));  
    table[c] = d;  
    table[e] = f;  
    cout << "table[e]:" << table[e] << endl;  
    it = table.find(c);
```

Equivalent behavior



Returns iterator (end it not found).  
Can also use map.count() to see if  
a key exists.



```
    cout << "PrintOut(*it), where it = table.find(c)" << endl;  
    PrintOut(*it);
```

```
    cout << "iterating:" << endl;  
    for_each(table.begin(), table.end(), PrintOut);  
    return EXIT_SUCCESS;
```

```
}
```

# Unordered Containers (C++11)

`unordered_map`, `unordered_set`

- Average case for key access is  $O(1)$ 
  - But range iterators can be less efficient than ordered `map/set`
  - Elements are not stored in contiguous order (stored based on the hash).
- See *C++ Primer*, online references for details



# Demo: Animals



# C++ standard lib is built around templates

**Containers** store data using various underlying data structures

- The specifics of the data structures define properties and operations for the container

**Iterators** allow you to traverse container data

- Iterators form the common interface to containers
- Different flavors based on underlying data structure

**Algorithms** perform common, useful operations on containers

- Use the common interface of iterators, but different algorithms require different 'complexities' of iterators

# Common C++ STL Containers (and Java equiv)

Sequence containers can be accessed sequentially

- `vector<Item>` uses a dynamically-sized contiguous array (like `ArrayList`)
- `list<Item>` uses a doubly-linked list (like `LinkedList`)

Associative containers use search trees and are sorted by keys

- `set<Key>` only stores keys (like `TreeSet`)
- `map<Key, Value>` stores key-value pair<>'s (like `TreeMap`)

Unordered associative containers are hashed

- `unordered_map<Key, Value>` (like `HashMap`)