

CSE 374 Programming concepts and tools

Winter 2024

Instructor: Alex Luo & Alex McKinney



Review: C++ Standard Template Library

Containers store data using various underlying data structures

- The specifics of the data structures define properties and operations for the container

Iterators allow you to traverse container data

- Iterators form the common interface to containers
- Different flavors based on underlying data structure

Algorithms perform common, useful operations on containers

- Use the common interface of iterators, but different algorithms require different 'complexities' of iterators

Common C++ STL Containers (and Java equiv)

Sequence containers can be accessed sequentially

- `vector<Item>` uses a dynamically-sized contiguous array (like `ArrayList`)
- `list<Item>` uses a doubly-linked list (like `LinkedList`)

Associative containers use search trees and are sorted by keys

- `set<Key>` only stores keys (like `TreeSet`)
- `map<Key, Value>` stores key-value pair<>'s (like `TreeMap`)

Unordered associative containers are hashed

- `unordered_map<Key, Value>` (like `HashMap`)

Smart Pointers

Intro and toy_ptr

Smart Pointers 101

C++ Smart Pointers

A **smart pointer** is an **object** that stores a pointer to a heap-allocated object

- A smart pointer looks and behaves like a regular C++ pointer
 - By overloading `*`, `->`, `[]`, etc.
- These can help you manage memory
 - The smart pointer will delete the pointed-to object *at the right time* including invoking the object's destructor
 - When that is depends on what kind of smart pointer you use
 - With correct use of smart pointers, you no longer have to remember when to `delete` heap memory! (*If it's owned by a smart pointer*)

A Toy Smart Pointer

We can implement a simple one with:

- A constructor that accepts a pointer
- A destructor that frees the pointer
- Overloaded `*` and `->` operators that access the pointer

A smart pointer is just a Template object.

ToyPtr Class Template

ToyPtr.h

```
#ifndef _TOYPTR_H_
#define _TOYPTR_H_

template <typename T> class ToyPtr {
public:
    ToyPtr(T* ptr) : ptr_(ptr) { }           // constructor
    ~ToyPtr() { delete ptr_; }                // destructor
```

Takes advantage of implicit calling of destructor to clean up for us

```
T& operator*() { return *ptr_; } // * operator
T* operator->() { return ptr_; }  // -> operator

private:
    T* ptr_;                       // the pointer itself
};

#endif // _TOYPTR_H_
```


ToyPtr Example


usetoy.cc

```
#include <iostream>
#include "ToyPtr.h"

int main(int argc, char **argv) {
    // Create a dumb pointer
    std::string* leak = new std::string("apple");

    // Create a "smart" pointer (OK, it's still pretty dumb)
    ToyPtr<std::string> notleak(new std::string("banana"));

    std::cout << "    *leak: " << *leak << std::endl;
    std::cout << "    *notleak: " << *notleak << std::endl;
    return 0;
}
```



Demo: ToyPtr




ToyPtr Class Template Issues

toyuse.cc

```
#include "ToyPtr.h"

int main(int argc, char **argv) {
    // We want two pointers!
    ToyPtr<int> x(new int(5));
    ToyPtr<int> y = x;
    return 0;
}
```



!! Double delete !!

What Makes This a Toy?

Can't handle:

- Arrays
 - Needs to use `delete[]`
- Copying
- Reassignment
- Comparison
- ... plus many other subtleties...

Luckily, others have built non-toy smart pointers for us!

unique_ptr

Smart Pointers pro

`std::unique_ptr`

A `unique_ptr` is the ***sole owner*** of a pointer

- A template: template parameter is the type that the “owned” pointer references (i.e., the `T` in pointer type `T*`)
- Part of C++’s standard library (C++11)
- Once we give a vanilla pointer a `unique_ptr`, we should stop using the original (non-smart) pointer
- Its destructor invokes `delete` on the owned pointer
 - Invoked when `unique_ptr` object is `delete`’d or falls out of scope via the `unique_ptr` destructor

Guarantees uniqueness by disabling copy and assignment.

Using `unique_ptr`


unique.cc

```
#include <iostream>    // for std::cout, std::endl
#include <memory>       // for std::unique_ptr
#include <cstdlib>      // for EXIT_SUCCESS
```

```
void Leaky() {
    int* x = new int(5); // heap-allocated
    (*x)++;
    std::cout << *x << std::endl;
} // never used delete, therefore leak
```

```
void NotLeaky() {
    std::unique_ptr<int> x(new int(5)); // wrapped, heap-allocated
    (*x)++;
    std::cout << *x << std::endl;
} // never used delete, but no leak
```

```
int main(int argc, char **argv) {
    Leaky();
    NotLeaky();
    return EXIT_SUCCESS;
}
```



Why are `unique_ptr`s useful?

If you have many potential exits out of a function, it's easy to forget to call `delete` on all of them

- `unique_ptr` will `delete` its pointer when it falls out of scope
- Thus, a `unique_ptr` also helps with *exception safety*

```
void NotLeaky() {  
    std::unique_ptr<int> x(new int(5));  
    ...  
    // lots of code, including several returns  
    // lots of code, including potential exception throws  
    ...  
}
```


unique_ptr Cannot Be Copied

`std::unique_ptr` has disabled its copy constructor and assignment operator

- You cannot copy a `unique_ptr`, helping maintain “uniqueness” or “ownership”

`uniquefail.cc`

```
#include <memory>    // for std::unique_ptr
#include <cstdlib>    // for EXIT_SUCCESS

int main(int argc, char **argv) {
    std::unique_ptr<int> x(new int(5));    // OK

    std::unique_ptr<int> y(x);              // fail - no copy ctor

    std::unique_ptr<int> z;                // OK - z is nullptr

    z = x;                                // fail - no assignment op

    return EXIT_SUCCESS;
}
```


Transferring Ownership

Use **reset()** and **release()** to transfer ownership

- **release** returns the pointer, sets wrapped pointer to `nullptr`
- **reset** **delete's** the current pointer and stores a new one

uniquepass.cc

```
int main(int argc, char **argv) {  
    unique_ptr<int> x(new int(5));  
    cout << "x: " << x.get() << endl;  
  
    unique_ptr<int> y(x.release()); // x abdicates ownership to y  
    cout << "x: " << x.get() << endl;  
    cout << "y: " << y.get() << endl;  
  
    unique_ptr<int> z(new int(10));  
  
    // y transfers ownership of its pointer to z.  
    // z's old pointer was delete'd in the process.  
    z.reset(y.release());  
    return EXIT_SUCCESS;  
}
```



unique_ptr and Arrays

unique_ptr can store arrays as well

- Will call delete[] on destruction

uniquearray.cc

```
#include <memory>    // for std::unique_ptr
#include <cstdlib>    // for EXIT_SUCCESS

using namespace std;

int main(int argc, char **argv) {
    unique_ptr<int[]> x(new int[5]);


    x[0] = 1;
    x[2] = 2;

    return EXIT_SUCCESS;
}
```

Demo: `unique_ptr` and `Array`



Questions?



shared_ptr weak_ptr

Reference counting and more
smart pointers...

What is Reference Counting?

Idea: associate a *reference count* with each object

- Reference count holds number of references (pointers) to the object
- Adjusted whenever pointers are changed:
 - Increase by 1 each time we have a new pointer to an object
 - Decrease by 1 each time a pointer to an object is removed
- When reference counter decreased to 0, no more pointers to the object, so delete it (automatically)

Used by C++ `shared_ptr`, not used in general for C++ memory management

Example

Suppose for the moment that we have a new C++ -like language that uses reference counting for heap data

As in C++, a struct is a type with public fields, so we can implement lists of integers using the following Node type

```
struct Node {  
    int payload;    // node payload  
    Node* next;    // next Node or nullptr  
};
```

The reference counts would be handled behind the scenes by the memory manager code – they are not accessible to the programmer

Example 1

Let's execute the following code. Heap data is shown using rectangles; associated reference counts with ovals

p 

q 


r 



```
Node * p = new Node();  
Node * q = new Node();  
Node * r = p;  
q->next = new Node();  
p = nullptr;  
r = nullptr;  
q = nullptr;
```

Example 1


Let's execute the following code. Heap data is shown using rectangles; associated reference counts with ovals



```
Node * p = new Node();  
Node * q = new Node();  
Node * r = p;  
q->next = new Node();  
p = nullptr;  
r = nullptr;  
q = nullptr;
```

Example 1


Let's execute the following code. Heap data is shown using rectangles; associated reference counts with ovals



```
Node * p = new Node();  
Node * q = new Node();  
Node * r = p;  
q->next = new Node();  
p = nullptr;  
r = nullptr;  
q = nullptr;
```

Example 1


Let's execute the following code. Heap data is shown using rectangles; associated reference counts with ovals



```
Node * p = new Node();  
Node * q = new Node();  
Node * r = p;  
→ q->next = new Node();  
p = nullptr;  
r = nullptr;  
q = nullptr;
```

Example 1


Let's execute the following code. Heap data is shown using rectangles; associated reference counts with ovals



```
Node * p = new Node();  
Node * q = new Node();  
Node * r = p;  
q->next = new Node();  
→ p = nullptr;  
  r = nullptr;  
  q = nullptr;
```

Example 1


Let's execute the following code. Heap data is shown using rectangles; associated reference counts with ovals



```
Node * p = new Node();  
Node * q = new Node();  
Node * r = p;  
q->next = new Node();  
p = nullptr;  
r = nullptr;  
q = nullptr;
```

Example 1

Let's execute the following code. Heap data is shown using rectangles; associated reference counts with ovals



```
Node * p = new Node();  
Node * q = new Node();  
Node * r = p;  
q->next = new Node();  
p = nullptr;  
r = nullptr;  
q = nullptr;
```



Example 1

Let's execute the following code. Heap data is shown using rectangles; associated reference counts with ovals

p 

q 

r 



```
Node * p = new Node();  
Node * q = new Node();  
Node * r = p;  
q->next = new Node();  
p = nullptr;  
r = nullptr;  
q = nullptr;
```



`std::shared_ptr`

`shared_ptr` is similar to `unique_ptr` but we allow shared objects to have multiple owners

- The copy/assign operators are not disabled and *increment* **reference counts** as needed
 - After a copy/assign, the two `shared_ptr` objects point to the same pointed-to object and the (shared) reference count is incremented by **1**
- When a `shared_ptr` is destroyed, the reference count is *decremented*
 - When the reference count hits **0**, we **delete** the pointed-to object!
- Allows us to create complex linked structures (double-linked lists, graphs, etc.) at the cost of maintaining reference counts

shared_ptr Example

shared.cc


```
#include <cstdlib>    // for EXIT_SUCCESS
#include <iostream>   // for std::cout, std::endl
#include <memory>     // for std::shared_ptr

int main(int argc, char **argv) {
    std::shared_ptr<int> x(new int(10)); // ref count: 1

    // temporary inner scope with local y (!)
    {
        std::shared_ptr<int> y = x;      // ref count: 2
        std::cout << *y << std::endl;
    }                                     // exit scope, y deleted

    std::cout << *x << std::endl;        // ref count: 1

    return EXIT_SUCCESS;
}
```



shared_ptr and STL Containers

Safe to store `shared_ptr`s in containers, since copy & assign maintain a shared reference count; Also avoid extra object copies

sharedvec.cc

```
vector<std::shared_ptr<int>> vec;

vec.push_back(std::shared_ptr<int>(new int(9)));
vec.push_back(std::shared_ptr<int>(new int(5)));
vec.push_back(std::shared_ptr<int>(new int(7)));

int& z = *vec[1];
std::cout << "z is: " << z << std::endl;

std::shared_ptr<int> copied = vec[1]; // works!
std::cout << "*copied: " << *copied << std::endl;

vec.pop_back(); // removes smart ptr & deallocate 7
```

Demo: `shared_ptr` and STL



Questions?




Example 2

Similar to the previous code, but slightly different

q 


r 



```
Node * q = new Node();  
Node * r = new Node();  
q->next = r;  
r->next = q;  
r = nullptr;  
q = nullptr;
```

Example 2


Similar to the previous code, but slightly different



```
Node * q = new Node();  
Node * r = new Node();  
q->next = r;  
r->next = q;  
r = nullptr;  
q = nullptr;
```

Example 2


Similar to the previous code, but slightly different



```
Node * q = new Node();  
Node * r = new Node();  
→ q->next = r;  
  r->next = q;  
  r = nullptr;  
  q = nullptr;
```


Example 2


Similar to the previous code, but slightly different



```
Node * q = new Node();  
Node * r = new Node();  
q->next = r;  
→ r->next = q;  
r = nullptr;  
q = nullptr;
```

Example 2


Similar to the previous code, but slightly different



```
Node * q = new Node();  
Node * r = new Node();  
q->next = r;  
r->next = q;  
→ r = nullptr;  
q = nullptr;
```

Example 2

Similar to the previous code, but slightly different




```
Node * q = new Node();  
Node * r = new Node();  
q->next = r;  
r->next = q;  
r = nullptr;  
q = nullptr;
```



Example 2

Similar to the previous code, but slightly different



Memory leak!

```
Node * q = new Node();  
Node * r = new Node();  
q->next = r;  
r->next = q;  
r = nullptr;  
q = nullptr;
```

Cycle of shared_ptrs

sharedcycle.cc


```
#include <cstdlib>
#include <memory>

using std::shared_ptr;

struct A {
    shared_ptr<A> next;
    shared_ptr<A> prev;
};

int main(int argc, char **argv) {
    shared_ptr<A> head(new A());
    head->next = shared_ptr<A>(new A());
    head->next->prev = head;

    return EXIT_SUCCESS;
}
```



What happens when we delete head?

Cycle of shared_ptrs

sharedcycle.cc


```
#include <cstdlib>
#include <memory>

using std::shared_ptr;

struct A {
    shared_ptr<A> next;
    shared_ptr<A> prev;
};

int main(int argc, char **argv) {
    shared_ptr<A> head(new A());
    head->next = shared_ptr<A>(new A());
    head->next->prev = head;

    return EXIT_SUCCESS;
}
```



What happens when we **delete** head? Nodes unreachable but not deleted because ref counts > 0

`std::weak_ptr`

`weak_ptr` is similar to a `shared_ptr` but doesn't affect the reference count

- Can *only* “point to” an object that is managed by a `shared_ptr`
- Not *really* a pointer – can't actually dereference unless you “get” its associated `shared_ptr`
- Because it doesn't influence the reference count, `weak_ptr`s can become “*dangling*”
 - Object referenced may have been `delete'd`
 - But you can check to see if the object still exists

Can be used to break our cycle problem!

Breaking the Cycle with weak_ptr


weakcycle.cc

```
#include <cstdlib>
#include <memory>

using std::shared_ptr;
using std::weak_ptr;

struct A {
    shared_ptr<A> next;
    weak_ptr<A> prev;
};

int main(int argc, char **argv) {
    shared_ptr<A> head(new A());
    head->next = shared_ptr<A>(new A());
    head->next->prev = head;
    return EXIT_SUCCESS;
}
```



Now what happens when we
delete head?

Breaking the Cycle with weak_ptr


weakcycle.cc

```
#include <cstdlib>
#include <memory>

using std::shared_ptr;
using std::weak_ptr;

struct A {
    shared_ptr<A> next;
    weak_ptr<A> prev;
};

int main(int argc, char **argv) {
    shared_ptr<A> head(new A());
    head->next = shared_ptr<A>(new A());
    head->next->prev = head;
    return EXIT_SUCCESS;
}
```




Now what happens when we `delete` head? Ref counts go to 0 and nodes deleted!

Using a weak_ptr

usingweak.cc

```
#include <cstdlib>    // for EXIT_SUCCESS
#include <iostream>   // for std::cout, std::endl
#include <memory>     // for std::shared_ptr, std::weak_ptr
int main(int argc, char **argv) {
    std::weak_ptr<int> w;
    { // temporary inner scope with local x
        std::shared_ptr<int> x;
        { // temporary inner-inner scope with local y
            std::shared_ptr<int> y(new int(10));
            w = y;           // weak ref; ref count for "10" node is same
            x = w.lock();    // get "promoted" shared_ptr, ref cnt = 2
            std::cout << *x << std::endl;
        } // y deleted; ref count now 1
        std::cout << *x << std::endl;
    } // x deleted; ref count now 0; mem freed
    std::shared_ptr<int> a = w.lock(); // nullptr
    std::cout << a << std::endl;      // output is 0 (null)
    return EXIT_SUCCESS;
}
```



Demo: weak_ptr fixed code



Lecture Summary

A `unique_ptr` **takes ownership** of a pointer

- Cannot be copied, but can be moved
- Use **`release()`** to release ownership and stop managing the pointer for you
- **`reset()`** **deletes** old pointer value and stores a new one

A `shared_ptr` allows shared objects to have multiple owners by doing *reference counting*

- **deletes** an object once its reference count reaches zero

A `weak_ptr` works with a shared object but doesn't affect the reference count

- Can't actually be dereferenced, but can check if the object still exists and can get a `shared_ptr` from the `weak_ptr` if it does

Some Important Smart Pointer Functions

`std::unique_ptr U;`

- `U.get()`
- `U.release()`
- `U.reset(q)`

Returns the raw pointer U is managing (⚠ **Dangerous!**)

U stops managing its raw pointer and returns the raw pointer

U cleans up its raw pointer and takes ownership of q

`std::shared_ptr S;`

- `make_shared<T>(args)`
- `S.use_count()`
- `S.unique()`

Returns a `shared_ptr` pointer of a heap-allocated object

`shared_ptr<int> p3 = make_shared<int>(42);`

Returns the reference count

Returns true iff `S.use_count() == 1`

`std::weak_ptr W;`

- `W.lock()`
- `W.use_count()`
- `W.expired()`


Constructs a shared pointer based off of W and returns it

Returns the reference count

Returns true iff W is expired (`W.use_count() == 0`)

Questions?





Poll Question ([PollEv.com/cs374](https://pollev.com/cs374))

Which of the following statements about `shared_ptr` and `weak_ptr` in C++ are correct?

- A. Both `shared_ptr` and `weak_ptr` share ownership of the managed object.
- B. `shared_ptr`s allow multiple `weak_ptr` instances to interact with the same managed object.
- C. `shared_ptr` does not provide a way to check whether the managed object still exists.
- D. `shared_ptr` and `weak_ptr` are interchangeable and can be used interchangeably in all situations.

W Which of the following statements about `shared_ptr` and `weak_ptr` in C++ is correct?

0

Both `shared_ptr` and `weak_ptr` share ownership of the managed object.

0%

`shared_ptr` allows multiple `weak_ptr` instances to interact with the same managed object.

0%

`shared_ptr` does not provide a way to check whether the managed object still exists.

0%

`shared_ptr` and `weak_ptr` are interchangeable and can be used interchangeably in all situations.

0%



Caution

Smart pointers are smart... ? 🤖

“Smart” Pointers

Smart pointers still don't know everything, you must be careful with what pointers you give it to manage.

- Smart pointers can't tell if a pointer is on the heap or not.
- Still uses `delete` on default.
- Smart pointers can't tell if you are re-using a raw pointer.
- Don't point smart pointers at the stack.

Using a non-heap pointer

```
#include <cstdlib>
#include <memory>

using std::shared_ptr;
using std::weak_ptr;

int main(int argc, char **argv) {
    int x = 374;
    shared_ptr<int> p1(&x);
    return EXIT_SUCCESS;
}
```

Smart pointers can't tell if the pointer you gave points to the heap!

- Will still call delete on the pointer when destructed.

Re-using a raw pointer

```
#include <cstdlib>
#include <memory>

using std::unique_ptr;


int main(int argc, char **argv) {
    int* x = new int(374);

    unique_ptr<int> p1(x);

    unique_ptr<int> p2(x);

    return EXIT_SUCCESS;
}
```

Smart pointers can't tell if you are re-using a raw pointer.



Re-using a raw pointer

```
#include <cstdlib>
#include <memory>

using std::shared_ptr;


int main(int argc, char **argv) {
    int* x = new int(374);

    shared_ptr<int> p1(x);

    shared_ptr<int> p2(x);

    return EXIT_SUCCESS;
}
```

Smart pointers can't tell if you are re-using a raw pointer.



Automatic memory management

Different paradigms

	Tracing (mark & sweep)	Reference counting
Method	Mark all variables reachable from root objects, then sweep remaining ones	Automatically frees memory when <code>ref_count == 0</code>
Language	Java	C++ w/ Smart Pointers
Perf cost	Running the garbage collector can pause the entire program	Added overhead to every allocation/deallocation and assignment
Possible issues	Dangling references, GC behavior might be unpredictable	Cycles, overhead

Ex20 due Wednesday, HW8 due Sunday!

Ex20 is due before the beginning of the next lecture

- Link available on the website:

<https://courses.cs.washington.edu/courses/cse374/24wi/exercises/>

HW8 due Sunday 11.59pm!

- Expr class with smart pointers & inheritance
- Instructions on course website:

<https://courses.cs.washington.edu/courses/cse374/24wi/homeworks/hw8/>