

How to Start MySQL Server

Download latest version of XAMPP From <https://www.apachefriends.org/download.html>

Install XAMPP and open XAMPP Control Panel

From Control panel you need to start two services apache, mysql

Now open browser and enter URL <http://localhost/phpmyadmin/> or press admin button from XAMPP control panel.

Now you are connected with MySQL server home page

MySQL Tutorial

MySQL is a widely used relational database management system (RDBMS).

MySQL is free and open-source.

MySQL is ideal for both small and large applications.

Introduction to MySQL

MySQL is a very popular open-source relational database management system (RDBMS).

What is MySQL?

- MySQL is a relational database management system
- MySQL is open-source
- MySQL is free
- MySQL is ideal for both small and large applications
- MySQL is very fast, reliable, scalable, and easy to use
- MySQL is cross-platform
- MySQL is compliant with the ANSI SQL standard
- MySQL was first released in 1995
- MySQL is developed, distributed, and supported by **Oracle Corporation**
- MySQL is named after co-founder Monty Widenius's daughter: My

Who Uses MySQL?

- Huge websites like Facebook, Twitter, Airbnb, Booking.com, Uber, GitHub, YouTube, etc.
- Content Management Systems like WordPress, Drupal, Joomla!, Contao, etc.
- A very large number of web developers around the world

Show Data On Your Web Site

To build a web site that shows data from a database, you will need:

- An RDBMS database program (like MySQL)
- A server-side scripting language, like PHP
- To use SQL to get the data you want
- To use HTML / CSS to style the page

What is RDBMS?

RDBMS stands for Relational Database Management System.

RDBMS is a program used to maintain a relational database.

RDBMS is the basis for all modern database systems such as MySQL, Microsoft SQL Server, Oracle, and Microsoft Access.

RDBMS uses [SQL queries](#) to access the data in the database.

What is a Database Table?

A table is a collection of related data entries, and it consists of columns and rows.

A column holds specific information about every record in the table.

A record (or row) is each individual entry that exists in a table.

Look at a selection from the Northwind "Customers" table:

CustomerID	CustomerName	ContactName	Address	City	PostalCode	Country
1	Alfreds Futterkiste	Maria Anders	Obere Str. 57	Berlin	12209	Germany
2	Ana Trujillo Emparedados y helados	Ana Trujillo	Avda. de la Constitución 2222	México D.F.	05021	Mexico
3	Antonio Moreno Taquería	Antonio Moreno	Mataderos 2312	México D.F.	05023	Mexico
4	Around the Horn	Thomas Hardy	120 Hanover Sq.	London	WA1 1DP	UK

The columns in the "Customers" table above are: CustomerID, CustomerName, ContactName, Address, City, PostalCode and Country. The table has 4 records (rows).

What is a Relational Database?

A relational database defines database relationships in the form of tables. The tables are related to each other - based on data common to each.

Look at the following three tables "Customers", "Orders", and "Shippers" from the Northwind database:

Customers Table

CustomerID	CustomerName	ContactName	Address	City	PostalCode	Country
1	Alfreds Futterkiste	Maria Anders	Obere Str. 57	Berlin	12209	Germany
2	Ana Trujillo Emparedados y helados	Ana Trujillo	Avda. de la Constitución 2222	México D.F.	05021	Mexico
3	Antonio Moreno Taquería	Antonio Moreno	Mataderos 2312	México D.F.	05023	Mexico
4	Around the Horn	Thomas Hardy	120 Hanover Sq.	London	WA1 1DP	UK
5	Berglunds snabbköp	Christina Berglund	Berguvsvägen 8	Luleå	S-958 22	Sweden

The relationship between the "Customers" table and the "Orders" table is the CustomerID column:

Orders Table

OrderID	CustomerID	EmployeeID	OrderDate	ShipperID
10278	5	8	1996-08-12	2
10280	5	2	1996-08-14	1
10308	2	7	1996-09-18	3
10355	4	6	1996-11-15	1
10365	3	3	1996-11-27	2
10383	4	8	1996-12-16	3
10384	5	3	1996-12-16	3

The relationship between the "Orders" table and the "Shippers" table is the ShipperID column:

Shippers Table

ShipperID	ShipperName	Phone
1	Speedy Express	(503) 555-9831
2	United Package	(503) 555-3199
3	Federal Shipping	(503) 555-9931

MySQL SQL

What is SQL (Structured Query Language)?

SQL is the standard language for dealing with Relational Databases.

SQL is used to insert, search, update, and delete database records.

How to Use SQL

The following SQL statement selects all the records in the "Customers" table:

```
SELECT * FROM Customers;
```

Keep in Mind That...

- SQL keywords are NOT case sensitive: `select` is the same as `SELECT`

In this tutorial we will write all SQL keywords in upper-case.

Semicolon after SQL Statements?

Some database systems require a semicolon at the end of each SQL statement.

Semicolon is the standard way to separate each SQL statement in database systems that allow more than one SQL statement to be executed in the same call to the server.

In this tutorial, we will use semicolon at the end of each SQL statement.

Some of The Most Important SQL Commands

- `SELECT` - extracts data from a database
- `UPDATE` - updates data in a database
- `DELETE` - deletes data from a database
- `INSERT INTO` - inserts new data into a database
- `CREATE DATABASE` - creates a new database
- `ALTER DATABASE` - modifies a database
- `CREATE TABLE` - creates a new table
- `ALTER TABLE` - modifies a table
- `DROP TABLE` - deletes a table
- `CREATE INDEX` - creates an index (search key)
- `DROP INDEX` - deletes an index

Create Database and Table as like following

Server: 127.0.0.1 » Database: 9211_2324 » Table: students										
Browse Structure SQL Search Insert Export Import Privileges Operations Tracking Triggers										
Table structure Relation view										
#	Name	Type	Collation	Attributes	Null	Default	Comments	Extra	Action	
<input type="checkbox"/>	1 roll	int(11)			No	None		AUTO_INCREMENT		
<input type="checkbox"/>	2 fname	varchar(20)	utf8mb4_general_ci		No	None				
<input type="checkbox"/>	3 lname	varchar(20)	utf8mb4_general_ci		No	None				
<input type="checkbox"/>	4 city	varchar(20)	utf8mb4_general_ci		No	None				
<input type="checkbox"/>	5 email	varchar(128)	utf8mb4_general_ci		No	None				
<input type="checkbox"/>	6 phone	varchar(15)	utf8mb4_general_ci		No	None				
<input type="checkbox"/>	7 gender	varchar(10)	utf8mb4_general_ci		No	None				
<input type="checkbox"/>	8 dateofbirth	date			No	None				
<input type="checkbox"/>	9 admissiondata	timestamp			No	current_timestamp()				

And add some data as following

Server: 127.0.0.1 » Database: 9211_2324 » Table: students

Browse

Structure

SQL

Search

Insert

Export

Import

Privileges

Operations

Tracking

roll

fname

lname

city

email

phone

gender

dateofbirth

admissiondata

Edit

Copy

Delete

1

hetvi

Maheswari

Morbi

hetvi@gmail.com

8787678678

female

2004-02-14

2024-02-14 10:03:04

Edit

Copy

Delete

2

kenil

sangani

Rajkot

kenil@gmail.com

2457834578

male

2004-02-13

2024-02-14 10:04:10

Edit

Copy

Delete

3

ridham

vishnuswami

Ahamdabad

ridham@gmail.com

989898989

male

2005-02-12

2024-02-14 10:04:10

Edit

Copy

Delete

4

bhalabhai

bavaliya

Rajkot

bhalabhai@gmail.com

2457834578

male

2004-02-13

2024-02-14 10:04:51

Edit

Copy

Delete

5

sumit

talsaniya

Ahamdabad

sumit@gmail.com

989898989

male

2005-02-12

2024-02-14 10:04:51

Edit

Copy

Delete

6

het

dadhaniya

Rajkot

het@gmail.com

2457834578

male

2004-02-13

2024-02-14 10:05:28

Edit

Copy

Delete

7

deepak

vavdiya

Ahamdabad

deepak@gmail.com

989898989

male

2005-02-12

2024-02-14 10:05:28

Edit

Copy

Delete

8

dhrumil

nathani

Rajkot

dhrumin@gmail.com

2457834578

male

2004-02-13

2024-02-14 10:06:01

Edit

Copy

Delete

9

sujal

khachariya

Ahamdabad

sujal@gmail.com

989898989

male

2005-02-12

2024-02-14 10:06:01

Edit

Copy

Delete

10

riya

barad

Rajkot

riya@gmail.com

2457834578

female

2004-02-13

2024-02-14 10:06:40

Edit

Copy

Delete

11

khushi

thakar

Ahamdabad

khushi@gmail.com

989898989

female

2005-02-12

2024-02-14 10:06:40

Edit

Copy

Delete

12

hasti

vala

Rajkot

hasti@gmail.com

2457834578

female

2004-02-13

2024-02-14 10:07:22

Edit

Copy

Delete

13

priya

thakar

Ahamdabad

priya@gmail.com

989898989

female

2005-02-12

2024-02-14 10:07:22

MySQL SELECT Statement

The MySQL SELECT Statement

The `SELECT` statement is used to select data from a database.

The data returned is stored in a result table, called the result-set.

SELECT Syntax

`SELECT column1, column2, ... FROM table_name;`

Here, column1, column2, ... are the field names of the table you want to select data from. If you want to select all the fields available in the table, use the following syntax:

`SELECT * FROM table_name;`

`SELECT * from students;`

`SELECT roll, fname, lname, city from students`

The MySQL SELECT DISTINCT Statement

The `SELECT DISTINCT` statement is used to return only distinct (different) values.

Inside a table, a column often contains many duplicate values; and sometimes you only want to list the different (distinct) values.

SELECT DISTINCT Syntax

`SELECT DISTINCT column1, column2, ... FROM table_name;`

`SELECT city from students;`

`SELECT DISTINCT city from students;`

The following SQL statement counts and returns the number of different (distinct) city in the "Students" table:

`SELECT count(DISTINCT city) from students;`

MySQL WHERE Clause

The MySQL WHERE Clause

The `WHERE` clause is used to filter records.

It is used to extract only those records that fulfill a specified condition.

WHERE Syntax

`SELECT column1, column2, ...`

`FROM table_name`

`WHERE condition;`

Note: The *WHERE* clause is not only used in *SELECT* statements, it is also used in *UPDATE*, *DELETE*, etc.!

```
SELECT * FROM students WHERE roll = 1
```

```
SELECT * FROM students WHERE roll > 5;
```

```
SELECT * FROM students WHERE not roll > 5;
```

```
SELECT * FROM students WHERE city = 'rajkot';
```

```
SELECT * FROM students WHERE city <> 'rajkot';
```

```
SELECT * FROM students WHERE not city = 'rajkot';
```

```
SELECT * FROM students WHERE roll BETWEEN 1 and 5
```

MySQL AND, OR and NOT Operators

The MySQL AND, OR and NOT Operators

The `WHERE` clause can be combined with `AND`, `OR`, and `NOT` operators.

The `AND` and `OR` operators are used to filter records based on more than one condition:

- The `AND` operator displays a record if all the conditions separated by `AND` are `TRUE`.
- The `OR` operator displays a record if any of the conditions separated by `OR` is `TRUE`.

The `NOT` operator displays a record if the condition(s) is `NOT TRUE`.

AND Syntax

```
SELECT column1, column2, ... FROM table_name WHERE condition1 AND condition2 AND condition3 ...;
```

```
SELECT * from students WHERE roll = 1
```

```
SELECT * from students WHERE roll = 1 and city = 'Rajkot';
```

OR Syntax

```
SELECT column1, column2, ... FROM table_name WHERE condition1 OR condition2 OR condition3 ...;
```

```
SELECT * from students WHERE city = 'morbi' or city = 'Rajkot';
```

NOT Syntax

```
SELECT column1, column2, ... FROM table_name WHERE NOT condition;
```

```
SELECT * from students WHERE not city = 'morbi' ;
```

Combining AND, OR and NOT

You can also combine the `AND`, `OR` and `NOT` operators.

```
SELECT * from students WHERE roll = 1 and city = 'rajkot' or city = 'morbi'
```

```
SELECT * from students WHERE roll = 1 and (city = 'rajkot' or city = 'morbi')
```

MySQL ORDER BY Keyword

The MySQL ORDER BY Keyword

The `ORDER BY` keyword is used to sort the result-set in ascending or descending order.

The `ORDER BY` keyword sorts the records in ascending order by default. To sort the records in descending order, use the `DESC` keyword.

ORDER BY Syntax

```
SELECT column1, column2, .. FROM table_name ORDER BY column1, column2, ... ASC|DESC;
```

```
SELECT * from students;
```

```
SELECT * from students ORDER by fname;
```

ORDER BY DESC Example

The following SQL statement selects all customers from the "students" table, sorted DESCENDING by the "fname" column:

```
SELECT * from students ORDER by fname DESC;
```

ORDER BY Several Columns Example

```
SELECT * from students ORDER by fname, city;
```

```
SELECT * from students ORDER by fname asc, city DESC;
```

MySQL INSERT INTO Statement

The MySQL INSERT INTO Statement

The `INSERT INTO` statement is used to insert new records in a table.

INSERT INTO Syntax

It is possible to write the `INSERT INTO` statement in two ways:

1. Specify both the column names and the values to be inserted:

```
INSERT INTO table_name (column1, column2, column3, ...) VALUES (value1, value2, value3, ...);
```

2. If you are adding values for all the columns of the table, you do not need to specify the column names in the SQL query. However, make sure the order of the values is in the same order as the columns in the table. Here, the `INSERT INTO` syntax would be as follows:

```
INSERT INTO table_name VALUES (value1, value2, value3, ...);
```

```
INSERT into students (fname, lname, city, email, phone, gender, dateofbirth) VALUES ('Demo', 'text', 'example', 'demo@example.com', '9876543210', 'male', '2001-01-01')
```

Did you notice that we did not insert any number into the CustomerID field?

The CustomerID column is an [auto-increment](#) field and will be generated automatically when a new record is inserted into the table.

Insert Data Only in Specified Columns

It is also possible to only insert data in specific columns.

```
INSERT into students (fname, lname, city, email, phone) VALUES ('Demo', 'text', 'example', 'demo@example.com', '9876543210')
```

MySQL NULL Values

What is a NULL Value?

A field with a NULL value is a field with no value.

If a field in a table is optional, it is possible to insert a new record or update a record without adding a value to this field. Then, the field will be saved with a NULL value.

Note: A NULL value is different from a zero value or a field that contains spaces. A field with a NULL value is one that has been left blank during record creation!

```
INSERT into students (fname, lname, city, email, phone) VALUES ('Demo', 'text', 'example', 'demo@example.com', '9876543210')
```

```
SELECT * FROM `students` WHERE gender = '';
```

```
SELECT * FROM `students` WHERE gender = 'NULL';
```

```
SELECT * FROM `students` WHERE gender is null;
```

How to Test for NULL Values?

It is not possible to test for NULL values with comparison operators, such as =, <, or <>.

We will have to use the `IS NULL` and `IS NOT NULL` operators instead.

IS NULL Syntax

```
SELECT column_names FROM table_name WHERE column_name IS NULL;
```

```
SELECT * FROM `students` WHERE gender is null;
```

IS NOT NULL Syntax

```
SELECT column_names FROM table_name WHERE column_name IS NOT NULL;
```

```
SELECT * FROM `students` WHERE gender is not null;
```

MySQL UPDATE Statement

The MySQL UPDATE Statement

The `UPDATE` statement is used to modify the existing records in a table.

UPDATE Syntax

`UPDATE table_name SET column1 = value1, column2 = value2, ...`

Note: Be careful when updating records in a table! Notice the `WHERE` clause in the `UPDATE` statement. The `WHERE` clause specifies which record(s) that should be updated. If you omit the `WHERE` clause, all records in the table will be updated!`WHERE condition;`

```
UPDATE students set gender = 'male' WHERE roll = 15 or roll = 16
```

```
UPDATE students set city = 'rajkot'
```

```
UPDATE students set city = 'surat' WHERE roll > 10
```

```
UPDATE students set city = 'ahamdabad' WHERE roll > 5 and roll < 10;
```

UPDATE Multiple Records

It is the `WHERE` clause that determines how many records will be updated.

```
UPDATE students set gender = 'female', dateofbirth = '2001-01-15' WHERE roll >= 15
```

Update Warning!

Be careful when updating records. If you omit the `WHERE` clause, ALL records will be updated!

MySQL LIMIT Clause

The MySQL LIMIT Clause

The `LIMIT` clause is used to specify the number of records to return.

The `LIMIT` clause is useful on large tables with thousands of records. Returning a large number of records can impact performance.

LIMIT Syntax

`SELECT column_name(s) FROM table_name WHERE condition LIMIT number;`

```
SELECT * FROM `students`
```

```
SELECT * FROM `students` limit 5;
```

What if we want to select records 6-10 (inclusive)?

MySQL provides a way to handle this: by using `OFFSET`.

The SQL query below says "return only 5 records, start on record 6 (`OFFSET 5`)":

```
SELECT * FROM `students` limit 5 OFFSET 5;
```

```
SELECT * FROM `students` limit 5 OFFSET 10;
```

```
SELECT * FROM students WHERE city = 'rajkot' LIMIT 10 ;
```

```
SELECT * from students LIMIT 5 OFFSET 10
```

```
SELECT * from students LIMIT 10, 5; -- offset 10 limit 5
```

MySQL MIN() and MAX() Functions

MySQL MIN() and MAX() Functions

The `MIN()` function returns the smallest value of the selected column.

The `MAX()` function returns the largest value of the selected column.

MIN() Syntax

```
SELECT MIN(column_name)  
FROM table_name  
WHERE condition;
```

MAX() Syntax

```
SELECT MAX(column_name)  
FROM table_name  
WHERE condition;
```

```
SELECT max(dateofbirth) FROM students
```

```
SELECT min(dateofbirth) FROM students;
```

```
SELECT min(roll) FROM students;
```

```
SELECT max(roll) FROM students;
```

MySQL COUNT(), AVG() and SUM() Functions

MySQL COUNT(), AVG() and SUM() Functions

The `COUNT()` function returns the number of rows that matches a specified criterion.

`COUNT()` Syntax

```
SELECT COUNT(column_name)  
FROM table_name  
WHERE condition;
```

The `AVG()` function returns the average value of a numeric column.

`AVG()` Syntax

```
SELECT AVG(column_name)  
FROM table_name  
WHERE condition;
```

The `SUM()` function returns the total sum of a numeric column.

`SUM()` Syntax

```
SELECT SUM(column_name)  
FROM table_name  
WHERE condition;
```

```
SELECT COUNT(roll) from students
```

```
SELECT COUNT(roll) from students WHERE city = 'rajkot';
```

```
SELECT COUNT(roll) from students WHERE not city = 'rajkot';
```

```
SELECT sum(roll) from students
```

```
SELECT avg(roll) from students
```

```
SELECT sum(roll), avg(roll) from students;
```

MySQL DELETE Statement

The MySQL DELETE Statement

The `DELETE` statement is used to delete existing records in a table.

DELETE Syntax

`DELETE FROM table_name WHERE condition;`

Note: Be careful when deleting records in a table! Notice the `WHERE` clause in the `DELETE` statement. The `WHERE` clause specifies which record(s) should be deleted. If you omit the `WHERE` clause, all records in the table will be deleted!

Backup all the data of students table to studentsBackup table

```
create table studentsBackup as SELECT * FROM students
```

SQL DELETE Example

```
DELETE from students WHERE ROLL = 1
```

```
DELETE from students WHERE city = 'rajkot'
```

Delete All Records

It is possible to delete all rows in a table without deleting the table. This means that the table structure, attributes, and indexes will be intact:

```
DELETE FROM table_name;
```

```
DELETE from students
```

```
// restore
```

```
INSERT into students SELECT * from studentsbackup
```

```
// when you delete all the data from table the auto increment is not reset to zero
```

```
INSERT INTO `students` (`roll`, `fname`, `lname`, `city`, `email`, `phone`, `gender`, `dateofbirth`,  
`admissiondata`) VALUES (NULL, 'brijesh', 'sinojiya', 'Morbi', 'demo@gmail.com', '998899889900',  
'male', '2004-02-13', current_timestamp());
```

A new record get a roll number as you leave before delete all the data

Use truncate table to delete all the data from table and also reset all auto increments

```
TRUNCATE TABLE students
```

```
INSERT INTO `students` (`roll`, `fname`, `lname`, `city`, `email`, `phone`, `gender`, `dateofbirth`,  
`admissiondata`) VALUES (NULL, 'brijesh', 'sinojiya', 'Morbi', 'demo@gmail.com', '998899889900',  
'male', '2004-02-13', current_timestamp());
```

Tuncate table students

Insert into students select * from studentsbackup

DROP TABLE studentsbackup

MySQL LIKE Operator

The MySQL LIKE Operator

The `LIKE` operator is used in a `WHERE` clause to search for a specified pattern in a column.

There are two wildcards often used in conjunction with the `LIKE` operator:

- The percent sign (%) represents zero, one, or multiple characters
- The underscore sign (_) represents one, single character

The percent sign and the underscore can also be used in combinations!

LIKE Syntax

```
SELECT column1, column2, ... FROM table_name WHERE columnN LIKE pattern;
```

Tip: You can also combine any number of conditions using `AND` or `OR` operators.

```
SELECT * from students WHERE fname like 'a%'
```

```
SELECT * from students WHERE fname like 'a%'
```

```
SELECT * from students WHERE fname like '%a%';
```

```
SELECT * from students WHERE fname like '_a%';
```

```
SELECT * from students WHERE fname like '__a%';
```

```
SELECT * from students WHERE fname like '____';
```

Here are some examples showing different `LIKE` operators with '%' and '_' wildcards:

LIKE Operator	Description
WHERE CustomerName LIKE 'a%'	Finds any values that start with "a"
WHERE CustomerName LIKE '%a'	Finds any values that end with "a"
WHERE CustomerName LIKE '%or%'	Finds any values that have "or" in any position
WHERE CustomerName LIKE '_r%'	Finds any values that have "r" in the second position
WHERE CustomerName LIKE 'a_%'	Finds any values that start with "a" and are at least 2 characters in length
WHERE CustomerName LIKE 'a__%'	Finds any values that start with "a" and are at least 3 characters in length
WHERE ContactName LIKE 'a%o'	Finds any values that start with "a" and ends with "o"

MySQL Wildcards

MySQL Wildcard Characters

A wildcard character is used to substitute one or more characters in a string.

Wildcard characters are used with the [LIKE](#) operator. The `LIKE` operator is used in a `WHERE` clause to search for a specified pattern in a column.

Wildcard Characters in MySQL

Symbol	Description	Example
%	Represents zero or more characters	bl% finds bl, black, blue, and blob
_	Represents a single character	h_t finds hot, hat, and hit

The wildcards can also be used in combinations!

Here are some examples showing different `LIKE` operators with '%' and '_' wildcards:

LIKE Operator	Description
WHERE CustomerName LIKE 'a%'	Finds any values that starts with "a"
WHERE CustomerName LIKE '%a'	Finds any values that ends with "a"
WHERE CustomerName LIKE '%or%'	Finds any values that have "or" in any position
WHERE CustomerName LIKE '_r%'	Finds any values that have "r" in the second position
WHERE CustomerName LIKE 'a_%_%'	Finds any values that starts with "a" and are at least 3 characters in length
WHERE ContactName LIKE 'a%o'	Finds any values that starts with "a" and ends with "o"

MySQL IN Operator

The MySQL IN Operator

The `IN` operator allows you to specify multiple values in a `WHERE` clause.

The `IN` operator is a shorthand for multiple `OR` conditions.

IN Syntax

```
SELECT column_name(s) FROM table_name WHERE column_name IN (value1, value2, ...);
```

or:

```
SELECT column_name(s) FROM table_name WHERE column_name IN (SELECT  
STATEMENT);
```

```
SELECT * from students WHERE city = 'rajkot' or city = 'surat' or city = 'baroda'
```

```
SELECT * from students WHERE city in ('rajkot', 'baroda', 'surat')
```

```
SELECT * from students WHERE city not in ('rajkot', 'baroda', 'surat');
```


MySQL BETWEEN Operator

The MySQL BETWEEN Operator

The `BETWEEN` operator selects values within a given range. The values can be numbers, text, or dates.

The `BETWEEN` operator is inclusive: begin and end values are included.

BETWEEN Syntax

```
SELECT column_name(s) FROM table_name WHERE column_name BETWEEN value1 AND value2;
```

```
SELECT * from students WHERE roll BETWEEN 1 and 5
```

```
SELECT * from students WHERE roll not BETWEEN 1 and 5;
```

```
SELECT * from students WHERE fname BETWEEN 'bhalabhai' and 'riya';
```

```
SELECT * from students WHERE fname not BETWEEN 'bhalabhai' and 'riya';
```

```
SELECT * FROM `students` WHERE dateofbirth BETWEEN '2001-01-01' and '2004-12-31'
```

```
SELECT * FROM `students` WHERE dateofbirth not BETWEEN '2001-01-01' and '2004-12-31';
```

MySQL Aliases

MySQL Aliases

Aliases are used to give a table, or a column in a table, a temporary name.

Aliases are often used to make column names more readable.

An alias only exists for the duration of that query.

An alias is created with the `AS` keyword.

Alias Column Syntax

```
SELECT column_name AS alias_name FROM table_name;
```

Alias Table Syntax

```
SELECT column_name(s) FROM table_name AS alias_name;
```

```
SELECT roll, fname, lname, email, city, phone, dateofbirth from students
```

```
SELECT roll as "Roll Number", fname as "First Name", lname as "Last Name", email as "Email Address", city as HomeTown, phone as 'Phone Number', dateofbirth from students;
```

```
SELECT roll "Roll Number", fname "First Name", lname "Last Name", email "Email Address", city HomeTown, phone 'Phone Number', dateofbirth from students;
```

```
SELECT concat_ws("_", roll, fname, lname, email, city, phone, gender, dateofbirth) as "Student Information" from students
```

```
SELECT concat_ws(" * ", roll, fname, lname, email, city, phone, gender, dateofbirth) as "Student Information" from students;
```

The following SQL statement is the same as above, but without aliases:

```
SELECT students.roll, students.fname, students.lname, students.city, students.email, students.phone, students.gender, students.dateofbirth, students.admissiondata, marks.total, marks.result FROM students, marks WHERE students.roll = 1 and students.roll = marks.roll
```

The following SQL statement is the same as above, but with aliases:

```
SELECT s.roll, s.fname, s.lname, s.city, s.email, s.phone, s.gender, s.dateofbirth, s.admissiondata, m.total, m.result FROM students as s, marks as m WHERE s.roll = 1 and s.roll = m.roll;
```

```
SELECT s.roll, s.fname, s.lname, s.city, s.email, s.phone, s.gender, s.dateofbirth, s.admissiondata, m.total, m.result FROM students s, marks m WHERE s.roll = 1 and s.roll = m.roll;
```

Aliases can be useful when:

- There are more than one table involved in a query
- Functions are used in the query
- Column names are big or not very readable
- Two or more columns are combined together

```
SELECT s.roll, s.fname, s.lname, s.city, s.email, s.phone, s.gender, s.dateofbirth, s.admissiondata,  
a.absents, a.presents FROM students s, attendance a WHERE s.roll = 1 and s.roll = a.roll;
```

```
SELECT s.roll, s.fname, s.lname, s.city, s.email, s.phone, s.gender, s.dateofbirth, s.admissiondata,  
a.absents, a.presents, (a.absents+a.presents) FROM students s, attendance a WHERE s.roll = 1 and  
s.roll = a.roll;
```

```
SELECT s.roll, s.fname, s.lname, s.city, s.email, s.phone, s.gender, s.dateofbirth, s.admissiondata,  
a.absents, a.presents, (a.absents+a.presents) "Total Days" FROM students s, attendance a WHERE  
s.roll = 1 and s.roll = a.roll;
```