

Problem A. Network Saboteur

Author: Far-Eastern Subregional

Input file: input.txt

Output file: output.txt

Time limit: 3 sec

Memory limit: 8 Mb

Statement

A university network is composed of N computers. System administrators gathered information on the traffic between nodes, and carefully divided the network into two subnetworks in order to minimize traffic between parts.

A disgruntled computer science student Vasya, after being expelled from the university, decided to have his revenge. He hacked into the university network and decided to reassign computers to *maximize* the traffic between two subnetworks.

Unfortunately, he found that calculating such worst subdivision is one of those problems he, being a student, failed to solve. So he asks you, a more successful CS student, to help him.

The traffic data are given in the form of matrix C , where C_{ij} is the amount of data sent between i th and j th nodes ($C_{ij} = C_{ji}$, $C_{ii} = 0$). The goal is to divide the network nodes into the two disjointed subsets A and B so as to maximize the sum of all C_{ij} , where i belongs to A , and j belongs to B .

Input file format

The first line of input file contains a number of nodes N . The following N lines, containing N space-separated integers each, represent the traffic matrix C .

Output file format

Output file must contain a single integer - the maximum traffic between the subnetworks.

Constraints

$2 \leq N \leq 20$; $0 \leq C_{ij} \leq 10000$.

Sample tests

No.	Input file (input.txt)	Output file (output.txt)
1	3 0 50 30 50 0 40 30 40 0	90