Ex 13. Implementation of ping program using sockets

Aim: To write a java program to ping a host name or IP address using the inet address class and check whether the host.

Procedure:

1. Open a java IDE terminal and create a file named myping.java
2. Import Inet address and scanner classes
3. Get the hostname or ip address from the user
4. Use Inet address get By name() to obtain the Ip address
5. Calculate and display the response time in milliseconds
6. Repeat the ping a time with a second delay between each attempt
7. Display reply from if the host is readable otherwise display request time out
9. Compile and execute the program

Result:

The java program was successfully executed to ping given hostname/ ip address. It displays whether the host is reachable and shows the response time

Program:

```
import java.net.InetAddress;
import java.util.Scanner;
public class myping {
    public static void main(String[] args) {
    Scanner sc = new Scanner(System.in);
    String host = sc.nextLine();
    try {
        InetAddress address = InetAddress.getByName(host);
        System.out.println("Pinging " + host + "...");
        long startTime = System.currentTimeMillis();
        long endTime = System.currentTimeMillis();
        if (reachable) {
            System.out.println("Reply from " + address.getHost
            System.out.println("Host is reachable."); }
        else {
            System.out.println("Request time out.");
            System.out.println("Host is not reachable.");
        }
    } catch (Exception e) {
            System.out.println("Error: " + e.getMessage
    }
    sc.close();
} }
```