

Docker Volumes Features


VISHWANATH M S

VISHWACLOUDLAB.COM

Docker Storage mount points

- Volumes
- Bind mounts
- tmpfs mounts

Docker Storage mount points



Docker Storage -- Volumes

- Volumes are easier to back up or migrate than bind mounts.
- You can manage volumes using Docker CLI commands or the Docker API.
- Volumes work on both Linux and Windows containers.
- Volumes can be more safely shared among multiple containers.
- Volume drivers let you store volumes on remote hosts or cloud providers, to encrypt the contents of volumes, or to add other functionality.
- New volumes can have their content pre-populated by a container.

Docker Storage - Volumes - Command

- Syntax → “-v”
- Create volume: \$ ***docker volume create*** my-vol
- List Volumes: → \$ **docker volume ls**
- Remove Volumes: → \$ **docker volume rm** my-vol

Docker Storage - Volumes - Command

- Start a container with a volume
- `$ docker run -d --name devtest -v my-vol:/app tomcat:latest`
- Use a read-only volume
- `$ docker run -d --name devtest -v my-vol:/app:ro tomcat:latest`

Docker Storage - Bind mounts

- Bind mounts have limited functionality compared to Volumes.
- The file or directory is referenced by its full or relative path on the host machine.
- The file or directory does not need to exist on the Docker host already.
- You can't use Docker CLI commands to directly manage bind mounts.

Docker Storage - bind mounts - Command

- Start a container with a bind mounts
- `$ docker run -d --name devtest -v "$(pwd)"/target:/app tomcat:latest`
- Use a read-only bind mounts
- `$ docker run -d --name devtest -v "$(pwd)"/target:/app:ro tomcat:latest`

Docker Storage - tmpfs mounts

- The container can create files outside the container's writable layer.
- ***tmpfs*** mount is temporary and only persisted in the host memory.
- When the container stops, the ***tmpfs*** mount is removed, and files written there **won't** be persisted.

