- Compute Match — Backend API Reference (Summary)
  - Public
  - Customers APIs
  - Providers APIs (NCP and admin)
  - Access Request APIs (only when NPN integration is enabled, otherwise 404)
  - Inventory APIs (reference data)
  - Users APIs
  - Operations APIs (role `operations`)
  - Feedback APIs
  - System APIs (Temporal worker service account)
  - Internal APIs (hidden from schema)
  - Cross-cutting behaviour

Compute Match — Backend API Reference (Summary)

Interactive documentation runs at `http://localhost:8082/docs` locally. A snapshot is in `backend/openapi.json` (it omits Access Request and internal routes). Routers are in `backend/infrastructure/driving/http/routers/` and are mounted in `main.py`. All business APIs are under `/api/v1` (one v2 endpoint).

Public

Method	Path	Purpose
GET	`/health`	Liveness check, no auth

Customers APIs

Method	Path	Purpose	Scope
POST	`/api/v1/reservation-request`	Create a reservation or custom request	`create_reservation_request`
GET	`/api/v1/customer/reservation-requests`	List my requests	`requester_view_reservation_request`
GET	`/api/v1/customer/reservation-request/{id}`	Request detail	same
POST	`/api/v1/reservation-request/{id}/cancel`	Cancel	`requester_manage_reservation_request`

Method	Path	Purpose	Scope
POST	`/api/v1/reservation-request/{id}/offering/{oid}/extend-acceptance-expiry`	Extend acceptance window	`accept_contract_extension`
POST	`/api/v1/reservation-request/{id}/offering/{oid}/extend-contract-expiry`	Extend contract window	`accept_contract_extension`
GET	`/api/v1/gpu-offerings`	Browse offerings	`view_capacity`
GET	`/api/v1/gpu-offerings/availability`	Availability	`view_capacity`
GET	`/api/v1/gpu-offerings/capacity-overview`	Capacity overview	`view_capacity`
GET	`/api/v2/gpu-offerings/availability-by-filters`	Filtered availability	`view_capacity`
GET	`/api/v1/organizations/suggest`	Organization name suggestions	authenticated

Providers APIs (NCP and admin)

Method	Path	Purpose	Scope
GET	`/api/v1/provider/reservation-requests`	List requests for my NCP (all for admins)	`approver_view_reservation_request`
GET	`/api/v1/provider/reservation-request/{id}`	Detail	same
POST	`/api/v1/provider/offering/{id}/accept`	Accept offering	`approver_manage_reservation_request`
POST	`/api/v1/provider/offering/{id}/reject`	Reject (remarks required)	same
POST	`/api/v1/provider/offering/{id}/contract`	Confirm contract	same
POST	`/api/v1/provider/offering/{id}/resend-magic-link`	Resend magic link	provider/admin
GET	`/api/v1/provider/custom-demand-requests`	List custom requests	`approver_view_custom_reservation_request`
(status update)	custom demand transition endpoints	In Review / Matched / Unserviceable	`approver_manage_custom_reservation_request`

Method	Path	Purpose	Scope
GET	`/api/v1/provider/gpu-offerings`	My inventory	`view_provider_inventory`
POST	`/api/v1/provider/gpu-offerings/import`	Upload capacity CSV (202)	`manage_inventory`
GET	`/api/v1/provider/gpu-offerings/import/history`	Upload history	`manage_inventory` / admin
POST	`/api/v1/provider/gpu-offerings/import/{id}/approve`	Accept future capacity	`review_capacity`
POST	`/api/v1/provider/gpu-offerings/import/{id}/reject`	Reject future capacity	`review_capacity`
POST	`/api/v1/provider/onboard-providers`	Bulk onboard NCPs (CSV)	`manage_ncp`
GET	`/api/v1/provider/global-capacity-map`	Global capacity	`global_capacity_view`

Access Request APIs (only when NPN integration is enabled, otherwise 404)

Method	Path	Scope
GET	`/api/v1/provider/access-requests`	`manage_ncp`
GET	`/api/v1/provider/access-requests/{id}`	`manage_ncp`
POST	`/api/v1/provider/access-requests/{id}/approve`	`manage_ncp`
POST	`/api/v1/provider/access-requests/{id}/reject`	`manage_ncp`

Inventory APIs (reference data)

Countries, geographical regions, GPU models, hosting providers, interconnect types, regions — read with `view_capacity`; create geographical region or GPU model with `manage_inventory`.

Users APIs

Method	Path	Purpose
POST	`/api/v1/user`	Provision the signed-in user from JWT claims (organization, partner domain checks; may create an access request)
GET	`/api/v1/user`	Current user

Method	Path	Purpose
POST	`/api/v1/users/me/terms-acceptance`	Record Terms and Conditions acceptance
POST	`/api/v1/auth/logout`	Logout

Operations APIs (role `operations`)

Activate user, list users, resend activation magic link, delete user.

Feedback APIs

Submit feedback, check eligibility (`/api/v1/feedback/eligibility`), record prompt state (`/api/v1/feedback/prompt`). Feedback kinds: `POST_TASK` , `GENERAL` , `CANCELLATION` , `DROP_OFF` . Journeys: `capacity_upload` , `reservation_request` , `app_general` . Categories: `suggest_feature` , `report_problem` , `general` . Prompt states: `SHOWN` , `SUBMITTED` , `SKIPPED` , `DISMISSED` .

System APIs (Temporal worker service account)

Group	Scope
`/api/v1/notification/*` (all emails, reminders, magic links)	`notification:send`
`/api/v1/multi-provider/expire-acceptance` , `/expire-contract`	`notification:send`
`/api/v1/reservation-request/expire`	`reservation-request:write`
`/api/v1/offering/validate-nonce`	Keycloak extension
`/api/v1/system/csv-import/*` , `/api/v1/system/provider-onboarding/process`	`capacity:sync`

Internal APIs (hidden from schema)

- `POST /api/v1/internal/salesforce/offtake-sync` , `/notify-failure` , `/partner-domain-sync` — caller `client_id` must equal `SFDC_SYNC_CALLER_CLIENT_ID` .
- `POST /api/v1/internal/audit/keycloak-event` — Keycloak audit listener ingest.

Cross-cutting behaviour

- JWT validation against Keycloak; permissions from `scope` , `realm_access.roles` and `resource_access.*.roles` claims.
- Middleware blocks users who are PENDING or have not accepted terms (with an allowlist for the endpoints needed to finish setup).
- Request body limit 15 MB; CSV upload limit 10 MB.
- Redis-backed rate limiting per bucket.