

Stream API introduced in 👉 Java 8

Main package 👉 java.util.stream

📖 1 What is Stream API?

A **Stream** is a sequence of elements that supports functional-style operations to process data.

👉 It does **NOT** store data

👉 It processes data from collections (List, Set, Map, etc.)

Think like:

Collection (data) → Stream (processing pipeline) → Result

📖 2 Why Stream API?

Before Java 8:

```
List<Integer> list = Arrays.asList(10,20,30,40);
```

```
for(Integer i : list){  
    if(i % 2 == 0){  
        System.out.println(i);  
    }  
}
```

After Stream:

```
list.stream()  
    .filter(i -> i % 2 == 0)  
    .forEach(System.out::println);
```

- ✓ Less code
 - ✓ Readable
 - ✓ Functional style
 - ✓ Parallel processing support
-

📖 3 Stream Characteristics

- Does NOT modify original collection
 - Lazy evaluation
 - Can be used only once
 - Supports parallel processing
-

📖 4 How to Create Stream?

1 From Collection

```
list.stream();
```

2 From Array

```
Arrays.stream(array);
```

3 Using Stream.of()

```
Stream.of(1,2,3,4);
```

4 Infinite Stream

```
Stream.iterate(1, n -> n+1);  
Stream.generate(Math::random);
```

5 Stream Pipeline Structure

Every stream has 3 parts:

1. Source
2. Intermediate Operations
3. Terminal Operation

Example:

```
list.stream()      // Source  
  .filter(x -> x>10) // Intermediate  
  .sorted()        // Intermediate  
  .collect(Collectors.toList()); // Terminal
```

6 Intermediate Operations

These return Stream again.

◆ filter()

```
.filter(x -> x % 2 == 0)
```

Keeps only matching elements.

◆ map()

Transforms elements.

```
.map(x -> x * 2)
```

Example:

```
[1,2,3] → [2,4,6]
```

◆ flatMap()

Used for nested collections.

```
.flatMap(list -> list.stream())
```

Example:

```
[[1,2],[3,4]] → [1,2,3,4]
```

◆ sorted()

Default → ascending

```
.sorted()
```

Custom:

```
.sorted((a,b) -> b-a) // descending
```

◆ distinct()

Removes duplicates.

◆ limit() / skip()

```
.limit(3)
```

```
.skip(2)
```

■ 7 Terminal Operations

Ends stream.

◆ forEach()

```
.forEach(System.out::println);
```

◆ collect()

Most powerful.

```
.collect(Collectors.toList());
```

```
.collect(Collectors.toSet());
```

```
.collect(Collectors.toMap());
```

Collectors class → `java.util.stream.Collectors`

◆ **reduce()**

Used for aggregation.

```
.reduce(0, (a,b) -> a+b);
```

Example:

```
[1,2,3,4]
```

```
Step1: 0+1=1
```

```
Step2: 1+2=3
```

```
Step3: 3+3=6
```

```
Step4: 6+4=10
```

◆ **count()**

```
.count();
```

◆ **findFirst() / findAny()**

Returns Optional.

◆ **allMatch / anyMatch / noneMatch**

```
.allMatch(x -> x>0)
```

```
.anyMatch(x -> x<0)
```

```
.noneMatch(x -> x<0)
```

8 Comparator in Stream

Default sorting → natural order.

Custom:

```
.sorted((a,b) -> a.compareTo(b))
```

Descending:

```
.sorted(Comparator.reverseOrder())
```

9 Grouping & Partitioning

◆ **groupingBy()**

Returns Map

```
.collect(Collectors.groupingBy(x -> x));
```

Example:

```
["apple","apple","banana"]  
→ {apple=2, banana=1}
```

◆ partitioningBy()

Returns Map<Boolean, List>

```
.collect(Collectors.partitioningBy(x -> x%2==0));
```

10 Optional Class

Stream returns Optional sometimes.

Class → java.util.Optional

Used to avoid NullPointerException.

```
Optional<Integer> opt = list.stream().findFirst();  
opt.get();  
opt.orElse(0);
```

1 1 Parallel Stream

```
list.parallelStream()
```

Used for multi-core processing.

⚠ Not good for small data.

1 2 Difference: Collection vs Stream

Collection	Stream
------------	--------

Stores data	Processes data
-------------	----------------

Eager	Lazy
-------	------

Can reuse	One time use
-----------	--------------

1 3 Common Interview Questions

- ✓ Difference between map and flatMap
- ✓ Difference between reduce and collect
- ✓ Why stream is lazy?
- ✓ How parallel stream works?
- ✓ Why Optional used?

1 4 Internal Working (Concept)

Stream works like pipeline:

Data → filter → map → sorted → collect

Lazy evaluation:

Operations execute only when terminal operation runs.

1 5 Real-World Example (Employee)

```
employees.stream()
    .filter(e -> e.getSalary() > 50000)
    .sorted(Comparator.comparing(Employee::getSalary))
    .collect(Collectors.toList());
```

1 6 Performance Notes

- ✓ Avoid using stream in simple loops
 - ✓ Prefer parallel only for large data
 - ✓ Avoid modifying shared variables
-

1 7 Summary Cheat Sheet

Most Used:

filter
map
flatMap
sorted
distinct
limit
skip
collect
reduce
groupingBy
partitioningBy