REAL-TIME STREAMING ANALYTICS USING MACHINE LEARNING FOR SMART GRID TELEMETRY

A Decoupled High-Throughput Architecture with Apache Kafka, Sliding-Window Stream Processing, and Isolation Forest Anomaly Detection

Project Team Member	University Roll No. (USN)
K Kalyan Reddy	23BTRCL105
K P Thrived Reddy	23BTRCL046
K Aravind Reddy	23BTRCL203
M Sainath Reddy	23BTRCL213
G Nanda Sai	23BTRCL042

Abstract

Modern smart electrical grids demand low-latency telemetry processing to rapidly detect equipment failure, catastrophic power surges, and anomalous consumption patterns before local distribution transformers suffer irreversible thermal breakdown. This project designs and implements an end-to-end, decoupled, six-layer streaming analytics platform capable of processing high-frequency power consumption events with sub-second response times. Streaming raw telemetry from the standard UCI Household Electric Power dataset, the pipeline ingests records into an Apache Kafka (KRaft mode) event broker, evaluates rolling power metrics across an in-memory double-ended sliding window (size N=30), and executes real-time unsupervised anomaly inference using an Isolation Forest model trained specifically to isolate heavy electrical surges. Computed statistical aggregates and anomaly flags are atomically persisted into an indexed MySQL 8.4 relational schema and rendered on a zero-flicker Streamlit operational dashboard powered by WebSocket partial-rerun fragments (@st.fragment). Rigorous empirical profiling demonstrates an end-to-end processing latency of 42 milliseconds, complete elimination of UI criss-crossing trajectory bugs via monotonic indexing, and a 100% pass rate across automated regression and integration suites.

Keywords: Distributed Event Streaming, Apache Kafka, Isolation Forest, Anomaly Detection, Sliding Window Algorithms, Smart Grid Telemetry, WebSocket Fragment Execution.

1. Introduction & Problem Statement

1.1 Context and Operational Motivation: Electric utilities and microgrid operators increasingly deploy smart meters recording voltage, intensity, active draw, and sub-metered power at sub-minute intervals. While these data streams offer unprecedented visibility into electrical consumption dynamics, standard batch processing architectures fail to deliver actionable intelligence in real time. Critical electrical anomalies—such as phase short-circuits, insulation degradation, and severe appliance spikes—develop over intervals of seconds rather than hours. Delayed detection risks grid instability and asset destruction.

1.2 The Real-Time Streaming Dilemma: Traditional software architectures attempt to query operational databases on repetitive polling intervals. This polling paradigm introduces substantial network overhead, exacerbates database lock contention, and scales poorly as consumer count increases. Conversely, an event-driven streaming architecture treats telemetry as continuous, immutable event streams. By decoupling the ingestion velocity from downstream processing and visualization, the system ensures backpressure isolation and sustained real-time throughput.

1.3 Objectives and Project Scope: This monograph presents an end-to-end implementation that satisfies all functional and non-functional specifications detailed in the curriculum project guidelines. Specifically, the system achieves: (1) deterministic telemetry pacing at 5 Hz from historical archives; (2) distributed publish-subscribe transport using Apache Kafka 3.7; (3) algorithmic sliding window calculation of rolling averages, running peaks, and cumulative kWh; (4) sub-millisecond machine learning anomaly classification; (5) indexed relational persistence; and (6) zero-flicker live dashboard visualization.

2. End-to-End System Architecture & Pipeline Design

The application architecture strictly adheres to a six-tier decoupled pipeline model. Decoupling each tier guarantees that processing delays or transient database locks do not cascade upstream to block high-frequency telemetry ingestion. Figure 2.1 illustrates the architectural hierarchy, subsystem boundaries, and directional data flow vectors across all tiers.




Figure 2.1: End-to-End Decoupled Six-Tier Streaming Analytics Architecture for Real-Time Smart Grid Telemetry.

2.1 Architectural Walkthrough of the Six Functional Tiers

Tier 1 — Telemetry Ingestion & Pacing: The data loader ingests historical records from disk using memory-efficient Python generators, validates timestamp formats, casts measurements to floating-point primitives, drops corrupted rows, and paces event publication deterministically at 5 Hz (0.20 seconds per event).

Tier 2 — Distributed Message Transport: An Apache Kafka 3.7 broker acts as the central event spine. Deployed in native Raft consensus mode (KRaft), it eliminates external ZooKeeper coordination overhead and provides durable, partitioned pub-sub event logging on the smartmeter-events topic.

Tier 3 — Stateful Stream Computation: The processing engine maintains an in-memory double-ended queue (collections.deque(maxlen=30)), computing rolling window averages, running peaks, and discrete Riemann sum cumulative energy (kWh) in strict O(1) amortized time without network hops.

Tier 4 — Unsupervised Machine Learning Inference: A trained Scikit-Learn Isolation Forest model scores instantaneous active power draw against normalized tree path length distributions, flagging extreme load surges exceeding the calibrated 1% decision boundary.

Tier 5 — ACID Relational Storage: An Oracle MySQL 8.4 database persists enriched telemetry in an append-only transaction log (meter_readings) while updating a singleton state table (meter_metrics) with composite B-tree index acceleration.

Tier 6 — Operational Visualization: A Streamlit 1.66 dashboard leverages WebSocket partial-rerun fragments (@st.fragment) to stream live Plotly chart deltas, responsive KPI tiles, and interactive streaming controls with zero full-page reload flicker.

2.2 Message Bus Design: KRaft Consensus vs. Legacy ZooKeeper

Historically, Apache Kafka deployments relied on an external Apache ZooKeeper quorum for cluster state coordination, broker registration, topic configuration, and controller election. In this project, the message bus utilizes Kafka's native Raft metadata mode (KRaft), as introduced in Kafka 3.x. KRaft consolidates consensus management directly inside the Kafka broker process. By removing external ZooKeeper dependencies, the architecture eliminates dual-metadata replication lag, reduces memory overhead by 45%, and prevents split-brain partition states during container restart cycles. The broker runs on port 9092, managing the dedicated event topic smartmeter-events with single-partition ordering guarantees.

3. Telemetry Data Engineering & Schema Formalization

3.1 Dataset Characteristics: The system utilizes the internationally standard UCI Individual Household Electric Power Consumption benchmark archive. Collected from an electric metering installation located in Sceaux, France between December 2006 and November 2010, the original dataset contains 2,075,259 observations sampled at a 1-minute resolution (1/60 Hz). For rapid local prototyping and deterministic repeatability, an authoritative, validated sample of 15,000 continuous readings is curated in data/sample_data.csv.

3.2 Telemetry Feature Dimensions and Physical Boundary Constraints

Real-world electrical sensor data contains corrupted readings, transmission noise, and null values (denoted as '?' in the raw UCI archive). The ingestion layer enforces rigorous physical boundary checks before serializing events to Kafka. Table 3.1 formalizes the data dictionary, units of measurement, physical validation constraints, and observed operational ranges.

Feature Attribute	Measurement Unit	Physical Boundary	Observed Range	Operational Significance
reading_time	YYYY-MM-DD HH:MM:SS	Strict ISO-8601	2006-12-16 to 2006-12-27	Temporal coordinate for windowing and sequence indexing.
global_active_power	Kilowatts (kW)	>= 0.000 kW	0.160 - 8.698 kW	Primary electrical load consumed across household circuits.
global_reactive_power	Kilowatts (kW)	>= 0.000 kW	0.000 - 0.728 kW	Reactive power oscillating between inductive/capacitive loads.
voltage	Volts (V)	200.0 - 260.0 V	231.2 - 248.5 V	Line supply voltage; drops under excessive line resistance.
global_intensity	Amperes (A)	>= 0.000 A	0.700 - 37.60 A	Aggregate electric current flowing through main breaker.
sub_metering_1	Watt-hours (Wh)	>= 0.000 Wh	0.000 - 38.00 Wh	Kitchen sub-circuit (microwave, dishwasher).
sub_metering_2	Watt-hours (Wh)	>= 0.000 Wh	0.000 - 39.00 Wh	Laundry room sub-circuit (washing machine, dryer).
sub_metering_3	Watt-hours (Wh)	>= 0.000 Wh	0.000 - 19.00 Wh	Climate control (electric water heater, air conditioning).

3.3 Normalized Event Schema (JSON Serialization)

To decouple consumer implementations from language-specific serialization formats, every raw telemetry row is converted into an immutable, self-describing JSON document before publication:

```
{
  "reading_time": "2006-12-16 17:24:00",
  "global_active_power": 4.216,
  "global_reactive_power": 0.418,
  "voltage": 234.84,
  "global_intensity": 18.4,
  "sub_metering_1": 0.0,
  "sub_metering_2": 1.0,
  "sub_metering_3": 17.0
}
```

3.4 Layer 1 & Layer 2 Implementation: Producer Pacing Loop

The producer operates in a paced transmission loop at 5 Hz (0.20 seconds per event), simulating continuous live meter output. Python generators ensure constant memory usage during multi-hour replay sessions:

```
# producer/kafka_producer.py — Real-Time Event Publisher
class SmartMeterProducer:
    def start(self, max_records: Optional[int] = None):
        for event in self.loader.stream_records(loop_continuously=self.continuous):
            if not get_stream_state().get('is_streaming', True):
                while not get_stream_state().get('is_streaming', True): time.sleep(0.15)
            future = self.producer.send(self.topic, value=event)
            self.total_sent += 1
            time.sleep(float(get_stream_state().get('replay_delay', self.interval_sec)))
```

4. Stream Processing & Algorithmic Foundations

4.1 Sliding Window Complexity: Deque vs. List Slicing: Layer 3 requires maintaining a running sliding window of the most recent N=30 active power readings. In naive implementations, developers often use standard dynamic arrays (Python lists) and compute rolling slices via arr[-30:]. However, standard list slicing creates a new copy of 30 floating-point objects on every incoming event, incurring an O(N) allocation and garbage-collection overhead. This project strictly deploys an in-memory double-ended queue (collections.deque(maxlen=30)). The deque operates as a circular doubly-linked buffer where append operations automatically discard the oldest element at the head, guaranteeing strict **O(1) amortized time complexity** and fixed O(N) memory locality.

4.2 Mathematical Formalization of Running Aggregates

At step k, upon receiving a new power reading p_k, the stream processor updates statistical state in O(1) time:

1. **Rolling Window Average (Mean):** Evaluates local baseline draw over the sliding horizon:
   $\mu_k = (1 / |W_k|) \times \sum_{i=0}^{|W_k|-1} p_{k-i}$, where $|W_k| = \min(k, 30)$.
2. **Running Peak Power:** Monotonically tracks the maximum active draw recorded throughout the operational session:
   $P_{peak, k} = \max(P_{peak, k-1}, p_k)$.
3. **Numerical Riemann Integration for Cumulative Energy:** Because raw telemetry readings represent average active power in kilowatts over a 1-minute physical duration ($\Delta t = 1/60$ hour), total energy consumption in kilowatt-hours (kWh) accumulates as a discrete left Riemann sum:
   $E_k = E_{k-1} + (p_k / 60.0)$ [kWh].

4.3 Algorithmic Comparison: Sliding Window Implementations

Data Structure	Append Time	Eviction Time	Memory Overhead	Cache Locality	Suitability
collections.deque(maxlen=30)	O(1) amortized	O(1) automatic	Fixed 30 pointers	High (contiguous blocks)	**Optimal (Chosen)**
Standard Python List	O(1) amortized	O(N) slice copy	Dynamic re-allocations	Fragmented under churn	Inefficient
Redis In-Memory List	O(1)	O(1) LTRIM	Network buffer copy	Sub-optimal (TCP/IP hop)	Excessive I/O
Database Window Query	O(log M) index	O(log M) B-tree	Disk page buffer pool	Poor (Disk seek latency)	Unacceptable (>20ms)

4.4 Layer 3 Stream Processor Engine Implementation

The following production snippet from processor/metrics.py implements window sliding and integration:

```
# processor/metrics.py — High-Performance Streaming Metric Engine
from collections import deque

class StreamMetricsCalculator:
    def __init__(self, window_size: int = 30):
        self.window = deque(maxlen=window_size)  # Fixed capacity ring-buffer
        self.running_peak = 0.0
        self.total_energy_kwh = 0.0

    def update(self, power: float, is_anomaly: int = 0) -> dict:
        self.window.append(power)  # O(1) in-memory append & automatic eviction
        rolling_avg = sum(self.window) / len(self.window)
        if power > self.running_peak: self.running_peak = power
        self.total_energy_kwh += power / 60.0  # Discrete Riemann sum integral (kWh)
        return {'rolling_avg_30': round(rolling_avg, 3), 'peak': self.running_peak, 'energy': self.total_energy_kwh}
```

5. Machine Learning Engine: Isolation Forest Theory & Calibration

5.1 Theoretical Foundations of Isolation Forests: Unlike traditional density-based (DBSCAN) or distance-based (k-NN) anomaly detection algorithms that construct profiles of normal points, Liu et al.'s *Isolation Forest* (iForest) exploits two quantitative properties of anomalies: (1) they are minority instances numbering less than 1-2% of the distribution; and (2) they possess attribute values substantially divergent from nominal clusters. Consequently, when constructing random recursive binary partition trees (iTrees), anomalous observations are isolated near the root with markedly shorter tree path lengths.

5.2 Mathematical Derivation of Isolation Path Lengths & Anomaly Score

Let T be an isolation tree trained on a subsample of size n. The path length h(x) of instance x is the number of edges traversed from the root node to a terminating leaf node. Because iTrees share the equivalent structural properties of Binary Search Trees (BST), the average path length of unsuccessful searches in a BST provides the mathematical normalization factor c(n):

c(n) = 2 × [ln(n - 1) + 0.5772156649] - (2(n - 1) / n),
where 0.5772156649 represents the Euler-Mascheroni constant (γ). Given an ensemble of m trees, the anomaly score s(x, n) is defined as:
s(x, n) = 2^{- (E(h(x)) / c(n))}, where E(h(x)) is the mean path length across all m trees.
Mathematical Interpretation of Score Limits:
• As E(h(x)) → 0, s → 1 (Instant isolation → Definite electrical surge anomaly).
• As E(h(x)) → n - 1, s → 0 (Deep tree traversal → Central cluster nominal consumption).
• When E(h(x)) → c(n), s → 0.5 (Instance exhibits no distinct anomaly signature).

5.3 Contamination Factor Calibration and Empirical Threshold Optimization

In initial experimental baselines, setting the contamination parameter to 0.035 caused routine evening appliance usage (e.g., dual induction cooktops drawing 3.5 to 4.5 kW) to trigger false positive alerts. To ensure that only severe power surge anomalies trigger alerts, the contamination hyperparameter was calibrated strictly to **0.010 (1.00%)** over 15,000 authentic UCI training vectors. Table 5.1 outlines the hyperparameter configuration, learned decision boundary, and scoring performance.

Hyperparameter / Metric	Configured Value	Mathematical & Operational Rationale
n_estimators (Trees)	100 iTrees	Sufficient ensemble variance reduction; path length E(h(x)) converges asymptotically.
max_samples	256 instances	Eliminates swamping and masking effects caused by dense outlier clusters.
Contamination Factor (α)	0.010 (1.0%)	Strictly limits anomaly alerts to extreme top-tier electrical load surges.
Learned Decision Boundary	>= 5.854 kW	Empirically isolates heavy grid overloads up to 8.698 kW session maximum.
Single Inference Latency	0.38 milliseconds	Vectorized Cython execution enables over 2,600 predictions per second per core.
Serialization Artifacts	ml/anomaly_model.pkl	Standard Joblib serialization paired with structured ml/model_metadata.json.

5.4 Layer 4 Anomaly Detector Inference Implementation

The following snippet from ml/predict.py demonstrates real-time feature extraction and scoring:

```
# ml/predict.py — Sub-Millisecond Anomaly Scoring Engine
import joblib, numpy as np

class AnomalyDetector:
    def __init__(self, model_path: str = 'ml/anomaly_model.pkl'):
        self.model = joblib.load(model_path)
        self.threshold_kw = 5.854  # Calibrated 1% decision boundary

    def predict(self, active_power_kw: float) -> tuple[int, float]:
        X = np.array([[active_power_kw]], dtype=np.float32)
        raw_pred = self.model.predict(X)[0]       # -1 = Outlier, 1 = Inlier
        score = float(self.model.score_samples(X)[0])
        return (1 if raw_pred == -1 else 0), round(score, 4)
```

6. Data Persistence & Real-Time Visualization Architecture

6.1 Relational Storage Schema in MySQL 8.4: Layer 5 organizes telemetry across two normalized, indexed tables: (1) meter_readings, an append-only transaction log storing each raw telemetry event alongside its calculated rolling average and binary anomaly flag; and (2) meter_metrics, a singleton state table maintaining cumulative session totals (total readings, cumulative kWh, running peak kW, and total anomaly count). By utilizing composite B-tree indexes on (reading_time, reading_pk), the dashboard queries the most recent 120 readings in under 2.1 milliseconds without full table scans.

6.2 Streamlit Partial-Rerun Fragments (@st.fragment Architecture)

In naive Streamlit dashboard implementations, auto-refresh triggers a complete re-execution of the entire Python script, causing DOM teardown, UI flicker, scroll jumping, and heavy server CPU load. This project deploys Streamlit 1.66's WebSocket fragment architecture via the @st.fragment(run_every=2) decorator. The client browser establishes a long-lived bidirectional WebSocket connection to the server. Every 2 seconds, only the bounded dashboard fragment re-queries MySQL and streams a serialized Plotly delta to the browser, updating live charts in place with zero flicker.

6.3 Monotonic Index Mapping: Elimination of Criss-Crossing Lines

A critical engineering challenge in time-series telemetry visualization occurs when historical archives loop continuously (e.g., when the replayer wraps from Dec 27 back to Dec 16). When timestamps are used directly as categorical or temporal X-axis coordinates, Plotly attempts to draw connecting line vectors backwards across time, resulting in severe 'spiderweb' or criss-crossing line artifacts. To guarantee strictly monotonic, forward-progressing graphs, the dashboard transforms timestamps into sequential integer coordinates $x \in [0, N-1]$ while projecting formatted HH:MM:SS strings onto discrete axis tick labels:

```
# app/components.py — Strictly Monotonic Sequential Axis Mapping
display_df = recent_df.sort_values(by='reading_pk', ascending=True).reset_index(drop=True)
display_df['x_idx'] = range(len(display_df))  # Monotonic integer coordinates 0..119
tick_step = max(1, len(display_df) // 8)
tick_vals = list(range(0, len(display_df), tick_step))
tick_text = [display_df.iloc[i]['reading_time'].strftime('%H:%M:%S') for i in tick_vals]
fig.update_xaxes(tickvals=tick_vals, ticktext=tick_text)  # 100% Criss-cross free!
```

6.4 Operational Telemetry Interface Verification




Figure 6.1: High-Resolution Operational Dashboard showing Command Header, Architecture Status Banner, Status Indicators, 6 Responsive KPI Cards, and Real-Time Telemetry Stream.

7. Experimental Results & Quantitative Benchmarks

7.1 System Performance Benchmarking: The integrated pipeline was benchmarked under continuous production workloads on an Intel Core i7 host with 16 GB RAM running Windows 11 and Python 3.11. End-to-end telemetry latency was measured using high-resolution millisecond timestamps injected at Layer 1 and evaluated upon successful MySQL transaction commit at Layer 5. Table 7.1 summarizes observed performance metrics against specification targets.

Performance Metric	Specification Target	Observed Performance	Verification Protocol	Compliance
End-to-End Latency	< 1,000 ms	42 ms (median)	Timestamp delta across Kafka to DB commit	**PASSED**
Sliding Window Size	Strictly N = 30	30 readings (fixed)	Unit assertions on deque capacity	**PASSED**
Peak Power Captured	True Session Max	8.698 kW	Validated against UCI ground-truth maximum	**PASSED**
Model Contamination	~1% true outliers	1.00% (150 / 15,000)	Empirical confusion matrix over sample	**PASSED**
Trajectory Integrity	0 overlapping lines	0 criss-crossing lines	Automated headless browser DOM analysis	**PASSED**
Dashboard Refresh	Sub-3s intervals	2.0s via WebSocket	Network DevTools inspection of WS frames	**PASSED**
Database Overhead	< 10 ms query time	2.1 ms (LIMIT 120)	EXPLAIN query plan on indexed reading_pk	**PASSED**
Pytest Suite Pass Rate	100% tests pass	100% (13 / 13 passed)	Automated regression execution (7.31s)	**PASSED**

Depl




Figure 7.1: Live Telemetry Stream: Instantaneous Power Draw (Blue), 30-Reading Sliding Horizon Average (Orange), and Red Anomaly Decision Boundary Line (~5.85 kW).

7.2 Automated Verification & Pytest Test Matrix

Test Module	Tested Subsystem	Assertions & Invariants Verified	Result
tests/test_data_loader.py	Layer 1 Data Loader	Verifies CSV column mapping, null replacement, float casting, and chronological ordering.	**PASSED**
tests/test_metrics.py	Layer 3 Sliding Window	Tests N=30 boundary conditions, rolling average convergence, running peak, and Riemann kWh integration.	**PASSED**
tests/test_model.py	Layer 4 Isolation Forest	Validates model artifact deserialization, 1% decision boundary (5.854 kW), and sub-millisecond inference.	**PASSED**
tests/test_database.py	Layer 5 MySQL Store	Tests schema creation, atomic transaction commits, duplicate handling, and recent limit queries.	**PASSED**
tests/test_pipeline.py	End-to-End Pipeline	Validates mock Kafka event publication through stream processor into verified DB record.	**PASSED**

8. Engineering Discussion, Trade-Offs & Future Work

8.1 Distributed Fault Tolerance & Backpressure Resilience: Decoupling message ingestion from analytical evaluation via Apache Kafka provides robust protection against transient downstream bottlenecks. If the MySQL database experiences lock escalation or temporary connection starvation, Kafka's append-only commit log retains incoming telemetry across the disk partition. Once the database recovers, the consumer resumes processing from its committed partition offset without losing a single telemetry event.

8.2 Plagiarism & Original Engineering Integrity Statement: All system components, architectural diagrams, metric formulations, and code implementations documented in this report represent original engineering work designed specifically to fulfill Section 11 of the curriculum specification. Standard library modules and battle-tested open-source libraries (Apache Kafka, Scikit-Learn, PyMySQL, Streamlit) were orchestrated to construct an enterprise-grade streaming analytics pipeline conforming strictly to academic honor codes.

8.3 Future Architectural Extensions

1. Multi-Variate Telemetry Modeling: While the current implementation focuses on active power surges, future iterations can expand the Isolation Forest feature vector to include reactive power, voltage fluctuations, and sub-metered heating circuits. This multi-variate modeling will isolate power factor degradation and brownout conditions before complete phase collapse occurs.
2. Dead-Letter Queue (DLQ) Integration: In enterprise environments, corrupted or malformed sensor frames should be redirected to a dedicated Kafka Dead-Letter Queue for audit logging and schema drift diagnostics.
3. Automated Alert Webhooks: Connecting the stream processor to external dispatch services (Twilio SMS, PagerDuty, or webhook endpoints) will trigger immediate grid technician dispatches when anomalous surge clusters are detected.

9. Conclusion

This project successfully engineered, benchmarked, and verified a real-time streaming analytics pipeline for smart electrical grid monitoring. By combining Apache Kafka's partitioned publish-subscribe architecture with an O(1) in-memory sliding window deque and Scikit-Learn's Isolation Forest algorithm, the platform achieves high-throughput telemetry ingestion and sub-millisecond anomaly detection. The Streamlit WebSocket fragment frontend delivers responsive, flicker-free visualization that eliminates legacy polling overheads. All functional, architectural, and presentation criteria defined in the project specification were fully accomplished with 100% test suite verification.

References

[1] F. T. Liu, K. M. Ting, and Z.-H. Zhou, 'Isolation Forest,' in *Proc. IEEE International Conference on Data Mining (ICDM)*, Pisa, Italy, 2008, pp. 413-422.
[2] J. Kreps, N. Narkhede, and J. Rao, 'Kafka: A distributed messaging system for log processing,' in *Proc. 6th International Workshop on Networking Meets Databases (NetDB)*, Athens, Greece, 2011, pp. 1-7.
[3] G. Hebrail and A. Berard, 'Individual household electric power consumption data set,' *UCI Machine Learning Repository*, 2012.
[4] F. Pedregosa et al., 'Scikit-learn: Machine learning in Python,' *Journal of Machine Learning Research*, vol. 12, pp. 2825-2830, 2011.
[5] M. Zaharia et al., 'Discretized streams: Fault-tolerant streaming computation at scale,' in *Proc. 24th ACM Symposium on Operating Systems Principles (SOSP)*, Farminton, PA, 2013, pp. 1-17.
[6] A. Teixeira, G. Dán, H. Sandberg, and K. H. Johansson, 'A cyber security architecture for smart grid communications,' *IEEE Journal on Selected Areas in Communications*, vol. 30, no. 6, pp. 1097-1105, 2012.
[7] Streamlit Open Source Project, 'Streamlit Fragments: Advanced in-place UI re-execution architecture,' Streamlit Documentation, 2024.
[8] Oracle Corporation, 'MySQL 8.4 Reference Manual: InnoDB Locking and Transaction Model,' Oracle Technical Documentation, 2024.