

Amortization :

P-0/1

- Suppose our data structure supports operations A, B, C

- We say the "amortized costs" of these operations are t_A, t_B, t_C if ~~any~~ s_a respectively, if any sequence n_A of A operations, n_B of B operations, n_C of C operations

$$\text{takes time} \leq n_A t_A + n_B t_B + n_C t_C$$

- Common way to prove amortized bounds is via potential function method.

Define potential $\phi: \phi\{\text{state (space) of data structure}\} \rightarrow \mathbb{R}^+$

$$\phi\{\text{empty structure}\} = 0$$

- Let us say ~~that~~ we perform k operations with actual times t_1, t_2, \dots, t_k ,

States of the data structure are

$$S_0, S_1, S_2, \dots, S_i, \dots, S_k$$

\uparrow
before
any operation

\downarrow
after i th
operation

- amortized cost of ~~an~~ ^{i th} operation is ~~defined to~~ ^{bounded} by $t_i + \phi(S_i) - \phi(S_{i+1})$

- The total amortized cost is bounded by

$$\sum t_i + \Delta \phi = \sum t_i + \phi(S_k) - \phi(S_0)$$

$$= \sum t_i + \phi(S_k) \geq \sum t_i$$

Stack operations

push, pop, multipop

Define potential Φ on a stack to be the number of object in the stack.

i.e., $\Phi\{\text{state of the stack}\} \rightarrow \text{number of object in the stack.}$

• $\Phi(S_0) = 0$ [$\because S_0$ is the empty stack]

• If the i th operation on a stack containing s object is a push operation, then the potential difference is $\Delta\Phi = \Phi(S_i) - \Phi(S_{i-1}) = (s+1) - s = 1$

\therefore The amortized cost of push operation is equal to

$$t_i + \Delta\Phi = 1 + 1 = 2$$

↓
actual cost of push operation

• Suppose the i th operation on the stack is $\text{multipop}(S, k)$, which caused $k' = \min(k, s)$ object to be ~~popped~~ popped off the stack, the actual cost of the operation is k' , and the potential difference $\Delta\Phi = \Phi(S_i) - \Phi(S_{i-1}) = -k'$

\therefore The amortized cost of multipop operation is equal to $t_i + \Delta\Phi = k' - k' = 0$

Similarly, the amortized cost of an ordinary pop operation is 0.

Incrementing a binary counter (k bits)

$\Phi\{\text{state of the counter}\} \rightarrow \# \text{ of 1s in the counter.}$

Let b_i be the number of 1s after i th increment operation.

Suppose that the i th increment operation resets t_i bits.
 \downarrow from 1 to 0

\therefore Actual cost of the i th operation is $t_i + 1$

— If $b_i = 0$, then i th operation resets all k values, and so $b_{i-1} = t_i = k$

— If $b_i > 0$, then $b_i = b_{i-1} - t_i + 1$

In either case, $b_i \leq b_{i-1} - t_i + 1$, and the potential difference $\Phi(s_i) - \Phi(s_{i-1})$
 $\leq (b_{i-1} - t_i + 1) - b_{i-1}$
 $= 1 - t_i$

\therefore The amortized cost
 $= \text{actual cost} + \text{potential difference}$
 $= (t_i + 1) + (1 - t_i)$
 $= 2$

It is a k bits counter

Handwritten header or title at the top of the page.

Main body of handwritten text, consisting of several lines of cursive script.

Handwritten text at the bottom of the page, possibly a signature or concluding remarks.

- Heap (H) (abstract data structure)

P-1

• supports

- insert (x)

- deleteMin(H) \rightarrow return min $x \in H$, then delete it

~~decrease key~~

- decrease key (decrease key value of an item)

Dijkstra run time \rightarrow
 $O(n \cdot (t_I + t_{delmin}) + m \cdot t_{decrease})$

Implementation of heap

- Binary heaps (Williams, 1984)

• Insertion (t_I) = deleteMin (t_{dm}) =

decrease (t_{dk}) = $O(\log n)$

- ~~Binomial~~ ^{Binomial} heaps (Vuillemin, 1978)

• amortized $t_I = O(1)$ $t_{dm} = O(\log n)$

• worst case $t_{dm} = t_{dk} = O(\log n)$

worst case $t_I = O(\log n)$

- Fibonacci heaps (Fredman, Tarjan, JACM '87)

• amortized $t_I = t_{decrease} = O(1)$, ~~t_{dm}~~

$t_{delmin} = O(\log n)$

[• Brodal SODA '96

- gets all the same bound as Fibonacci heap but worst case

• Brodal, Logarithm, Tarjan, STOC '12]

- Same as above, just using pointer machine pointer


• Kaplan, Tarjan, Zwick
arXiv '14

Binomial Heap

P-2


- ① • Each item is a node, and we maintain these nodes in a forest.
- ② • If $x = \text{parent}(y)$, then $\text{key}(x) \leq \text{key}(y)$
- ③ • For a tree in a heap, its "rank" is the degree of its root
- ④ • A tree with rank k has 2^k nodes in it
- ⑤ • For each k , we will have at most 1 tree of rank k .
- ⑥ • Root of rank k has k subtrees, these are trees of rank $0, 1, \dots, k-1$

Example:



DecreaseKey: change the key, then keep swapping upwards as necessary.

Insert(x): Add a new singleton tree to forest, then repeatedly merge trees of equal rank.



It looks like a binary number addition


1111

10000


→ Result structure contains only 1 tree with

After adding new node it is violating condⁿ ⑤


rank 4 (by merging)




2 nodes have rank 0




2 nodes have rank 1



2 nodes have rank 2



2 nodes have rank 3



• worst-case running time $O(\log n)$

• amortized time $O(1)$.

binary counter
in amortized
time complexity

Insertion cost:

Worst case: all operation takes $O(\log n)$ time

~~Explain~~

potential ~~tree~~:

• $\Phi(\text{data structure state}) = \# \text{ trees}$

• Actual cost of an insertion is

$$O(T - t + 1)$$

↑
old
number of
trees

↘
new
number of
trees

amortized cost of insertion

$$\begin{aligned} & \text{actual cost} + \text{potential difference} \\ &= \text{actual cost} + \Phi - \Phi \end{aligned}$$

$$T - t + 1 + t - T$$

$$= 1$$

→ ~~cost~~ ⇒ amortized cost of insertion is $O(1)$.

DeleteMin: ~~delete~~ remove root of pull
some tree (mainly min), and
insert all its children as root in the main
forest. now merge equal rank trees.

- worst case running time $O(\log n)$

- Amortized time $O(\log n)$. ~~binning counter~~ is amortized time complexity.

Fibonacci Heap

Dekey: amortized $O(1)$

- No reason for insertions to spend time ~~consolidating~~
consolidating. Do all consolidation during DeleteMin.

- Really, lazy dekey

de x 's key, and if x 's new ^{key} is smaller
than parent, cut x 's tree out and place as
a top level tree.

~~•~~ If node p loses one child due to
dekey, no problem. If p loses a second
child, we cut p out of its tree too, and
make p 's tree a top level tree.


size
rank

1
0
2
1
0

4 → 3


8 → 5

P-5



can't afford dekey
as it parent lost two
childs, so it will be
place on top
level tree \Rightarrow it will tra
~~verse~~ will do it
rank 3.

rank 4 size - 16 \rightarrow 8



Claim: amortized $t_{\text{I}}, t_{\text{dk}} = O(1)$, $t_{\text{dm}} = O(\log n)$.

Insertion: amortized $O(1)$

Deletion: $O(\log n)$

dekey: amortized $O(1) \rightarrow$ How?

let $\text{mark}(x) = \begin{cases} 1 & \text{if } x \text{ has lost child} \\ 0 & \text{otherwise} \end{cases}$

$$\Phi(\text{state}) = \underbrace{\# \text{ trees}}_{T(H)} + 2(\underbrace{\# \text{ marked items}}_{m(H)})$$

\downarrow It is coming from the fact that
after the operation dekey the changes happen
on (i) $\#$ trees, and (ii) $\#$ marked items

Insertion:

P-6

$$\underbrace{\text{actual cost}}_{O(1)} + \underbrace{\Delta \phi}_1 = O(1)$$

delete min:

$$T + \underbrace{\Delta T(H)}_{t-T} + \underbrace{\Delta m(H)}_{\leq 0}$$
$$= O(t) = O(\log n)$$

dekey:

case 1: \times ~~does~~ does not cut out

$$\underbrace{\text{actual cost}}_{O(1)} + \underbrace{\Delta \phi}_0 = O(1)$$

case 2: we do some number $c > 0$ of cascaded cut

$$\underbrace{\text{actual cost}}_c + \underbrace{\Delta T(H)}_c + \underbrace{2 \Delta m(H)}_{-2c + 1}$$
$$= O(1)$$

4/02/2023

200123055
210123006
210123041
222123014
200106055
200106019
210123062
200123010
200123025
200123045
222123029

13/02/2024

200106055
200106019
236123006
210123030
210123029
210123006
222123015
222123043
200123021
200123045
222123045
222123001
210123014
210123041