

MLS Integration Setup Guide

CONFIGURATION, LICENSING, & ENVIRONMENT VARIABLES

Status: MLS "Not Configured"

The application contains all core functionality for pulling real estate listings. However, access requires a feed address and key from an authorized MLS data provider, granted through a paid license agreement.

1. Required Credentials & Licensing

- MLS Data License (IDX or VOW):** Acquire a license from your local Multiple Listing Service (MLS). You or an affiliated broker must be an active member. Request *"IDX or VOW data feed access through the RESO Web API."*
- MLS Data Vendor Identification:** Confirm which platform manages your MLS data. Supported vendor specifications:

Vendor	Credentials Provided
Bridge Interactive	Feed URL + Access Token
MLS Grid	Feed URL + Access Token
Spark / Flexmls	Feed URL + Access Token
Trestle (CoreLogic)	Client ID + Client Secret + OAuth Token URL

2. Environment Configuration

Add the credential details to **Vercel** (*Project Settings* → *Environment Variables*) or to your local `.env.local` file:

```
# Standard RESO Provider Configuration
MLS_RESO_URL=https://api.vendor.com/reso/v1/
MLS_ACCESS_TOKEN=your_vendor_access_token
MLS_NAME=Your_Local_MLS_Name
# Trestle (CoreLogic) Specific Credentials
MLS_OAUTH_TOKEN_URL=https://trestle.corelogic.com/connect/token
MLS_CLIENT_ID=your_client_id
MLS_CLIENT_SECRET=your_client_secret
```

* Refer to `.env.example` in the repository for specific vendor formatting.

3. Deployment & Synchronization

- Manual Sync:** Once environment variables are configured and deployed, navigate to **Listings** in the app and click **Sync MLS now**.
- Automatic Daily Sync:** Automatic updates require setting the `CRON_SECRET` environment variable (detailed in project `README.md`).

Immediate Sandbox Testing (No License Required)

To test the end-to-end integration pipeline today without an active MLS license, set the variable below and redeploy:

`MLS_PROVIDER=bridge-test`

This connects to Bridge Interactive's public sandbox using mock listings tagged as **TEST DATA**. The app automatically purges test records upon the first successful sync of a live MLS feed.

SECURITY NOTICE: Never commit tokens or client secrets to Git repositories, public chats, or frontend client bundles. Store sensitive values exclusively in secure environment configuration settings.